




Exceptions



What? Why?

An exception signals that something went *exceptionally* wrong.

- Development mistakes
- Errors produced by external (to the program) resources
- System errors

Why use exceptions:

- To separate error-handling code from regular code
- To propagate errors up the call stack – maybe someone knows how to deal with the error
- To group and differentiate error types

Do NOT use exceptions for:

- Control flow
- Manageable errors

How?

```
fun main() {  
    throw Exception("Hello, world!")  
}
```

Or even better:

```
fun main() {  
    val nullableString: String? = null  
    println("Hello, NPE! ${nullableString!!}")  
}
```

Exception in thread "main" java.lang.NullPointerException

Example

```
fun main() {  
    try {  
        throw Exception("An exception", RuntimeException("A cause"))  
    } catch (e: Exception) {  
        println("Message: ${e.message}")  
        println("Cause: ${e.cause}")  
        println("Exception: $e") // toString() is called "under the hood"  
        e.printStackTrace()  
    } finally {  
        println("Finally always executes")  
    }  
}
```

```
Message: An exception  
Cause: java.lang.RuntimeException: A cause  
Exception: java.lang.Exception: An exception  
Finally always executes  
java.lang.Exception: An exception  
    at MainKt.main(Main.kt:3)  
    at MainKt.main(Main.kt)  
Caused by: java.lang.RuntimeException: A cause  
    ... 2 more
```

Another meaningful example


```
data class Person(val name: String, val surname: String, val age: Int) {  
    init {  
        if (age < 0) {  
            throw IllegalStateException("Age cannot be negative")  
        }  
        if (name.isEmpty() || surname.isEmpty()) {  
            throw IllegalArgumentException("For blank names/surnames use -")  
        }  
    }  
}
```

Dealing with exceptions

```
try {  
    val (n, s, a) = readLine()!!.split('/')  
    val person = Person(n, s, a.toInt())  
    addToDataBase(person)  
} catch (e: IllegalStateException) {  
    println("You've entered a negative age! Why?")  
} catch (e: IllegalArgumentException) {  
    println(e.message)  
} catch (e: NullPointerException) {  
    println("NPE ;^")  
} catch (e: Exception) {  
    println("Something else went wrong")  
    throw Exception("Failed to add to the database", e)  
} finally {  
    println("See you in the next episodes!")  
}
```

You might:

- Handle the error properly and continue execution
- Handle something on your side and re-throw the exception



And a lot in `java.util`

Kotlin sugar

`try` is an expression:

```
val a: Int? = try { input.toInt() } catch (e: NumberFormatException) { null }
```

More sugar:

```
require(count ≥ 0) { "Count must be non-negative, was $count" }  
// IllegalArgumentException
```

```
error("Error message")  
// IllegalStateException
```

Thanks!



@kotlin | Developed by JetBrains