**SAMARA YACHTING**
ERP Platform

# JSON REST API Specification Document

ERP Bot API (Read-Only Data Access)
Release 1.0.0

October, 2026

**Confidentiality**
*This document contains proprietary information that is confidential to Samara Yachting. It describes access to internal business data. Disclosure of this document, or of any API key issued under it, in full or in part, to a third party requires prior written permission from Samara Yachting.*

## Table of Contents


CHAPTER 1 — OVERVIEW . . . . . 4

CHAPTER 2 — AUTHENTICATION . . . . . 5

CHAPTER 3 — GENERAL CONVENTIONS . . . . . 6

- 3.1 Data Types . . . . . 6
- 3.2 Pagination . . . . . 6
- 3.3 Ordering . . . . . 6
- 3.4 Date Range . . . . . 6
- 3.5 Field Filters . . . . . 6
- 3.6 Response Envelope . . . . . 6
- 3.7 Global Response Codes . . . . . 6
- 3.8 Usage Guidelines . . . . . 7

CHAPTER 4 — ENDPOINTS . . . . . 8

- 4.1 Resource Catalog . . . . . 8
- 4.2 List Records . . . . . 9
- 4.3 Retrieve Record . . . . . 10

CHAPTER 5 — RESOURCE REFERENCE . . . . . 12

- 5.1 Sales & Booking . . . . . 14
- 5.2 Finance . . . . . 22
- 5.3 Fleet & Operations . . . . . 26
- 5.4 Purchasing . . . . . 30
- 5.5 Stock & Warehouse . . . . . 36
- 5.6 POS / Cashier . . . . . 43
- 5.7 Marketing . . . . . 47

CHAPTER 6 — DATA ACCESS RESTRICTIONS . . . . . 49

- 6.1 Modules Not Exposed . . . . . 49
- 6.2 Columns Always Removed . . . . . 49

CHAPTER 7 — APPENDIX . . . . . 50

- A. API Key Format . . . . . 50
- B. Issuing, Revoking and Rotating Keys . . . . . 50
- C. Client Examples . . . . . 50

## Document Change Control

| Version | Date | Authors | Summary of Changes |
|---|---|---|---|
| 0.9.0 | 09/10/2026 | ERP Engineering | BOT role introduced: read-only, deny-by-default access limited to GET /api/bot/* (session login). |
| 1.0.0 | 15/10/2026 | ERP Engineering | Add API key authentication (Authorization: Bearer sbk_...) for external analysis tools.<br>API key carries exactly the BOT role access, no more.<br>Add revocation via BOT user password change, account deactivation and BOT_API_KEY_SECRET rotation.<br>First release of this specification: 64 resources. |

CHAPTER 1

# OVERVIEW

***Summary***

The ERP Bot API gives AI bots and external analysis tools **read-only** access to Samara Yachting ERP business data: bookings, revenue, payments, costs, purchasing, stock, fleet operations, onboard POS and marketing campaigns. It is designed for reporting and analysis; it can never create, change, approve or delete anything.

| Method | URL | Description |
|---|---|---|
| GET | /api/bot | Catalog: every resource the API key can read, with its columns |
| GET | /api/bot/{resource} | List records of a resource (paginated, filterable) |
| GET | /api/bot/{resource}/{id} | Retrieve a single record by id |

***Access Model***

- Every API key is bound to one ERP user account with role **BOT** and authenticates as that user. It receives exactly the BOT role's access.
- Only **GET** and **HEAD** are accepted. POST, PUT, PATCH and DELETE are refused (HTTP 403) before any handler runs.
- Only paths under **/api/bot** accept the key. On every other ERP route the Authorization header is ignored.
- Only whitelisted resources (Chapter 5) are reachable. Only their scalar columns are returned; relations are never embedded.
- Sensitive columns are removed server-side on every response (Chapter 6), including keys nested inside JSON columns.
- If a request carries both an API key and a browser session cookie, only the API key is considered.

***Environment***

| Item | Value |
|---|---|
| Base URL | https://{erp-domain} (the production ERP host) |
| Protocol | HTTPS only |
| Content type | application/json; charset=utf-8 |
| Time zone | All DateTime values are UTC, ISO-8601 (e.g. 2026-10-01T08:00:00.000Z) |
| Tenant | Bound to the API key; one key reads one company database |

CHAPTER 2

# AUTHENTICATION

***Summary***

Authentication uses a static **API key** sent in the Authorization header of every request. There is no token exchange step and no expiry: a key stays valid until it is revoked (Appendix B). Keys are issued by an ERP administrator and must be stored as a secret on the calling system.

***Input Parameters***

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Header** | | | | |
| | Authorization | M | String | Bearer {API Key}<br>Format: **sbk_<base64url payload>.<base64url HMAC-SHA256>** |
| | Accept | O | String | application/json |

***Sample Request***

```
GET /api/bot HTTP/1.1
Host: {erp-domain}
Authorization: Bearer sbk_eyJ0IjoiPHRlbmFudD4iLCJ1IjoiPHVzZXI+In0.<signature>
Accept: application/json
```

***Response Message***

| HTTP Code | Response Body | Description |
|---|---|---|
| 200 | (resource payload) | Key valid, request served |
| 401 | {"error":"Invalid API key"} | Malformed key, wrong signature, key revoked, BOT user deleted / changed role / deactivated, or tenant inactive |
| 403 | {"error":"Bot API keys are read-only"} | Method other than GET / HEAD sent with an API key |
| 307 | (redirect to /login) | No Authorization header and no session: the request is treated as an anonymous browser visit |

CHAPTER 3

# GENERAL CONVENTIONS

## 3.1 Data Types

| Type | JSON representation | Sample |
|---|---|---|
| String | string | "Samara I" |
| Int | number (integer) | 12 |
| Float | number | 18500000.5 |
| Boolean | boolean | true |
| DateTime | string, ISO-8601 UTC | "2026-10-01T08:00:00.000Z" |
| Json | object / array (sensitive keys removed) | {"note":"..."} |
| Enum | string, one of the listed values (Chapter 5) | "CONFIRMED" |
| (any) | null when the column is empty | null |

## 3.2 Pagination

List endpoints use cursor pagination. Request up to **limit** rows (default 100, maximum 500). When more rows exist, the response carries **nextCursor** (the id of the last row returned); send it back as **cursor** to get the next page. **nextCursor = null** means the last page. Keep every other query parameter identical between pages.

## 3.3 Ordering

Rows are returned newest first: by the resource's date column descending (see "Date column" per resource), then by id descending. Resources without a date column are ordered by id descending.

## 3.4 Date Range

**from** and **to** (YYYY-MM-DD or full ISO-8601) filter the resource's date column inclusively (*from* <= value <= *to*). A bare date means midnight UTC, so **to=2026-12-31** excludes rows later on 31 Dec; use **to=2026-12-31T23:59:59Z** for the full day.

## 3.5 Field Filters

Any column listed for a resource can be used as an exact-match filter: **?{column}={value}**. Several filters are combined with AND. Values are converted by column type (Int, Float, Boolean "true"/"false", DateTime). The literal value **null** matches empty columns. A column that is not listed (unknown or hidden) is rejected with HTTP 400, never silently ignored. Partial-text, range (other than the date column) and OR filters are not supported; fetch and filter client-side.

## 3.6 Response Envelope

| Endpoint | Body |
|---|---|
| List | { "resource": string, "count": number, "nextCursor": string\|null, "data": [ {record}, ... ] } |
| Detail | { "resource": string, "data": {record} } |
| Error | { "error": string } |

## 3.7 Global Response Codes

| HTTP Code | Response Body | Description |
|---|---|---|
| 200 | Success envelope | Success |
| 400 | {"error":"Invalid from/to date"} | from or to cannot be parsed as a date |
| 400 | {"error":"Unknown or non-filterable field: {field}"} | Filter on a column that does not exist or is hidden |
| 400 | {"error":"Query failed — check filter values"} | Filter value of the wrong type, or invalid cursor |

| HTTP Code | Response Body | Description |
|---|---|---|
| 401 | {"error":"Invalid API key"} | See Chapter 2 |
| 403 | {"error":"Bot API keys are read-only"} | Write method attempted |
| 404 | {"error":"Unknown resource — see GET /api/bot"} | Resource name not in the whitelist |
| 404 | {"error":"Not found"} | Detail: no record with this id (or the record is excluded, e.g. salary expense) |
| 500 | (server error) | Unexpected error in the ERP. Retry later; report if persistent |

## 3.8 Usage Guidelines

- Fetch incrementally with from/to rather than re-downloading full history on every run.
- Use limit=500 for bulk export and page with nextCursor; avoid more than a few requests per second.
- Join resources client-side through their *Id columns (e.g. payments.bookingId = bookings.id).
- Never log or commit the API key. Treat exported data as confidential company data.

CHAPTER 4

# ENDPOINTS

## 4.1 Resource Catalog

Lists every resource readable with the key, its path and its columns. Use it to discover the schema at runtime; it always reflects the live server, including columns added after this document.
**GET** : /api/bot

### *Input Parameter*

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **HTTP Header** | | | | |
| | Authorization | M | String | Bearer {API Key}. Format **sbk_<payload>.<signature>**. See Appendix A. |
| | Accept | O | String | application/json |
| **Query** | | | | |
| | (none) | - | - | - |

### *Output Parameter*

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Body** | | | | |
| | readOnly | M | Boolean | Always true |
| | usage | M | Object | Short usage notes: auth, list, detail, notes |
| | resources | M | Array of Object | One entry per resource |
| | name | M | String | Resource name used in the URL |
| | path | M | String | /api/bot/{name} |
| | description | M | String | What the resource contains |
| | fields | M | Array of Object | { name, type } for every readable column |

### *Sample Response*

```
{
  "readOnly": true,
  "usage": {
    "auth": "Header \"Authorization: Bearer sbk_...\" (BOT API key), or a logged-in BOT session cookie",
    "list": "GET /api/bot/{resource}?limit=100&cursor={lastId}&from=YYYY-MM-DD&to=YYYY-MM-DD&{field}={value}",
    "detail": "GET /api/bot/{resource}/{id}",
    "notes": "limit max 500. from/to filter the resource's main date column. ..."
  },
  "resources": [
    {
      "name": "bookings",
      "path": "/api/bot/bookings",
      "description": "Bookings (charter & open trip), prices, status",
      "fields": [ { "name": "id", "type": "String" }, { "name": "startDate", "type": "DateTime" }, ... ]
    },
    ...
  ]
}
```

## 4.2 List Records

Returns records of one resource, newest first, with optional date range and exact-match column filters.
**GET** : /api/bot/{resource}

### *Input Parameter*

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **HTTP Header** | | | | |
| | Authorization | M | String | Bearer {API Key}. Format **sbk_<payload>.<signature>**. See Appendix A. |
| | Accept | O | String | application/json |
| **Path** | | | | |
| | resource | M | String | Resource name, e.g. bookings. See Chapter 5 |
| **Query** | | | | |
| | limit | O | Int | Rows per page. Default 100, min 1, max 500 |
| | cursor | O | String | nextCursor from the previous page |
| | from | O | String | Lower bound (inclusive) of the date column. YYYY-MM-DD or ISO-8601 |
| | to | O | String | Upper bound (inclusive) of the date column |
| | {column} | O | per column | Exact-match filter on any listed column; "null" = empty. Repeatable for different columns |

### *Output Parameter*

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Body** | | | | |
| | resource | M | String | Echo of the resource name |
| | count | M | Int | Number of rows in this page |
| | nextCursor | M | String / null | Cursor for the next page; null on the last page |
| | data | M | Array of Object | Records; keys = the resource's columns (Chapter 5) |

### *Sample Request*

```
GET /api/bot/payments?from=2026-09-01&to=2026-09-30T23:59:59Z&status=PAID&limit=2 HTTP/1.1
Authorization: Bearer sbk_...
```

### *Sample Response (on normal condition)*

```
{
  "resource": "payments",
  "count": 2,
  "nextCursor": "cmxxxxxxxxxxxxxxxxxxxxxx",
  "data": [
    {
      "id": "cmxxxxxxxxxxxxxxxxxxxxxx",
      "bookingId": "cmxxxxxxxxxxxxxxxxxxxxxx",
      "invoiceNumber": "XX-2026-0001",
      "paymentType": "string",
      "paymentMethod": "string",
      "amount": 2500000,
      "previouslyPaid": 2500000,
      "paymentDate": "2026-10-01T08:00:00.000Z"
    },
    { ... }
  ]
}
```

### *Response Message*

| HTTP Code | Response Body | Description |
|---|---|---|
| 200 | List envelope | Success (count may be 0) |
| 400 | Invalid from/to date | from/to not a date |
| 400 | Unknown or non-filterable field: {field} | Filter column not listed for this resource |
| 400 | Query failed — check filter values | Value type mismatch (e.g. text on an Int column, unknown enum value) or bad cursor |
| 401 | Invalid API key | Authentication failed |
| 403 | Bot API keys are read-only | Non-GET method |
| 404 | Unknown resource — see GET /api/bot | Resource not whitelisted |

## 4.3 Retrieve Record

Returns one record by id. Same columns as the list endpoint.
**GET** : /api/bot/{resource}/{id}

### *Input Parameter*

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **HTTP Header** | | | | |
| | Authorization | M | String | Bearer {API Key}. Format **sbk_<payload>.<signature>**. See Appendix A. |
| | Accept | O | String | application/json |
| **Path** | | | | |
| | resource | M | String | Resource name |
| | id | M | String | Record id (the "id" column) |

### *Output Parameter*

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Body** | | | | |
| | resource | M | String | Echo of the resource name |
| | data | M | Object | The record |

### *Sample Request*

```
GET /api/bot/bookings/cmxxxxxxxxxxxxxxxxxxxxxx HTTP/1.1
Authorization: Bearer sbk_...
```

### *Sample Response (on normal condition)*

```
{
  "resource": "bookings",
  "data": {
    "id": "cmxxxxxxxxxxxxxxxxxxxxx",
    "bookingCode": "XX-2026-0001",
    "customerId": "cmxxxxxxxxxxxxxxxxxxxxxx",
    "agentId": "cmxxxxxxxxxxxxxxxxxxxxx",
    "agentContactId": "cmxxxxxxxxxxxxxxxxxxxxxx",
    "openTripId": "cmxxxxxxxxxxxxxxxxxxxxx",
    "source": "AGENT",
    "tripType": "PRIVATE_CHARTER"
  }
}
```

### *Response Message*

| HTTP Code | Response Body | Description |
|---|---|---|
| 200 | Detail envelope | Success |
| 401 | Invalid API key | Authentication failed |
| 403 | Bot API keys are read-only | Non-GET method |
| 404 | Unknown resource — see GET /api/bot | Resource not whitelisted |
| 404 | Not found | No such id, or the record is excluded from bot access |

CHAPTER 5

# RESOURCE REFERENCE

Every resource below supports both **GET /api/bot/{resource}** and **GET /api/bot/{resource}/{id}**. All listed columns are returned and all of them can be used as exact-match filters. Columns ending in **Id** reference the **id** of another resource. Attrib.: **M** = always present, **O** = may be null. Enum value lists are given in the Comment column.

| No | Category | Resource | Description | Date column |
|---|---|---|---|---|
| 1 | Sales & Booking | bookings | Bookings (charter & open trip), prices, status | startDate |
| 2 | Sales & Booking | booking-guests | Guest ↔ booking ↔ cabin links, flights/pickup | - |
| 3 | Sales & Booking | booking-services | Add-on services sold on bookings | - |
| 4 | Sales & Booking | customers | Guests — name/contact only (no passport, medical, DOB, address) | createdAt |
| 5 | Sales & Booking | leads | Sales leads & pipeline stage | createdAt |
| 6 | Sales & Booking | inquiries | Inbound inquiries | createdAt |
| 7 | Sales & Booking | agents | B2B agents & commission rates | createdAt |
| 8 | Sales & Booking | agent-contacts | Agent contact persons | createdAt |
| 9 | Sales & Booking | agent-clawback-entries | Agent commission clawbacks | createdAt |
| 10 | Sales & Booking | vouchers | Discount vouchers | createdAt |
| 11 | Sales & Booking | waiting-lists | Open-trip waiting list | createdAt |
| 12 | Finance | payments | Invoices & payments received | paymentDate |
| 13 | Finance | banks | Receiving bank names (no account numbers) | createdAt |
| 14 | Finance | expenses | Operating expenses (salary/payroll rows excluded) | date |
| 15 | Finance | po-payment-requests | PO payment requests (read-only) | createdAt |
| 16 | Finance | po-reimbursements | PO reimbursements (no payee account) | createdAt |
| 17 | Finance | delivery-fees | Delivery fees | createdAt |
| 18 | Finance | delivery-fee-payment-requests | Delivery fee payment requests | createdAt |
| 19 | Finance | delivery-fee-reimbursements | Delivery fee reimbursements (no payee account) | createdAt |
| 20 | Fleet & Operations | yachts | Boats | createdAt |
| 21 | Fleet & Operations | cabins | Cabins per boat | - |
| 22 | Fleet & Operations | cabin-pricing-tiers | Cabin pricing tiers | - |
| 23 | Fleet & Operations | destinations | Destinations | createdAt |
| 24 | Fleet & Operations | yacht-destination-prices | Charter price per boat × destination | - |
| 25 | Fleet & Operations | open-trips | Scheduled open trips | startDate |
| 26 | Fleet & Operations | crew | Crew roster per boat (name/position only) | createdAt |
| 27 | Fleet & Operations | maintenance | Boat maintenance records | createdAt |
| 28 | Fleet & Operations | internal-events | Internal calendar blocks | createdAt |
| 29 | Purchasing | purchase-requests | Purchase requests | createdAt |
| 30 | Purchasing | purchase-request-items | Purchase request lines | - |
| 31 | Purchasing | purchase-quotations | Supplier quotations | createdAt |
| 32 | Purchasing | purchase-orders | Purchase orders | createdAt |
| 33 | Purchasing | purchase-order-items | Purchase order lines | - |
| 34 | Purchasing | goods-receipts | Goods receipts | receivedAt |

| No | Category | Resource | Description | Date column |
|---|---|---|---|---|
| 35 | Purchasing | goods-receipt-items | Goods receipt lines | - |
| 36 | Purchasing | suppliers | Suppliers | createdAt |
| 37 | Purchasing | purchase-items | Item master (purchasing) | createdAt |
| 38 | Purchasing | purchase-item-categories | Item categories | createdAt |
| 39 | Stock & Warehouse | stock-locations | Warehouses / boats / stock locations | createdAt |
| 40 | Stock & Warehouse | stock-lots | Stock on hand by lot | createdAt |
| 41 | Stock & Warehouse | stock-movements | Stock movement ledger | createdAt |
| 42 | Stock & Warehouse | stock-transfers | Stock transfers | createdAt |
| 43 | Stock & Warehouse | stock-transfer-items | Stock transfer lines | - |
| 44 | Stock & Warehouse | stock-counts | Stock counts | createdAt |
| 45 | Stock & Warehouse | stock-count-items | Stock count lines | - |
| 46 | Stock & Warehouse | inventory-exceptions | Inventory exceptions | createdAt |
| 47 | Stock & Warehouse | crew-requests | Crew requests | createdAt |
| 48 | Stock & Warehouse | crew-request-items | Crew request lines | - |
| 49 | Stock & Warehouse | inventory-rooms | Inventory rooms | createdAt |
| 50 | Stock & Warehouse | inventory-categories | Inventory categories | createdAt |
| 51 | Stock & Warehouse | inventory-items | Inventory items | createdAt |
| 52 | Stock & Warehouse | inventory-opnames | Inventory opname sessions | createdAt |
| 53 | Stock & Warehouse | inventory-opname-entries | Inventory opname entries | createdAt |
| 54 | POS / Cashier | cashier-sales | Onboard POS sales | createdAt |
| 55 | POS / Cashier | cashier-sale-items | Onboard POS sale lines | createdAt |
| 56 | POS / Cashier | pos-categories | POS categories | createdAt |
| 57 | POS / Cashier | pos-menu-items | POS menu items | createdAt |
| 58 | POS / Cashier | pos-packages | POS packages | createdAt |
| 59 | POS / Cashier | pos-package-items | POS package lines | - |
| 60 | POS / Cashier | pos-recipes | POS recipes | createdAt |
| 61 | POS / Cashier | pos-recipe-lines | POS recipe ingredients | - |
| 62 | POS / Cashier | pos-discounts | POS discounts | createdAt |
| 63 | Marketing | campaigns | Marketing campaigns | createdAt |
| 64 | Marketing | email-campaigns | Email campaigns & stats | createdAt |

## 5.1 Sales & Booking

### *5.1.1 bookings*

Bookings (charter & open trip), prices, status.

**GET** : /api/bot/bookings | **GET** : /api/bot/bookings/{id} | Date column: **startDate** | 47 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | bookingCode | M | String | |
| | customerId | M | String | Reference id |
| | agentId | O | String | Reference id |
| | agentContactId | O | String | Reference id |
| | openTripId | O | String | Reference id |
| | source | M | Enum BookingSource | Enum: AGENT, DIRECT |
| | tripType | M | Enum TripType | Enum: PRIVATE_CHARTER, OPEN_TRIP |
| | useB2BCommission | M | Boolean | |
| | yachtId | O | String | Reference id |
| | startDate | M | DateTime | Date column (from/to) |
| | endDate | M | DateTime | |
| | destination | O | String | |
| | destinationId | O | String | Reference id |
| | status | M | Enum BookingStatus | Enum: on_hold, pending, partially_paid, fully_paid, completed, cancelled, confirmed, pending_refund |
| | tripNumber | O | Int | |
| | totalPrice | M | Float | |
| | depositPaid | M | Float | |
| | discount | M | Float | |
| | vatType | O | String | |
| | vatValue | M | Float | |
| | depositDueDate | O | DateTime | |
| | finalDueDate | O | DateTime | |
| | depositDueDateInvoiceOverride | O | DateTime | |
| | finalDueDateInvoiceOverride | O | DateTime | |
| | holdUntil | O | DateTime | |
| | guestCount | M | Int | |
| | crewRequired | M | Boolean | |
| | hasDiving | M | Boolean | |
| | hasSurfing | M | Boolean | |
| | hasPhotoPackage | M | Boolean | |
| | masterFormExpiresAt | O | DateTime | |
| | travelingWith | O | String | |
| | salesperson | O | String | |
| | salespersonId | O | String | Reference id |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | notes | O | String | |
| | cancelReason | O | String | |
| | refundStatus | O | String | |
| | refundDecision | O | String | |
| | refundReason | O | String | |
| | refundConfirmedAt | O | DateTime | |
| | refundConfirmedBy | O | String | |
| | voucherCode | O | String | |
| | currency | M | String | |
| | exchangeRate | O | Float | |
| | createdAt | M | DateTime | |
| | updatedAt | M | DateTime | |

### *5.1.2 booking-guests*

Guest ↔ booking ↔ cabin links, flights/pickup.

**GET** : /api/bot/booking-guests | **GET** : /api/bot/booking-guests/{id} | Date column: **-** | 11 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | bookingId | M | String | Reference id |
| | customerId | O | String | Reference id |
| | cabinId | O | String | Reference id |
| | isLead | M | Boolean | |
| | arrivalPickupTime | O | String | |
| | arrivalHotel | O | String | |
| | arrivalFlight | O | String | |
| | departurePickupTime | O | String | |
| | departureHotel | O | String | |
| | departureFlight | O | String | |

### *5.1.3 booking-services*

Add-on services sold on bookings.

**GET** : /api/bot/booking-services | **GET** : /api/bot/booking-services/{id} | Date column: **-** | 5 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | bookingId | M | String | Reference id |
| | name | M | String | |
| | price | M | Float | |
| | quantity | M | Int | |

### *5.1.4 customers*

Guests — name/contact only (no passport, medical, DOB, address).

**GET** : /api/bot/customers | **GET** : /api/bot/customers/{id} | Date column: **createdAt** | 25 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | firstName | O | String | |
| | lastName | O | String | |
| | gender | O | String | |
| | email | O | String | |
| | phone | O | String | |
| | isChild | M | Boolean | |
| | dietaryRequirements | O | String | |
| | allergies | O | String | |
| | equipmentSizes | O | String | |
| | operationalNotes | O | String | |
| | nationality | O | String | |
| | drinkPreferences | O | String | |
| | guestFormExpiresAt | O | DateTime | |
| | freshsalesContactId | O | String | Reference id |
| | foodData | O | Json | |
| | drinksData | O | Json | |
| | divingData | O | Json | |
| | surfingData | O | Json | |
| | pastDestinations | O | String | |
| | pastDestinationsOther | O | String | |
| | deletedAt | O | DateTime | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.1.5 leads*

Sales leads & pipeline stage.

**GET** : /api/bot/leads | **GET** : /api/bot/leads/{id} | Date column: **createdAt** | 31 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | firstName | O | String | |
| | lastName | O | String | |
| | nationality | O | String | |
| | email | O | String | |
| | phone | O | String | |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | notes | O | String | |
| | freshsalesContactId | O | String | Reference id |
| | deletedAt | O | DateTime | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |
| | stage | M | Enum LeadStage | Enum: NEW, CONTACTED, QUALIFIED, UNQUALIFIED, OPPORTUNITY, CLOSED_WON, CLOSED_LOST |
| | stageUpdatedAt | O | DateTime | |
| | stageUpdatedById | O | String | Reference id |
| | productInterest | O | String | |
| | destinationId | O | String | Reference id |
| | travelStartDate | O | DateTime | |
| | travelEndDate | O | DateTime | |
| | travelSeason | O | String | |
| | guestCount | O | Int | |
| | leadQuality | O | Enum LeadQuality | Enum: HOT, WARM, COLD |
| | budgetMin | O | Float | |
| | budgetMax | O | Float | |
| | budgetCurrency | O | String | |
| | proposalSentAt | O | DateTime | |
| | lostReason | O | Enum LeadLostReason | Enum: PRICE, DATES, COMPETITOR, NO_RESPONSE, OTHER |
| | lostNote | O | String | |
| | ownerId | O | String | Reference id |
| | ownerAssignedAt | O | DateTime | |
| | source | O | String | |

### *5.1.6 inquiries*

Inbound inquiries.

**GET** : /api/bot/inquiries | **GET** : /api/bot/inquiries/{id} | Date column: **createdAt** | 38 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | source | M | String | |
| | leadId | O | String | Reference id |
| | customerId | O | String | Reference id |
| | checkInDate | O | DateTime | |
| | checkOutDate | O | DateTime | |
| | guestCount | O | Int | |
| | tripType | O | String | |
| | message | O | String | |
| | website | O | String | |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | url | O | String | |
| | utmSource | O | String | |
| | utmMedium | O | String | |
| | utmCampaign | O | String | |
| | utmTerm | O | String | |
| | utmContent | O | String | |
| | gclid | O | String | |
| | gbraid | O | String | |
| | wbraid | O | String | |
| | fbclid | O | String | |
| | leadSource | O | String | |
| | refererField | O | String | |
| | mobileNumberBackup | O | String | |
| | reference | O | String | |
| | lastSource | O | String | |
| | lastMedium | O | String | |
| | lastCampaign | O | String | |
| | lastTerm | O | String | |
| | lastContent | O | String | |
| | lastGclid | O | String | |
| | lastGbraid | O | String | |
| | lastWbraid | O | String | |
| | lastFbclid | O | String | |
| | latestSource | O | String | |
| | latestMedium | O | String | |
| | latestCampaign | O | String | |
| | rawPayload | O | Json | |
| | createdAt | M | DateTime | Date column (from/to) |

### *5.1.7 agents*

B2B agents & commission rates.

**GET** : /api/bot/agents | **GET** : /api/bot/agents/{id} | Date column: **createdAt** | 23 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | commission | M | Float | |
| | commissionOpenTrip | M | Float | |
| | commissionPrivateCharter | M | Float | |
| | commissionB2B | M | Float | |
| | isActive | M | Boolean | |
| | country | O | String | |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | address | O | String | |
| | email | O | String | |
| | whatsapp | O | String | |
| | note | O | String | |
| | website | O | String | |
| | instagram | O | String | |
| | source | O | String | |
| | currentCondition | O | String | |
| | contract | O | String | |
| | calendarActive | M | Boolean | |
| | portalActive | M | Boolean | |
| | salespersonId | O | String | Reference id |
| | clawbackRatePerNight | M | Float | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.1.8 agent-contacts*

Agent contact persons.

**GET** : /api/bot/agent-contacts | **GET** : /api/bot/agent-contacts/{id} | Date column: **createdAt** | 10 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | agentId | M | String | Reference id |
| | name | M | String | |
| | email | O | String | |
| | whatsapp | O | String | |
| | jobTitle | O | String | |
| | addedById | O | String | Reference id |
| | addedByName | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.1.9 agent-clawback-entries*

Agent commission clawbacks.

**GET** : /api/bot/agent-clawback-entries | **GET** : /api/bot/agent-clawback-entries/{id} | Date column: **createdAt** | 8 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | agentId | M | String | Reference id |
| | amount | M | Float | |
| | bookingId | O | String | Reference id |
| | note | O | String | |
| | createdByUserId | O | String | Reference id |
| | createdByName | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |

### *5.1.10 vouchers*

Discount vouchers.

**GET** : /api/bot/vouchers | **GET** : /api/bot/vouchers/{id} | Date column: **createdAt** | 14 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | code | M | String | |
| | name | M | String | |
| | description | O | String | |
| | type | M | Enum VoucherType | Enum: PERCENTAGE, FIXED |
| | value | M | Float | |
| | minBooking | O | Float | |
| | maxUses | O | Int | |
| | usedCount | M | Int | |
| | validFrom | O | DateTime | |
| | validUntil | O | DateTime | |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.1.11 waiting-lists*

Open-trip waiting list.

**GET** : /api/bot/waiting-lists | **GET** : /api/bot/waiting-lists/{id} | Date column: **createdAt** | 17 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | bookingId | O | String | Reference id |
| | yachtId | O | String | Reference id |
| | openTripId | O | String | Reference id |
| | startDate | M | DateTime | |
| | endDate | M | DateTime | |
| | customerId | O | String | Reference id |
| | contactName | M | String | |
| | contactPhone | O | String | |
| | contactEmail | O | String | |
| | notes | O | String | |
| | priority | M | Int | |
| | status | M | Enum WaitingListStatus | Enum: waiting, promoted, cancelled |
| | salespersonId | O | String | Reference id |
| | promotedBookingId | O | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

## 5.2 Finance

### *5.2.1 payments*

Invoices & payments received.

**GET** : /api/bot/payments | **GET** : /api/bot/payments/{id} | Date column: **paymentDate** | 26 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | bookingId | M | String | Reference id |
| | invoiceNumber | M | String | |
| | paymentType | M | String | |
| | paymentMethod | O | String | |
| | amount | M | Float | |
| | previouslyPaid | M | Float | |
| | paymentDate | O | DateTime | Date column (from/to) |
| | currency | M | String | |
| | exchangeRate | O | Float | |
| | status | M | Enum PaymentStatus | Enum: requested, invoice_ready, pending_confirmation, confirmed, rejected, cancelled, refunded |
| | notes | O | String | |
| | billToType | O | String | |
| | showNetAmount | M | Boolean | |
| | showCommissionNote | M | Boolean | |
| | bankId | O | String | Reference id |
| | submittedByUserId | O | String | Reference id |
| | submittedByName | O | String | |
| | invoiceGeneratedBy | O | String | |
| | invoiceGeneratedAt | O | DateTime | |
| | confirmedBy | O | String | |
| | confirmedAt | O | DateTime | |
| | hasDocument | M | Boolean | |
| | parentPaymentId | O | String | Reference id |
| | createdAt | M | DateTime | |
| | updatedAt | M | DateTime | |

### *5.2.2 banks*

Receiving bank names (no account numbers).

**GET** : /api/bot/banks | **GET** : /api/bot/banks/{id} | Date column: **createdAt** | 8 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | bankAddress | O | String | |
| | beneficiaryName | O | String | |
| | address | O | String | |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.2.3 expenses*

Operating expenses (salary/payroll rows excluded).

**GET** : /api/bot/expenses | **GET** : /api/bot/expenses/{id} | Date column: **date** | 9 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | category | M | String | |
| | amount | M | Float | |
| | description | O | String | |
| | date | M | DateTime | Date column (from/to) |
| | yachtId | O | String | Reference id |
| | bookingId | O | String | Reference id |
| | createdAt | M | DateTime | |
| | updatedAt | M | DateTime | |

*Note: rows whose description or category contains salary, gaji, payroll, wage, upah or bonus are never returned (list and detail).*

### *5.2.4 po-payment-requests*

PO payment requests (read-only).

**GET** : /api/bot/po-payment-requests | **GET** : /api/bot/po-payment-requests/{id} | Date column: **createdAt** | 16 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | orderId | M | String | Reference id |
| | requestedById | M | String | Reference id |
| | amount | M | Float | |
| | notes | O | String | |
| | notaDate | O | DateTime | |
| | status | M | Enum POPaymentRequestStatus | Enum: PENDING, PAID, REJECTED |
| | paymentMethod | M | String | |
| | paidAt | O | DateTime | |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | paidById | O | String | Reference id |
| | paidNotes | O | String | |
| | rejectedAt | O | DateTime | |
| | rejectedById | O | String | Reference id |
| | rejectionReason | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.2.5 po-reimbursements*

PO reimbursements (no payee account).

**GET** : /api/bot/po-reimbursements | **GET** : /api/bot/po-reimbursements/{id} | Date column: **createdAt** | 15 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | orderId | M | String | Reference id |
| | requestedById | M | String | Reference id |
| | amount | M | Float | |
| | notes | O | String | |
| | notaDate | O | DateTime | |
| | requesterName | M | String | |
| | bankName | M | String | |
| | accountHolderName | M | String | |
| | status | M | Enum POReimbursementStatus | Enum: PENDING, PAID |
| | paidAt | O | DateTime | |
| | paidById | O | String | Reference id |
| | paidNotes | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.2.6 delivery-fees*

Delivery fees.

**GET** : /api/bot/delivery-fees | **GET** : /api/bot/delivery-fees/{id} | Date column: **createdAt** | 7 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | feeNumber | M | String | |
| | purchaseOrderId | O | String | Reference id |
| | notes | O | String | |
| | createdById | O | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.2.7 delivery-fee-payment-requests*

Delivery fee payment requests.

**GET** : /api/bot/delivery-fee-payment-requests | **GET** : /api/bot/delivery-fee-payment-requests/{id} | Date column: **createdAt** | 13 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | deliveryFeeId | M | String | Reference id |
| | requestedById | M | String | Reference id |
| | amount | M | Float | |
| | notes | O | String | |
| | notaDate | O | DateTime | |
| | status | M | Enum DeliveryFeePaymentRequestStatus | Enum: PENDING, PAID |
| | paymentMethod | M | String | |
| | paidAt | O | DateTime | |
| | paidById | O | String | Reference id |
| | paidNotes | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.2.8 delivery-fee-reimbursements*

Delivery fee reimbursements (no payee account).

**GET** : /api/bot/delivery-fee-reimbursements | **GET** : /api/bot/delivery-fee-reimbursements/{id} | Date column: **createdAt** | 15 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | deliveryFeeId | M | String | Reference id |
| | requestedById | M | String | Reference id |
| | amount | M | Float | |
| | notes | O | String | |
| | notaDate | O | DateTime | |
| | requesterName | M | String | |
| | bankName | M | String | |
| | accountHolderName | M | String | |
| | status | M | Enum DeliveryFeeReimbursementStatus | Enum: PENDING, PAID |
| | paidAt | O | DateTime | |
| | paidById | O | String | Reference id |
| | paidNotes | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

## 5.3 Fleet & Operations

### *5.3.1 yachts*

Boats.

**GET** : /api/bot/yachts | **GET** : /api/bot/yachts/{id} | Date column: **createdAt** | 20 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | model | O | String | |
| | year | O | Int | |
| | capacity | M | Int | |
| | cabinCount | M | Int | |
| | length | O | Float | |
| | description | O | String | |
| | hourlyRate | M | Float | |
| | dailyRate | M | Float | |
| | extraBedTiers | M | Json | |
| | canDiving | M | Boolean | |
| | canSurfing | M | Boolean | |
| | status | M | Enum YachtStatus | Enum: available, booked, maintenance |
| | tagline | O | String | |
| | type | O | String | |
| | sortOrder | M | Int | |
| | deletedAt | O | DateTime | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.3.2 cabins*

Cabins per boat.

**GET** : /api/bot/cabins | **GET** : /api/bot/cabins/{id} | Date column: **-** | 8 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | yachtId | M | String | Reference id |
| | name | M | String | |
| | capacity | M | Int | |
| | price | M | Float | |
| | deck | O | String | |
| | bedType | O | String | |
| | extraBeds | M | Int | |

### *5.3.3 cabin-pricing-tiers*

Cabin pricing tiers.

**GET** : /api/bot/cabin-pricing-tiers | **GET** : /api/bot/cabin-pricing-tiers/{id} | Date column: **-** | 5 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | cabinId | M | String | Reference id |
| | destinationId | O | String | Reference id |
| | nights | M | Int | |
| | price | M | Float | |

### *5.3.4 destinations*

Destinations.

**GET** : /api/bot/destinations | **GET** : /api/bot/destinations/{id} | Date column: **createdAt** | 7 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | region | O | String | |
| | isActive | M | Boolean | |
| | deletedAt | O | DateTime | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.3.5 yacht-destination-prices*

Charter price per boat × destination.

**GET** : /api/bot/yacht-destination-prices | **GET** : /api/bot/yacht-destination-prices/{id} | Date column: **-** | 5 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | yachtId | M | String | Reference id |
| | destinationId | M | String | Reference id |
| | price | M | Float | |
| | relocationFee | O | Float | |

### *5.3.6 open-trips*

Scheduled open trips.

**GET** : /api/bot/open-trips | **GET** : /api/bot/open-trips/{id} | Date column: **startDate** | 18 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | title | M | String | |
| | description | O | String | |
| | yachtId | M | String | Reference id |
| | startDate | M | DateTime | Date column (from/to) |
| | endDate | M | DateTime | |
| | destination | M | String | |
| | destinationId | O | String | Reference id |
| | region | O | String | |
| | departurePort | O | String | |
| | arrivalPort | O | String | |
| | pricePerCabin | M | Float | |
| | maxCapacity | M | Int | |
| | status | M | Enum OpenTripStatus | Enum: open, closed, full, completed, cancelled |
| | closedReason | O | String | |
| | tripNumber | O | Int | |
| | createdAt | M | DateTime | |
| | updatedAt | M | DateTime | |

### *5.3.7 crew*

Crew roster per boat (name/position only).

**GET** : /api/bot/crew | **GET** : /api/bot/crew/{id} | Date column: **createdAt** | 9 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | yachtId | M | String | Reference id |
| | name | M | String | |
| | position | M | String | |
| | isActive | M | Boolean | |
| | startDate | M | DateTime | |
| | endDate | O | DateTime | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.3.8 maintenance*

Boat maintenance records.

**GET** : /api/bot/maintenance | **GET** : /api/bot/maintenance/{id} | Date column: **createdAt** | 10 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | yachtId | M | String | Reference id |
| | title | M | String | |
| | description | O | String | |
| | scheduledDate | M | DateTime | |
| | completedAt | O | DateTime | |
| | status | M | Enum MaintenanceStatus | Enum: scheduled, in_progress, completed, cancelled |
| | cost | O | Float | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.3.9 internal-events*

Internal calendar blocks.

**GET** : /api/bot/internal-events | **GET** : /api/bot/internal-events/{id} | Date column: **createdAt** | 11 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | type | M | Enum InternalEventType | Enum: DOCKING, CROSSING, OVERHAUL, COMPANY_NEED |
| | title | M | String | |
| | notes | O | String | |
| | startDate | M | DateTime | |
| | endDate | M | DateTime | |
| | yachtId | O | String | Reference id |
| | internalOnly | M | Boolean | |
| | createdById | O | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

## 5.4 Purchasing

### *5.4.1 purchase-requests*

Purchase requests.

**GET** : /api/bot/purchase-requests | **GET** : /api/bot/purchase-requests/{id} | Date column: **createdAt** | 27 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | prNumber | M | String | |
| | requestedById | M | String | Reference id |
| | requestedByEmployeeId | O | String | Reference id |
| | approverEmployeeId | O | String | Reference id |
| | deliveryLocationId | O | String | Reference id |
| | notes | O | String | |
| | status | M | Enum PurchaseRequestStatus | Enum: DRAFT, PENDING_APPROVAL, ON_PROCESS, CONVERTED, REJECTED, CANCELLED |
| | purpose | M | Enum PurchaseRequestPurpose | Enum: STOCK_INVENTORY, TRIP, REPLACEMENT |
| | tripBookingId | O | String | Reference id |
| | openTripId | O | String | Reference id |
| | division | O | Enum PurchaseRequestDivision | Enum: BOAT_OPERATION, BUILDING_MATERIAL |
| | neededByDate | O | DateTime | |
| | isUrgent | M | Boolean | |
| | urgentReason | O | String | |
| | approvedById | O | String | Reference id |
| | approvedAt | O | DateTime | |
| | verifiedById | O | String | Reference id |
| | verifiedAt | O | DateTime | |
| | convertedById | O | String | Reference id |
| | convertedAt | O | DateTime | |
| | rejectedById | O | String | Reference id |
| | rejectedAt | O | DateTime | |
| | cancelledById | O | String | Reference id |
| | cancelledAt | O | DateTime | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.4.2 purchase-request-items*

Purchase request lines.

**GET** : /api/bot/purchase-request-items | **GET** : /api/bot/purchase-request-items/{id} | Date column: **-** | 31 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | requestId | M | String | Reference id |
| | itemId | O | String | Reference id |
| | itemName | M | String | |
| | quantity | M | Float | |
| | unit | M | String | |
| | estimatedCost | M | Float | |
| | supplierId | O | String | Reference id |
| | supplierName | O | String | |
| | notes | O | String | |
| | isStockItem | M | Boolean | |
| | exemptionReason | O | String | |
| | selectionJustification | O | String | |
| | quotationSubmittedById | O | String | Reference id |
| | quotationApproverId | O | String | Reference id |
| | quotationSubmittedAt | O | DateTime | |
| | quotationApprovedById | O | String | Reference id |
| | quotationApprovedAt | O | DateTime | |
| | quotationRejectedById | O | String | Reference id |
| | quotationRejectedAt | O | DateTime | |
| | quotationRejectionReason | O | String | |
| | convertedAt | O | DateTime | |
| | convertedPoId | O | String | Reference id |
| | verifyRejectedById | O | String | Reference id |
| | verifyRejectedAt | O | DateTime | |
| | verifyRejectionReason | O | String | |
| | warehouseDecision | O | Enum PurchaseRequestItemWarehouseDecision | Enum: TRANSFER, PURCHASE |
| | warehouseCheckedById | O | String | Reference id |
| | warehouseCheckedAt | O | DateTime | |
| | warehouseCheckNote | O | String | |
| | sourceInventoryItemId | O | String | Reference id |

### *5.4.3 purchase-quotations*

Supplier quotations.

**GET** : /api/bot/purchase-quotations | **GET** : /api/bot/purchase-quotations/{id} | Date column: **createdAt** | 8 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | requestItemId | M | String | Reference id |
| | supplierId | O | String | Reference id |
| | supplierName | M | String | |
| | price | M | Float | |
| | submittedAt | M | DateTime | |
| | createdById | M | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |

### *5.4.4 purchase-orders*

Purchase orders.

**GET** : /api/bot/purchase-orders | **GET** : /api/bot/purchase-orders/{id} | Date column: **createdAt** | 32 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | poNumber | M | String | |
| | requestId | O | String | Reference id |
| | orderType | M | Enum PurchaseOrderKind | Enum: GOODS, SERVICE |
| | supplierId | O | String | Reference id |
| | supplierName | O | String | |
| | deliveryLocationId | O | String | Reference id |
| | bookingId | O | String | Reference id |
| | openTripId | O | String | Reference id |
| | status | M | Enum PurchaseOrderStatus | Enum: DRAFT, ORDERED, IN_TRANSIT, PARTIALLY_RECEIVED, RECEIVED, COMPLETED, CANCELLED, REJECTED |
| | dispatchedAt | O | DateTime | |
| | dispatchedByName | O | String | |
| | confirmedByName | O | String | |
| | notes | O | String | |
| | orderedAt | M | DateTime | |
| | expectedAt | O | DateTime | |
| | cancelledAt | O | DateTime | |
| | cancelledByName | O | String | |
| | cancellationReason | O | String | |
| | completedAt | O | DateTime | |
| | completedByName | O | String | |
| | createdById | O | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | updatedAt | M | DateTime | |
| | extraCharges | O | Json | |
| | discountType | O | String | |
| | discountValue | M | Float | |
| | requestedByEmployeeId | O | String | Reference id |
| | requestedByName | O | String | |
| | requestedByOffice | O | String | |
| | requestedByDepartment | O | String | |
| | requestedByRole | O | String | |

### *5.4.5 purchase-order-items*

Purchase order lines.

**GET** : /api/bot/purchase-order-items | **GET** : /api/bot/purchase-order-items/{id} | Date column: **-** | 11 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | orderId | M | String | Reference id |
| | itemId | O | String | Reference id |
| | itemName | M | String | |
| | unit | O | String | |
| | orderedQty | M | Float | |
| | receivedQty | M | Float | |
| | unitCost | M | Float | |
| | inventoryRoomId | O | String | Reference id |
| | inventoryCategoryId | O | String | Reference id |
| | sourceInventoryItemId | O | String | Reference id |

### *5.4.6 goods-receipts*

Goods receipts.

**GET** : /api/bot/goods-receipts | **GET** : /api/bot/goods-receipts/{id} | Date column: **receivedAt** | 10 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | grNumber | M | String | |
| | orderId | M | String | Reference id |
| | receivedById | O | String | Reference id |
| | receivedByEmployeeId | O | String | Reference id |
| | receiverName | O | String | |
| | locationId | M | String | Reference id |
| | notes | O | String | |
| | receivedAt | M | DateTime | Date column (from/to) |
| | createdAt | M | DateTime | |

### *5.4.7 goods-receipt-items*

Goods receipt lines.

**GET** : /api/bot/goods-receipt-items | **GET** : /api/bot/goods-receipt-items/{id} | Date column: **-** | 12 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | receiptId | M | String | Reference id |
| | itemId | O | String | Reference id |
| | itemName | M | String | |
| | receivedQty | M | Float | |
| | unitCost | M | Float | |
| | outcome | M | String | |
| | condition | M | String | |
| | batch | O | String | |
| | expiryDate | O | DateTime | |
| | notes | O | String | |
| | sourceInventoryItemId | O | String | Reference id |

### *5.4.8 suppliers*

Suppliers.

**GET** : /api/bot/suppliers | **GET** : /api/bot/suppliers/{id} | Date column: **createdAt** | 10 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | locations | M | Json | |
| | contact | O | String | |
| | phone | O | String | |
| | email | O | String | |
| | notes | O | String | |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.4.9 purchase-items*

Item master (purchasing).

**GET** : /api/bot/purchase-items | **GET** : /api/bot/purchase-items/{id} | Date column: **createdAt** | 19 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | sku | M | String | |
| | name | M | String | |
| | type | M | String | |
| | category | M | String | |
| | baseUnit | M | String | |
| | purchaseUnit | M | String | |
| | conversionFactor | M | Float | |
| | standardCost | M | Float | |
| | sellingPrice | M | Float | |
| | valuationMethod | M | String | |
| | minStock | M | Float | |
| | reorderQty | M | Float | |
| | isActive | M | Boolean | |
| | isSoldInPos | M | Boolean | |
| | isStockTracked | M | Boolean | |
| | currentLocationId | O | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.4.10 purchase-item-categories*

Item categories.

**GET** : /api/bot/purchase-item-categories | **GET** : /api/bot/purchase-item-categories/{id} | Date column: **createdAt** | 7 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | typeCode | M | String | |
| | name | M | String | |
| | skuPrefix | M | String | |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

## 5.5 Stock & Warehouse

### *5.5.1 stock-locations*

Warehouses / boats / stock locations.

**GET** : /api/bot/stock-locations | **GET** : /api/bot/stock-locations/{id} | Date column: **createdAt** | 13 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | type | M | Enum StockLocationType | Enum: WAREHOUSE, VESSEL, TRANSIT, SITE, ADJUSTMENT |
| | yachtId | O | String | Reference id |
| | parentId | O | String | Reference id |
| | manager | O | String | |
| | address | O | String | |
| | storageClass | O | String | |
| | managedBy | M | String | |
| | consumptionMode | O | Enum StockConsumptionMode | Enum: HOLD_AS_STOCK, EXPENSE_ON_RECEIVE |
| | isPosBar | M | Boolean | |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |

### *5.5.2 stock-lots*

Stock on hand by lot.

**GET** : /api/bot/stock-lots | **GET** : /api/bot/stock-lots/{id} | Date column: **createdAt** | 12 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | itemId | O | String | Reference id |
| | itemName | O | String | |
| | unit | O | String | |
| | sourcePoId | O | String | Reference id |
| | locationId | M | String | Reference id |
| | quantity | M | Float | |
| | costPerUnit | M | Float | |
| | batch | O | String | |
| | expiresAt | O | DateTime | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.3 stock-movements*

Stock movement ledger.

**GET** : /api/bot/stock-movements | **GET** : /api/bot/stock-movements/{id} | Date column: **createdAt** | 18 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | itemId | O | String | Reference id |
| | itemName | O | String | |
| | fromLocationId | O | String | Reference id |
| | toLocationId | O | String | Reference id |
| | quantity | M | Float | |
| | type | M | String | |
| | referenceId | O | String | Reference id |
| | referenceType | O | String | |
| | notes | O | String | |
| | unitCost | O | Float | |
| | totalCost | O | Float | |
| | usageType | O | Enum StockUsageType | Enum: SHIP_USAGE, BAR_COGS, COMPLIMENTARY, SHRINKAGE |
| | yachtId | O | String | Reference id |
| | openTripId | O | String | Reference id |
| | tripBookingId | O | String | Reference id |
| | createdById | M | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |

### *5.5.4 stock-transfers*

Stock transfers.

**GET** : /api/bot/stock-transfers | **GET** : /api/bot/stock-transfers/{id} | Date column: **createdAt** | 25 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | transferNumber | M | String | |
| | fromLocationId | M | String | Reference id |
| | toLocationId | M | String | Reference id |
| | crewRequestId | O | String | Reference id |
| | purchaseRequestId | O | String | Reference id |
| | tripBookingId | O | String | Reference id |
| | openTripId | O | String | Reference id |
| | purchaseOrderId | O | String | Reference id |
| | originGoodsReceiptId | O | String | Reference id |
| | legSequence | O | Int | |
| | status | M | Enum TransferStatus | Enum: PENDING, DISPATCHED, RECEIVED, CANCELLED |
| | dispatchedById | O | String | Reference id |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | receivedById | O | String | Reference id |
| | expectedReceiverId | O | String | Reference id |
| | expectedReceiverName | O | String | |
| | receivedByName | O | String | |
| | notes | O | String | |
| | dispatchedAt | O | DateTime | |
| | receivedAt | O | DateTime | |
| | departAt | O | DateTime | |
| | etaAt | O | DateTime | |
| | cargoName | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.5 stock-transfer-items*

Stock transfer lines.

**GET** : /api/bot/stock-transfer-items | **GET** : /api/bot/stock-transfer-items/{id} | Date column: **-** | 9 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | transferId | M | String | Reference id |
| | itemId | O | String | Reference id |
| | itemName | M | String | |
| | requestedQty | M | Float | |
| | dispatchedQty | M | Float | |
| | receivedQty | M | Float | |
| | unitCost | M | Float | |
| | orderedByEmployeeId | O | String | Reference id |

### *5.5.6 stock-counts*

Stock counts.

**GET** : /api/bot/stock-counts | **GET** : /api/bot/stock-counts/{id} | Date column: **createdAt** | 11 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | countNumber | M | String | |
| | locationId | M | String | Reference id |
| | status | M | Enum StockCountStatus | Enum: DRAFT, IN_PROGRESS, COMPLETED, APPROVED |
| | type | M | Enum StockCountType | Enum: NORMAL, INITIAL |
| | notes | O | String | |
| | countedById | M | String | Reference id |
| | approvedById | O | String | Reference id |
| | approvedAt | O | DateTime | |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.7 stock-count-items*

Stock count lines.

**GET** : /api/bot/stock-count-items | **GET** : /api/bot/stock-count-items/{id} | Date column: **-** | 7 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | countId | M | String | Reference id |
| | itemId | O | String | Reference id |
| | itemName | M | String | |
| | systemQty | M | Float | |
| | countedQty | M | Float | |
| | reason | O | String | |

### *5.5.8 inventory-exceptions*

Inventory exceptions.

**GET** : /api/bot/inventory-exceptions | **GET** : /api/bot/inventory-exceptions/{id} | Date column: **createdAt** | 17 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | type | M | String | |
| | itemId | O | String | Reference id |
| | itemName | M | String | |
| | locationId | O | String | Reference id |
| | locationName | M | String | |
| | qty | M | Float | |
| | value | M | Float | |
| | reason | O | String | |
| | referenceId | O | String | Reference id |
| | referenceType | O | String | |
| | status | M | String | |
| | resolution | O | String | |
| | resolvedAt | O | DateTime | |
| | resolvedById | O | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.9 crew-requests*

Crew requests.

**GET** : /api/bot/crew-requests | **GET** : /api/bot/crew-requests/{id} | Date column: **createdAt** | 7 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | yachtId | M | String | Reference id |
| | requestedById | M | String | Reference id |
| | status | M | Enum CrewRequestStatus | Enum: PENDING, REVIEWED, IN_PROGRESS, FULFILLED, CANCELLED |
| | notes | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.10 crew-request-items*

Crew request lines.

**GET** : /api/bot/crew-request-items | **GET** : /api/bot/crew-request-items/{id} | Date column: **-** | 7 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | requestId | M | String | Reference id |
| | itemId | O | String | Reference id |
| | itemName | M | String | |
| | quantity | M | Float | |
| | unit | M | String | |
| | notes | O | String | |

### *5.5.11 inventory-rooms*

Inventory rooms.

**GET** : /api/bot/inventory-rooms | **GET** : /api/bot/inventory-rooms/{id} | Date column: **createdAt** | 6 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | locationId | M | String | Reference id |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.12 inventory-categories*

Inventory categories.

**GET** : /api/bot/inventory-categories | **GET** : /api/bot/inventory-categories/{id} | Date column: **createdAt** | 6 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | roomId | M | String | Reference id |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.13 inventory-items*

Inventory items.

**GET** : /api/bot/inventory-items | **GET** : /api/bot/inventory-items/{id} | Date column: **createdAt** | 20 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | itemNumber | M | String | |
| | name | M | String | |
| | categoryId | M | String | Reference id |
| | brand | O | String | |
| | purchaseDate | O | DateTime | |
| | webLink | O | String | |
| | phone | O | String | |
| | vendorName | O | String | |
| | quantity | M | Int | |
| | unitPrice | M | Float | |
| | notes | O | String | |
| | isActive | M | Boolean | |
| | roomId | M | String | Reference id |
| | locationId | M | String | Reference id |
| | sourcePoId | O | String | Reference id |
| | sourcePurchaseItemId | O | String | Reference id |
| | createdById | M | String | Reference id |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.14 inventory-opnames*

Inventory opname sessions.

**GET** : /api/bot/inventory-opnames | **GET** : /api/bot/inventory-opnames/{id} | Date column: **createdAt** | 10 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | opnameNumber | M | String | |
| | locationId | M | String | Reference id |
| | roomId | M | String | Reference id |
| | status | M | Enum InventoryOpnameStatus | Enum: DRAFT, IN_PROGRESS, COMPLETED |
| | notes | O | String | |
| | countedById | M | String | Reference id |
| | completedAt | O | DateTime | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.5.15 inventory-opname-entries*

Inventory opname entries.

**GET** : /api/bot/inventory-opname-entries | **GET** : /api/bot/inventory-opname-entries/{id} | Date column: **createdAt** | 8 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | opnameId | M | String | Reference id |
| | itemId | M | String | Reference id |
| | unitIndex | M | Int | |
| | rating | O | Int | |
| | notes | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | replacementRequestItemId | O | String | Reference id |

## 5.6 POS / Cashier

### *5.6.1 cashier-sales*

Onboard POS sales.

**GET** : /api/bot/cashier-sales | **GET** : /api/bot/cashier-sales/{id} | Date column: **createdAt** | 23 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | yachtId | M | String | Reference id |
| | locationId | M | String | Reference id |
| | bookingId | O | String | Reference id |
| | guestId | O | String | Reference id |
| | guestName | O | String | |
| | employeeId | O | String | Reference id |
| | employeeName | O | String | |
| | complimentaryReason | O | String | |
| | status | M | String | |
| | payMethod | O | String | |
| | total | M | Float | |
| | discountId | O | String | Reference id |
| | discountName | O | String | |
| | discountAmount | M | Float | |
| | openedBy | O | String | |
| | closedAt | O | DateTime | |
| | needsReview | M | Boolean | |
| | reviewNote | O | String | |
| | reviewedAt | O | DateTime | |
| | reviewedBy | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.6.2 cashier-sale-items*

Onboard POS sale lines.

**GET** : /api/bot/cashier-sale-items | **GET** : /api/bot/cashier-sale-items/{id} | Date column: **createdAt** | 11 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | saleId | M | String | Reference id |
| | itemId | O | String | Reference id |
| | packageId | O | String | Reference id |
| | recipeId | O | String | Reference id |
| | name | M | String | |
| | unit | M | String | |
| | price | M | Float | |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | qty | M | Float | |
| | round | M | Int | |
| | createdAt | M | DateTime | Date column (from/to) |

### *5.6.3 pos-categories*

POS categories.

**GET** : /api/bot/pos-categories | **GET** : /api/bot/pos-categories/{id} | Date column: **createdAt** | 6 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | sortOrder | M | Int | |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.6.4 pos-menu-items*

POS menu items.

**GET** : /api/bot/pos-menu-items | **GET** : /api/bot/pos-menu-items/{id} | Date column: **createdAt** | 9 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | itemId | M | String | Reference id |
| | categoryId | M | String | Reference id |
| | yachtId | O | String | Reference id |
| | price | M | Float | |
| | isActive | M | Boolean | |
| | sortOrder | M | Int | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.6.5 pos-packages*

POS packages.

**GET** : /api/bot/pos-packages | **GET** : /api/bot/pos-packages/{id} | Date column: **createdAt** | 10 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | description | O | String | |
| | categoryId | M | String | Reference id |
| | yachtId | O | String | Reference id |
| | price | M | Float | |
| | isActive | M | Boolean | |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | sortOrder | M | Int | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.6.6 pos-package-items*

POS package lines.

**GET** : /api/bot/pos-package-items | **GET** : /api/bot/pos-package-items/{id} | Date column: **-** | 4 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | packageId | M | String | Reference id |
| | itemId | M | String | Reference id |
| | qty | M | Float | |

### *5.6.7 pos-recipes*

POS recipes.

**GET** : /api/bot/pos-recipes | **GET** : /api/bot/pos-recipes/{id} | Date column: **createdAt** | 10 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | description | O | String | |
| | categoryId | M | String | Reference id |
| | yachtId | O | String | Reference id |
| | price | M | Float | |
| | isActive | M | Boolean | |
| | sortOrder | M | Int | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.6.8 pos-recipe-lines*

POS recipe ingredients.

**GET** : /api/bot/pos-recipe-lines | **GET** : /api/bot/pos-recipe-lines/{id} | Date column: **-** | 4 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | recipeId | M | String | Reference id |
| | itemId | M | String | Reference id |
| | qty | M | Float | |

### *5.6.9 pos-discounts*

POS discounts.

**GET** : /api/bot/pos-discounts | **GET** : /api/bot/pos-discounts/{id} | Date column: **createdAt** | 10 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | type | M | String | |
| | value | M | Float | |
| | yachtId | O | String | Reference id |
| | startDate | O | DateTime | |
| | endDate | O | DateTime | |
| | isActive | M | Boolean | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

## 5.7 Marketing

### *5.7.1 campaigns*

Marketing campaigns.

**GET** : /api/bot/campaigns | **GET** : /api/bot/campaigns/{id} | Date column: **createdAt** | 22 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | brand | O | String | |
| | stage | M | Enum CampaignStage | Enum: PLANNING, IN_PRODUCTION, APPROVAL, LIVE, COMPLETED |
| | objective | O | String | |
| | targetResult | O | String | |
| | promise | O | String | |
| | offer | O | String | |
| | startDate | O | DateTime | |
| | endDate | O | DateTime | |
| | plannedBudget | O | Float | |
| | ownerName | O | String | |
| | audienceSegments | O | Json | |
| | markets | O | Json | |
| | masterLanguage | O | String | |
| | additionalLanguages | O | Json | |
| | exclusions | O | Json | |
| | utmSlug | O | String | |
| | createdByUserId | O | String | Reference id |
| | createdByName | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

### *5.7.2 email-campaigns*

Email campaigns & stats.

**GET** : /api/bot/email-campaigns | **GET** : /api/bot/email-campaigns/{id} | Date column: **createdAt** | 21 columns

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| **Response record (data)** | | | | |
| | id | M | String | Primary key |
| | name | M | String | |
| | subject | M | String | |
| | previewText | O | String | |
| | fromEmail | M | String | |
| | fromName | O | String | |
| | templateId | O | String | Reference id |
| | blocksJson | M | Json | |

| | Field Name | Attrib. | Type | Comment |
|---|---|---|---|---|
| | bodyHtml | M | String | |
| | status | M | Enum CampaignStatus | Enum: DRAFT, SCHEDULED, SENDING, PAUSED, SENT, FAILED, CANCELED |
| | audienceSources | M | Json | |
| | scheduledAt | O | DateTime | |
| | sentAt | O | DateTime | |
| | totalRecipients | M | Int | |
| | sentCount | M | Int | |
| | failedCount | M | Int | |
| | errorMessage | O | String | |
| | createdByUserId | O | String | Reference id |
| | createdByName | O | String | |
| | createdAt | M | DateTime | Date column (from/to) |
| | updatedAt | M | DateTime | |

CHAPTER 6

# DATA ACCESS RESTRICTIONS

## 6.1 Modules Not Exposed

The following ERP data is unreachable through this API, by design. No parameter, filter or id can reach it.

| Area | Detail |
|---|---|
| HR & Payroll | Employees, payslips, salaries, payroll totals, attendance, leave, recruitment, separation |
| Salary expenses | Expense rows mentioning salary / gaji / payroll / wage / upah / bonus |
| User accounts | ERP users, roles, permissions, login sessions |
| System settings | Integrations, API credentials, tenant configuration |
| Communications | WhatsApp, Instagram and email conversations (may contain passport scans) |
| Relations | Nested related records are never embedded; only scalar columns of the requested resource |

## 6.2 Columns Always Removed

On every resource, any column whose name matches the rules below is removed from the response and cannot be used as a filter. The same rules are applied again to keys nested inside JSON columns.

| Rule | Matches (case-insensitive) |
|---|---|
| Credentials | password, token, secret, apikey, pinhash, hash |
| Identity documents | passport, nikpassport, niksnap, npwp, bpjs |
| Personal / medical | medical, health, religion, marital, dateofbirth, birthdate, placeofbirth, emergencycontact, personalemail |
| Bank / payment | accountnumber, idraccount, usdaccount, swift, iban, cardnumber, cvv, proof |
| Compensation | salary |
| Signatures | signature |
| Stored files (suffix) | ...file, ...files, ...filename, ...key, ...keys, ...image, ...attachments |
| Per resource | customers.address, agent-contacts.address, crew.phone, crew.email, payments.paymentLink, payments.changeProofUrl, agents.portalPasswordSetById |

CHAPTER 7

# APPENDIX

## A. API Key Format

- Key = **"sbk_" + Payload + "." + Signature**
- Payload = base64url( JSON { "t": <tenant id>, "u": <BOT user id> } )
- Signature = base64url( HMAC-SHA256( key = "bot-api-key:v1:" + BOT_API_KEY_SECRET, data = Payload + "|" + <BOT user password hash> ) )
- The server recomputes the signature on every request with the user's current password hash and compares in constant time.
- The key contains no secret data; the payload only identifies the tenant and user. It cannot be forged without BOT_API_KEY_SECRET.

## B. Issuing, Revoking and Rotating Keys

| Action | How | Effect |
|---|---|---|
| Issue a key | On the ERP server: **npx tsx scripts/create-bot-api-key.ts <bot-email> [tenant-slug]** | Prints a new key for that BOT user. The user must have role BOT |
| Revoke one user's keys | Change the password of that BOT user in Users | All keys of that user stop working at once |
| Suspend | Deactivate the account, change its role, or delete the user | Keys rejected while inactive / not BOT |
| Revoke all keys | Set a new value for **BOT_API_KEY_SECRET** in the server .env and restart | Every key in every tenant stops working |
| Secret fallback | If BOT_API_KEY_SECRET is unset, NEXTAUTH_SECRET is used | Rotating NEXTAUTH_SECRET would then also revoke keys |

## C. Client Examples

***cURL***

```
curl -s -H "Authorization: Bearer $ERP_BOT_KEY" \
  "https://{erp-domain}/api/bot/bookings?from=2026-01-01&to=2026-12-31T23:59:59Z&limit=500"
```

***Python - fetch all pages***

```
import os, requests

BASE = "https://{erp-domain}/api/bot"
HEADERS = {"Authorization": f"Bearer {os.environ['ERP_BOT_KEY']}"}

def fetch_all(resource, **params):
    params = {"limit": 500, **params}
    rows = []
    while True:
        r = requests.get(f"{BASE}/{resource}", headers=HEADERS, params=params, timeout=60)
        r.raise_for_status()
        body = r.json()
        rows += body["data"]
        if not body["nextCursor"]:
            return rows
        params["cursor"] = body["nextCursor"]

payments = fetch_all("payments", **{"from": "2026-01-01", "status": "PAID"})
```

### *JavaScript (Node 18+) - fetch all pages*

```
const BASE = 'https://{erp-domain}/api/bot'
const headers = { Authorization: `Bearer ${process.env.ERP_BOT_KEY}` }

async function fetchAll(resource, params = {}) {
  const q = new URLSearchParams({ limit: '500', ...params })
  const rows = []
  for (;;) {
    const res = await fetch(`${BASE}/${resource}?${q}`, { headers })
    if (!res.ok) throw new Error(`${res.status} ${(await res.json()).error}`)
    const body = await res.json()
    rows.push(...body.data)
    if (!body.nextCursor) return rows
    q.set('cursor', body.nextCursor)
  }
}
```