SAMARA YACHTING
ERP Platform

JSON REST API Specification Document

ERP Bot API (Read-Only Data Access)
Release 1.0.0

October, 2026

Confidentiality
This document contains proprietary information that is confidential to Samara Yachting. It describes access to internal business data. Disclosure of this document, or of any API key issued under it, in full or in part, to a third party requires prior written permission from Samara Yachting.

Table of Contents

CHAPTER 1 — OVERVIEW 4

CHAPTER 2 — AUTHENTICATION 5

CHAPTER 3 — GENERAL CONVENTIONS 6

- 3.1 Data Types 6
- 3.2 Pagination 6
- 3.3 Ordering 6
- 3.4 Date Range 6
- 3.5 Field Filters 6
- 3.6 Response Envelope 6
- 3.7 Global Response Codes 6
- 3.8 Usage Guidelines 7

CHAPTER 4 — ENDPOINTS 8

- 4.1 Resource Catalog 8
- 4.2 List Records 9
- 4.3 Retrieve Record 10

CHAPTER 5 — RESOURCE REFERENCE 12

- 5.1 Sales & Booking 14
- 5.2 Finance 22
- 5.3 Fleet & Operations 26
- 5.4 Purchasing 30
- 5.5 Stock & Warehouse 36
- 5.6 POS / Cashier 43
- 5.7 Marketing 47

CHAPTER 6 — DATA ACCESS RESTRICTIONS 49

- 6.1 Modules Not Exposed 49
- 6.2 Columns Always Removed 49

CHAPTER 7 — APPENDIX 50

- A. API Key Format 50
- B. Issuing, Rotating and Revoking the Key 50
- C. Client Examples 50

Document Change Control

Version	Date	Authors	Summary of Changes
0.9.0	09/10/2026	ERP Engineering	BOT role introduced: read-only, deny-by-default access limited to GET /api/bot/* (session login).
1.0.0	15/10/2026	ERP Engineering	Add API key authentication (Authorization: Bearer sbk_...) for external analysis tools. API key carries exactly the BOT role access, no more. Key configured in server env (BOT_API_KEY / BOT_API_KEY_USER / BOT_API_KEY_TENANT); rotate by editing .env. First release of this specification: 64 resources.

CHAPTER 1

OVERVIEW

Summary

The ERP Bot API gives AI bots and external analysis tools **read-only** access to Samara Yachting ERP business data: bookings, revenue, payments, costs, purchasing, stock, fleet operations, onboard POS and marketing campaigns. It is designed for reporting and analysis; it can never create, change, approve or delete anything.

Method	URL	Description
GET	/api/bot	Catalog: every resource the API key can read, with its columns
GET	/api/bot/{resource}	List records of a resource (paginated, filterable)
GET	/api/bot/{resource}/{id}	Retrieve a single record by id

Access Model

- Every API key is bound to one ERP user account with role **BOT** and authenticates as that user. It receives exactly the BOT role's access.
- Only **GET** and **HEAD** are accepted. POST, PUT, PATCH and DELETE are refused (HTTP 403) before any handler runs.
- Only paths under **/api/bot** accept the key. On every other ERP route the Authorization header is ignored.
- Only whitelisted resources (Chapter 5) are reachable. Only their scalar columns are returned; relations are never embedded.
- Sensitive columns are removed server-side on every response (Chapter 6), including keys nested inside JSON columns.
- If a request carries both an API key and a browser session cookie, only the API key is considered.

Environment

Item	Value
Base URL	https://{erp-domain} (the production ERP host)
Protocol	HTTPS only
Content type	application/json; charset=utf-8
Time zone	All DateTime values are UTC, ISO-8601 (e.g. 2026-10-01T08:00:00.000Z)
Tenant	Bound to the API key; one key reads one company database

CHAPTER 2

AUTHENTICATION

Summary

Authentication uses a static **API key** sent in the Authorization header of every request. There is no token exchange step and no expiry: a key stays valid until it is revoked (Appendix B). Keys are issued by an ERP administrator and must be stored as a secret on the calling system.

Input Parameters

	Field Name	Attrib.	Type	Comment
Header				
	Authorization	M	String	Bearer {API Key} Format: **sbk_<random string>**
	Accept	O	String	application/json

Sample Request

```
GET /api/bot HTTP/1.1
Host: {erp-domain}
Authorization: Bearer sbk_xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx
Accept: application/json
```

Response Message

HTTP Code	Response Body	Description
200	(resource payload)	Key valid, request served
401	{"error":"Invalid API key"}	Key does not match the configured key, key access disabled, BOT user missing / not BOT / deactivated, or tenant inactive
403	{"error":"Bot API keys are read-only"}	Method other than GET / HEAD sent with an API key
307	(redirect to /login)	No Authorization header and no session: the request is treated as an anonymous browser visit

CHAPTER 3

GENERAL CONVENTIONS

3.1 Data Types

Type	JSON representation	Sample
String	string	"Samara I"
Int	number (integer)	12
Float	number	18500000.5
Boolean	boolean	true
DateTime	string, ISO-8601 UTC	"2026-10-01T08:00:00.000Z"
Json	object / array (sensitive keys removed)	{"note":"..."}
Enum	string, one of the listed values (Chapter 5)	"CONFIRMED"
(any)	null when the column is empty	null

3.2 Pagination

List endpoints use cursor pagination. Request up to **limit** rows (default 100, maximum 500). When more rows exist, the response carries **nextCursor** (the id of the last row returned); send it back as **cursor** to get the next page. **nextCursor = null** means the last page. Keep every other query parameter identical between pages.

3.3 Ordering

Rows are returned newest first: by the resource's date column descending (see "Date column" per resource), then by id descending. Resources without a date column are ordered by id descending.

3.4 Date Range

from and **to** (YYYY-MM-DD or full ISO-8601) filter the resource's date column inclusively (*from* <= value <= *to*). A bare date means midnight UTC, so **to=2026-12-31** excludes rows later on 31 Dec; use **to=2026-12-31T23:59:59Z** for the full day.

3.5 Field Filters

Any column listed for a resource can be used as an exact-match filter: **?{column}={value}**. Several filters are combined with AND. Values are converted by column type (Int, Float, Boolean "true"/"false", DateTime). The literal value **null** matches empty columns. A column that is not listed (unknown or hidden) is rejected with HTTP 400, never silently ignored. Partial-text, range (other than the date column) and OR filters are not supported; fetch and filter client-side.

3.6 Response Envelope

Endpoint	Body
List	{ "resource": string, "count": number, "nextCursor": string|null, "data": [{record}, ...] }
Detail	{ "resource": string, "data": {record} }
Error	{ "error": string }

3.7 Global Response Codes

HTTP Code	Response Body	Description
200	Success envelope	Success
400	{"error":"Invalid from/to date"}	from or to cannot be parsed as a date
400	{"error":"Unknown or non-filterable field: {field}"}	Filter on a column that does not exist or is hidden
400	{"error":"Query failed — check filter values"}	Filter value of the wrong type, or invalid cursor

HTTP Code	Response Body	Description
401	{"error":"Invalid API key"}	See Chapter 2
403	{"error":"Bot API keys are read-only"}	Write method attempted
404	{"error":"Unknown resource — see GET /api/bot"}	Resource name not in the whitelist
404	{"error":"Not found"}	Detail: no record with this id (or the record is excluded, e.g. salary expense)
500	(server error)	Unexpected error in the ERP. Retry later; report if persistent

3.8 Usage Guidelines

- Fetch incrementally with from/to rather than re-downloading full history on every run.
- Use limit=500 for bulk export and page with nextCursor; avoid more than a few requests per second.
- Join resources client-side through their *Id columns (e.g. payments.bookingId = bookings.id).
- Never log or commit the API key. Treat exported data as confidential company data.

CHAPTER 4

ENDPOINTS

4.1 Resource Catalog

Lists every resource readable with the key, its path and its columns. Use it to discover the schema at runtime; it always reflects the live server, including columns added after this document.
GET : /api/bot

Input Parameter

	Field Name	Attrib.	Type	Comment
HTTP Header				
	Authorization	M	String	Bearer {API Key}. Format **sbk_<random>**. See Appendix A.
	Accept	O	String	application/json
Query				
	(none)	-	-	-

Output Parameter

	Field Name	Attrib.	Type	Comment
Body				
	readOnly	M	Boolean	Always true
	usage	M	Object	Short usage notes: auth, list, detail, notes
	resources	M	Array of Object	One entry per resource
	name	M	String	Resource name used in the URL
	path	M	String	/api/bot/{name}
	description	M	String	What the resource contains
	fields	M	Array of Object	{ name, type } for every readable column

Sample Response

```
{
  "readOnly": true,
  "usage": {
    "auth": "Header \"Authorization: Bearer sbk_...\" (BOT API key), or a logged-in BOT session cookie",
    "list": "GET /api/bot/{resource}?limit=100&cursor={lastId}&from=YYYY-MM-DD&to=YYYY-MM-DD&{field}={value}",
    "detail": "GET /api/bot/{resource}/{id}",
    "notes": "limit max 500. from/to filter the resource's main date column. ..."
  },
  "resources": [
    {
      "name": "bookings",
      "path": "/api/bot/bookings",
      "description": "Bookings (charter & open trip), prices, status",
      "fields": [ { "name": "id", "type": "String" }, { "name": "startDate", "type": "DateTime" }, ... ]
    },
    ...
  ]
}
```

4.2 List Records

Returns records of one resource, newest first, with optional date range and exact-match column filters.
GET : /api/bot/{resource}

Input Parameter

	Field Name	Attrib.	Type	Comment
HTTP Header				
	Authorization	M	String	Bearer {API Key}. Format **sbk_<random>**. See Appendix A.
	Accept	O	String	application/json
Path				
	resource	M	String	Resource name, e.g. bookings. See Chapter 5
Query				
	limit	O	Int	Rows per page. Default 100, min 1, max 500
	cursor	O	String	nextCursor from the previous page
	from	O	String	Lower bound (inclusive) of the date column. YYYY-MM-DD or ISO-8601
	to	O	String	Upper bound (inclusive) of the date column
	{column}	O	per column	Exact-match filter on any listed column; "null" = empty. Repeatable for different columns

Output Parameter

	Field Name	Attrib.	Type	Comment
Body				
	resource	M	String	Echo of the resource name
	count	M	Int	Number of rows in this page
	nextCursor	M	String / null	Cursor for the next page; null on the last page
	data	M	Array of Object	Records; keys = the resource's columns (Chapter 5)

Sample Request

```
GET /api/bot/payments?from=2026-09-01&to=2026-09-30T23:59:59Z&status=PAID&limit=2 HTTP/1.1
Authorization: Bearer sbk_...
```

Sample Response (on normal condition)

```
{
  "resource": "payments",
  "count": 2,
  "nextCursor": "cmxxxxxxxxxxxxxxxxxxxxxxx",
  "data": [
    {
      "id": "cmxxxxxxxxxxxxxxxxxxxxxxx",
      "bookingId": "cmxxxxxxxxxxxxxxxxxxxxxxx",
      "invoiceNumber": "XX-2026-0001",
      "paymentType": "string",
      "paymentMethod": "string",
      "amount": 2500000,
      "previouslyPaid": 2500000,
      "paymentDate": "2026-10-01T08:00:00.000Z"
    },
    { ... }
  ]
}
```

Response Message

HTTP Code	Response Body	Description
200	List envelope	Success (count may be 0)
400	Invalid from/to date	from/to not a date
400	Unknown or non-filterable field: {field}	Filter column not listed for this resource
400	Query failed — check filter values	Value type mismatch (e.g. text on an Int column, unknown enum value) or bad cursor
401	Invalid API key	Authentication failed
403	Bot API keys are read-only	Non-GET method
404	Unknown resource — see GET /api/bot	Resource not whitelisted

4.3 Retrieve Record

Returns one record by id. Same columns as the list endpoint.
GET : /api/bot/{resource}/{id}

Input Parameter

	Field Name	Attrib.	Type	Comment
HTTP Header				
	Authorization	M	String	Bearer {API Key}. Format **sbk_<random>**. See Appendix A.
	Accept	O	String	application/json
Path				
	resource	M	String	Resource name
	id	M	String	Record id (the "id" column)

Output Parameter

	Field Name	Attrib.	Type	Comment
Body				
	resource	M	String	Echo of the resource name
	data	M	Object	The record

Sample Request

```
GET /api/bot/bookings/cmxxxxxxxxxxxxxxxxxxxxxx HTTP/1.1
Authorization: Bearer sbk_...
```

Sample Response (on normal condition)

```
{
  "resource": "bookings",
  "data": {
    "id": "cmxxxxxxxxxxxxxxxxxxxxx",
    "bookingCode": "XX-2026-0001",
    "customerId": "cmxxxxxxxxxxxxxxxxxxxxxx",
    "agentId": "cmxxxxxxxxxxxxxxxxxxxxx",
    "agentContactId": "cmxxxxxxxxxxxxxxxxxxxxxx",
    "openTripId": "cmxxxxxxxxxxxxxxxxxxxxx",
    "source": "AGENT",
    "tripType": "PRIVATE_CHARTER"
  }
}
```

Response Message

HTTP Code	Response Body	Description
200	Detail envelope	Success
401	Invalid API key	Authentication failed
403	Bot API keys are read-only	Non-GET method
404	Unknown resource — see GET /api/bot	Resource not whitelisted
404	Not found	No such id, or the record is excluded from bot access

CHAPTER 5

RESOURCE REFERENCE

Every resource below supports both **GET /api/bot/{resource}** and **GET /api/bot/{resource}/{id}**. All listed columns are returned and all of them can be used as exact-match filters. Columns ending in **Id** reference the **id** of another resource. Attrib.: **M** = always present, **O** = may be null. Enum value lists are given in the Comment column.

No	Category	Resource	Description	Date column
1	Sales & Booking	bookings	Bookings (charter & open trip), prices, status	startDate
2	Sales & Booking	booking-guests	Guest ↔ booking ↔ cabin links, flights/pickup	-
3	Sales & Booking	booking-services	Add-on services sold on bookings	-
4	Sales & Booking	customers	Guests — name/contact only (no passport, medical, DOB, address)	createdAt
5	Sales & Booking	leads	Sales leads & pipeline stage	createdAt
6	Sales & Booking	inquiries	Inbound inquiries	createdAt
7	Sales & Booking	agents	B2B agents & commission rates	createdAt
8	Sales & Booking	agent-contacts	Agent contact persons	createdAt
9	Sales & Booking	agent-clawback-entries	Agent commission clawbacks	createdAt
10	Sales & Booking	vouchers	Discount vouchers	createdAt
11	Sales & Booking	waiting-lists	Open-trip waiting list	createdAt
12	Finance	payments	Invoices & payments received	paymentDate
13	Finance	banks	Receiving bank names (no account numbers)	createdAt
14	Finance	expenses	Operating expenses (salary/payroll rows excluded)	date
15	Finance	po-payment-requests	PO payment requests (read-only)	createdAt
16	Finance	po-reimbursements	PO reimbursements (no payee account)	createdAt
17	Finance	delivery-fees	Delivery fees	createdAt
18	Finance	delivery-fee-payment-requests	Delivery fee payment requests	createdAt
19	Finance	delivery-fee-reimbursements	Delivery fee reimbursements (no payee account)	createdAt
20	Fleet & Operations	yachts	Boats	createdAt
21	Fleet & Operations	cabins	Cabins per boat	-
22	Fleet & Operations	cabin-pricing-tiers	Cabin pricing tiers	-
23	Fleet & Operations	destinations	Destinations	createdAt
24	Fleet & Operations	yacht-destination-prices	Charter price per boat × destination	-
25	Fleet & Operations	open-trips	Scheduled open trips	startDate
26	Fleet & Operations	crew	Crew roster per boat (name/position only)	createdAt
27	Fleet & Operations	maintenance	Boat maintenance records	createdAt
28	Fleet & Operations	internal-events	Internal calendar blocks	createdAt
29	Purchasing	purchase-requests	Purchase requests	createdAt
30	Purchasing	purchase-request-items	Purchase request lines	-
31	Purchasing	purchase-quotations	Supplier quotations	createdAt
32	Purchasing	purchase-orders	Purchase orders	createdAt
33	Purchasing	purchase-order-items	Purchase order lines	-
34	Purchasing	goods-receipts	Goods receipts	receivedAt

No	Category	Resource	Description	Date column
35	Purchasing	goods-receipt-items	Goods receipt lines	-
36	Purchasing	suppliers	Suppliers	createdAt
37	Purchasing	purchase-items	Item master (purchasing)	createdAt
38	Purchasing	purchase-item-categories	Item categories	createdAt
39	Stock & Warehouse	stock-locations	Warehouses / boats / stock locations	createdAt
40	Stock & Warehouse	stock-lots	Stock on hand by lot	createdAt
41	Stock & Warehouse	stock-movements	Stock movement ledger	createdAt
42	Stock & Warehouse	stock-transfers	Stock transfers	createdAt
43	Stock & Warehouse	stock-transfer-items	Stock transfer lines	-
44	Stock & Warehouse	stock-counts	Stock counts	createdAt
45	Stock & Warehouse	stock-count-items	Stock count lines	-
46	Stock & Warehouse	inventory-exceptions	Inventory exceptions	createdAt
47	Stock & Warehouse	crew-requests	Crew requests	createdAt
48	Stock & Warehouse	crew-request-items	Crew request lines	-
49	Stock & Warehouse	inventory-rooms	Inventory rooms	createdAt
50	Stock & Warehouse	inventory-categories	Inventory categories	createdAt
51	Stock & Warehouse	inventory-items	Inventory items	createdAt
52	Stock & Warehouse	inventory-opnames	Inventory opname sessions	createdAt
53	Stock & Warehouse	inventory-opname-entries	Inventory opname entries	createdAt
54	POS / Cashier	cashier-sales	Onboard POS sales	createdAt
55	POS / Cashier	cashier-sale-items	Onboard POS sale lines	createdAt
56	POS / Cashier	pos-categories	POS categories	createdAt
57	POS / Cashier	pos-menu-items	POS menu items	createdAt
58	POS / Cashier	pos-packages	POS packages	createdAt
59	POS / Cashier	pos-package-items	POS package lines	-
60	POS / Cashier	pos-recipes	POS recipes	createdAt
61	POS / Cashier	pos-recipe-lines	POS recipe ingredients	-
62	POS / Cashier	pos-discounts	POS discounts	createdAt
63	Marketing	campaigns	Marketing campaigns	createdAt
64	Marketing	email-campaigns	Email campaigns & stats	createdAt

5.1 Sales & Booking

5.1.1 bookings

Bookings (charter & open trip), prices, status.

GET : /api/bot/bookings | **GET** : /api/bot/bookings/{id} | Date column: **startDate** | 47 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	bookingCode	M	String	
	customerId	M	String	Reference id
	agentId	O	String	Reference id
	agentContactId	O	String	Reference id
	openTripId	O	String	Reference id
	source	M	Enum BookingSource	Enum: AGENT, DIRECT
	tripType	M	Enum TripType	Enum: PRIVATE_CHARTER, OPEN_TRIP
	useB2BCommission	M	Boolean	
	yachtId	O	String	Reference id
	startDate	M	DateTime	Date column (from/to)
	endDate	M	DateTime	
	destination	O	String	
	destinationId	O	String	Reference id
	status	M	Enum BookingStatus	Enum: on_hold, pending, partially_paid, fully_paid, completed, cancelled, confirmed, pending_refund
	tripNumber	O	Int	
	totalPrice	M	Float	
	depositPaid	M	Float	
	discount	M	Float	
	vatType	O	String	
	vatValue	M	Float	
	depositDueDate	O	DateTime	
	finalDueDate	O	DateTime	
	depositDueDateInvoiceOverride	O	DateTime	
	finalDueDateInvoiceOverride	O	DateTime	
	holdUntil	O	DateTime	
	guestCount	M	Int	
	crewRequired	M	Boolean	
	hasDiving	M	Boolean	
	hasSurfing	M	Boolean	
	hasPhotoPackage	M	Boolean	
	masterFormExpiresAt	O	DateTime	
	travelingWith	O	String	
	salesperson	O	String	
	salespersonId	O	String	Reference id

	Field Name	Attrib.	Type	Comment
	notes	O	String	
	cancelReason	O	String	
	refundStatus	O	String	
	refundDecision	O	String	
	refundReason	O	String	
	refundConfirmedAt	O	DateTime	
	refundConfirmedBy	O	String	
	voucherCode	O	String	
	currency	M	String	
	exchangeRate	O	Float	
	createdAt	M	DateTime	
	updatedAt	M	DateTime	

5.1.2 booking-guests

Guest ↔ booking ↔ cabin links, flights/pickup.

GET : /api/bot/booking-guests | **GET** : /api/bot/booking-guests/{id} | Date column: **-** | 11 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	bookingId	M	String	Reference id
	customerId	O	String	Reference id
	cabinId	O	String	Reference id
	isLead	M	Boolean	
	arrivalPickupTime	O	String	
	arrivalHotel	O	String	
	arrivalFlight	O	String	
	departurePickupTime	O	String	
	departureHotel	O	String	
	departureFlight	O	String	

5.1.3 booking-services

Add-on services sold on bookings.

GET : /api/bot/booking-services | **GET** : /api/bot/booking-services/{id} | Date column: **-** | 5 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	bookingId	M	String	Reference id
	name	M	String	
	price	M	Float	
	quantity	M	Int	

5.1.4 customers

Guests — name/contact only (no passport, medical, DOB, address).

GET : /api/bot/customers | **GET** : /api/bot/customers/{id} | Date column: **createdAt** | 25 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	firstName	O	String	
	lastName	O	String	
	gender	O	String	
	email	O	String	
	phone	O	String	
	isChild	M	Boolean	
	dietaryRequirements	O	String	
	allergies	O	String	
	equipmentSizes	O	String	
	operationalNotes	O	String	
	nationality	O	String	
	drinkPreferences	O	String	
	guestFormExpiresAt	O	DateTime	
	freshsalesContactId	O	String	Reference id
	foodData	O	Json	
	drinksData	O	Json	
	divingData	O	Json	
	surfingData	O	Json	
	pastDestinations	O	String	
	pastDestinationsOther	O	String	
	deletedAt	O	DateTime	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.1.5 leads

Sales leads & pipeline stage.

GET : /api/bot/leads | **GET** : /api/bot/leads/{id} | Date column: **createdAt** | 31 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	firstName	O	String	
	lastName	O	String	
	nationality	O	String	
	email	O	String	
	phone	O	String	

	Field Name	Attrib.	Type	Comment
	notes	O	String	
	freshsalesContactId	O	String	Reference id
	deletedAt	O	DateTime	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	
	stage	M	Enum LeadStage	Enum: NEW, CONTACTED, QUALIFIED, UNQUALIFIED, OPPORTUNITY, CLOSED_WON, CLOSED_LOST
	stageUpdatedAt	O	DateTime	
	stageUpdatedById	O	String	Reference id
	productInterest	O	String	
	destinationId	O	String	Reference id
	travelStartDate	O	DateTime	
	travelEndDate	O	DateTime	
	travelSeason	O	String	
	guestCount	O	Int	
	leadQuality	O	Enum LeadQuality	Enum: HOT, WARM, COLD
	budgetMin	O	Float	
	budgetMax	O	Float	
	budgetCurrency	O	String	
	proposalSentAt	O	DateTime	
	lostReason	O	Enum LeadLostReason	Enum: PRICE, DATES, COMPETITOR, NO_RESPONSE, OTHER
	lostNote	O	String	
	ownerId	O	String	Reference id
	ownerAssignedAt	O	DateTime	
	source	O	String	

5.1.6 inquiries

Inbound inquiries.

GET : /api/bot/inquiries | **GET** : /api/bot/inquiries/{id} | Date column: **createdAt** | 38 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	source	M	String	
	leadId	O	String	Reference id
	customerId	O	String	Reference id
	checkInDate	O	DateTime	
	checkOutDate	O	DateTime	
	guestCount	O	Int	
	tripType	O	String	
	message	O	String	
	website	O	String	

	Field Name	Attrib.	Type	Comment
	url	O	String	
	utmSource	O	String	
	utmMedium	O	String	
	utmCampaign	O	String	
	utmTerm	O	String	
	utmContent	O	String	
	gclid	O	String	
	gbraid	O	String	
	wbraid	O	String	
	fbclid	O	String	
	leadSource	O	String	
	refererField	O	String	
	mobileNumberBackup	O	String	
	reference	O	String	
	lastSource	O	String	
	lastMedium	O	String	
	lastCampaign	O	String	
	lastTerm	O	String	
	lastContent	O	String	
	lastGclid	O	String	
	lastGbraid	O	String	
	lastWbraid	O	String	
	lastFbclid	O	String	
	latestSource	O	String	
	latestMedium	O	String	
	latestCampaign	O	String	
	rawPayload	O	Json	
	createdAt	M	DateTime	Date column (from/to)

5.1.7 agents

B2B agents & commission rates.

GET : /api/bot/agents | **GET** : /api/bot/agents/{id} | Date column: **createdAt** | 23 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	commission	M	Float	
	commissionOpenTrip	M	Float	
	commissionPrivateCharter	M	Float	
	commissionB2B	M	Float	
	isActive	M	Boolean	
	country	O	String	

	Field Name	Attrib.	Type	Comment
	address	O	String	
	email	O	String	
	whatsapp	O	String	
	note	O	String	
	website	O	String	
	instagram	O	String	
	source	O	String	
	currentCondition	O	String	
	contract	O	String	
	calendarActive	M	Boolean	
	portalActive	M	Boolean	
	salespersonId	O	String	Reference id
	clawbackRatePerNight	M	Float	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.1.8 agent-contacts

Agent contact persons.

GET : /api/bot/agent-contacts | **GET** : /api/bot/agent-contacts/{id} | Date column: **createdAt** | 10 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	agentId	M	String	Reference id
	name	M	String	
	email	O	String	
	whatsapp	O	String	
	jobTitle	O	String	
	addedById	O	String	Reference id
	addedByName	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.1.9 agent-clawback-entries

Agent commission clawbacks.

GET : /api/bot/agent-clawback-entries | **GET** : /api/bot/agent-clawback-entries/{id} | Date column: **createdAt** | 8 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	agentId	M	String	Reference id
	amount	M	Float	
	bookingId	O	String	Reference id
	note	O	String	
	createdByUserId	O	String	Reference id
	createdByName	O	String	
	createdAt	M	DateTime	Date column (from/to)

5.1.10 vouchers

Discount vouchers.

GET : /api/bot/vouchers | **GET** : /api/bot/vouchers/{id} | Date column: **createdAt** | 14 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	code	M	String	
	name	M	String	
	description	O	String	
	type	M	Enum VoucherType	Enum: PERCENTAGE, FIXED
	value	M	Float	
	minBooking	O	Float	
	maxUses	O	Int	
	usedCount	M	Int	
	validFrom	O	DateTime	
	validUntil	O	DateTime	
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.1.11 waiting-lists

Open-trip waiting list.

GET : /api/bot/waiting-lists | **GET** : /api/bot/waiting-lists/{id} | Date column: **createdAt** | 17 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	bookingId	O	String	Reference id
	yachtId	O	String	Reference id
	openTripId	O	String	Reference id
	startDate	M	DateTime	
	endDate	M	DateTime	
	customerId	O	String	Reference id
	contactName	M	String	
	contactPhone	O	String	
	contactEmail	O	String	
	notes	O	String	
	priority	M	Int	
	status	M	Enum WaitingListStatus	Enum: waiting, promoted, cancelled
	salespersonId	O	String	Reference id
	promotedBookingId	O	String	Reference id
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.2 Finance

5.2.1 payments

Invoices & payments received.

GET : /api/bot/payments | **GET** : /api/bot/payments/{id} | Date column: **paymentDate** | 26 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	bookingId	M	String	Reference id
	invoiceNumber	M	String	
	paymentType	M	String	
	paymentMethod	O	String	
	amount	M	Float	
	previouslyPaid	M	Float	
	paymentDate	O	DateTime	Date column (from/to)
	currency	M	String	
	exchangeRate	O	Float	
	status	M	Enum PaymentStatus	Enum: requested, invoice_ready, pending_confirmation, confirmed, rejected, cancelled, refunded
	notes	O	String	
	billToType	O	String	
	showNetAmount	M	Boolean	
	showCommissionNote	M	Boolean	
	bankId	O	String	Reference id
	submittedByUserId	O	String	Reference id
	submittedByName	O	String	
	invoiceGeneratedBy	O	String	
	invoiceGeneratedAt	O	DateTime	
	confirmedBy	O	String	
	confirmedAt	O	DateTime	
	hasDocument	M	Boolean	
	parentPaymentId	O	String	Reference id
	createdAt	M	DateTime	
	updatedAt	M	DateTime	

5.2.2 banks

Receiving bank names (no account numbers).

GET : /api/bot/banks | **GET** : /api/bot/banks/{id} | Date column: **createdAt** | 8 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	bankAddress	O	String	
	beneficiaryName	O	String	
	address	O	String	
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.2.3 expenses

Operating expenses (salary/payroll rows excluded).

GET : /api/bot/expenses | **GET** : /api/bot/expenses/{id} | Date column: **date** | 9 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	category	M	String	
	amount	M	Float	
	description	O	String	
	date	M	DateTime	Date column (from/to)
	yachtId	O	String	Reference id
	bookingId	O	String	Reference id
	createdAt	M	DateTime	
	updatedAt	M	DateTime	

Note: rows whose description or category contains salary, gaji, payroll, wage, upah or bonus are never returned (list and detail).

5.2.4 po-payment-requests

PO payment requests (read-only).

GET : /api/bot/po-payment-requests | **GET** : /api/bot/po-payment-requests/{id} | Date column: **createdAt** | 16 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	orderId	M	String	Reference id
	requestedById	M	String	Reference id
	amount	M	Float	
	notes	O	String	
	notaDate	O	DateTime	
	status	M	Enum POPaymentRequestStatus	Enum: PENDING, PAID, REJECTED
	paymentMethod	M	String	
	paidAt	O	DateTime	

	Field Name	Attrib.	Type	Comment
	paidById	O	String	Reference id
	paidNotes	O	String	
	rejectedAt	O	DateTime	
	rejectedById	O	String	Reference id
	rejectionReason	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.2.5 po-reimbursements

PO reimbursements (no payee account).

GET : /api/bot/po-reimbursements | **GET** : /api/bot/po-reimbursements/{id} | Date column: **createdAt** | 15 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	orderId	M	String	Reference id
	requestedById	M	String	Reference id
	amount	M	Float	
	notes	O	String	
	notaDate	O	DateTime	
	requesterName	M	String	
	bankName	M	String	
	accountHolderName	M	String	
	status	M	Enum POReimbursementStatus	Enum: PENDING, PAID
	paidAt	O	DateTime	
	paidById	O	String	Reference id
	paidNotes	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.2.6 delivery-fees

Delivery fees.

GET : /api/bot/delivery-fees | **GET** : /api/bot/delivery-fees/{id} | Date column: **createdAt** | 7 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	feeNumber	M	String	
	purchaseOrderId	O	String	Reference id
	notes	O	String	
	createdById	O	String	Reference id
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.2.7 delivery-fee-payment-requests

Delivery fee payment requests.

GET : /api/bot/delivery-fee-payment-requests | **GET** : /api/bot/delivery-fee-payment-requests/{id} | Date column: **createdAt** | 13 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	deliveryFeeId	M	String	Reference id
	requestedById	M	String	Reference id
	amount	M	Float	
	notes	O	String	
	notaDate	O	DateTime	
	status	M	Enum DeliveryFeePaymentRequestStatus	Enum: PENDING, PAID
	paymentMethod	M	String	
	paidAt	O	DateTime	
	paidById	O	String	Reference id
	paidNotes	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.2.8 delivery-fee-reimbursements

Delivery fee reimbursements (no payee account).

GET : /api/bot/delivery-fee-reimbursements | **GET** : /api/bot/delivery-fee-reimbursements/{id} | Date column: **createdAt** | 15 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	deliveryFeeId	M	String	Reference id
	requestedById	M	String	Reference id
	amount	M	Float	
	notes	O	String	
	notaDate	O	DateTime	
	requesterName	M	String	
	bankName	M	String	
	accountHolderName	M	String	
	status	M	Enum DeliveryFeeReimbursementStatus	Enum: PENDING, PAID
	paidAt	O	DateTime	
	paidById	O	String	Reference id
	paidNotes	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.3 Fleet & Operations

5.3.1 yachts

Boats.

GET : /api/bot/yachts | **GET** : /api/bot/yachts/{id} | Date column: **createdAt** | 20 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	model	O	String	
	year	O	Int	
	capacity	M	Int	
	cabinCount	M	Int	
	length	O	Float	
	description	O	String	
	hourlyRate	M	Float	
	dailyRate	M	Float	
	extraBedTiers	M	Json	
	canDiving	M	Boolean	
	canSurfing	M	Boolean	
	status	M	Enum YachtStatus	Enum: available, booked, maintenance
	tagline	O	String	
	type	O	String	
	sortOrder	M	Int	
	deletedAt	O	DateTime	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.3.2 cabins

Cabins per boat.

GET : /api/bot/cabins | **GET** : /api/bot/cabins/{id} | Date column: **-** | 8 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	yachtId	M	String	Reference id
	name	M	String	
	capacity	M	Int	
	price	M	Float	
	deck	O	String	
	bedType	O	String	
	extraBeds	M	Int	

5.3.3 cabin-pricing-tiers

Cabin pricing tiers.

GET : /api/bot/cabin-pricing-tiers | **GET** : /api/bot/cabin-pricing-tiers/{id} | Date column: **-** | 5 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	cabinId	M	String	Reference id
	destinationId	O	String	Reference id
	nights	M	Int	
	price	M	Float	

5.3.4 destinations

Destinations.

GET : /api/bot/destinations | **GET** : /api/bot/destinations/{id} | Date column: **createdAt** | 7 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	region	O	String	
	isActive	M	Boolean	
	deletedAt	O	DateTime	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.3.5 yacht-destination-prices

Charter price per boat × destination.

GET : /api/bot/yacht-destination-prices | **GET** : /api/bot/yacht-destination-prices/{id} | Date column: **-** | 5 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	yachtId	M	String	Reference id
	destinationId	M	String	Reference id
	price	M	Float	
	relocationFee	O	Float	

5.3.6 open-trips

Scheduled open trips.

GET : /api/bot/open-trips | **GET** : /api/bot/open-trips/{id} | Date column: **startDate** | 18 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	title	M	String	
	description	O	String	
	yachtId	M	String	Reference id
	startDate	M	DateTime	Date column (from/to)
	endDate	M	DateTime	
	destination	M	String	
	destinationId	O	String	Reference id
	region	O	String	
	departurePort	O	String	
	arrivalPort	O	String	
	pricePerCabin	M	Float	
	maxCapacity	M	Int	
	status	M	Enum OpenTripStatus	Enum: open, closed, full, completed, cancelled
	closedReason	O	String	
	tripNumber	O	Int	
	createdAt	M	DateTime	
	updatedAt	M	DateTime	

5.3.7 crew

Crew roster per boat (name/position only).

GET : /api/bot/crew | **GET** : /api/bot/crew/{id} | Date column: **createdAt** | 9 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	yachtId	M	String	Reference id
	name	M	String	
	position	M	String	
	isActive	M	Boolean	
	startDate	M	DateTime	
	endDate	O	DateTime	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.3.8 maintenance

Boat maintenance records.

GET : /api/bot/maintenance | **GET** : /api/bot/maintenance/{id} | Date column: **createdAt** | 10 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	yachtId	M	String	Reference id
	title	M	String	
	description	O	String	
	scheduledDate	M	DateTime	
	completedAt	O	DateTime	
	status	M	Enum MaintenanceStatus	Enum: scheduled, in_progress, completed, cancelled
	cost	O	Float	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.3.9 internal-events

Internal calendar blocks.

GET : /api/bot/internal-events | **GET** : /api/bot/internal-events/{id} | Date column: **createdAt** | 11 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	type	M	Enum InternalEventType	Enum: DOCKING, CROSSING, OVERHAUL, COMPANY_NEED
	title	M	String	
	notes	O	String	
	startDate	M	DateTime	
	endDate	M	DateTime	
	yachtId	O	String	Reference id
	internalOnly	M	Boolean	
	createdById	O	String	Reference id
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.4 Purchasing

5.4.1 purchase-requests

Purchase requests.

GET : /api/bot/purchase-requests | **GET** : /api/bot/purchase-requests/{id} | Date column: **createdAt** | 27 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	prNumber	M	String	
	requestedById	M	String	Reference id
	requestedByEmployeeId	O	String	Reference id
	approverEmployeeId	O	String	Reference id
	deliveryLocationId	O	String	Reference id
	notes	O	String	
	status	M	Enum PurchaseRequestStatus	Enum: DRAFT, PENDING_APPROVAL, ON_PROCESS, CONVERTED, REJECTED, CANCELLED
	purpose	M	Enum PurchaseRequestPurpose	Enum: STOCK_INVENTORY, TRIP, REPLACEMENT
	tripBookingId	O	String	Reference id
	openTripId	O	String	Reference id
	division	O	Enum PurchaseRequestDivision	Enum: BOAT_OPERATION, BUILDING_MATERIAL
	neededByDate	O	DateTime	
	isUrgent	M	Boolean	
	urgentReason	O	String	
	approvedById	O	String	Reference id
	approvedAt	O	DateTime	
	verifiedById	O	String	Reference id
	verifiedAt	O	DateTime	
	convertedById	O	String	Reference id
	convertedAt	O	DateTime	
	rejectedById	O	String	Reference id
	rejectedAt	O	DateTime	
	cancelledById	O	String	Reference id
	cancelledAt	O	DateTime	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.4.2 purchase-request-items

Purchase request lines.

GET : /api/bot/purchase-request-items | **GET** : /api/bot/purchase-request-items/{id} | Date column: **-** | 31 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	requestId	M	String	Reference id
	itemId	O	String	Reference id
	itemName	M	String	
	quantity	M	Float	
	unit	M	String	
	estimatedCost	M	Float	
	supplierId	O	String	Reference id
	supplierName	O	String	
	notes	O	String	
	isStockItem	M	Boolean	
	exemptionReason	O	String	
	selectionJustification	O	String	
	quotationSubmittedById	O	String	Reference id
	quotationApproverId	O	String	Reference id
	quotationSubmittedAt	O	DateTime	
	quotationApprovedById	O	String	Reference id
	quotationApprovedAt	O	DateTime	
	quotationRejectedById	O	String	Reference id
	quotationRejectedAt	O	DateTime	
	quotationRejectionReason	O	String	
	convertedAt	O	DateTime	
	convertedPoId	O	String	Reference id
	verifyRejectedById	O	String	Reference id
	verifyRejectedAt	O	DateTime	
	verifyRejectionReason	O	String	
	warehouseDecision	O	Enum PurchaseRequestItemWarehouseDecision	Enum: TRANSFER, PURCHASE
	warehouseCheckedById	O	String	Reference id
	warehouseCheckedAt	O	DateTime	
	warehouseCheckNote	O	String	
	sourceInventoryItemId	O	String	Reference id

5.4.3 purchase-quotations

Supplier quotations.

GET : /api/bot/purchase-quotations | **GET** : /api/bot/purchase-quotations/{id} | Date column: **createdAt** | 8 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	requestItemId	M	String	Reference id
	supplierId	O	String	Reference id
	supplierName	M	String	
	price	M	Float	
	submittedAt	M	DateTime	
	createdById	M	String	Reference id
	createdAt	M	DateTime	Date column (from/to)

5.4.4 purchase-orders

Purchase orders.

GET : /api/bot/purchase-orders | **GET** : /api/bot/purchase-orders/{id} | Date column: **createdAt** | 32 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	poNumber	M	String	
	requestId	O	String	Reference id
	orderType	M	Enum PurchaseOrderKind	Enum: GOODS, SERVICE
	supplierId	O	String	Reference id
	supplierName	O	String	
	deliveryLocationId	O	String	Reference id
	bookingId	O	String	Reference id
	openTripId	O	String	Reference id
	status	M	Enum PurchaseOrderStatus	Enum: DRAFT, ORDERED, IN_TRANSIT, PARTIALLY_RECEIVED, RECEIVED, COMPLETED, CANCELLED, REJECTED
	dispatchedAt	O	DateTime	
	dispatchedByName	O	String	
	confirmedByName	O	String	
	notes	O	String	
	orderedAt	M	DateTime	
	expectedAt	O	DateTime	
	cancelledAt	O	DateTime	
	cancelledByName	O	String	
	cancellationReason	O	String	
	completedAt	O	DateTime	
	completedByName	O	String	
	createdById	O	String	Reference id
	createdAt	M	DateTime	Date column (from/to)

	Field Name	Attrib.	Type	Comment
	updatedAt	M	DateTime	
	extraCharges	O	Json	
	discountType	O	String	
	discountValue	M	Float	
	requestedByEmployeeId	O	String	Reference id
	requestedByName	O	String	
	requestedByOffice	O	String	
	requestedByDepartment	O	String	
	requestedByRole	O	String	

5.4.5 purchase-order-items

Purchase order lines.

GET : /api/bot/purchase-order-items | **GET** : /api/bot/purchase-order-items/{id} | Date column: **-** | 11 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	orderId	M	String	Reference id
	itemId	O	String	Reference id
	itemName	M	String	
	unit	O	String	
	orderedQty	M	Float	
	receivedQty	M	Float	
	unitCost	M	Float	
	inventoryRoomId	O	String	Reference id
	inventoryCategoryId	O	String	Reference id
	sourceInventoryItemId	O	String	Reference id

5.4.6 goods-receipts

Goods receipts.

GET : /api/bot/goods-receipts | **GET** : /api/bot/goods-receipts/{id} | Date column: **receivedAt** | 10 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	grNumber	M	String	
	orderId	M	String	Reference id
	receivedById	O	String	Reference id
	receivedByEmployeeId	O	String	Reference id
	receiverName	O	String	
	locationId	M	String	Reference id
	notes	O	String	
	receivedAt	M	DateTime	Date column (from/to)
	createdAt	M	DateTime	

5.4.7 goods-receipt-items

Goods receipt lines.

GET : /api/bot/goods-receipt-items | **GET** : /api/bot/goods-receipt-items/{id} | Date column: **-** | 12 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	receiptId	M	String	Reference id
	itemId	O	String	Reference id
	itemName	M	String	
	receivedQty	M	Float	
	unitCost	M	Float	
	outcome	M	String	
	condition	M	String	
	batch	O	String	
	expiryDate	O	DateTime	
	notes	O	String	
	sourceInventoryItemId	O	String	Reference id

5.4.8 suppliers

Suppliers.

GET : /api/bot/suppliers | **GET** : /api/bot/suppliers/{id} | Date column: **createdAt** | 10 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	locations	M	Json	
	contact	O	String	
	phone	O	String	
	email	O	String	
	notes	O	String	
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.4.9 purchase-items

Item master (purchasing).

GET : /api/bot/purchase-items | **GET** : /api/bot/purchase-items/{id} | Date column: **createdAt** | 19 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	sku	M	String	
	name	M	String	
	type	M	String	
	category	M	String	
	baseUnit	M	String	
	purchaseUnit	M	String	
	conversionFactor	M	Float	
	standardCost	M	Float	
	sellingPrice	M	Float	
	valuationMethod	M	String	
	minStock	M	Float	
	reorderQty	M	Float	
	isActive	M	Boolean	
	isSoldInPos	M	Boolean	
	isStockTracked	M	Boolean	
	currentLocationId	O	String	Reference id
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.4.10 purchase-item-categories

Item categories.

GET : /api/bot/purchase-item-categories | **GET** : /api/bot/purchase-item-categories/{id} | Date column: **createdAt** | 7 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	typeCode	M	String	
	name	M	String	
	skuPrefix	M	String	
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5 Stock & Warehouse

5.5.1 stock-locations

Warehouses / boats / stock locations.

GET : /api/bot/stock-locations | **GET** : /api/bot/stock-locations/{id} | Date column: **createdAt** | 13 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	type	M	Enum StockLocationType	Enum: WAREHOUSE, VESSEL, TRANSIT, SITE, ADJUSTMENT
	yachtId	O	String	Reference id
	parentId	O	String	Reference id
	manager	O	String	
	address	O	String	
	storageClass	O	String	
	managedBy	M	String	
	consumptionMode	O	Enum StockConsumptionMode	Enum: HOLD_AS_STOCK, EXPENSE_ON_RECEIVE
	isPosBar	M	Boolean	
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)

5.5.2 stock-lots

Stock on hand by lot.

GET : /api/bot/stock-lots | **GET** : /api/bot/stock-lots/{id} | Date column: **createdAt** | 12 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	itemId	O	String	Reference id
	itemName	O	String	
	unit	O	String	
	sourcePoId	O	String	Reference id
	locationId	M	String	Reference id
	quantity	M	Float	
	costPerUnit	M	Float	
	batch	O	String	
	expiresAt	O	DateTime	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.3 stock-movements

Stock movement ledger.

GET : /api/bot/stock-movements | **GET** : /api/bot/stock-movements/{id} | Date column: **createdAt** | 18 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	itemId	O	String	Reference id
	itemName	O	String	
	fromLocationId	O	String	Reference id
	toLocationId	O	String	Reference id
	quantity	M	Float	
	type	M	String	
	referenceId	O	String	Reference id
	referenceType	O	String	
	notes	O	String	
	unitCost	O	Float	
	totalCost	O	Float	
	usageType	O	Enum StockUsageType	Enum: SHIP_USAGE, BAR_COGS, COMPLIMENTARY, SHRINKAGE
	yachtId	O	String	Reference id
	openTripId	O	String	Reference id
	tripBookingId	O	String	Reference id
	createdById	M	String	Reference id
	createdAt	M	DateTime	Date column (from/to)

5.5.4 stock-transfers

Stock transfers.

GET : /api/bot/stock-transfers | **GET** : /api/bot/stock-transfers/{id} | Date column: **createdAt** | 25 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	transferNumber	M	String	
	fromLocationId	M	String	Reference id
	toLocationId	M	String	Reference id
	crewRequestId	O	String	Reference id
	purchaseRequestId	O	String	Reference id
	tripBookingId	O	String	Reference id
	openTripId	O	String	Reference id
	purchaseOrderId	O	String	Reference id
	originGoodsReceiptId	O	String	Reference id
	legSequence	O	Int	
	status	M	Enum TransferStatus	Enum: PENDING, DISPATCHED, RECEIVED, CANCELLED
	dispatchedById	O	String	Reference id

	Field Name	Attrib.	Type	Comment
	receivedById	O	String	Reference id
	expectedReceiverId	O	String	Reference id
	expectedReceiverName	O	String	
	receivedByName	O	String	
	notes	O	String	
	dispatchedAt	O	DateTime	
	receivedAt	O	DateTime	
	departAt	O	DateTime	
	etaAt	O	DateTime	
	cargoName	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.5 stock-transfer-items

Stock transfer lines.

GET : /api/bot/stock-transfer-items | **GET** : /api/bot/stock-transfer-items/{id} | Date column: **-** | 9 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	transferId	M	String	Reference id
	itemId	O	String	Reference id
	itemName	M	String	
	requestedQty	M	Float	
	dispatchedQty	M	Float	
	receivedQty	M	Float	
	unitCost	M	Float	
	orderedByEmployeeId	O	String	Reference id

5.5.6 stock-counts

Stock counts.

GET : /api/bot/stock-counts | **GET** : /api/bot/stock-counts/{id} | Date column: **createdAt** | 11 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	countNumber	M	String	
	locationId	M	String	Reference id
	status	M	Enum StockCountStatus	Enum: DRAFT, IN_PROGRESS, COMPLETED, APPROVED
	type	M	Enum StockCountType	Enum: NORMAL, INITIAL
	notes	O	String	
	countedById	M	String	Reference id
	approvedById	O	String	Reference id
	approvedAt	O	DateTime	

	Field Name	Attrib.	Type	Comment
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.7 stock-count-items

Stock count lines.

GET : /api/bot/stock-count-items | **GET** : /api/bot/stock-count-items/{id} | Date column: **-** | 7 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	countId	M	String	Reference id
	itemId	O	String	Reference id
	itemName	M	String	
	systemQty	M	Float	
	countedQty	M	Float	
	reason	O	String	

5.5.8 inventory-exceptions

Inventory exceptions.

GET : /api/bot/inventory-exceptions | **GET** : /api/bot/inventory-exceptions/{id} | Date column: **createdAt** | 17 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	type	M	String	
	itemId	O	String	Reference id
	itemName	M	String	
	locationId	O	String	Reference id
	locationName	M	String	
	qty	M	Float	
	value	M	Float	
	reason	O	String	
	referenceId	O	String	Reference id
	referenceType	O	String	
	status	M	String	
	resolution	O	String	
	resolvedAt	O	DateTime	
	resolvedById	O	String	Reference id
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.9 crew-requests

Crew requests.

GET : /api/bot/crew-requests | **GET** : /api/bot/crew-requests/{id} | Date column: **createdAt** | 7 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	yachtId	M	String	Reference id
	requestedById	M	String	Reference id
	status	M	Enum CrewRequestStatus	Enum: PENDING, REVIEWED, IN_PROGRESS, FULFILLED, CANCELLED
	notes	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.10 crew-request-items

Crew request lines.

GET : /api/bot/crew-request-items | **GET** : /api/bot/crew-request-items/{id} | Date column: **-** | 7 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	requestId	M	String	Reference id
	itemId	O	String	Reference id
	itemName	M	String	
	quantity	M	Float	
	unit	M	String	
	notes	O	String	

5.5.11 inventory-rooms

Inventory rooms.

GET : /api/bot/inventory-rooms | **GET** : /api/bot/inventory-rooms/{id} | Date column: **createdAt** | 6 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	locationId	M	String	Reference id
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.12 inventory-categories

Inventory categories.

GET : /api/bot/inventory-categories | **GET** : /api/bot/inventory-categories/{id} | Date column: **createdAt** | 6 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	roomId	M	String	Reference id
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.13 inventory-items

Inventory items.

GET : /api/bot/inventory-items | **GET** : /api/bot/inventory-items/{id} | Date column: **createdAt** | 20 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	itemNumber	M	String	
	name	M	String	
	categoryId	M	String	Reference id
	brand	O	String	
	purchaseDate	O	DateTime	
	webLink	O	String	
	phone	O	String	
	vendorName	O	String	
	quantity	M	Int	
	unitPrice	M	Float	
	notes	O	String	
	isActive	M	Boolean	
	roomId	M	String	Reference id
	locationId	M	String	Reference id
	sourcePoId	O	String	Reference id
	sourcePurchaseItemId	O	String	Reference id
	createdById	M	String	Reference id
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.14 inventory-opnames

Inventory opname sessions.

GET : /api/bot/inventory-opnames | **GET** : /api/bot/inventory-opnames/{id} | Date column: **createdAt** | 10 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	opnameNumber	M	String	
	locationId	M	String	Reference id
	roomId	M	String	Reference id
	status	M	Enum InventoryOpnameStatus	Enum: DRAFT, IN_PROGRESS, COMPLETED
	notes	O	String	
	countedById	M	String	Reference id
	completedAt	O	DateTime	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.5.15 inventory-opname-entries

Inventory opname entries.

GET : /api/bot/inventory-opname-entries | **GET** : /api/bot/inventory-opname-entries/{id} | Date column: **createdAt** | 8 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	opnameId	M	String	Reference id
	itemId	M	String	Reference id
	unitIndex	M	Int	
	rating	O	Int	
	notes	O	String	
	createdAt	M	DateTime	Date column (from/to)
	replacementRequestItemId	O	String	Reference id

5.6 POS / Cashier

5.6.1 cashier-sales

Onboard POS sales.

GET : /api/bot/cashier-sales | **GET** : /api/bot/cashier-sales/{id} | Date column: **createdAt** | 23 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	yachtId	M	String	Reference id
	locationId	M	String	Reference id
	bookingId	O	String	Reference id
	guestId	O	String	Reference id
	guestName	O	String	
	employeeId	O	String	Reference id
	employeeName	O	String	
	complimentaryReason	O	String	
	status	M	String	
	payMethod	O	String	
	total	M	Float	
	discountId	O	String	Reference id
	discountName	O	String	
	discountAmount	M	Float	
	openedBy	O	String	
	closedAt	O	DateTime	
	needsReview	M	Boolean	
	reviewNote	O	String	
	reviewedAt	O	DateTime	
	reviewedBy	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.6.2 cashier-sale-items

Onboard POS sale lines.

GET : /api/bot/cashier-sale-items | **GET** : /api/bot/cashier-sale-items/{id} | Date column: **createdAt** | 11 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	saleId	M	String	Reference id
	itemId	O	String	Reference id
	packageId	O	String	Reference id
	recipeId	O	String	Reference id
	name	M	String	
	unit	M	String	
	price	M	Float	

	Field Name	Attrib.	Type	Comment
	qty	M	Float	
	round	M	Int	
	createdAt	M	DateTime	Date column (from/to)

5.6.3 pos-categories

POS categories.

GET : /api/bot/pos-categories | **GET** : /api/bot/pos-categories/{id} | Date column: **createdAt** | 6 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	sortOrder	M	Int	
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.6.4 pos-menu-items

POS menu items.

GET : /api/bot/pos-menu-items | **GET** : /api/bot/pos-menu-items/{id} | Date column: **createdAt** | 9 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	itemId	M	String	Reference id
	categoryId	M	String	Reference id
	yachtId	O	String	Reference id
	price	M	Float	
	isActive	M	Boolean	
	sortOrder	M	Int	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.6.5 pos-packages

POS packages.

GET : /api/bot/pos-packages | **GET** : /api/bot/pos-packages/{id} | Date column: **createdAt** | 10 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	description	O	String	
	categoryId	M	String	Reference id
	yachtId	O	String	Reference id
	price	M	Float	
	isActive	M	Boolean	

	Field Name	Attrib.	Type	Comment
	sortOrder	M	Int	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.6.6 pos-package-items

POS package lines.

GET : /api/bot/pos-package-items | **GET** : /api/bot/pos-package-items/{id} | Date column: **-** | 4 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	packageId	M	String	Reference id
	itemId	M	String	Reference id
	qty	M	Float	

5.6.7 pos-recipes

POS recipes.

GET : /api/bot/pos-recipes | **GET** : /api/bot/pos-recipes/{id} | Date column: **createdAt** | 10 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	description	O	String	
	categoryId	M	String	Reference id
	yachtId	O	String	Reference id
	price	M	Float	
	isActive	M	Boolean	
	sortOrder	M	Int	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.6.8 pos-recipe-lines

POS recipe ingredients.

GET : /api/bot/pos-recipe-lines | **GET** : /api/bot/pos-recipe-lines/{id} | Date column: **-** | 4 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	recipeId	M	String	Reference id
	itemId	M	String	Reference id
	qty	M	Float	

5.6.9 pos-discounts

POS discounts.

GET : /api/bot/pos-discounts | **GET** : /api/bot/pos-discounts/{id} | Date column: **createdAt** | 10 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	type	M	String	
	value	M	Float	
	yachtId	O	String	Reference id
	startDate	O	DateTime	
	endDate	O	DateTime	
	isActive	M	Boolean	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.7 Marketing

5.7.1 campaigns

Marketing campaigns.

GET : /api/bot/campaigns | **GET** : /api/bot/campaigns/{id} | Date column: **createdAt** | 22 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	brand	O	String	
	stage	M	Enum CampaignStage	Enum: PLANNING, IN_PRODUCTION, APPROVAL, LIVE, COMPLETED
	objective	O	String	
	targetResult	O	String	
	promise	O	String	
	offer	O	String	
	startDate	O	DateTime	
	endDate	O	DateTime	
	plannedBudget	O	Float	
	ownerName	O	String	
	audienceSegments	O	Json	
	markets	O	Json	
	masterLanguage	O	String	
	additionalLanguages	O	Json	
	exclusions	O	Json	
	utmSlug	O	String	
	createdByUserId	O	String	Reference id
	createdByName	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

5.7.2 email-campaigns

Email campaigns & stats.

GET : /api/bot/email-campaigns | **GET** : /api/bot/email-campaigns/{id} | Date column: **createdAt** | 21 columns

	Field Name	Attrib.	Type	Comment
Response record (data)				
	id	M	String	Primary key
	name	M	String	
	subject	M	String	
	previewText	O	String	
	fromEmail	M	String	
	fromName	O	String	
	templateId	O	String	Reference id
	blocksJson	M	Json	

	Field Name	Attrib.	Type	Comment
	bodyHtml	M	String	
	status	M	Enum CampaignStatus	Enum: DRAFT, SCHEDULED, SENDING, PAUSED, SENT, FAILED, CANCELED
	audienceSources	M	Json	
	scheduledAt	O	DateTime	
	sentAt	O	DateTime	
	totalRecipients	M	Int	
	sentCount	M	Int	
	failedCount	M	Int	
	errorMessage	O	String	
	createdByUserId	O	String	Reference id
	createdByName	O	String	
	createdAt	M	DateTime	Date column (from/to)
	updatedAt	M	DateTime	

CHAPTER 6

DATA ACCESS RESTRICTIONS

6.1 Modules Not Exposed

The following ERP data is unreachable through this API, by design. No parameter, filter or id can reach it.

Area	Detail
HR & Payroll	Employees, payslips, salaries, payroll totals, attendance, leave, recruitment, separation
Salary expenses	Expense rows mentioning salary / gaji / payroll / wage / upah / bonus
User accounts	ERP users, roles, permissions, login sessions
System settings	Integrations, API credentials, tenant configuration
Communications	WhatsApp, Instagram and email conversations (may contain passport scans)
Relations	Nested related records are never embedded; only scalar columns of the requested resource

6.2 Columns Always Removed

On every resource, any column whose name matches the rules below is removed from the response and cannot be used as a filter. The same rules are applied again to keys nested inside JSON columns.

Rule	Matches (case-insensitive)
Credentials	password, token, secret, apikey, pinhash, hash
Identity documents	passport, nikpassport, niksnap, npwp, bpjs
Personal / medical	medical, health, religion, marital, dateofbirth, birthdate, placeofbirth, emergencycontact, personalemail
Bank / payment	accountnumber, idraccount, usdaccount, swift, iban, cardnumber, cvv, proof
Compensation	salary
Signatures	signature
Stored files (suffix)	...file, ...files, ...filename, ...key, ...keys, ...image, ...attachments
Per resource	customers.address, agent-contacts.address, crew.phone, crew.email, payments.paymentLink, payments.changeProofUrl, agents.portalPasswordSetById

CHAPTER 7

APPENDIX

A. API Key Format

- Key = **"sbk_" + random string** (recommended: 48 hex characters, e.g. **sbk_$(openssl rand -hex 24)**).
- The key is configured on the ERP server, not stored in the database. The server compares the presented key with its configured key in constant time.
- The key carries no information itself; which account it acts as is decided by the server configuration below.

Server Configuration (.env)

Variable	Attrib.	Comment
BOT_API_KEY	M	The API key value, must start with sbk_. Unset = API key access disabled
BOT_API_KEY_USER	M	Email of an ERP user with role BOT. The key authenticates as this user
BOT_API_KEY_TENANT	O	Company (tenant) slug the key reads. Default: samara

B. Issuing, Rotating and Revoking the Key

Action	How	Effect
Issue / rotate	Generate a new sbk_ value, set it as **BOT_API_KEY** in the server .env, restart the ERP	The new key works; the previous key stops working immediately
Revoke	Remove **BOT_API_KEY** from .env and restart	All API key access disabled (session login of the BOT user unaffected)
Suspend	Deactivate the BOT user, change its role, or delete it	Key rejected (401) while the user is inactive / not BOT
Switch account	Change **BOT_API_KEY_USER** to another BOT user and restart	Same key, now acting as the other BOT user

C. Client Examples

cURL

```
curl -s -H "Authorization: Bearer $ERP_BOT_KEY" \
  "https://{erp-domain}/api/bot/bookings?from=2026-01-01&to=2026-12-31T23:59:59Z&limit=500"
```

Python - fetch all pages

```
import os, requests

BASE = "https://{erp-domain}/api/bot"
HEADERS = {"Authorization": f"Bearer {os.environ['ERP_BOT_KEY']}"}

def fetch_all(resource, **params):
    params = {"limit": 500, **params}
    rows = []
    while True:
        r = requests.get(f"{BASE}/{resource}", headers=HEADERS, params=params, timeout=60)
        r.raise_for_status()
        body = r.json()
        rows += body["data"]
        if not body["nextCursor"]:
            return rows
        params["cursor"] = body["nextCursor"]

payments = fetch_all("payments", **{"from": "2026-01-01", "status": "PAID"})
```

JavaScript (Node 18+) - fetch all pages

```
const BASE = 'https://{erp-domain}/api/bot'
const headers = { Authorization: `Bearer ${process.env.ERP_BOT_KEY}` }

async function fetchAll(resource, params = {}) {
  const q = new URLSearchParams({ limit: '500', ...params })
  const rows = []
  for (;;) {
    const res = await fetch(`${BASE}/${resource}?${q}`, { headers })
    if (!res.ok) throw new Error(`${res.status} ${(await res.json()).error}`)
    const body = await res.json()
    rows.push(...body.data)
    if (!body.nextCursor) return rows
    q.set('cursor', body.nextCursor)
  }
}
```