

[Striver's DSA
Sheets](#)[Striver's DSA
Playlists](#)[System
Design](#)[CS
Subjects](#)[Interview Prep
Sheets](#)[Striver's CP
Sheet](#)

August 7, 2022 • Graph

Search

 Search

Breadth First Search (BFS): Level Order Traversal


Problem Statement: Given an undirected graph, return a vector of all nodes by traversing the graph using breadth-first search (BFS).

Pre-req: Graph Representation, Queue STL

Examples:

Example 1:

Input:



Output: 1 2 5 3 4

Example 2:

Input:

Latest Video on
takeUforward



L2...



Latest Video on
Striver




I L...



The Easier Life

Air Conditioner
for all families

1.0 TON | 1.5 TON



Solution

Disclaimer: Don't jump directly to the solution, try it out yourself first.

Approach:

Initial Configuration:

- Queue data structure: follows FIFO, and will always contain the starting.
 - Visited array: an array initialized to 0
1. In BFS, we start with a "starting" node, mark it as visited, and push it into the queue data structure.
 2. In every iteration, we pop out the node 'v' and put it in the solution vector, as we are traversing this node.
 3. All the unvisited adjacent nodes from 'v' are visited next and are pushed into the queue. The list of adjacent neighbors of the node can be accessed from the adjacency list.
 4. Repeat steps 2 and 3 until the queue becomes empty, and this way you can easily traverse all the nodes in the graph.

In this way, all the nodes are traversed in a breadthwise manner.

Recent Posts

[Print Nodes at Distance K in a Binary Tree](#)


[LCA in Binary Search Tree](#)

[Check if a tree is a Binary Search Tree or Binary Tree](#)

[Delete a Node in Binary Search Tree](#)


[Insert a Given Node in Binary Search Tree](#)





0	→	{ }
1	→	{ 2, 5 }
2	→	{ 1, 5, 3 }
3	→	{ 2, 4, 5 }
4	→	{ 3, 5 }
5	→	{ 1, 2, 3, 4 }

Adjacency List



0	1	2	3	4	5
0	0	0	0	0	0

Visited Array

Queue

Code:

C++ Code

```
#include <bits/stdc++.h>
using namespace std;

class Solution {
public:
    // Function to return Breadth First Traversal of the graph
    vector<int> bfsOfGraph(int V, vector<int> adj[]) {
        int vis[V] = {0};
        vis[0] = 1;
        queue<int> q;
        // push the initial starting node
        q.push(0);
        vector<int> bfs;
        // iterate till the queue is empty
        while(!q.empty()) {
            // get the topmost element in the queue
            int node = q.front();
            q.pop();
            bfs.push_back(node);
            // traverse for all its neighbours
            for(auto it : adj[node]) {
                // if the neighbour has not been visited
```

```

        }
    }
    return bfs;
}
};

void addEdge(vector <int> adj[], int u, int v) {
    adj[u].push_back(v);
    adj[v].push_back(u);
}

void printAns(vector <int> &ans) {
    for (int i = 0; i < ans.size(); i++) {
        cout << ans[i] << " ";
    }
}

int main()
{
    vector <int> adj[6];

    addEdge(adj, 0, 1);
    addEdge(adj, 1, 2);
    addEdge(adj, 1, 3);
    addEdge(adj, 0, 4);

    Solution obj;
    vector <int> ans = obj.bfsOfGraph(5, adj);
    printAns(ans);

    return 0;
}

```

Output: 0 1 4 2 3

Time Complexity: $O(N) + O(2E)$, Where N = Nodes, $2E$ is for total degrees as we traverse all adjacent nodes.

Space Complexity: $O(3N) \sim O(N)$, Space for queue data structure visited array and an adjacency list

Java Code

```

import java.util.*;
class Solution {

```

```

Queue < Integer > q = new LinkedList<Integer>();

q.add(0);
vis[0] = true;

while (!q.isEmpty()) {
    Integer node = q.poll();
    bfs.add(node);

    // Get all adjacent vertices of the node
    // If a adjacent has not been visited
    // visited and enqueue it
    for (Integer it: adj.get(node)) {
        if (vis[it] == false) {
            vis[it] = true;
            q.add(it);
        }
    }
}

return bfs;
}

public static void main(String args[]) {
    ArrayList<ArrayList<Integer>> adj = new ArrayList<>();
    for (int i = 0; i < 5; i++) {
        adj.add(new ArrayList<>());
    }
    adj.get(0).add(1);
    adj.get(1).add(0);
    adj.get(0).add(4);
    adj.get(4).add(0);
    adj.get(1).add(2);
    adj.get(2).add(1);
    adj.get(1).add(3);
    adj.get(3).add(1);

    Solution sl = new Solution();
    ArrayList<Integer> ans = sl.bfsOfGraph(5, adj);
    int n = ans.size();
    for(int i = 0; i < n; i++) {
        System.out.print(ans.get(i) + " ");
    }
}
}

```



Space Complexity: $O(3N) \sim O(N)$, Space for queue data structure visited array and an adjacency list

Special thanks to [Vanshika Singh Gour](#) for contributing to this article on takeUforward. If you also wish to share your knowledge with the takeUforward fam, [please check out this article](#). If you want to suggest any improvement/correction in this article please mail us at write4tuf@gmail.com

G-5. Breadth-First Search (BFS) | C++ and ...



« Previous Post

Connected Components in Graphs

Next Post »

Depth First Search (DFS)

Load Comments



The best place to learn data structures, algorithms, most asked coding interview questions, real interview experiences free of cost.

Follow Us



[DSA Playlist](#)

[DSA Sheets](#)

[Contribute](#)



Copyright © 2023 takeuforward | All rights reserved

