

# SECD2523 – DATABASE

# **SEMESTER 1/20232024**

# **SECTION 10**

**LAB 4: DML 3 PART 1** 

**NAME: LIM XIAO XUAN** 

MATRIC NO: A22EC0071

LECTURER: DR. ROZILAWATI BINTI DOLLAH@MD.ZAIN



# **Database Design Project**

# **Oracle Baseball League Store Database**

# **Project Scenario:**

You are a small consulting company specializing in database development. You have just been awarded the contract to develop a data model for a database application system for a small retail store called Oracle Baseball League (OBL).

The Oracle Baseball League store serves the entire surrounding community selling baseball kit. The OBL has two types of customer, there are individuals who purchase items like balls, cleats, gloves, shirts, screen printed t-shirts, and shorts. Additionally customers can represent a team when they purchase uniforms and equipment on behalf of the team.

Teams and individual customers are free to purchase any item from the inventory list, but teams get a discount on the list price depending on the number of players. When a customer places an order we record the order items for that order in our database.

OBL has a team of three sales representatives that officially only call on teams but have been known to handle individual customer complaints.

# **Section 6 Lesson 9 Exercise 1: Joining Tables Using JOIN**

# Write SELECT Statements Using Data From Multiple Tables Using Equijoins and Non-Equijoins (S6L9 Objective 1)

In this exercise you will write SELECT statements to access data from more than one table.

## Part 1: Creating Natural Joins.

1. Display all of the information about sales representatives and their addresses using a natural join.

SELECT \*
FROM sales\_representatives
NATURAL JOIN sales\_rep\_addresses;

ID	EMAIL	FIRST_NAME	LAST_NAME	PHONE_NUMBER	COMMISSION_RATE	SUPERVISOR_ID	ADDRESS_LINE_1	ADDRESS_LINE_2	СІТУ	ZIP_CODE
sr01	chray@obl.com	Charles	Raymond	0134598761	10	sr01	12 Cherry Lane	Denton	Detroit	DT48211
sr02	vwright@obl.com	Victoria	Wright	0134598762		sr01	87 Blossom Hill	Uptown	Detroit	DT52314
sr03	bspeed@obl.com	Barry	Speed	0134598763		sr01	12 Junction Row	Skinflats	Detroit	DT52564

2. Adapt the query from the previous question to only show the id, first name, last name, address line 1, address line 2, city, email and phone\_number for the sales representatives.

SELECT id, first\_name, last\_name, address\_line\_1, address\_line\_2, city, email, phone\_number FROM sales\_representatives NATURAL JOIN sales\_rep\_addresses a;

ID	FIRST_NAME	LAST_NAME	ADDRESS_LINE_1	ADDRESS_LINE_2	СІТУ	EMAIL	PHONE_NUMBER
sr01	Charles	Raymond	12 Cherry Lane	Denton	Detroit	chray@obl.com	0134598761
sr02	Victoria	Wright	87 Blossom Hill	Uptown	Detroit	vwright@obl.com	0134598762
sr03	Barry	Speed	12 Junction Row	Skinflats	Detroit	bspeed@obl.com	0134598763

## Part 2: Creating Joins with the USING Clause

1. Adapt the previous query answer to use the USING clause instead of a natural join.

SELECT id, first\_name, last\_name, address\_line\_1, address\_line\_2, city, email, phone\_number FROM sales\_representatives

JOIN sales\_rep\_addresses USING (id);

ID	FIRST_NAME	LAST_NAME	ADDRESS_LINE_1	ADDRESS_LINE_2	СІТУ	EMAIL	PHONE_NUMBER
sr01	Charles	Raymond	12 Cherry Lane	Denton	Detroit	chray@obl.com	0134598761
sr02	Victoria	Wright	87 Blossom Hill	Uptown	Detroit	vwright@obl.com	0134598762
sr03	Barry	Speed	12 Junction Row	Skinflats	Detroit	bspeed@obl.com	0134598763

2. Display all of the information about items and their price history by joining the items and price\_history tables.

SELECT \*

FROM items

JOIN price\_history ON items.itm\_number = price\_history.itm\_number;

ITM_NUMBER	NAME	DESCRIPTION	CATEGORY	COLOR	Size	ILT_ID	START_DATE	START_TIME	PRICE	END_DATE	END_TIME	ITM_NUMBER
im01101044	gloves	catcher mitt	clothing	brown		i1010230124	17-JUN-17	17-JUN-16	4.99			im01101044
im01101045	under shirt	top worn under the game top	clothing	white		i1010230125	25-NOV-16	25-NOV-16	14.99	25-JAN-17	25-JAN-17	im01101045
im01101045	under shirt	top worn under the game top	clothing	white		i1010230125	25-JAN-17	25-JAN-17	8.99	25-JAN-17	25-JAN-17	im01101045
im01101045	under shirt	top worn under the game top	clothing	white		i1010230125	26-JAN-17	26-JAN-17	15.99			im01101045
im01101046	socks	team socks with emblem	clothing	range		i1010230126	12-FEB-17	12-FEB-17	7.99			im01101046
im01101047	game top	team shirt with emblem	clothing	range		il010230127	25-APR-17	25-APR-17	24.99			im01101047
im01101048	premium bat	high quaity basball bat	equipment			i1010230128	31-MAY-17	31-MAY-17	149	22-DEC-23	22-DEC-23	im01101048
im01101048	premium bat	high quaity basball bat	equipment			i1010230128	22-DEC-23	22-DEC-23	99.99			im01101048

### Part 3: Creating Joins with the ON Clause

1. Use an ON clause to join the customer and sales representative table so that you display the customer number, customer fist name, customer last name, customer phone number, customer email, sales representative id, sales representative first name, sales representative last name and sales representative email. You will need to use a table alias in your answer as both tables have columns with the same name.

```
c.first_name AS "Customer First Name",
c.last_name AS "Customer Last Name",
c.phone_number AS "Customer Phone Number",
c.email AS "Customer Email",
s.id AS "Sales Representative ID",
s.first_name AS "Sales Representative First Name",
s.last_name AS "Sales Representative Last Name",
s.email AS "Sales Representative Email"
```

FROM customers c

JOIN sales\_representatives s ON c.sre\_id = s.id;

CTR_NUMBER	Customer First Name	Customer Last Name	Customer Phone Number	Customer Email	Sales Representative ID	Sales Representative First Name	Sales Representative Last Name	Sales Representative Email
c00001	Robert	Thornberry	01234567898	bob.thornberry@heatmail.com	sr01	Charles	Raymond	chray@obl.com
c00101	John	Doe	03216547808	unknown@here.com	sr01	Charles	Raymond	chray@obl.com
c01986	Maria	Galant	01442736589	margal87@delphiview.com	sr03	Barry	Speed	bspeed@obl.com

### Part 4- Creating Three-Way Joins with the ON Clause

1. Using the answer to Task 3 add a join that will allow the team name that the customer represents to be included in the results.

#### **SELECT**

```
c.ctr_number,
c.first_name AS "Customer First Name",
c.last_name AS "Customer Last Name",
c.phone_number AS "Customer Phone Number",
c.email AS "Customer Email",
s.id AS "Sales Representative ID",
s.first_name AS "Sales Representative First Name",
s.last_name AS "Sales Representative Last Name",
s.email AS "Sales Representative Email",
t.name AS "Team Name"
```

#### FROM customers c

JOIN sales\_representatives s ON c.sre\_id = s.id

# JOIN teams t ON c.tem\_id = t.id;

CTR_NUMBER	Customer First Name	Customer Last Name	Customer Phone Number	Customer Email	Sales Representative ID	Sales Representative First Name	Sales Representative Last Name	Sales Representative Email	Team Name
c00001	Robert	Thornberry	01234567898	bob.thornberry@heatmail.com	sr01	Charles	Raymond	chray@obl.com	Rockets
c00101	John	Doe	03216547808	unknown@here.com	sr01	Charles	Raymond	chray@obl.com	Celtics
c <b>01</b> 986	Maria	Galant	01442736589	margal87@delphiview.com	sr03	Barry	Speed	bspeed@obl.com	Rovers

## Part 5: Applying Additional Conditions to a Join

1. Using the answer to Task 4 add an additional condition to only show the results for the customer that has the number - c00001.

#### **SELECT**

```
c.ctr_number,
c.first_name AS "Customer First Name",
c.last_name AS "Customer Last Name",
c.phone_number AS "Customer Phone Number",
c.email AS "Customer Email",
s.id AS "Sales Representative ID",
s.first_name AS "Sales Representative First Name",
s.last_name AS "Sales Representative Last Name",
s.email AS "Sales Representative Email",
t.name AS "Team Name"

FROM customers c

JOIN sales_representatives s ON c.sre_id = s.id
JOIN teams t ON c.tem_id = t.id
WHERE c.ctr_number = 'c00001';
```

CTR_NUMBER	Customer First Name	Customer Last Name	Customer Phone Number	Customer Email	Sales Representative ID	Sales Representative First Name	Sales Representative Last Name	Sales Representative Email	Team Name
c00001	Robert	Thornberry	01234567898	bob.thornberry@heatmail.com	sr01	Charles	Raymond	chray@obl.com	Rockets

### Part 6: Retrieving Records with Nonequijoins

1. Write a query that will display name and cost of the item with the number im01101045 on the 12<sup>th</sup> of December 2016. The output of the query should look like this:

The cost of the under shirt on this day was 14.99

SELECT 'The cost of the ' || i.name || ' on this day was ' || ph.price AS output FROM items i

LEFT JOIN price\_history ph ON i.itm\_number = ph.itm\_number

WHERE i.itm\_number = 'im01101045'

AND TO\_DATE('12-Dec-2016', 'DD-Mon-YYYY') BETWEEN ph.start\_date AND NVL(ph.end\_date, TO\_DATE('31-Dec-9999', 'DD-Mon-YYYY'));

OUTPUT

The cost of the under shirt on this day was 14.99

 $Copyright \, @\,\, 2020, Oracle\, and/or\, its\, affiliates.\, All\, rights\, reserved.\, Oracle\, and\, Java\, are\, registered\, trademarks\, of\, Oracle\, and/or\, its\, affiliates.\, Other\, names\, may\, be\, trademarks\, of\, their\, respective\, owners.\, The contraction of their respective owners.\, The contraction of the contraction o$