DML Part 1

Part 1

- There is no error occurs when running

Part 2

(1) INSERT INTO teams (id, name, number_of_players, discount)
VALUES ('t004', 'JETS', '10', '5');

(2) INSERT INTO customers (ctr_number, email, first_name, last_name, phone_number, current_balance, sre_id, tem_id, loyalty_card_member)
VALUES ('CO2001', 'brianrog @ hootech.com', 'Brian', 'Rogers', '01654564898', '-5', 'IC4587', NULL, NULL);

(3) UPDATE customers
SET current_balance = '50'
WHERE ctr_number = 'CO2001';

DML Part 2

Part 1

(1)

| START_DATE | TO_CHAR (START_TIME, 'H24:MI:SS') | PRICE |
|---|---|---|
| 17-JUN-17 | 09:00:00 | 4:99 |
| 25-NOV-16 | 09:00:00 | 14:99 |
| 25-JAN-17 | 17:01:00 | 8.99 |
| 26-JAN-17 | 09:00:00 | 15.99 |
| 12-FEB-17 | 12:30:00 | 7.99 |
| 25-APR-17 | 10:10:10 | 24.99 |
| 31-MAY-17 | 16:35:30 | 14.9 |

| END_DATE | TO_CHAR (END_TIME 'H24:MI') |
|---|---|
| - | - |
| 25-JAN-17 | 17:00 |
| 25-JAN-17 | 19:00 |
| - | - |
| - | - |
| - | - |
| - | - |

(2)  UPDATE price-history
        SET end-date : SYSDATE,
            end-time: SYSDATE.
     WHERE itm_number : 'im 01101048' AND end-time is NULL;

(3)  SELECT start_date, TO-CHAR (start_time, 'HH 24:MI:SS'), price,
     end-date, TO-CHAR (end-time, 'HH24:MI')
     FROM price-history;

| START _DATE | TO - CHAR (START_TIME , 'HH24 : MI : SS') | PRICE |
|---|---|---|
| 17 - JUN - 17 | 09 : 00 : 00 | 4.99 |
| 25 - NOV - 16 | 09 : 00 : 00 | 14.99 |
| 25 - JAN - 17 | 17 : 01 : 00 | 8.99 |
| 26 - JAN - 17 | 09 : 00 : 00 | 15.99 |
| 12 - FEB - 17 | 12 : 30 : 00 | 4.99 |
| 26 - APP - 17 | 10 : 10 : 10 | 24.99 |
| 31 - MAY - 17 | 16 : 35 : 30 | 14.9 |

| END _DATE | TO - CHAR (END_TIME , HH20 : MI) |
|---|---|
| - | - |
| 26 - JAN - 17 | 17 : 00 |
| 25 - JAN - 17 | 19 : 00 |
| - | - |
| - | - |
| - | - |
| 04 - NOV - 23 | 7 : 50 |

(4) INSERT INTO price _history (stort.date , stort _time , price , itm-numbee)
VALUES ( SYSDATE , SYSDATE , 99.99 , 'imollo1048' );