

# Computability

Rasmus Guldberg Pedersen

January 2015

# Turing machines as a model universal computer

Give a formal definition of a Turing Machine. Describe the language accepted by a Turing machine and what it means that a Turing machine is total.

# Turing Machine

$$T = (Q, \Sigma, \Gamma, q_0, \delta)$$

$Q$ , a finite set of states

$\Sigma$ , the input alphabet ( $\Sigma \subseteq \Gamma$ )

$\Gamma$ , the tape alphabet ( $\Delta \notin \Gamma$ )

$q_0$ , the initial state ( $q_0 \in Q$ )

$\delta$ , the transition function

$$\delta : Q \times (\Gamma \cup \{\Delta\}) \rightarrow (Q \cup \{h_a, h_r\}) \times (\Gamma \cup \{\Delta\} \times \{R, L, S\})$$

# Language accepted by a TM

If  $x \in \Sigma$  then  $x$  is accepted by  $T$  if

$$q_0 \Delta x \vdash_T^* wh_a y$$

$L \subseteq \Sigma^*$  is accepted by  $T$  if  $L = L(T)$  where

$$L(T) = \{x \in \Sigma^* \mid x \text{ is accepted by } T\}$$

# Total Turing Machine

A TM that always halts.

# Total Turing Machine

A TM that always halts.

Let  $T$  be a TM that takes a description  $T_1$  of a TM as input.  
 $T$  *accepts* if the  $T_1$  halts, and *rejects* otherwise.

# Total Turing Machine

A TM that always halts.

Let  $T$  be a TM that takes a description  $T_1$  of a TM as input.

$T$  *accepts* if the  $T_1$  halts, and *rejects* otherwise.

$T'$  is an extended  $T_1$  where if  $T_1$  accepts it will loop forever, and if  $T$  rejects it will accept.

# Total Turing Machine

A TM that always halts.

Let  $T$  be a TM that takes a description  $T_1$  of a TM as input.

$T$  *accepts* if the  $T_1$  halts, and *rejects* otherwise.

$T'$  is an extended  $T_1$  where if  $T_1$  accepts it will loop forever, and if  $T$  rejects it will accept.

Feed  $T'$  to  $T$ .



The End

The End