

# AUTOMATIC INSTANCE GENERATION FOR CLASSICAL PLANNING

ÁLVARO TORRALBA, JENDRIK SEIPP AND SILVAN SIEVERS alto@cs.aau.dk, jendrik.seipp@liu.se, silvan.sievers@unibas.ch

## EVALUATION IN CLASSICAL PLANNING

Usually, the evaluation in Planning follows the ICAPS/IPC way:

- Measure coverage.
- Time limit 5 or 30 minutes.
- Memory limit 2-8 GB.
- Use the benchmarks from the International Planning Competition.

Why? Having a standard evaluation setting is beneficial:

- Reproducibility.
- Interpretability.
- Avoid hand picking results.

Benchmarks are an important part of evaluation in Planning

### But... The IPC benckmark set has some flaws

- Different number of instances per domain.
- Instance scaling: On some domains, IPC benchmarks do not show differences between planners even if they exist.

		IPC						
	#	L	D	0				
Grid	5	5	5	5				
Driverlog	20	20	20	20				
Rovers	40	40	40	40				
Snake	20	5	15	12				
Total	85	70	80	77				

Coverage of LAMA (L), DUAL-BFWS(D) and OLCFF (O)

#### AUTOSCALE'21: THE BENCHMARK SET

New set of benchmarks for Optimal and Satisficing Planning:

- Uniform number of instances (30 instances)
- Includes almost all IPC STRIPS domains
- Optimization based on IPC'11, IPC'14 AND IPC'18 planners →Useful to evaluate current and future planners.
- Example of Evaluation using Autoscale'14 (which didn't use IPC'18 planners):

		<u>IP</u>	C		Autoscale				
	#	L	D	0	#	L	D	0	
Grid	5	5	5	5	30	17	14	16	
Driverlog	20	20	20	20	30	15	10	25	
Rovers	40	40	40	40	30	30	23	28	
Snake	20	5	15	12	30	6	19	16	
Total	85	70	80	77	120	68	66	85	

Coverage of LAMA (L), DUAL-BFWS(D) and OLCFF (O)

## AUTOSCALE: AN AUTOMATIC TOOL TO SELECT INSTANCES


## **Principles:**

- Useful to evaluate current planners.
- Avoid bias.
- Keep the Spirit of the Domain.


## **Rules:**

1. Agnostic to individual Planner Performance:

Don't consider the individual results of all planners available for the optimization (only the best and the worst per instance).



- 2. Smooth Scaling: The instance set should have:
  - Easy instances
- Hard instances
- Scale smoothly



- 3. Parameter-based Selection: Avoid selecting the ramdom seed.
- 4. Sequence-based Selection: The parameter configurations can be organized in one or more sequences.
- 5. User Constraints: The domain designer specifies guidelines on which parameters to scale.

#### **Optimization Process**

- Generate candidate sequences with smooth scaling (using SMAC)
- Choose sub-sequences including easy, hard and diverse instances

C S I	time(s)	C	S	I	time(s)	C	S	Ι	time(s)	_	C	S	Ι	time(s)
5 6 3	10.1	1	3	2	1.8	1	5	4	4.2		1	3	5	2.8
6 7 3	25.6	1	4	2	2.2	1	6	4	21		1	4	5	3.7
7 8 3	101.7	1	5	2	2.9	1	7	4	62		1	5	5	6.1
9 10 3	300	1	6	2	4.5	1	8	4	250		1	6	5	16
10 11 3	900	1	7	2	8.3	2	10	4	990		1	7	5	62
11 12 3	2700	1	8	2	26	2	11	4	4000		2	9	5	200
13 14 3	8100	1	9	2	120	2	12	4	16000		2	10	5	660

# HOW TO USE AUTOSCALE TO GENERATE INSTANCE SETS?

```
generator_command = "nomystery -1 {locations}
-p {packages} -n {edgefactor} -m {edgeweight}
-c {constrainedness} -s {seed} -e 0"
parameters = [
    LinearParam("locations", lower_b=3, upper_b=10,
    lower_m=0.1, upper_m=1),
    LinearParam("packages",lower_b=2,upper_b=20,lower_m=1),
    ConstantParam("edgefactor", "1.5"),
    ConstantParam("edgeweight", "25"),
    EnumParam("constrainedness", [1.1, 1.5, 2.0])]
```

#### EXPERIMENTS

### How evaluate the quality of a benchmark set?

- Coverage range:
- Some instances are solved by all planners
- No planner solves all instances
- Comparisons: pairs (X,Y) of planners with different coverage

Comparison between Autoscale' 14 and IPC:

- Instance Selection: 6 planners up to IPC'14
- Evaluation: 8 planners from IPC'18

Domain	#IPC	OPT	AGL	Domain	#IPC	OPT	AGL
Barman	34/40	+12	+19	Nomystery	20	+10	+4
Blocksworld	35	+6	+26	Openstacks	70	-17	+25
Childsnack	20	+8	+1	Parking	40	-2	+5
Data-Network	20	-2	+2	Rovers	40	-4	+20
Depots	22	0	+25	Satellite	36	+5	+2
Driverlog	20	+5	+25	Scanalyzer	50	0	+8
Elevators	50	-3	+11	Snake	20	-1	0
Floortile	40	-3	+7	Storage	30	+6	+1
Grid	5	+7	+21	TPP	30	+2	+11
Gripper	20	0	+7	Transport	70	-8	+14
Hiking	20	+4	+3	Visitall	40	0	+17
Logistics	63	-3	+4	Woodworking	50	+5	+14
Miconic	150	0	0	Zenotravel	20	+4	+22
		•	•	•		•	

#### CONCLUSIONS

- 1. A tool to automatically select instances which:
  - Create useful benchmarks
  - Is based on sequences of parameters
  - Avoids bias with respect of the planners used
  - Keeps the spirit of the domain
- 2. Autoscale'21: New benchmark set: TRY IT OUT!

https://github.com/AI-Planning/autoscale https://github.com/AI-Planning/autoscale-benchmarks