


https://rpires71.github.io/milestone1/about-me.html





Values are estimated and may vary. The <u>performance score is calculated</u> directly from these metrics. <u>See calculator.</u>

▲ 0-49 50-89 90-100



METRICS Expand view

First Contentful Paint

2.1 s

Largest Contentful Paint

2.7 s

about:blank 1/27

Total Blocking Time

0 ms

Cumulative Layout Shift

0

Speed Index

2.1 s

View Treemap



Later this year, insights will replace performance audits. Learn more and provide feedback

<u>here</u>.

Try insights

Show audits relevant to: All FCP LCP TBT CLS

DIAGNOSTICS

▲ Properly size images — Est savings of 65 KiB

Serve images that are appropriately-sized to save cellular data and improve load time. Learn how to size images. FCP LCP

Resource Est URL Size Savings GitHub (Utility) 1st Party 125.3 KiB 65.1 KiB ...images/badgev2.webp (rpires71.github.io) 51.0 KiB 18.2 KiB img.img-fluid 37.2 KiB 17.6 KiB images/skills_iconsv4.webp (rpires71.github.io) img.main-illustration.img-fluid

22.40	about.blailk		
	URL	Resource Size	Est Savings
img.section-icon	images/skill_icon2.webp (rpires71.github.io)	11.9 KiB	8.6 KiB
img.logo.logo-navbar	images/logodbg2.webp (rpires71.github.io)	8.6 KiB	8.6 KiB
img.section-icon	images/lifelong_learning_icon2.webp (rpires71 .github.io)	10.8 KiB	7.8 KiB
img.section-icon	images/pro_bio2.webp (rpires71.github.io)	5.8 KiB	4.2 KiB

▲ Eliminate render-blocking resources — Est savings of 970 ms

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. <u>Learn how to eliminate render-blocking resources</u>. FCP LCP

URL	Transfer Size	Est Savings
JSDelivr CDN Cdn	27.1 KiB	1,050 ms
css/bootstrap.min.css (cdn.jsdelivr.net)	27.1 KiB	1,050 ms
Google Fonts Cdn	2.2 KiB	870 ms
/css2?family= (fonts.googleapis.com)	2.2 KiB	870 ms

about:blank 3/27


▲ Reduce unused CSS — Est savings of 26 KiB

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn how to reduce unused CSS. FCP LCP

URL	Transfer Size	Est Savings
JSDelivr CDN Cdn	26.8 KiB	25.8 KiB
css/bootstrap.min.css (cdn.jsdelivr.net)	26.8 KiB	25.8 KiB

▲ Largest Contentful Paint element — 2,700 ms

This is the largest contentful element painted within the viewport. <u>Learn more about the Largest Contentful Paint element</u> [LCP]



Phase	% of LCP	Timing
TTFB	33%	900 ms
Load Delay	0%	0 ms
Load Time	25%	680 ms
Render Delay	42%	1,120 ms

Image elements do not have explicit width and height

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. <u>Learn how to set image</u> <u>dimensions</u> <u>(CLS)</u>

about:blank 4/27

	URL
GitHub Utility 1st Party	
img.logo.logo-navbar	images/logodbg2.webp (rpires71.github.io)
img.main-illustration.img-fluid	images/skills_iconsv4.webp (rpires71.github.io)
img.logo.logo-header.img-fluid	images/badgev2.webp (rpires71.github.io)
img.img-fluid	images/badgev2.webp (rpires71.github.io)
img.section-icon	images/pro_bio2.webp (rpires71.github.io)
img.section-icon	images/skill_icon2.webp (rpires71.github.io)
img.section-icon	images/lifelong_learning_icon2.webp (rpires71.github.io)
img.footer-icon.me-2	icons/award.svg (rpires71.github.io)

	URL
img.footer-icon.me-2	icons/map-pin.svg (rpires71.github.io)
img.footer-icon.me-2	icons/send.svg (rpires71.github.io)
img.footer-icon.me-2	icons/phone.svg (rpires71.github.io)
img.footer-icon.me-2	icons/message-circle.svg (rpires71.github.io)
img.social-icon.me-2	icons/linkedin.svg (rpires71.github.io)
img.social-icon.me-2	icons/facebook.svg (rpires71.github.io)
img.social-icon	icons/instagram.svg (rpires71.github.io)

Minify CSS — Est savings of 5 KiB

Minifying CSS files can reduce network payload sizes. <u>Learn how to minify CSS</u>. FCP <u>LCP</u>

URL	Transfer Size	Est Savings
GitHub Utility 1st Party	7.3 KiB	4.8 KiB
css/style.css (rpires71.github.io)	7.3 KiB	4.8 KiB

Serve static assets with an efficient cache policy $\,-\,$ 15 resources found

A long cache lifetime can speed up repeat visits to your page. Learn more about efficient cache policies.

URL	Cache TTL	Transfer Size
GitHub Utility 1st Party		137 KiB
images/badgev2.webp (rpires71.github.io)	10m	51 KiB
images/skills_iconsv4.webp (rpires71.github.io)	10m	37 KiB
images/skill_icon2.webp (rpires71.github.io)	10m	12 KiB
images/lifelong_learning_icon2.webp (rpires71.github.io)	10m	11 KiB
images/logodbg2.webp (rpires71.github.io)	10m	9 KiB
css/style.css (rpires71.github.io)	10m	7 KiB
images/pro_bio2.webp (rpires71.github.io)	10m	6 KiB
icons/phone.svg (rpires71.github.io)	10m	1 KiB
icons/award.svg (rpires71.github.io)	10m	1 KiB
icons/message-circle.svg (rpires71.github.io)	10m	0 KiB
icons/linkedin.svg (rpires71.github.io)	10m	0 KiB
icons/instagram.svg (rpires71.github.io)	10m	0 KiB
icons/map-pin.svg (rpires71.github.io)	10m	0 KiB

about:blank 7/27

URL	Cache TTL	Transfer Size
icons/facebook.svg (rpires71.github.io)	10m	0 KiB
icons/send.svg (rpires71.github.io)	10m	0 KiB

O Avoid chaining critical requests — 4 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn how to avoid chaining critical requests.

Maximum critical path latency: 1,124.646 ms

Initial Navigation

```
/milestone1/about-me.html (rpires71.github.io)
```

...css/bootstrap.min.css (cdn.jsdelivr.net) - 163.402 ms, 27.11 KiB

...css/style.css (rpires71.github.io)

/css2?family=... (fonts.googleapis.com)

...v43/memvYaGs1....woff2 (fonts.gstatic.com) - 162.372 ms, 42.12 KiB

...v30/JTUSjlg1_....woff2 (fonts.gstatic.com) - 345.764 ms, 34.67 KiB

...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) - 166.613 ms, 22.56 KiB

Minimize third-party usage — Third-party code blocked the main thread for 0 ms

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. <u>Learn how to minimize third-party impact</u>. TBT

Third-Party	Transfer Size	Main-Thread Blocking Time
Google Fonts Cdn	79 KiB	0 ms
v43/memvYaGs1woff2 (fonts.gstatic.com)	42 KiB	0 ms
v30/JTUSjlg1woff2 (fonts.gstatic.com)	35 KiB	0 ms
/css2?family= (fonts.googleapis.com)	2 KiB	0 ms
JSDelivr CDN Cdn	50 KiB	0 ms
css/bootstrap.min.css (cdn.jsdelivr.net)	27 KiB	0 ms
js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	23 KiB	0 ms

Avoid long main-thread tasks — 4 long tasks found

about:blank 8/27

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. <u>Learn how to avoid long main-thread tasks</u> (TBT)

URL	Start Time	Duration
Unattributable		200 ms
Unattributable	1,115 ms	135 ms
Unattributable	1,050 ms	65 ms
GitHub Utility 1st Party		146 ms
/milestone1/about-me.html (rpires71.github.io)	1,313 ms	83 ms
/milestone1/about-me.html (rpires71.github.io)	1,250 ms	63 ms

More information about the performance of your application. These numbers don't <u>directly affect</u> the Performance score.

SSED AUDITS (28)	Hide
Defer offscreen images	^
Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. <u>Learn how to defer offscreen images</u> . FCP LCP	
Minify JavaScript	^
Minifying JavaScript files can reduce payload sizes and script parse time. <u>Learn how to minify JavaScript</u> . FCP <u>LCP</u>	
Reduce unused JavaScript	^
Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network act Learn how to reduce unused JavaScript. FCP LCP	ivity.
Efficiently encode images	^
Optimized images load faster and consume less cellular data. <u>Learn how to efficiently encode images</u> . FCP <u>LCP</u>	
Serve images in next-gen formats	^
Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads less data consumption. <u>Learn more about modern image formats</u> . [FCP] LCP	and

about:blank 9/27

Enable text compression	^
Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. <u>Leadout text compression</u> . <u>FCP</u> <u>LCP</u>	arn more
Preconnect to required origins	^
Consider adding preconnect or dns-prefetch resource hints to establish early connections to important third-part origins. Learn how to preconnect to required origins. LCP FCP	ty
Initial server response time was short — Root document took 160 ms	^
Keep the server response time for the main document short because all other requests depend on it. <u>Learn more about 100 Time to First Byte metric</u> . FCP LCP	out the
URL	Spent
GitHub Utility 1st Party	60 ms
/milestone1/about-me.html (rpires71.github.io)	160 ms
Avoid multiple page redirects	^
Redirects introduce additional delays before the page can be loaded. <u>Learn how to avoid page redirects</u> . <u>LCP</u> <u>FCP</u>	
Use HTTP/2	^
HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn more about HTTP/2. [FCP]	CP
Use video formats for animated content	^
Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. Learn more about efficient video formats (FCP)	CP)
Remove duplicate modules in JavaScript bundles	^
Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activit LCP	cy. FCP
Avoid serving legacy JavaScript to modern browsers	^
Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for n	nodern

about:blank 10/27

browsers. Consider modifying your JavaScript build process to not transpile <u>Baseline</u> features, unless you know you must

support legacy browsers. Learn why most sites can deploy ES6+ code without transpiling FCP LCP

Preload Largest Contentful Paint image

If the LCP element is dynamically added to the page, you should preload the image in order to improve LCP. Learn more about preloading LCP elements. [LCP]

Avoids enormous network payloads — Total size was 272 KiB

✓ Show 3rd-party resources (4)

Large network payloads cost users real money and are highly correlated with long load times. Learn how to reduce payload sizes.

Transfer URL Size GitHub Utility 1st Party 127.6 KiB 51.2 KiB ...images/badgev2.webp (rpires71.github.io) 37.3 KiB ...images/skills_iconsv4.webp (rpires71.github.io) 12.0 KiB ...images/skill_icon2.webp (rpires71.github.io) 11.0 KiB ...images/lifelong_learning_icon2.webp (rpires71.github.io) 8.8 KiB ...images/logodbg2.webp (rpires71.github.io) ...css/style.css (rpires71.github.io) 7.3 KiB Google Fonts [Cdn] 76.8 KiB ...v43/memvYaGs1....woff2 (fonts.gstatic.com) 42.1 KiB ...v30/JTUSjIg1_....woff2 (fonts.gstatic.com) 34.7 KiB JSDelivr CDN [Cdn] 49.7 KiB 27.1 KiB ...css/bootstrap.min.css (cdn.jsdelivr.net) ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) 22.6 KiB

Avoids an excessive DOM size — 121 elements

A large DOM will increase memory usage, cause longer style calculations, and produce costly layout reflows. Learn how to avoid an excessive DOM size. TBT

about:blank 11/27

Statistic	Element	Value
Total DOM Elements		121
Maximum DOM Depth	img.social-icon.me-2	8
Maximum Child Elements	div.footer-tile	10

User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. <u>Learn more about User Timing marks</u>.

JavaScript execution time — 0.0 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. Learn how to reduce Javascript execution time. TBT

URL	Total CPU Time	Script Evaluation	Script Parse
Unattributable	479 ms	14 ms	0 ms
Unattributable	479 ms	14 ms	0 ms
GitHub Utility 1st Party	408 ms	26 ms	4 ms
/milestone1/about-me.html (rpires71.github.io)	408 ms	26 ms	4 ms

Minimizes main-thread work — 1.0 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn how to minimize main-thread work</u> (TBT)

about:blank 12/27

Category	Time Spent
Other	575 ms
Style & Layout	231 ms
Script Evaluation	61 ms
Rendering	52 ms
Parse HTML & CSS	43 ms
Script Parsing & Compilation	19 ms

All text remains visible during webfont loads


Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. <u>Learn more about font-display</u>.

Lazy load third-party resources with facades

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. <u>Learn how to defer third-parties with a facade</u>. (TBT)

Largest Contentful Paint image was not lazily loaded

Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. <u>Learn more about optimal lazy loading.</u> [LCP]



Avoid large layout shifts

These are the largest layout shifts observed on the page. Each table item represents a single layout shift, and shows the element that shifted the most. Below each item are possible root causes that led to the layout shift. Some of these layout shifts may not be included in the CLS metric value due to <u>windowing</u>. <u>Learn how to improve CLS (CLS)</u>

Uses passive listeners to improve scrolling performance

about:blank 13/27

Consider marking your touch and wheel event listeners as passive to improve your page's scroll performance. <u>Learn more about adopting passive event listeners</u>.

Avoids document.write()

^

For users on slow connections, external scripts dynamically injected via document.write() can delay page load by tens of seconds. Learn how to avoid document.write().

Avoid non-composited animations

^

Animations which are not composited can be janky and increase CLS. Learn how to avoid non-composited animations (CLS)

Has a <meta name="viewport"> tag with width or initial-scale

_

A <meta name="viewport"> not only optimizes your app for mobile screen sizes, but also prevents <u>a 300 millisecond delay</u> to user input. Learn more about using the viewport meta tag.

Page didn't prevent back/forward cache restoration

^

Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. Learn more about the bfcache



Accessibility

These checks highlight opportunities to <u>improve the accessibility of your web app</u>. Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so <u>manual testing</u> is also encouraged.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

Interactive controls are keyboard focusable

^

Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn how to make custom controls focusable</u>.

Interactive elements indicate their purpose and state

^

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. Learn how to decorate interactive elements with affordance hints.

about:blank 14/27

O The page has a logical tab order	^
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more about logical tab ordering.</u>	
O Visual order on the page follows DOM order	^
DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more about DOM and visual ordering</u> .	
O User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn how to avoid focus traps</u> .	
O The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn how to direct focus to new content</u> .	
O HTML5 landmark elements are used to improve navigation	^
Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technolo Learn more about landmark elements.</nav></main>	gy.
Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. Learn how to properly hide offscreen content.	
Custom controls have associated labels	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more about custom controls and labels</u> .	
Custom controls have ARIA roles	^
Custom interactive controls have appropriate ARIA roles. <u>Learn how to add roles to custom controls</u> .	
These items address areas which an automated testing tool cannot cover. Learn more in our guide on <u>conducting an accessibility</u> review.	<u>ility</u>
PASSED AUDITS (19)	Hide
[aria-*] attributes match their roles	^

about:blank 15/27

Each ARIA role supports a specific subset of aria-* attributes. Mismatching these invalidates the aria-* attributes. <u>Learn</u> how to match ARIA attributes to their roles.

[aria-hidden="true"] is not present on the document <body>

Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. Learn how aria-hidden affects the document body.

[aria-*] attributes have valid values

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <u>Learn more about valid values</u> for ARIA attributes.

[aria-*] attributes are valid and not misspelled

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. <u>Learn more about valid ARIA attributes</u>.

Buttons have an accessible name

When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. <u>Learn how to make buttons more accessible</u>.

Image elements have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more about the alt attribute</u>.

[user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5.

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. <u>Learn more about the viewport meta tag.</u>

ARIA attributes are used as specified for the element's role

Some ARIA attributes are only allowed on an element under certain conditions. <u>Learn more about conditional ARIA attributes</u>.

[aria-hidden="true"] elements do not contain focusable descendents

Focusable descendents within an [aria-hidden="true"] element prevent those interactive elements from being available to users of assistive technologies like screen readers. <u>Learn how aria-hidden affects focusable elements</u>.

about:blank 16/27

Elements use only permitted ARIA attributes Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. Learn more about prohibited ARIA roles. Background and foreground colors have a sufficient contrast ratio Low-contrast text is difficult or impossible for many users to read. Learn how to provide sufficient color contrast. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more about document titles. <html> element has a [lang] attribute If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more about the lang attribute. <html> element has a valid value for its [lang] attribute Specifying a valid BCP 47 language helps screen readers announce text properly. Learn how to use the lang attribute. Links have a discernible name Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn how to make links accessible. No element has a [tabindex] value greater than 0 A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more about the tabindex attribute. Touch targets have sufficient size and spacing. Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. Learn more about touch targets. Heading elements appear in a sequentially-descending order Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more about heading order.

about:blank 17/27

Image elements do not have [alt] attributes that are redundant text. Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. Learn more about the alt attribute. NOT APPLICABLE (38) Hide [accesskey] values are unique Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more about access keys. Uses ARIA roles only on compatible elements Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. Learn more about ARIA roles. button, link, and menuitem elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to make command elements more accessible. Deprecated ARIA roles were not used Deprecated ARIA roles may not be processed correctly by assistive technology. Learn more about deprecated ARIA roles. Elements with role="dialog" or role="alertdialog" have accessible names. ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. Learn how to make ARIA dialog elements more accessible. ARIA input fields have accessible names When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about input field labels. ARIA meter elements have accessible names When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name meter elements. ARIA progressbar elements have accessible names

about:blank 18/27

When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn how to label progressbar elements</u>.

[role]s have all required [aria-*] attributes Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more about roles and required attributes. Elements with an ARIA [role] that require children to contain a specific [role] have all required children. Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more about roles and required children elements. O [role]s are contained by their required parent element Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more about ARIA roles and required parent element. [role] values are valid ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more about valid ARIA roles. Elements with the role=text attribute do not have focusable descendents. Adding role=text around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. Learn more about the role=text attribute. ARIA toggle fields have accessible names When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about toggle fields. ARIA tooltip elements have accessible names When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name tooltip elements. ARIA treeitem elements have accessible names When a treeitem element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about labeling treeitem elements. The page contains a heading, skip link, or landmark region

about:blank 19/27

<u>DIOCKS.</u>	
O <dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements.</td><td>^</td></tr><tr><td>When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. <u>Learn horstructure definition lists correctly</u>.</td><td><u>w to</u></td></tr><tr><td>O Definition list items are wrapped in <d1> elements</td><td>^</td></tr><tr><td>Definition list items (<dt> and <dd>) must be wrapped in a parent <dl> element to ensure that screen readers can proportion announce them. Learn how to structure definition lists correctly.</td><td>erly</td></tr><tr><td>O ARIA IDs are unique</td><td>^</td></tr><tr><td>The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. <u>Lea</u> how to fix duplicate ARIA IDs.</td><td><u>arn</u></td></tr><tr><td>O No form fields have multiple labels</td><td>^</td></tr><tr><td>Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use eithe first, the last, or all of the labels. <u>Learn how to use form labels</u>.</td><td>ther</td></tr><tr><td>O <frame> Or <iframe> elements have a title</td><td>^</td></tr><tr><td>Screen reader users rely on frame titles to describe the contents of frames. Learn more about frame titles.</td><td></td></tr><tr><td>O <html> element has an [xml:lang] attribute with the same base language as the [lang] attribute.</td><td>^</td></tr><tr><td>If the webpage does not specify a consistent language, then the screen reader might not announce the page's text corrected the language attribute.</td><td>ectly.</td></tr><tr><td>O Input buttons have discernible text.</td><td>^</td></tr><tr><td>Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. Learn more about input buttons.</td><td>out</td></tr><tr><td>O <input type="image"> elements have [alt] text</td><td>^</td></tr><tr><td></td><td></td></tr><tr><td>When an image is being used as an <input> button, providing alternative text can help screen reader users understand purpose of the button. Learn about input image alt text.</td><td>the</td></tr></tbody></table></script></dd></dt></dl>	

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more about bypass

about:blank 20/27

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Leaform element labels.	<u>ırn more about</u>
Links are distinguishable without relying on color.	^
Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the users with low vision. Learn how to make links distinguishable.	experience for
O Lists contain only elements and script supporting elements (<script> and <template>).</td><td>^</td></tr><tr><td>Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader our about proper list structure.</td><td>tput. <u>Learn more</u></td></tr><tr><td>O List items () are contained within , or <menu> parent elements</td><td>^</td></tr><tr><td>Screen readers require list items () to be contained within a parent , or <menu> to be annou Learn more about proper list structure.</td><td>inced properly.</td></tr><tr><td>The document does not use <meta http-equiv="refresh"></td><td>^</td></tr><tr><td>Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the p create a frustrating or confusing experience. <u>Learn more about the refresh meta tag</u>.</td><td>age. This may</td></tr><tr><td>O <object> elements have alternate text</td><td>^</td></tr><tr><td>Screen readers cannot translate non-text content. Adding alternate text to <object> elements helps scree meaning to users. Learn more about alt text for object elements.</td><td>n readers convey</td></tr><tr><td> Select elements have associated label elements. </td><td>^</td></tr><tr><td>Form elements without effective labels can create frustrating experiences for screen reader users. <u>Learn mosselect element</u>.</td><td>ore about the</td></tr><tr><td> Skip links are focusable. </td><td>^</td></tr><tr><td>Including a skip link can help users skip to the main content to save time. <u>Learn more about skip links</u>.</td><td></td></tr><tr><td> Tables have different content in the summary attribute and <caption>. </td><td>^</td></tr><tr><td>The summary attribute should describe the table structure, while <caption> should have the onscreen title mark-up helps users of screen readers. Learn more about summary and caption.</td><td>e. Accurate table</td></tr><tr><td> Cells in a element that use the [headers] attribute refer to table cells within the same table. </td><td>^</td></tr></tbody></table></script>	

about:blank 21/27

Screen readers have features to make navigating tables easier. Ensuring cells using the [headers] attribute only refer to other cells in the same table may improve the experience for screen reader users. <u>Learn more about the headers</u> attribute.

elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more about table headers</u>.

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn how to use the lang attribute</u>.

video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. <u>Learn more about video captions</u>.



Best Practices

TRUST AND SAFETY

Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. <u>Learn how to use a CSP to prevent XSS</u>

Description	Directive	Severity
No CSP found in enforcement mode		High

Use a strong HSTS policy

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. <u>Learn more about using a strong HSTS policy.</u>

about:blank 22/27

Description	Directive	Severity
No HSTS header found		High
Ensure proper origin isolat	tion with COOP	^
The Cross-Origin-Opener-Po ups. <u>Learn more about deplo</u>	olicy (COOP) can be used to isolate the top-level was bying the COOP header.	vindow from other documents such as pop-
Description	Directive	Severity
No COOP header found		High
Mitigate clickjacking with X	XFO or CSP	^
control where a page can be	n) header or the frame-ancestors directive in the embedded. These can mitigate clickjacking attacking about mitigating clickjacking.	
Description		Severity
No frame control policy fo	bund	High
	bund	High Hide
No frame control policy for PASSED AUDITS (15) Uses HTTPS	bund	
PASSED AUDITS (15) Uses HTTPS All sites should be protected where some resources are lo from tampering with or pass	I with HTTPS, even ones that don't handle sensitive baded over HTTP despite the initial request being sively listening in on the communications between the platform APIs. Learn more about HTTPS.	Hide A Te data. This includes avoiding mixed content, served over HTTPS. HTTPS prevents intruders
PASSED AUDITS (15) Uses HTTPS All sites should be protected where some resources are lo from tampering with or pass	I with HTTPS, even ones that don't handle sensitive aded over HTTP despite the initial request being sively listening in on the communications between	Hide A Te data. This includes avoiding mixed content, served over HTTPS. HTTPS prevents intruders
PASSED AUDITS (15) Uses HTTPS All sites should be protected where some resources are lo from tampering with or pass for HTTP/2 and many new work. Avoids deprecated APIs	I with HTTPS, even ones that don't handle sensitive aded over HTTP despite the initial request being sively listening in on the communications between	Hide re data. This includes avoiding mixed content, served over HTTPS. HTTPS prevents intruders a your app and your users, and is a prerequisite
PASSED AUDITS (15) Uses HTTPS All sites should be protected where some resources are lo from tampering with or pass for HTTP/2 and many new work. Avoids deprecated APIs	I with HTTPS, even ones that don't handle sensitive baded over HTTP despite the initial request being solvely listening in on the communications between the platform APIs. Learn more about HTTPS.	Hide re data. This includes avoiding mixed content, served over HTTPS. HTTPS prevents intruders a your app and your users, and is a prerequisite
PASSED AUDITS (15) Uses HTTPS All sites should be protected where some resources are lo from tampering with or pass for HTTP/2 and many new with the control of the contr	I with HTTPS, even ones that don't handle sensitive baded over HTTP despite the initial request being solvely listening in on the communications between the platform APIs. Learn more about HTTPS.	Hide de data. This includes avoiding mixed content, served over HTTPS. HTTPS prevents intruders a your app and your users, and is a prerequisite doubt deprecated APIs.

about:blank 23/27

Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. <u>Learn more about user-friendly input fields</u>.

Avoids requesting the geolocation permission on page load

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission.

Avoids requesting the notification permission on page load

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. <u>Learn more about responsibly getting permission for notifications</u>.

Displays images with correct aspect ratio

Image display dimensions should match natural aspect ratio. Learn more about image aspect ratio.

Serves images with appropriate resolution

Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. <u>Learn how to provide responsive images</u>.

Has a <meta name="viewport"> tag with width or initial-scale

A <meta name="viewport"> not only optimizes your app for mobile screen sizes, but also prevents a 300 millisecond delay to user input. Learn more about using the viewport meta tag.

Document uses legible font sizes — 100% legible text

Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text $\ge 12px$. Learn more about legible font sizes.

Source	Selector	% of Page Text	Font Size
Legible text		100.00%	≥ 12px

Page has the HTML doctype

Specifying a doctype prevents the browser from switching to quirks-mode. Learn more about the doctype declaration.

Properly defines charset

A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. <u>Learn more about declaring the character encoding</u>.

about:blank 24/27

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more about this errors in console diagnostic audit

No issues in the Issues panel in Chrome Devtools

Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. <u>Learn more about source maps</u>.

URL

JSDelivr CDN Cdn

...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)

...js/bootstrap.bundle.min.js.map (cdn.jsdelivr.net)

NOT APPLICABLE (2)

Redirects HTTP traffic to HTTPS

Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. Learn more.

Detected JavaScript libraries

All front-end JavaScript libraries detected on the page. Learn more about this JavaScript library detection diagnostic audit.



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not

about:blank 25/27

score here that may affect your search ranking, including performance on Core Web Vitals. Learn more about Google Search Essentials.

ADDITIONAL ITEMS TO MANUALLY CHECK (1)	Hide
O Structured data is valid	^
Run the <u>Structured Data Testing Tool</u> and the <u>Structured Data Linter</u> to validate structured data. <u>Learn more about Data.</u>	: Structured
Run these additional validators on your site to check additional SEO best practices.	
PASSED AUDITS (8)	Hide
Page isn't blocked from indexing	^
Search engines are unable to include your pages in search results if they don't have permission to crawl them. <u>Leadout crawler directives</u> .	arn more
Document has a <title> element</td><td>^</td></tr><tr><td>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determin is relevant to their search. Learn more about document titles.</td><td>e if a page</td></tr><tr><td>Document has a meta description</td><td>^</td></tr><tr><td>Meta descriptions may be included in search results to concisely summarize page content. <u>Learn more about the description</u>.</td><td><u>meta</u></td></tr><tr><td>Page has successful HTTP status code</td><td>^</td></tr><tr><td>Pages with unsuccessful HTTP status codes may not be indexed properly. <u>Learn more about HTTP status codes</u>.</td><td></td></tr><tr><td>Links have descriptive text</td><td>^</td></tr><tr><td>Descriptive link text helps search engines understand your content. <u>Learn how to make links more accessible</u>.</td><td></td></tr><tr><td>Links are crawlable</td><td>^</td></tr><tr><td>Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor element an appropriate destination, so more pages of the site can be discovered. Learn how to make links crawlable</td><td>ents links to</td></tr><tr><td>Image elements have [alt] attributes</td><td>^</td></tr><tr><td></td><td></td></tr></tbody></table></title>	

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt

about:blank 26/27

attribute. Learn more about the alt attribute.

Document has a valid hreflang

hreflang links tell search engines what version of a page they should list in search results for a given language or region. Learn more about hreflang.

NOT APPLICABLE (2) Hide

o robots.txt is valid

If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. <u>Learn more about robots.txt</u>.

Document has a valid rel=canonical

Canonical links suggest which URL to show in search results. Learn more about canonical links.

Captured at Aug 19, 2025, 10:44 PM GMT Initial page load Emulated Moto G Power with Lighthouse 12.6.1 Slow 4G throttling Single page session

Using Chromium 139.0.0.0 with devtools

Generated by **Lighthouse** 12.6.1 | File an issue

about:blank 27/27