




PLAN VIEW (TOP FACE)

SCALE 1:2 · BOTTOM LANDS OFFSET ½ PITCH



SECTION C–C (PART)

SCALE 2:1 · FACE SHEETS SHOWN PHANTOM



SECTION D–D (PART)

SCALE 2:1 · ON THE CENTRE LAND (x = 0), RUN-OUT FROM y = 150; TOP FLUTES MIRROR IT

NOTES

1. MATERIAL: PA-CF (CARBON-FIBRE-FILLED NYLON), E ≈ 4 GPa, ρ 1.18 g/cm³. DRY THE FILAMENT BEFORE PRINTING.
2. PRINT FLAT, 100 % SOLID: WALL 1.6 = 4 PERIMETERS (0.4 NOZZLE), 0.2 LAYERS. NO SUPPORTS (45° RUN-OUTS).
3. THICKNESS 8 ±0.1. BOTH FACES ARE BOND SURFACES, FLAT WITHIN 0.1.
4. WAVE RIB λ18, WALL 1.6, CENTRE-LINE AMPLITUDE 4; CRESTS CUT FLAT = LANDS 4.25 ON BOTH FACES.
5. FRAME 6, CLOSED. SOLID TO y = 150; EACH FLUTE STARTS WITH A 45° RUN-OUT, 8 LONG (D–D).
6. M4 INSERT BORE Ø5.6 × 10 + Ø4.5 × 16 IN THE BUTT FACE – SEE PB-GR-001.
7. BONDING: ABRADE (P120), DEGREASE, STRUCTURAL EPOXY, FILLET EVERY LAND EDGE.
8. MASS 179 g. 3D MODEL: output/cad/elongated_rib_core.step / .stl. y FROM THE BUTT-CAP BASE (CORE STARTS AT y = 4).

RIB CORE – ELONGATED

RIB CORE · 3D-PRINTED PA-CF · 386 × 200 × 8 mm

DRAWN	DATE	CHECKED	APPROVED
Claude Code	2026-10-23		

DRAWING No.	REV	SHEET	SIZE	SCALE	UNITS
PB-EL-001	B	3 / 3	A3	1:2, 2:1	mm

PROJECTION	MATERIAL	STATUS
	PA-CF (NOTE 1)	ISSUED FOR REVIEW