




FRONT VIEW




SIDE VIEW

LAY-UP 0.3/10/0.3




ISOMETRIC VIEW

SCALE 1:4 (BODY ONLY)



SECTION A–A

SCALE 1:2 · CF 0.3 / WAVE-RIB CORE 10 / CF 0.3 · CORE DETAIL: SHEET 3



SECTION B–B

SCALE 1:1 · REV-8 GRIP, SLOT 16: PB-GR-002

NOTES

1. ALL DIMENSIONS IN MILLIMETRES. DO NOT SCALE THE DRAWING. UNLESS STATED: LINEAR ±0.5, ANGULAR ±0.5°.
2. PROFILE SYMMETRICAL ABOUT THE CENTRE LINE. ALL ARCS TANGENT TO ADJOINING EDGES.
3. SANDWICH: CF FACE SHEET 0.3 + WAVE-RIB CORE 10 + CF FACE SHEET 0.3 = 10.6 ±0.2, UNIFORM OVER BLADE AND HANDLE. BODY (SHEETS + CORE) FROM y = 5 TO THE TIP; GRIP BASE y = 0 … 5.
4. FACE SHEETS (2 OFF, IDENTICAL): WOVEN CARBON/EPOXY 0.3 THK (CURED), CUT TO PB-HY-001_profile.dxf (TEMPLATE: SHEET 2), TRIMMED FLUSH WITH THE CORE EDGE.
5. RIB SUPPORT (CORE): CARBON FIBRE MOULDED IN ONE PIECE IN THE TWO-HALF WAVE MOULD (SHEET 4), CLOSED FRAME 10, WAVE RIB λ22 / WALL 1.6 / LANDS 5.00, SOLID TO y = 150, 45° FLUTE RAMPS – SEE SHEET 3.
6. SKINS BONDED TO THE CORE: EPOXY, ABRADED + PRIMED FACES, PRESSED FLAT BETWEEN PLATENS OR IN A VACUUM BAG.
7. STRENGTH: NOT QUALIFIED BY FEA. HAND CHECK (analysis/hand_check.json, README): THE 0.3 SKINS FAIL A TIP HIT (SKIN BUCKLING BETWEEN THE LANDS, HANDLE SKIN, CORE); 0.6 SKINS PASS.
8. GRIP: PRINTED PLA GRIP (ANY OF THE TEN REV-8 DESIGNS; DRAWN: CARBON MATRIX, 61 g), LOCKED BY A DIN 7984 M3 × 12 SCREW INTO A BONDED M3 INSERT. REV-8 SLOT 16 > HANDLE 10.6: REGENERATE – PB-GR-002.
9. USA PICKLEBALL LIMITS: L + W = 580 ≤ 609.6 (24 in), L = 390 ≤ 431.8 (17 in), INCL. GRIP. AN EDGE GUARD COUNTS TOWARDS THESE LIMITS (MARGIN 29.6).
10. MASS 379 g WITH THE GRIP, BALANCE POINT 201 FROM THE BUTT (FROM THE 3D MODEL).

PICKLEBALL PADDLE – HYBRID

GENERAL ARRANGEMENT · 390 × 190 × 10.6 mm · CF / WAVE-RIB SANDWICH

DRAWN	DATE	CHECKED	APPROVED
Claude Code	2026-11-09		

DRAWING No.	REV	SHEET	SIZE	SCALE	UNITS
PB-HY-001	G	1 / 4	A3	1:2	mm

PROJECTION	MATERIAL	STATUS
	SEE NOTES	ISSUED FOR REVIEW