
02 CELLULAR MOD

Staggered stacked cells; red cells are recessed pockets for swappable inserts.

57.8 g

PLA · 100 % infill · sealed core

✓ LIGHTENED CORE · SLOT + HOLE




3/4 view · rendered from the STL, colours are preview only

AT A GLANCE

Overall height	**135.00 mm**
Max footprint (foot)	**42.63 × 36.61 mm**
Paddle slot	**30.2 × 16.2 mm, 130.0 deep**
Textured band	**z 21.5 – 116.0 mm (94.5 tall)**
Outer size in band (max)	**38.1 × 31.9 mm**
Peak texture height	**3.04 mm above base**
Screw hole (butt)	**Ø 3.5 mm + Ø 6.2 × 3.2 counterbore**
Material volume / surface	**46.64 cm³ / 465 cm²**

WEIGHT · 100 % INFILL



COLOURWAY



#464648 #969692 #C81E22

3MF print palette

PRINT PROFILE

Infill / layer height	**100 % / 0.20 mm**
Layers	**675**
Orientation	**upright, butt end down**
Supports	**none required**
Sealed hollow core	**25.9 cm³, walls ≈ 1.2 mm**
Filament, 1.75 mm	**≈ 19.4 m (100 % flow)**

DESIGN INTENT

A wall of staggered, individually pillowed cells. Roughly one cell in five is recessed as an insert pocket (red in the colourway), sized to take a contrasting insert. No insert parts are included.

Cell edges are chamfered; nothing overhangs beyond 45 degrees.

KEY FEATURES

- 10 rows × 8 staggered cells with 1.4 mm gaps
- Three cell heights give a subtly stepped surface
- About 22% of cells are recessed 0.7 – 1.2 mm as insert pockets


VERIFIED ON THE STL

Paddle slot	**30.2 × 16.2 mm (30 × 16 + 0.2)**
Screw hole + counterbore	**Ø 3.5 mm + Ø 6.2 × 3.2**
Outer envelope vs reference	**+0.000 mm at most**
Outer body / sealed cavity	**1 / 1**
Wall around the cavity (min)	**1.10 mm**
Material under 0.4 mm wide	**0.000 % of volume**
Widest flat bridge	**3.4 mm**

FILES

stl/02_cellular_mod.stl	9.9 MB · 198,210 triangles
3mf/02_cellular_mod.3mf	2.1 MB · colour

✓ SLOT & HOLE VERIFIED ✓ ONE BODY · SEALED CORE ✓ PRINT-READY · 0.20 MM LAYERS ✓ 3MF VALIDATED




TOP VIEW (from +Z)

KEY DIMENSIONS

Overall height	**135.00**
Overall width × depth (foot)	**42.63 × 36.61**
Paddle slot width × depth	**30.20 × 16.20**
Slot depth (floor at z 5.0)	**130.00**
Outer W × D, textured band (max)	**38.14 × 31.89**
Foot top (z 20)	**39.15 × 33.13**
Butt face (z 0)	**40.56 × 34.54**
Peak texture height above base	**3.04**
Screw hole / counterbore	**Ø 3.50 / Ø 6.20 × 3.2**

All values in mm. Dashed lines: paddle slot and screw hole (hidden edges). Renders are the actual STL surface.



A, B, C: see sheet 3

FRONT VIEW (from −Y)

RIGHT VIEW (from +X)

SCALE 1 : 1



PART

CELLULAR MOD

Pickleball paddle grip sleeve, closed butt, open throat

GENERAL NOTES


1. Views are true size: print this sheet at 100 %, do not fit to page.
2. Dimensions are measured from the STL, not nominal.
3. Sealed hollow core, walls ≈ 1.2 mm; head above z 110 is solid.
4. Outer envelope matches the reference PickleballGrip_1.3mf (rim held ≥ 0.8 mm).

SCALE	UNITS	PROJECTION
1 : 1	millimetres	
MATERIAL	**INFILL**	**LAYER HEIGHT**
PLA / PETG / TPU	100 %	0.20 mm
MASS (PLA)	**VOLUME**	**SURFACE AREA**
57.8 g	46.64 cm³	465 cm²
REVISION	**DATE**	**SHEET**
5	2026-10-19	2 of 4

Sections & profiles


True-size cross-sections, how the outer surface and material change with height, and the dimension tables.

SECTION A–A z = 10 mm · foot




Skin offset min 4.51 max 4.52 mm
Area 278 mm² · outer perimeter 128.9 mm

SECTION B–B z = 60 mm · textured band




Skin offset min 1.20 max 1.46 mm
Area 249 mm² · outer perimeter 109.3 mm

SECTION C–C z = 128 mm · rim




Skin offset min 0.79 max 0.80 mm
Area 344 mm² · outer perimeter 105.5 mm

OUTER OFFSET FROM THE REFERENCE OUTLINE VS HEIGHT



MATERIAL CROSS-SECTION AREA VS HEIGHT



OVERALL & SLOT

Overall length (Z)	**135.00 mm**
Overall width (X)	**42.63 mm**
Overall depth (Y)	**36.61 mm**
Slot width × depth	**30.20 × 16.20 mm**
Slot area / perimeter	**489.2 mm² / 92.3 mm**
Slot depth (floor at z 5.0)	**130.00 mm**
Screw hole / counterbore (butt)	**Ø 3.50 / Ø 6.20 × 3.2**
Sealed cavity / min wall	**25.9 cm³ / 1.10 mm**
Outer W × D in band (max)	**38.14 × 31.89 mm**
Material volume / surface	**46.64 cm³ / 464.9 cm²**

ZONES BY HEIGHT

ZONE	Z FROM	Z TO	HEIGHT
Solid floor (butt)	0.0	5.0	**5.0**
Flared foot	0.0	20.0	**20.0**
Smooth collar	20.0	21.5	**1.5**
Textured band	21.5	116.0	**94.5**
Smooth neck (taper)	116.0	125.6	**9.6**
Rim (flat top, slot opening)	125.6	135.00	**9.4**


Relief floor above reference line (design / min)	**1.20 / 1.20 mm**
Min skin at the neck (design / measured)	**0.80 / 0.80 mm**
Peak texture height above base	**3.04 mm**

OUTER DIMENSIONS BY HEIGHT


Z (MM)	OUTER W	OUTER D	PERIMETER	AREA MM²	SKIN MIN	PEAK OFFSET
5.0	42.08	36.06	132.0	684	5.00	5.01
10.0	41.10	35.08	128.9	278	4.51	4.52
20.0	39.11	33.09	122.6	283	3.52	3.52
30.0	35.66	29.57	111.5	277	1.21	1.80
45.0	37.91	31.43	117.0	310	1.21	3.04
60.0	34.96	28.95	109.6	253	1.20	1.46
75.0	37.46	31.66	117.7	303	1.21	3.04
90.0	37.54	31.46	117.3	323	1.21	2.91
105.0	36.98	30.96	115.5	323	1.21	2.64
116.0	36.16	30.14	113.4	481	2.04	2.05
125.0	33.77	27.75	105.8	350	0.85	0.85
132.0	33.66	27.64	105.5	344	0.80	0.80


Views & surface

Four-way turntable, close-ups of the surface, and the unrolled height map with the design parameters.




Four views, 90° apart · rendered from the STL, colours are preview only





UNROLLED SURFACE · HEIGHT ABOVE BASE



DESIGN PARAMETERS

Rows × cells	**10 × 8 (staggered)**
Row pitch	**9.45 mm**
Cell size	**15.31 × 8.05 mm**
Gap between cells	**1.4 mm**
Cell heights	**2.58 / 2.81 / 3.04 mm**
Pocket floor	**1.84 mm above base**
Groove floor	**1.20 mm (base wall)**

PRINT & VERIFICATION

Result: slot & hole / print-ready	**PASS / PASS**
Outer body · genus · sealed cavity	**1 · 1 · 1**
Wall around the cavity (min)	**1.10 mm**
Paddle slot	**30.2 × 16.2 mm**
Envelope over reference	**+0.000 mm**
Material under 0.4 mm wide	**0.000 %**
Widest flat bridge	**3.4 mm**