
06 CARBON MATRIX

Continuous 2/2 twill weave with selective reinforcement patches.

89.5 g

PLA · 100 % infill · solid

✓ SOLID · SLOT + SCREW HOLE



3/4 view · rendered from the STL, colours are preview only

AT A GLANCE

Overall height	**132.82 mm**
Max footprint (foot)	**42.63 × 36.61 mm**
Paddle slot	**30.2 × 16.2 mm, 127.8 deep**
Textured band	**z 21.5 – 116.0 mm (94.5 tall)**
Outer size in band (max)	**37.5 × 31.4 mm**
Peak texture height	**2.73 mm above base**
Screw hole (butt)	**Ø 3.5 mm, through z 0 – 5**
Volume / surface area	**72.21 cm³ / 296 cm²**

WEIGHT · 100 % INFILL

PLA	1.24 g/cm³	**89.5 g**
PETG	1.27 g/cm³	**91.7 g**
TPU	1.21 g/cm³	**87.4 g**
ABS	1.04 g/cm³	**75.1 g**

0 — 120 g

COLOURWAY

#1C1C20 #80848A

3MF print palette

PRINT PROFILE

Infill / layer height	**100 % / 0.20 mm**
Layers	**665**
Orientation	**upright, butt end down**
Supports	**none required**
Filament, 1.75 mm	**≈ 30.0 m (100 % flow)**

DESIGN INTENT

A woven-carbon look built as real geometry: every tow rises over and dives under its neighbours in a 2/2 twill. Smooth, slightly raised patches suggest selective reinforcement where the palm loads the handle.

The weave is the finest texture in the set (0.4 mm relief on a 2 mm pitch).

KEY FEATURES

- 60 tows around, 2.04 mm pitch, 2/2 twill
- Weave relief about 0.4 mm; every tow is a rounded ridge
- Smooth reinforcement patches stand about 0.5 mm above the weave


VERIFIED ON THE STL

Paddle slot	**30.2 × 16.2 mm (30 × 16 + 0.2)**
Screw hole	**Ø 3.5 mm through the butt**
Outer envelope vs reference	**+0.000 mm at most**
Bodies / enclosed voids	**1 / none**
Material under 0.4 mm wide	**0.000 % of volume**
Overhangs / bridges	**none**

FILES

stl/06_carbon_matrix.stl	15.4 MB · 308,248 triangles
3mf/06_carbon_matrix.3mf	3.3 MB · colour

✓ SLOT & HOLE VERIFIED ✓ SOLID · ONE CLOSED BODY ✓ PRINT-READY · 0.20 MM LAYERS ✓ 3MF VALIDATED




TOP VIEW (from +Z)

KEY DIMENSIONS

Overall height	**132.82**
Overall width × depth (foot)	**42.63 × 36.61**
Paddle slot width × depth	**30.20 × 16.20**
Slot depth (floor at z 5.0)	**127.82**
Outer W × D, textured band (max)	**37.46 × 31.45**
Foot top (z 20)	**39.16 × 33.13**
Butt face (z 0)	**40.56 × 34.54**
Peak texture height above base	**2.73**
Screw hole through butt (z 0 – 5)	**Ø 3.50**

All values in mm. Dashed lines: paddle slot and screw hole (hidden edges). Renders are the actual STL surface.



FRONT VIEW (from −Y)

RIGHT VIEW (from +X)

SCALE 1 : 1

0 10 20 30 40 50 mm

PART

CARBON MATRIX

Pickleball paddle grip sleeve, closed butt, open throat

GENERAL NOTES


1. Views are true size: print this sheet at 100 %, do not fit to page.
2. Dimensions are measured from the STL, not nominal.
3. Solid body: only the 30.2 × 16.2 mm paddle slot and the Ø3.5 mm screw hole are open.
4. Outer envelope matches the reference PickleballGrip_1.3mf (rim held ≥ 0.8 mm).

SCALE **1 : 1**	UNITS **millimetres**	PROJECTION
MATERIAL **PLA / PETG / TPU**	INFILL **100 %**	LAYER HEIGHT **0.20 mm**
MASS (PLA) **89.5 g**	VOLUME **72.21 cm³**	SURFACE AREA **296 cm²**
REVISION **3**	DATE **2026-10-17**	SHEET **2 of 4**

Sections & profiles


True-size cross-sections, how the outer surface and material change with height, and the dimension tables.

SECTION A–A z = 10 mm · foot




Skin offset min 4.51 max 4.52 mm
Area 780 mm² · outer perimeter 128.9 mm

SECTION B–B z = 60 mm · textured band




Skin offset min 1.88 max 2.71 mm
Area 491 mm² · outer perimeter 114.4 mm

SECTION C–C z = 128 mm · rim




Skin offset min 0.79 max 0.80 mm
Area 344 mm² · outer perimeter 105.5 mm

OUTER OFFSET FROM THE REFERENCE OUTLINE VS HEIGHT



MATERIAL CROSS-SECTION AREA VS HEIGHT



OVERALL & SLOT

Overall length (Z)	**132.82 mm**
Overall width (X)	**42.63 mm**
Overall depth (Y)	**36.61 mm**
Slot width × depth	**30.20 × 16.20 mm**
Slot area / perimeter	**489.2 mm² / 92.3 mm**
Slot depth (floor at z 5.0)	**127.82 mm**
Screw hole (butt, z 0 – 5)	**Ø 3.50 mm**
Butt face (z 0)	**40.56 × 34.54 mm**
Outer W × D in band (max)	**37.46 × 31.45 mm**
Volume / surface area	**72.21 cm³ / 296.5 cm²**

ZONES BY HEIGHT

ZONE	Z FROM	Z TO	HEIGHT
Solid floor (butt)	0.0	5.0	**5.0**
Flared foot	0.0	20.0	**20.0**
Smooth collar	20.0	21.5	**1.5**
Textured band	21.5	116.0	**94.5**
Smooth neck (taper)	116.0	125.6	**9.6**
Rim (flat top, slot opening)	125.6	132.82	**7.3**


Relief floor above reference line (design / min)	**1.20 / 1.87 mm**
Min skin at the neck (design / measured)	**0.80 / 0.80 mm**
Peak texture height above base	**2.73 mm**

OUTER DIMENSIONS BY HEIGHT


Z (MM)	OUTER W	OUTER D	PERIMETER	AREA MM²	SKIN MIN	PEAK OFFSET
5.0	42.08	36.06	132.0	1,084	5.00	5.01
10.0	41.10	35.08	128.9	780	4.51	4.52
20.0	39.11	33.09	122.6	655	3.52	3.52
30.0	36.88	30.88	114.8	499	1.89	2.71
45.0	37.26	31.01	114.5	499	1.91	2.69
60.0	36.96	30.56	114.5	492	1.88	2.71
75.0	36.88	30.87	114.5	499	1.89	2.69
90.0	36.78	31.08	114.9	500	1.91	2.71
105.0	36.89	30.87	114.7	498	1.88	2.69
116.0	36.21	30.20	113.5	483	2.06	2.08
125.0	33.77	27.75	105.8	350	0.85	0.85
132.0	33.66	27.64	105.5	344	0.79	0.80


Views & surface

Four-way turntable, close-ups of the surface, and the unrolled height map with the design parameters.




Four views, 90° apart · rendered from the STL, colours are preview only





UNROLLED SURFACE · HEIGHT ABOVE BASE



DESIGN PARAMETERS

Tows around	**60 (2/2 twill)**
Tow pitch	**2.04 mm**
Weave heights	**1.7 – 2.2 mm above base**
Patch heights	**2.3 – 2.7 mm above base**
Patch coverage	**about 23% of the band**
Weave / patch colours	**carbon / grey**
Textured band	**94.5 mm tall**

PRINT & VERIFICATION

Result: slot & hole / print-ready	**PASS / PASS**
Bodies · genus	**1 · 1 (screw hole)**
Paddle slot	**30.2 × 16.2 mm**
Envelope over reference	**+0.000 mm**
Material under 0.4 mm wide	**0.000 %**
Overhangs / bridges	**none**