


PER-IMHOTEP

FUTURE'S ARCHITECT



RAREȘ DUNCA DRAGOȘ PETROVAN RADU DINU BOGDAN MIHEȚ ȘERBAN DEACONU

-----Table of contents-----

1.	Executive Summary	3.
2.	Introduction	3.
3.	Population	5.
3.1.	Selection and recruitment	6.
4.	Construction phases	6.
5.	Thrusters	7.
6.	Radiation Protection and Shielding	8.
7.	Shielding system	9.
8.	Materials used	11.
9.	Artificial gravity	13.
10.	Infrastructure	14.
10.1.	Secondary Bases	14.
10.2.	Cryogenic Fuel Production on Titan	15.
10.3.	Resources and Crew	15.
10.4.	Communication	16.
11.	Asteroid Mining	17.
11.1.	Strategic Perspective	18.
12.	Energy	18.
13.	Resource Gathering	20.
14.	Transportation	21.
14.1.	Technological requirements	21.
14.2.	Probabilistic risk assessment	21.
14.3.	Transportation around the settlement	21.
14.4.	Panel transportation	22.
14.5.	Cylinder transportation	23.
15.	Agricultural Production System	25.
15.1.	Robotic Vertical Farming Architecture	25.
15.2.	Performance Metrics	25.
15.3.	Water Conservation Architecture	26.
15.4.	Energy Profile	27.
15.5.	Genetic Engineering Integration	28.
16.	Biosynthesis and Bioprocessing Hub	28.
17.	Microbial Fermenters	29.
18.	Waste Management and Resource Recovery	30.
19.	Air Quality and Atmospheric Regulation	31.
20.	Death Protocol and Mortality Management	32.
21.	Nutrition and Meal Planning	34.
22.	Artificial Hibernation and Torpor Systems	36.
23.	Medical System and Healthcare Infrastructure	37.
24.	Employment and work sectors	38.
25.	Housing	40.
26.	Institutions	42.
27.	Appendix & Bibliography	49.

Executive Summary

Per-Imhotep is a space settlement designed to support **180,000 inhabitants** in orbit around Saturn's moon Titan. The settlement features a central cylindrical spine (300 m radius, 2,200 m height) supporting three toroidal habitation rings (major radius 1,825 m, minor radius 1,625 m, elliptical cross-section with 200 m semi-major and 100 m semi-minor axes) rotating at 0.7 RPM to generate approximately 1g of centrifugal gravity.

Torus T1 and T3 serve as primary habitation zones encompassing residential areas, entertainment, transportation networks, and daily amenities. Torus T2 is dedicated to agriculture and industrial operations. The central spine houses nuclear energy production facilities, while transport side panels (1,900 m tall, 100 m wide) provide inter-torus connectivity for both human and robotic transit.

The settlement's location near Titan offers strategic advantages: access to methane and nitrogen resources from Titan's atmosphere, water ice from Saturn's rings, and proximity to a rich system of moons for mining operations. Per-Imhotep represents a self-sustaining ecosystem engineered to support long-term human life in the outer solar system.

Introduction

Background

12241. 9614. 9. 1

12,241 nuclear warheads worldwide; 9,614 in military stockpiles; 9 principal actors. And just one human habitat, at least so far.

In recent years, the world has been reshaped at its foundations. We were struck by a pandemic; we now contend with a form of artificial intelligence that many perceive as uniquely perilous; and people seem increasingly unable to find peace. Meanwhile, political leaders appear to hold the planet's fate, often from the shadows, in their hands.

At the beginning of 2025, an estimated 12241 nuclear warheads existed globally. They are held by nine states, actors with direct access to, and decisive influence over, today's geopolitical landscape: the United States, Russia, the United Kingdom, France, China, India, Pakistan, North Korea, and Israel. Beyond the warheads themselves, an additional 22 states possess more than 1 kilogram of weapons-usable nuclear material, which, by its very existence, becomes a risk multiplier.

Why now?

For several years we have witnessed deepening geopolitical instability and an ever more visible polarization of the international system. This trajectory aligns ominously with the impending end of New START, the last major agreement that imposed clear, verifiable limits on the strategic arsenals of the world's two largest nuclear powers. Tensions intensified in the post-pandemic period, when inspections and consultations became entangled in political dispute. In this context, Russia restricted certain inspections and was met with U.S. accusations of non-compliance; in response, in February 2023, Russia declared a "suspension of participation", effectively obstructing meaningful transparency.

This strategic impasse does not concern only two countries. It concerns every human being who may be affected by decisions capable of altering the course of history in a single, catastrophic turn. And now we have arrived in 2026, when, this February, the aforementioned treaty is set to expire. Suddenly, no one is truly safe. Not even the human species.

It is the calm before the storm. And we must accept that anything is possible.

Name choice

For this mission, we will travel back 4,500 years, to an ancient companion of humankind. In Egyptian mythology stands a figure at once enigmatic and profound, something between human and deity. Born on the outskirts of the ancient city of Memphis, Imhotep is remembered as a vizier during the reign of Djoser, the second king of Egypt's Third Dynasty. More than a statesman, he is credited as the architect who raised the first pyramid of Ancient Egypt, the Step Pyramid of Saqqara, a work that endured as both symbol and template for the monumental constructions that would come to define Egypt's history as a foundation of human civilization.

Imhotep's legend returns precisely at the moment humanity resolves to open a new epoch. Last year, Eos Bastion embodied our orbital fortress, a first step into the spacefaring future, sheltering a limited number of lives and proving that survival beyond Earth is possible. Now, however, we require an architect, one who can lay the foundations of this new chapter; just as the first pyramid in Ancient Egypt remains astonishing even today, we will establish the groundwork for the first true spatial civilization.

Imhotep's legacy continues to inspire us for another reason as well. After his death, he was elevated to divine status as a god of healing, celebrated for medical insight and discovery, and remembered as the first non-royal figure to be granted such reverence. Perhaps this is what "healing" ultimately signifies: emancipation from absolute power concentrated in the hands of a few, and the re-empowerment of society. It was liberation. It was hope. It was a new beginning.

With this in mind, we will build a space settlement larger in scale than any attempted before. Welcome to Per-Imhotep, a name that, rendered from ancient Egyptian, conveys "the City of Imhotep". A new dimension, guided by the same architectural spirit.

Spaceship's purpose

The spacecraft's primary mission is to safeguard the human species by establishing a new civilization far removed from the political conflicts that increasingly dominate life on Earth. Although our planet has sustained life for millions of years, the current climate of uncertainty cannot be ignored, and we must therefore pursue viable alternatives.

Accordingly, drawing on the observations and lessons learned from Eos Bastion, we have decided to design a fully developed, autonomous, and far more comprehensive city in space. Our objective is to bring the first permanent generation of humans beyond Earth, a population that will settle completely and serve as the foundational pillars of this new community. There, humanity will be protected and able to endure, giving rise to an alternative human civilization.

Population

Given our goal of creating a sustainable habitat comparable to a city on Earth, the number of people embarking on this journey will be 180,000. Although this is far larger than in past missions, we have ensured that living conditions are adequate to support this population, whose roles within onboard life will be clearly defined.

To keep the population stable over time, we must account for demographic factors and maintain a balanced age structure. In what follows, we set the proportion of residents in each age group, based on the importance of each group to the ship's ecosystem.

**Note: the ages shown are the ages of the people upon arrival on the ship*

a) 32400 people (18%) aged 10–14

Children are primarily essential for generational continuity, ensuring that the workforce can be replenished as older cohorts eventually retire. We will not embark families with children under one year of age due to potential medical risks. Children aged 1–5 will undergo careful medical screening to ensure they are clinically healthy and ready for travel.

b) 23400 people (13%) aged 15–24

Although smaller in share, this group is critical because it represents the cohort entering the workforce, first as apprentices during schooling and later as junior professionals. Even without extensive experience, they will form the first core of ship-trained experts, deeply familiar with operational systems and living conditions.

c) 48600 people (27%) aged 25–44

This cohort constitutes the current backbone of the workforce, bringing high energy and strong adaptability to the new environment. It also includes the group most likely to establish families and support long-term population continuity onboard.

d) 57600 people (32%) aged 45–64

This age group offers an optimal combination of experience, operational discipline, risk management capacity, and advanced competencies. They will hold key roles across technical fields, legal affairs, governance, and mentorship programs for younger cohorts.

e) 18000 people (10%) aged 65–75

While they may not match the operational efficiency of younger cohorts, they are invaluable for mentorship, education, and governance due to the expertise accumulated over decades. Their productivity will also be supported by advanced medical systems onboard, enabling longer, healthier lives and extended participation in professional activity.

These proportions may shift slightly over time; however, overall they provide a stable demographic balance. If a significant increase or decrease in birth rates is observed, we will implement programs to encourage or discourage births onboard, without imposing strict limits on the number of children per family.

Selection and recruitment

Selection will closely follow the overarching objective of safeguarding the human species. Our primary priority will be recruiting individuals from regions experiencing severe geopolitical instability, such as wars, civil conflicts, or authoritarian regimes, where populations face the highest risk.

Because capacity is limited and the settlement requires highly specialized skills in vital domains, candidates from these regions will be selected based on demonstrated competences. The selection process will include general psychological and medical screening to confirm the individual's ability to adapt to life in space. This will be followed by a domain-specific assessment, in which the candidate chooses a professional field and must pass an examination tailored to that specialization. Results will then be reviewed and recruitment decisions made based on the spaceship's needs for each role.

Construction phases

Phase 1: Core Spine Assembly: The central cylindrical spine is constructed first, establishing the structural backbone of the settlement. This 2,200 m tall, 300 m radius cylinder houses the nuclear reactors and provides the central axis around which all other components are organized. The spine's structural framework includes mounting points for all subsequent attachments.



Phase 2: Transport Connectors: The side panel transport connectors are installed, extending outward from the spine. These 1,900 m tall, 100 m wide panels will serve as the primary transit corridors between torii, accommodating both human pathways and robotic logistics lanes. Conveyor systems with operational speeds of 2.5-2.8 m/s are integrated during this phase.



Phase 3: Structural Integrity Torii: Smaller structural torii are assembled and attached to the spine framework. These rings serve as the skeletal foundation that will bear the loads of the main habitation tori. They establish the rotational geometry and provide the mounting infrastructure for the full-scale rings.


Phase 4: Structural Integrity and Transport Connectors Integration: The structural torii are connected to the transport panels, creating a unified rigid framework. This integration phase ensures that centrifugal forces from torus rotation are properly distributed through the entire structure. Stress testing and alignment verification occur before proceeding.

Phase 5 — Main Torii Installation: The three primary toroidal habitation rings (T1, T2, T3) are constructed and mounted at 400 m intervals along the spine. Each torus features an elliptical cross-section (200 m × 100 m) and is engineered to rotate at 0.7 RPM. Interior buildout begins: T1 and T3 receive residential and civic infrastructure, while T2 is fitted for agricultural and industrial use.



Thrusters

For our space settlement in orbit around Titan, the “best” thruster is the one that can reliably nudge an enormous mass for decades without bleeding you dry on propellant logistics. That rules out chemical and nuclear-thermal as primary propulsion: they give great thrust, but they’re propellant-hungry, so every correction burn becomes a supply-chain headache. Pure ion thrusters beat Hall thrusters on exhaust velocity, but typically at the cost of lower thrust density for the same practical system complexity, so you need even more hardware to get useful authority. A clustered, megawatt-class Hall-effect electric propulsion system is the sweet spot: high enough exhaust velocity to keep propellant use low (Hall xenon exhaust velocities are commonly in the ~10–20 km/s range), while still producing meaningfully higher thrust than typical gridded ion at comparable power levels, exactly what you want for station-keeping, slow orbit trims, and momentum management in the Saturn–Titan environment.



A Hall-effect thruster basically works by using electricity to throw gas out the back at extremely high speed. We feed in a neutral gas like xenon, then use a magnetic field to trap and spin electrons inside a circular channel. Those electrons smash into the gas atoms and strip electrons off them, turning the gas into positively charged ions (plasma). At the same time, we apply a strong electric field that accelerates those ions straight out of the engine at tens of thousands of meters per second. When that fast stream shoots out the back, the spacecraft gets pushed

forward. Finally, we add some electrons back into the exhaust so everything stays electrically balanced. It doesn’t produce huge thrust like a chemical rocket, but it’s incredibly efficient and can run for years.

Radiation Protection and Shielding

Unlike Earth, which is protected by both a global magnetic field and a dense atmosphere, our space settlement is exposed to galactic cosmic rays (GCRs), solar particle events (SPEs), and energetic particles trapped within Saturn’s magnetosphere. While Titan orbits inside Saturn’s magnetosphere for much of its period, reducing direct solar wind exposure, this protection is incomplete and does not significantly attenuate high-energy cosmic radiation. Long-duration exposure above 100–200 mSv/year increases cancer risk, while acute doses above 2000 mSv can cause radiation sickness. Therefore, continuous passive radiation protection is mandatory for permanent habitation.

Non-ionizing radiation (UV, infrared, radiofrequency) is not a primary structural concern and is easily mitigated by metallic outer layers and multi-layer insulation. The real hazard comes from ionizing radiation: high-energy protons, heavy ions, gamma rays, X-rays, and secondary neutrons generated when cosmic rays interact with shielding materials. Alpha and beta particles are easily stopped by thin material layers, but gamma rays, high-energy protons, and neutron cascades require substantial mass shielding.

Magnetic shielding was evaluated as a primary solution. Although magnetic fields can deflect charged particles, they require extremely high power levels and superconducting infrastructure, introduce failure risks, and are ineffective against neutral radiation and high-energy GCRs. For these reasons, active magnetic shielding is not used as the main protection system. Instead, the settlement relies on a mass-based passive architecture, supplemented by localized protection for extravehicular missions.

For operations outside protected volumes, researchers are equipped with radiation vests made from hydrogen-rich high-density polyethylene (HDPE), which effectively reduces exposure to secondary neutrons and solar protons while maintaining mobility.

Material	Density (kg/m^2)
Regolith (packed / sintered / slag bags)	1500
Water (tanks as an annulus / wall)	1000
HDPE / Polyethylene blocks	940
Borate polyethylene	~1000
Aluminum alloy (pressure hull)	2700

The primary defense must be bulk regolith, packed or sintered to a thickness of roughly 3–4 meters, yielding approximately 450–600 g/cm² areal density, which provides strong protection against solar particle events and significantly reduces cumulative radiation dose. This outer mass layer also doubles as micrometeoroid and debris shielding, meaning radiation protection and impact protection are solved simultaneously. Beneath the regolith, the pressure hull (aluminum alloy, 2–6 cm) provides structural containment but is not relied upon for radiation attenuation. Inside the settlement, inhabited zones are further protected through strategic mass distribution: water reservoirs, agricultural volumes, food storage, and recycled waste blocks are arranged radially to create additional hydrogen-rich shielding, especially around sleeping quarters, hospitals, and schools. These core areas are designed to reach 600–800 g/cm², while distributed storm shelters are

reinforced up to 800–1200 g/cm², incorporating thick regolith overhead, multi-meter water walls, and 20–40 cm of borated polyethylene to absorb secondary neutrons generated by high-energy cosmic interactions. The result is a layered, mass-efficient system that prioritizes protection where humans spend t

Shielding system

The shielding strategy is based on a layered, mass-efficient structure optimized for Titan's environment. The primary protective barrier consists of 3–4 meters of compacted or sintered regolith sourced from icy-rock material within the Saturnian system. With an average density of approximately 1.5 g/cm³, this produces an areal density of 450–600 g/cm². At this thickness, solar particle events are effectively eliminated as a significant hazard, magnetospheric proton flux is strongly attenuated, and cumulative galactic cosmic ray exposure is substantially reduced.

This outer regolith layer performs multiple roles simultaneously: radiation attenuation, micrometeoroid and debris protection, thermal inertia in Titan's cryogenic environment, and structural stabilization. By combining these functions into one mass layer, the design avoids unnecessary structural duplication and reduces overall system complexity.

Beneath the regolith sits a 2–6 cm aluminum alloy pressure hull. This layer provides atmospheric containment and structural load transfer but is not relied upon for radiation attenuation. It serves as the mechanical backbone of the settlement, supporting docking systems, internal framing, and rotational stresses if artificial gravity is implemented.

Because high-energy cosmic rays interacting with regolith produce secondary neutrons, interior protection relies heavily on hydrogen-rich materials. Water reservoirs, hydroponic agricultural modules, food storage compartments, and compacted waste blocks are strategically arranged around high-occupancy zones. This increases effective shielding in core habitation areas to approximately 600–800 g/cm². Hydrogen-rich materials are critical because they efficiently moderate fast neutrons and reduce secondary particle cascades, offering superior biological shielding performance compared to dense metals such as tungsten or nickel.

Localized high-density materials such as tungsten are used selectively in equipment vaults and high-radiation interface zones where gamma attenuation is necessary. However, they are not used as primary hull shielding because high-Z materials increase secondary radiation production when struck by high-energy cosmic rays.

To protect against neutron radiation, 20–40 cm layers of borated polyethylene are integrated into interior structural partitions around sleeping quarters, medical facilities, and emergency shelters. Boron captures thermalized neutrons, significantly reducing biological dose from secondary interactions.

Distributed storm shelters are integrated throughout residential sectors to minimize evacuation time. These shelters achieve 800–1200 g/cm² total shielding by combining additional regolith overhead mass, multi-meter-thick water walls, and borated neutron-capture layers. This configuration ensures near-total protection during extreme solar particle events.

Micrometeoroid protection is achieved through a reinforced Whipple shield system integrated with the regolith shell. An outer bumper layer fragments incoming debris, an intermediate energy-absorbing layer composed of ceramic fabric and high-strength fibers dissipates impact energy, and the inner aluminum structural wall

maintains pressure containment. Real-time structural monitoring using embedded fiber-optic strain sensors and stress-detection systems ensures early detection of damage.

In conclusion, the final shielding system is a layered passive architecture composed of regolith bulk mass, hydrogen-rich interior zoning, neutron-absorbing borated layers, selective high-density reinforcement, and integrated Whipple impact protection. Rather than relying on experimental or energy-intensive solutions, the design prioritizes reliability, redundancy, and intelligent mass distribution. This approach ensures long-term habitability near Titan while maintaining structural feasibility and operational resilience.

Cost bucket	What's included	Basis	Cost range (USD)
Regolith ISRU & emplacement	mining robots, hauling, packing/sintering, anchors/cages, power, spares	handling $\sim 10^{11}$ kg	\$55B
Aluminum pressure hull program	raw Al + forming + welding/joining + leak testing + NDT/QA	1.8×10^9 kg	\$25B – \$35
Whipple debris system	bumper plates, spacing, Nextel/Kevlar layers, assembly & inspection	1.68×10^7 m ²	\$8B – \$12B
Borated polyethylene (localized)	20–40 cm around cores/shelters + install	2.52×10^6 m ²	\$7B – \$12B
Integration & verification	dosimetry mapping, structural validation, acceptance testing	program-level	\$10B – \$15B

Considering the spine and the side panels shielding, which is not included in the table above, the cost for our shield will vary between \$135B to \$145B dollars. This system will ensure our inhabitants safety, creating a unique way of protecting a space settlement from the radiations.

Materials used

Taking into consideration the importance of the space settlement and the unique role it serves, it is essential that it relies on carefully designed, resilient structures that function together as an integrated system. Every component must contribute to maintaining safety, stability, and long-term habitability in an environment that is both remote and inherently hostile. Below, there is a table with several materials that could be used to build the space settlement.

Material	Category	Primary Role	Why it's used	Main Limitations
Titanium alloys (Ti-6Al-4V)	Structural metal	Main load-bearing frame, trusses, docking arms	High strength with low mass; remains tough at very low temperatures; resistant to radiation and fatigue	Expensive; difficult to manufacture and machine
Aluminum-lithium alloys	Structural metal	Pressure shells, secondary panels	Lightweight; easy to weld; proven space use	Lower strength than titanium; weak radiation shielding
Carbon Fiber Reinforced Polymer (CFRP)	Composite	Habitat modules, rotating rings	Extremely strong in tension; very lightweight; good fatigue resistance	Not airtight; needs internal liner; vulnerable to radiation without shielding
Aluminum (liners)	Metal	Internal pressure liners	Airtight; predictable failure behavior	Adds mass; limited radiation protection

Aluminum alloy Al-Li 2219 is best used for habitat module walls, pressure vessel shells, and internal or secondary structural panels. Its low density reduces launch mass, and its tensile strength is sufficient for handling pressure loads. Additionally, its high thermal conductivity helps distribute heat across the habitat. However, its lower fracture toughness makes it unsuitable for high-stress or load-critical components.

After deeper analysis into the materials structures and their roles, we decided we should mainly use Titanium Alloys for the majority of the base structures. The most suitable titanium alloy for space structures is Ti-6Al-4V, an α - β titanium alloy composed of approximately 6% aluminum, 4% vanadium, and 90% titanium. Aluminum stabilizes the α phase, improving strength and oxidation resistance, while vanadium stabilizes the β phase, increasing toughness and ductility. We will use this alloy for the parts where stress, fatigue, and safety margins dominate, such as rotating ring supports, docking arms, structural joints and reactor supports.

Physical Property	Titanium Alloys (Ti-6Al-4V)	Aluminium Alloys (Al-Li / 2219)
Density (ρ)	~4.4 g/cm ³	~2.7 g/cm ³

Yield strength (σ_y)	~850 MPa	~300–500 MPa
Strength-to-weight ratio (σ_y/ρ)	High	Moderate
Young's modulus (E)	~110 GPa	~70 GPa
Fatigue Limit	550 MPa (10^7 cycles)	160–200 MPa (10^7 cycles)
Thermal Conductivity	~6.7 W/m·K	~120–130 W/m·K
Melting point	1,660 °C	635 °C

Artificial gravity

Artificial gravity within our space settlement is not a luxury feature, but a physiological and structural necessity that ensures long-term human survival, productivity, and psychological stability. Prolonged exposure to microgravity, as demonstrated aboard the International Space Station, leads to muscle atrophy, bone density loss, cardiovascular deconditioning, and fluid redistribution, all of which would critically affect a 180,000-person settlement operating near Saturn. Therefore, our position is that artificial gravity must be generated through rotational motion, using a large toroidal or cylindrical habitat structure in which centripetal acceleration mimics gravitational pull. By selecting a sufficiently large radius, we minimize angular velocity and thus reduce Coriolis effects and motion sickness, achieving a target acceleration close to 9.81 m/s^2 (or a slightly reduced value such as 0.8–1 g for structural optimization and energy efficiency).

The final numerical values for radius, rotation period, and tangential velocity were computed programmatically to ensure structural feasibility and human comfort thresholds, and the complete code used to obtain these end values is included in the Appendix. In conclusion, artificial gravity through controlled rotation represents the most realistic, scalable, and energy-efficient solution for sustaining a permanent deep-space civilization, balancing biomechanical requirements, engineering constraints, and long-term habitation goals.


Infrastructure

Secondary Bases

From an infrastructural perspective, our research indicates that the surrounding environment offers significant potential for resource exploitation. To maximise efficiency, we conclude that resilience should be achieved through a distributed system rather than reliance on centralised infrastructure. We want to operate our secondary bases as a network of specialised nodes, each optimised for the weather conditions, resources and strategic functions. This approach reduces single-point failures, improves resource-gathering efficiency, and enables long-term expansion beyond the primary settlement.

A secondary industrial base is established on Titan, selected for its dense nitrogen-rich atmosphere, low surface gravity, and extensive surface hydrocarbon reserves. The Titan base is strategically positioned


along the stable shorelines of Kraken Mare and Ligeia Mare (Figure no of chapter.1), where methane–ethane lakes provide direct access to liquid hydrocarbons while minimising seasonal shoreline migration and cryogenic erosion risks. Locating the base at these mid-latitude coastal regions enables efficient surface



pumping operations, short overland transport routes, and the deployment of floating extraction platforms, while the nearby solid terrain allows for subsurface pressurised habitats anchored within ice-rich regolith for structural stability and radiation protection. Methane and ethane harvested from the lakes are refined into chemical feedstock and propellant, while atmospheric nitrogen is captured for habitat pressurisation, fertiliser production, and radiation shielding composites, turning Titan into a primary exporter of industrial mass rather than a population center. The Titan facility operates as a

semi-autonomous mining and processing node, with most heavy industry conducted in low-temperature external environments to exploit Titan's naturally cryogenic conditions, reducing energy expenditure for cooling and long-term storage. Processed materials are transferred to orbit via reusable ascent vehicles and low-energy launch systems, then routed through nuclear-electric cargo tugs to the main settlement and future satellite bases.

(Figure 1) → our secondary base position



(<https://earthsky.org/space/titans-largest-sea-kraken-mare-is-1000-feet-deep/>)

(Figure 2)--> generative AI

Cryogenic Fuel Production on Titan

Cryogenic fuels produced on Titan are primarily used to support orbital ascent vehicles, intermoon cargo transport, and long-duration logistics operations throughout the Saturnian system, significantly reducing reliance on propellant launched from the inner Solar System. Liquid methane and ethane extracted from Titan's lakes are refined to propellant-grade fuel and stored under naturally cryogenic conditions, enabling efficient long-term stockpiling and export. At an initial operational scale, the Titan base is capable of producing approximately 50,000–100,000 tonnes of methane-based propellant per year, with production capacity designed to scale progressively as additional extraction platforms and processing modules are deployed. Our mining base is composed out of nitrogen capture and liquefaction pipelines, an industrial processing unit, liquid methane storage tanks, cooling towers, power modules and reusable ascent vehicles.

Resources and Crew

The Titan secondary base supports a limited human population of approximately 500 personnel, with most extraction, processing, and logistics tasks handled by autonomous and semi-autonomous robotic systems. Human crews focus on supervision, maintenance, and system management rather than continuous manual labor. Residents live in pressurized, partially subsurface habitats embedded in ice-rich regolith, providing natural radiation shielding and thermal stability. Life-support relies on atmospheric nitrogen extraction, closed-loop water recycling, hydroponic food production, and periodic resupply from the primary settlement, while continuous power is supplied by nuclear energy systems.

Other exploitation (We only show the materials we extract from several planets/moons, further information about choosing them will be presented in the resource gathering chapter)

Location	Key Extractable Resources	How / Why It's Useful
Enceladus	Hydrogen (H ₂), water ice, oxygen	Hydrogen is released naturally in plumes; ideal for fuel, chemical synthesis, and life support.
Rhea	Silicates, iron-rich minerals, sulfur traces	Structural metals, bulk construction mass, sulfur for industrial chemistry
Dione	Silicates, carbon compounds, sulfur-bearing materials	Feedstock for alloys, polymers, and chemical processing
Tethys	Water ice, rocky inclusions	Oxygen, hydrogen (via electrolysis), radiation shielding
Hyperion	Carbon-rich material, porous silicates	Lightweight carbon sources, specialty materials
Saturn (upper atmosphere)	Helium, hydrogen	Helium for cooling systems and scientific use; hydrogen for large-scale fuel production


Communication

Communication is approached differently based on the branch we will address:

1) Internal communications within the main space settlement

Communication inside the space settlement is designed around maximum reliability and controllability, using technologies that favour predictability over range. The

PER-IMHOTEP



core of the system is a fibre-optic network running through all structural modules, habitat rings, industrial sections, and command centres. Fibre optics provides extremely high bandwidth, negligible latency, and immunity to electromagnetic interference, making it ideal for life support control, propulsion monitoring, navigation, and safety systems. Wireless communication is used selectively: short-range radio waves support crew voice communication, maintenance activities, and mobile robotics, while optical wireless links (infrared or Li-Fi) enable high-speed data transfer in pressurised environments without adding RF noise.

2) *Communications with the secondary bases*

Communication between the main settlement and secondary bases, especially the Titan surface base, is built on dual complementary technologies that account for distance, atmosphere, and partial isolation. Radio wave communication provides the persistent backbone: multi-band RF links ensure that command authority, safety signals, and low-rate telemetry are always maintained, even during Titan's dense haze, methane clouds, or temporary misalignment of antennas. Alongside this, laser (optical) communication systems serve as the primary high-bandwidth channel, enabling efficient transfer of scientific data, industrial diagnostics, robotic video feeds, and system synchronisation.

The feasibility of this approach is supported by existing demonstrations such as Laser Communications Relay Demonstration and Deep Space Optical Communications, which validate precise pointing and long-distance optical data transfer. On Titan, laser wavelengths are selected to match atmospheric transmission windows, while local radio mesh networks allow robots and infrastructure to coordinate independently, reducing the need for constant high-rate communication with the main settlement.

3) *Long-distance communication with Earth*

Communication with Earth operates on fundamentally different priorities: strategic coordination and redundancy, rather than continuous control. Large high-gain radio antennas ensure guaranteed signal delivery across interplanetary distances, providing a robust channel for mission updates, emergency communication, and command verification. For high-volume data exchange, deep-space laser communication systems dramatically improve efficiency, reducing power consumption per transmitted bit while enabling the transfer of massive scientific datasets and long-term operational records. Programs such as Lunar Laser Communication Demonstration and TBIRD demonstrate the practicality of this approach.

Quantum communication technologies are introduced cautiously and only in supporting roles, such as quantum key distribution for secure encryption, while quantum teleportation remains strictly experimental. Overall, Earth communication is designed to tolerate delay and operate asynchronously, ensuring that the settlement remains fully autonomous while still deeply connected to terrestrial infrastructure and knowledge networks.

Asteroid Mining

We start from the Titan-orbit settlement with an uncrewed prospecting stack: 2–3 small survey craft (spectrometers + radar + gravimetry), a relay beacon, and a “tagger” drone that can attach reflectors/markers. The point is simple: in the Saturn system, you don't blindly chase rocks, you map a catalogue of nearby small bodies, rank them by water/volatile signature, metal signature, spin rate, and delta-v, then only send heavy equipment once a target proves it's worth the propellant.


Our first mining campaign focuses on Phoebe (even if it's not an asteroid, it's an important moon that has been studied, fact that offers us an advantage), because it's the one Saturn-system captured body with strong,



mission-useful constraints from Cassini: spectral data show water-related signatures and CO₂ ice, plus a chemically diverse surface (iron-bearing minerals, organics, etc.). This means Phoebe is not “just rock” and not “just ice”; it's a practical mixed feedstock. Technically, Phoebe is also easy to work: its escape velocity is ~0.1 km/s (so gentle material handling and low-thrust logistics are viable), its rotation

period is ~9.27 hours (predictable thermal cycling for bake-out operations), and Cassini imaging indicates an ice-rich interior with a darker surficial layer hundreds of meters thick, which is ideal for controlled strip-mining and thermal extraction without deep drilling. The “why” is simple: Phoebe gives the settlement water mass (life support + shielding + propellant feedstock) and mineral/organic feedstock with the lowest uncertainty.

Once the processing chain is proven on Phoebe, we expand to the Phoebe/Norse “subgroup” irregulars, small captured bodies on retrograde orbits that are likely fragments and/or compositionally related populations. The key technical reason these are suitable is operational: they are kilometer-scale, so (a) anchoring loads are tiny, (b) excavation is dominated by regolith handling rather than hard-rock mining, and (c) the safest method, bag-and-bake (contain, despin, heat, and cold-trap volatiles), is actually feasible because you can enclose the entire body or a large mining face. We prioritize neutral-color members (examples often discussed include Mundilfari and Phoebe itself) because Saturn's irregulars show a broad colour range; neutral colours are a practical first proxy for less extreme surface reddening and different regolith/organic maturity, which helps standardise processing recipes early on. → as бага параграфу аста ла resource gathering



Beyond Phoebe, the next tier of irregular satellites typically ranges from 5–20 km in diameter. Examples in this size class include bodies such as Ymir (~18 km), Suttungr (~7 km), and other Norse-group members. Objects in this range contain enormous material volume relative to settlement needs. A single 10 km object, assuming a density of ~1.5 g/cm³ (typical for icy-rock mixtures), contains on the order of 10¹⁵ kg of material, far beyond immediate consumption requirements. These bodies are mined in place, not captured.

The most strategically valuable class for early industrialization lies between 300 meters and 5 kilometers in diameter. This size range offers the best balance between extractable mass and operational controllability. A 1 km diameter body (density 1.5 g/cm³) contains roughly 8×10^{11} kg of material. Even if extracting just 1% yields 8 billion kilograms, we will collect enough water and shielding mass to improve our resource collection and the inhabitants' needs. These bodies are stable enough for anchoring systems but small enough to avoid extreme despinning challenges.

Once a target (e.g., Phoebe or a smaller irregular satellite) is selected, the mining stack performs three mandatory stabilisation steps before extraction begins. First, the body's rotation state is reduced or fully despun using low-thrust ion engines and momentum-exchange tethers; this is essential because even slow rotation can eject debris in microgravity. Second, the asteroid is either partially enclosed (large bodies) or fully wrapped in a flexible containment bag (small bodies, typically <50–100 m). This prevents material loss and creates a sealed processing environment. Third, anchoring harpoons and surface clamps secure excavation platforms to counteract reaction forces during drilling, cutting, or regolith scraping. Only after these steps does active mining begin, ensuring mechanical stability and crew safety (all operations remain robotic).

Strategic Perspective

The asteroid-mining strategy in the Saturn system is not about maximizing extraction volume, it is about minimizing uncertainty and propellant cost per delivered kilogram. Phoebe acts as the industrial proof-of-concept body. The Norse irregulars provide scalable feedstock nodes. Mid-size bodies (300 m–5 km) form the backbone of sustainable resource flow. Large irregularities remain long-term reserves. In this architecture, resource gathering becomes a controlled, catalog-driven expansion: robotic, modular, and thermally optimized methods turn our settlement into a distributed industrial belt that supports the Titan-orbit settlement without destabilizing its logistics chain.

Energy

A space settlement of 180,000 people near Saturn requires a reliable and continuous energy supply. Each resident consumes approximately 5 kWh per day, resulting in a total daily energy demand of 0.9 GWh just for basic personal needs such as lighting, electronics, and life-support systems. Additional energy is necessary for industrial operations, agriculture, heating, and communication, making a dependable power source absolutely critical for the settlement's survival.

Solar energy alone is insufficient in the Saturn system, as sunlight is only about 1% of what Earth receives. Therefore, the settlement relies on a combination of nuclear fission and tidal energy. Small nuclear reactors provide a stable, high-output base load capable of producing around 2.5 GWh per day (which is almost 104 MW continuous power), covering essential systems without interruption. Tidal energy, harvested from gravitational interactions with nearby moons such as Enceladus, supplements this supply, offering renewable power while adding redundancy and stabilizing the energy grid during peak demand. Together, these sources ensure a safe, sustainable, and independent energy infrastructure.

Part of this energy can be dedicated to lighting. Using advanced LED systems with an efficiency of 150 lumens per watt, the nuclear and tidal power output can produce over 15 billion lumens of continuous light. At a comfortable 400 lux illumination, this amount is sufficient to fully light approximately 39 million square meters of habitat space. For a population of 180,000, with roughly 40 m² per person allocated for homes, workspaces, and communal areas, this lighting capacity comfortably exceeds the settlement's essential needs, leaving room for public spaces, agriculture, and industrial facilities. (information better explained in the lighting section)


Tidal Energy	Nuclear Fission
--------------	-----------------

Tidal energy near Saturn is produced by the gravitational interactions between the planet and its moons, such as Enceladus and Titan. Saturn's immense gravity causes the moons to stretch and flex as they orbit, generating internal friction and heat through tidal deformation. This heat can be harnessed in several ways. One method is using geothermal turbines, where the warmed subsurface oceans or melted ice drive turbines connected to generators, producing electricity. Another approach involves mechanical flexing systems, where devices like piezoelectric materials or hydraulic pistons capture the continuous bending of the moon's crust and convert it into power. Additionally, underwater turbines can exploit subsurface ocean currents induced by tidal forces. Overall, tidal energy provides a continuous, renewable source of electricity, supplementing nuclear power and ensuring stable energy availability far from the Sun.(details about getting near Saturn's moons and actually exploiting them will be specified in the next chapter, resource gathering)

Nuclear fission generates energy by splitting the nuclei of heavy elements, such as uranium-235 or plutonium-239, releasing large amounts of heat. In a space settlement reactor, neutrons collide with fuel nuclei, causing them to split into smaller nuclei while emitting additional neutrons and thermal energy. This heat is absorbed by a coolant circulating through the reactor core, which then drives turbines either by producing steam or through direct mechanical conversion. The turbines turn generators, converting mechanical energy into electricity to power the settlement. Modern compact fission reactors suitable for space settlements are highly efficient, producing hundreds of megawatts of power while occupying only a few hundred square meters of space within the settlement, including shielding and control systems. Control rods regulate the reaction to maintain a stable energy output, and shielding ensures safety from radiation. Nuclear fission is an ideal energy source for a settlement near Saturn, providing high-output, continuous power independent of sunlight or environmental conditions.

Resource Gathering

Resource gathering on Titan is not limited to the obvious zones shown on the map; while Kraken Mare and Ligeia Mare anchor our primary methane industry, the equatorial dunes support carbon-based materials, and



the highland ice regions sustain oxygen and water production, we deliberately avoided concentrating extraction in only these highlighted areas. By running our surface-analysis C++ algorithm across Titan's full geospatial dataset, we identified additional high-scoring, contiguous zones with suitable slope, hazard distance, elevation, and resource presence, allowing us to designate secondary and tertiary mining regions beyond the main industrial cores. This data-driven approach reduces single-point failure risk, improves logistical balance between

hemispheres, and ensures that Titan functions not as one massive refinery, but as a distributed, resilient industrial platform integrated into the broader Saturn system.

After running one test, this is the output our C++ code gave us

Output:

```
== North Lakes Industrial ==
Top 1 regions:
Region #0 cells=9770 meanScore=0.752 bbox=[(0,0)->(29,359)]

== Equatorial Dune Fields ==
Top 1 regions:
Region #0 cells=10800 meanScore=0.817 bbox=[(75,0)->(104,359)]
```

Our long-term resource strategy extends beyond Titan by assigning specialized roles to nearby moons: Enceladus serves as a high-purity water and volatile supplier through plume capture, while Rhea and Dione provide structural mass and ice for radiation shielding and large-scale construction.

By distributing extraction across multiple bodies, we reduce dependency on any single source, lower transport energy where gravity is weaker, and transform the Saturnian system into an integrated, multi-node industrial network rather than a centralized mining operation. We've made a table with our research on key extractable resources from several moons, which will have a similar technique of extraction as the asteroids. For our future plans, more details will be found in the research opportunities chapter, but those represent a further goal for our space settlement, which will later develop several bases all across the proximity of Saturn.

Transportation

It is quite the journey from Earth to Saturn. Before getting there though, we must first consider the logistics involved in successfully transporting our ships to LEO.

Despite it making up less than 0.001% of the total distance required to reach Titan, getting so many spacecraft to this point is the most crucial and perhaps one of the toughest to get by.

To get the most Δv and payload capacity from the initial launch, we have chosen a point near the equator, as the land moves about 500 km/hour faster than at the poles, giving us a great advantage right from the get go. With this criteria in mind, we have selected the space centre in Kourou, French Guiana as launch location for the [NAME] mission. Located just 570 kilometres north of the Equator line, the Korou Space Centre is the perfect option for our needs, as more than 300 satellites and rockets have been sent into space since 1970, most of them to LEO.

Technological requirements

There is no way around getting the space shuttles to reach the orbital velocity of the Earth without using chemically-based rockets because we would not be able to overcome Earth's gravity otherwise. Their high-thrust capabilities (several thousands kilonewtons for launch vehicles) make it by far the superior option of take off, perhaps the only feasible one.

After the shuttles manage to get into the LEO (~200-400 km altitude), the shuttles may reside in it for a few hours or 1-2 days before igniting the NTP (Nuclear Thermal Propulsion) for the long haul trip to Titan's orbit. From LEO, the spacecraft performs a trans-planetary injection burn that places it onto a heliocentric Hohmann transfer orbit toward Saturn. This transfer orbit is an ellipse tangent to Earth's and Saturn's circular orbits and represents the minimum-energy trajectory between the two.

Equations:

$$E = -\frac{\mu}{2r}$$

Specific orbital energy of a circular orbit (μ = gravitational parameter of the sun; r = radius of the circular orbit)

$$v_{t,p} = \sqrt{\mu \left(\frac{2}{r_{t,p}} - \frac{1}{a_t} \right)}$$

Vis-visa equation - velocity at each burn at perihelion (departure)

A = semi -major axis of elliptical transfer orbit

$$v_{t,a} = \sqrt{\mu \left(\frac{2}{r_{t,a}} - \frac{1}{a_t} \right)}$$

Velocity at aphelion (arrival)

Why NTP?

We chose NTP over chemical going further because it offers much higher Specific Impulse, that being 800 seconds against the 350 offered by chemical propulsion.

NTP beats Ion thrusters despite them having 6000 seconds specific impulse because Ion thrusters have microscopic thrust potential. The problem that both VASIMIR (plasma) and Ion thrusters face is their inability to stop predictably and engage into orbit. In space, high exhaust velocity is not necessarily equivalent to operational efficiency, as we seriously risk not being able to break in time for the settlement, leaving many people stranded as a result.

We have also considered NEP (Nuclear Electric Propulsion) as a good alternative but the power conversion adds way too much mass and is ultimately not the realistic option, especially for such a large scale operation like ours, though it is definitely a great competitor.

Probabilistic risk assessment

To ensure the safety of the mission we need not forget about the Probabilistic Risk Assessment (PRA). While the odds are low, NTP reactors can go wrong, so the programme enforces constant surveillance by specialists and experts responsible for the engines, in order to get quick responses in the eventuality of any unfortunate mishaps that may happen during the approximately five year commute to Titan. While the reactor cannot be manhandled manually, humans still need to monitor: reactor power level, core temperature gradients, hydrogen mass flow rate, neutron flux, structural vibration, thrust vector alignment.

None of the possible failures of the reactor would be catastrophic, but they will be detrimental to the mission and may slow it down quite a bit.

Transportation around the settlement

There is no denying it, 180.000 is a lot of people. Thankfully, we have found the solution to providing every single one of them a safe, efficient, accessible, and pleasant way of commuting to wherever one may need to be on the ship, given our limited resources.

Due to the dimensions of the ship and RPM that we chose (0,7), we intentionally try to limit transportation speeds to 2.5 m/s, because of the undesirable Coriolis effects that may make travellers feel slightly unwell and uncomfortable. This is equivalent to a light jog, or a slightly faster-paced walk. For this matter, we decided on

using linear-motor assisted walkways, as they are the most accessible, clean and convenient way of moving at such slow values.

We will be having two sets of parallel walkways (A and B), each containing two different lanes with opposite traffic flows. Both will have boarding points, marked clearly with signs, forming a gap between the railings and giving people the space needed to step onto it. Around the boarding points, the speed slightly decreases, allowing for a smooth transition when getting on. Additionally, every station will function as a miniature interchange, being equipped with a small roundabout, whose purpose is providing the possibility of choosing the direction desired by every individual rider, without bothering the others already using it. The roundabout is motionless and it acts as a refuge as well.

Set A:


Designed for small distances and casual strolls, set A moves at about 1 m/s. There are frequent boarding points, every 200 metres. They are 3 metres wide on each traffic lane, and purposefully designed so that the disabled, elderly and those who enjoy walking more by themselves can have a relaxing and efficient way of moving around the torus. Everyone is welcome and encouraged to use these when not in a rush.

Set B:

A bit narrower than its counterpart, it is sitting at 2 metres of width per lane (4 metres total). Set B is an exception to the 2.5m/s rule, moving at 2.8 m/s, and its purpose is acceleration and quick transfer. Its boarding stations are much farther apart, and only around the travel cylinders and the panels connecting the tori. Here, the roundabouts represent a bit of an impediment, so infrequent stations are the key to ensuring that we don't waste time decreasing the speed too many times, while simultaneously making the most out of the stops, providing meaningful connections to people who need to either move through the inner ring around the central cylinder or for those who need to move to the other tori on the settlement.

Cylinder transportation

It is not recommended to try and travel the entire circumference along set B, since the speed may become fatiguing. Instead, commuters are encouraged to link with the other available connections, such as the cylinders and panels, that provide more tolerable transportation speeds. Residents are also obliged to be careful when beginning a commute on the public walkways, constantly checking if anyone is coming from the left hand side, especially when trying to reach a roundabout to go in the opposite direction of transit.



Self produced using SketchUp

This image illustrates how the walkways integrate in between the residential areas of a torus. As mentioned previously, the circumference of the exchange roundabout is not moving, making it easier to reach without the risk of possibly tripping or injuring oneself.

Panel transportation

Getting from one torus to the other is far from a complex procedure. The panels that surround the ship are equipped with a similar walkway to SET B, the only difference being that it is slightly slowed down to diminish Coriolis effects, since the average trips here cover vaster differences than the average trips inside the torus.

Cylinder transportation

Cylinders go all the way down to ground level into small hub nodes located along the rotational axis, designed to function as transition points between artificial gravity and microgravity zones.

They connect the torus with the spine and its inner ring, where people have the opportunity to continue their journey to the other side of the torus along a smaller circumference of walkways, shortening travel times.

Transportation inside the cylinders consists of a subway-like network based on linear synchronous motor propulsion and full magnetic levitation technology, inspired by the fundamentals of Japan's very own SCMaglev. We are not interested in the speeds it is capable of producing, though, as the Coriolis effects would cause significant motion sickness and nausea above speeds of 2.5 m/s. Instead, we limit the system to a controlled maximum velocity of 2.5 m/s, prioritizing comfort, frequency, and operational stability over raw speed, providing inhabitants with, in this context, the fastest and most convenient means of transport achievable.

Despite the significant implementation cost, LSM propulsion offers very low long-term maintenance requirements due to its contactless operation and reduced mechanical wear. A large-scale habitat like ours handles substantial passenger volumes daily, so a high-throughput network based on automation and frequency is essential to move people across the torus comfortably and efficiently. While alternative mechanical systems are possible, none provide the same combination of scalability, precision control within a rotating frame, and long-term durability as a full maglev-based solution.

Linear Synchronous Motors (LSMs) produce direct linear motion through electromagnetic forces. They maintain perfect synchronization between the magnetic field and the mover, enabling precise control without slip. LSMs feature a stator (stationary coils creating a traveling magnetic field via AC current) and a mover (often with permanent magnets that lock onto the field). The field "pulls" the mover along a straight path, with speed controlled by current frequency.

We will power the stator coils with phased AC to generate a moving magnetic wave so that the mover's magnets align synchronously, producing Lorentz force for smooth acceleration. No mechanical intermediaries mean zero backlash and low maintenance.




Image from: <https://itg-motor.com/linear-synchronous-motors-working-principle-advantages-and-applications>

Agricultural Production System

The settlement's food supply is produced within T2, the central torus dedicated to agriculture and industry. T2 orbits the central spine at a major radius of 1,825 m, where the rotational rate of 0.7 rpm generates approximately 1.00 g at the torus centreline. The elliptical cross-section (semi-major axis 200 m, semi-minor axis 100 m) provides a substantial internal volume of approximately 720 million m³, of which the agricultural sector occupies roughly 50% of the torus circumference, with the remaining arc allocated to industrial facilities, processing plants, and logistics infrastructure.

Robotic Vertical Farming Architecture

The primary food production technology employs a design similar to the Opollo Farms AutoStore system: a cube-based robotic vertical farming architecture that converges industrial warehouse automation with controlled-environment hydroponic agriculture. In this configuration, plants are cultivated in standardised bins arranged within a dense three-dimensional aluminium grid structure. Battery-powered robots traverse elevated rails on the grid's top surface, descending to retrieve, relocate, and manage plant containers with sub-centimetre precision, enabling plant-specific environmental optimisation. The hydroponic growing method eliminates soil entirely, with nutrient-rich water solutions delivered directly to root zones through integrated irrigation systems within each bin.

This technological approach fundamentally differs from conventional vertical farming designs that rely on static rack systems or linear conveyor-based plant movement. By dynamically repositioning plants throughout their development cycle to optimal locations within the facility's environmental gradients, adjusting



light exposure, air circulation, and proximity to climate control outputs, the system maintains ideal growing conditions at each growth stage rather than accepting suboptimal fixed positions. A single-port entry/exit design moves plants to centralised workstations rather than requiring workers to access growing areas, minimising human intervention and contamination risk while dramatically reducing labour intensity.

The software integration layer coordinates robot traffic, bin inventory, and environmental optimisation in real time. This digital infrastructure enables plant tracking from seeding through harvest, with algorithms optimising container positioning based on growth stage, environmental requirements, and harvest scheduling.

Hierarchical Agricultural Intelligence Architecture

The settlement's agricultural operations are orchestrated by a three-tier AI architecture designed for resilience, scalability, and autonomous decision-making across the full production chain. Rather than relying on a single centralised system, the hierarchical structure ensures that failure at any level does not compromise the entire food production network; lower tiers continue autonomous operation within their last-received parameters while upper tiers are restored

Tier	Scope	Functions
Tier 1: Module-Level AI Controllers (~50,000 units; one per cube farm module)	Individual module operations; real-time, granular control	Individual plant watering cycles and nutrient delivery timing; LED spectrum and intensity adjustment per bin; bin-level temperature and humidity regulation; crop health monitoring via multispectral imaging (leaf coloration, respiration signals, growth rate tracking); robotic task scheduling (seeding, repositioning, harvest retrieval). Executes autonomously within parameters set by Tier 2.
Tier 2: Zone Coordinators (5 units; one per agricultural zone A-E)	Zone-wide resource optimisation and pattern recognition	Aggregation and analysis of module-level data across the zone; water and energy load balancing between modules; harvest scheduling and logistics coordination with T2 processing and industry sectors; zone-wide disease and pest pattern detection; nutrient deficiency trend identification; inter-module crop rotation management.
Tier 3: Settlement Agricultural Intelligence (1 system)	Settlement-scale strategic orchestration	Cross-zone crop rotation and diversification strategy; population-level nutritional demand forecasting (integrated with SMN biosensor data and torpor cycle schedules); food reserve threshold management and emergency scaling protocols; energy budget negotiation with spine reactor allocation systems; integration with the Biosynthesis Hub (nutrient feedback loops, O2/CO2 balancing); long-term genetic improvement prioritisation via CRISPR lab coordination; waste stream optimisation with CWMS.

Table 1a. Three-tier hierarchical AI architecture for agricultural operations.

The Tier 3 system constitutes the strategic brain of the settlement's food production. Trained on Earth-derived agricultural datasets and continuously refined through on-station operational learning, it determines what is grown, when, and in what quantity, balancing food security against energy budgets,

population nutritional profiles, and reserve targets. Its integration with the Saturn Medical Network's biosensor data enables demand forecasting that accounts for population health trends, activity levels, and torpor cycle rotations, while its interface with the Biosynthesis Hub ensures that nutrient recovery from waste streams and algal byproducts is synchronised with hydroponic input requirements.

Performance Metrics

The cube-storage vertical farming system achieves performance substantially exceeding both traditional field agriculture and conventional static-rack vertical farms across all critical metrics.

Metric	Settlement System (AutoStore-type)	Conventional Vertical Farm	Traditional Field Agriculture
Harvest cycle (leafy greens)	15 days (24 cycles/year)	20-30 days (12-18 cycles/year)	30-60 days (2-3 cycles/year)
Water consumption	12.5-20 L/kg (95% reduction vs. field)	20-40 L/kg (90% reduction)	250-400 L/kg (baseline)
Yield density (floor-area basis)	70-120 kg/m2 /year (conservative estimate)	45-75 kg/m2 /year (industry avg.)	2-4 kg/m2 /year
Energy consumption	11-15 kWh/kg (estimated)	15-25 kWh/kg	0.6-0.9 kWh/kg (direct operations)
Production continuity	Year-round, continuous, predictable output	Year-round but manual-dependent	Seasonal, weatherdependent
Automation level	Full robotic handling, AI-optimised	Partial; manual labour-intensive	Mechanised but weather-exposed

Table 1. Comparative performance metrics for the settlement's cube-storage farming system versus alternatives.

The 15-day harvest cycle for leafy greens and herbs emerges from synergistic optimisation across multiple environmental parameters. The controlled indoor environment eliminates weather variability, pest pressure, and seasonal light limitation. LED lighting systems provide photosynthetically optimised spectrum and intensity continuously, operating at an efficacy of 3.4-3.5 micromol/J. Precision climate control maintains temperature (18-24 degrees C), humidity (60-70% RH), and CO2 concentration (800-1,200 ppm) at levels tuned for maximum photosynthetic efficiency. Direct root-zone nutrient delivery ensures immediate availability of essential elements.

Water Conservation Architecture

The claimed 95% water use reduction is achieved through multiple integrated engineering approaches within the closed-loop hydroponic system:

Mechanism	Function	Efficiency Contribution
Closed-loop hydroponic recirculation	Captures all drainage, filters, reconditions, and reuses nutrient solution	Eliminates percolation, runoff, and evaporative losses from soil-based systems
Precision root-zone delivery	Applies water directly to plant roots with volume and timing optimised for uptake	Minimises excess application and standing water exposure
Enclosed environment with dehumidification recovery	Captures plant-transpired moisture from atmosphere for return to irrigation system	Recovers 80-90% of transpiration losses
Robotic positioning optimisation	Dynamically relocates plants to minimise water stress and optimise uptake efficiency	Estimated 10-15% additional efficiency versus static systems

Table 2. Water conservation mechanisms in the cube-storage hydroponic system.

At the settlement scale, total agricultural water consumption is estimated at approximately 8,400 m³ /day (46.9 L per person per day for food production), with over 95% of this water continuously recirculated within the closed loop. Net water loss is limited primarily to water incorporated into harvested biomass and minor irrecoverable system losses.

Energy Profile

Energy consumption constitutes the primary operational cost of vertical farming, as artificial lighting and climate control substitute for free solar radiation. At the settlement's operational intensity (well below maximum capacity), energy demand is moderated significantly:

Energy Component	Estimated Consumption	Notes
LED lighting (dominant load)	~200 MW continuous	At 3.4-3.5 micromol/J efficacy; reduced by operating at ~15% capacity
Climate control (HVAC, dehumidification)	~60 MW continuous	Temperature, humidity, CO ₂ management across zones
Robotic automation (AutoStore fleet)	~5 MW continuous	10 robots consume ~100 W each; fleet of ~50,000 robots across T2
Nutrient delivery and water	~20 MW continuous	Pumping, filtration, reconditioning

systems		
Total agricultural energy demand	~285 MW continuous	Supplied by spine nuclear reactors; <10% of total settlement energy budget

Table 5. Energy consumption breakdown for the agricultural system.

The energy trajectory for vertical farming demonstrates sustained improvement: industry consumption has decreased approximately 30% since 2020, with projections targeting an additional 50% reduction by 2035 through next-generation LED systems (targeting 4.0+ micromol/J efficacy), liquid desiccant climate control, AI-driven predictive environmental management, and deeper automation integration. The settlement's nuclear power infrastructure, located in the spine, provides baseload electricity independent of solar availability, a critical advantage in the Saturnian system where solar irradiance is approximately 1% of Earth-surface levels.

Genetic Engineering Integration

Dedicated CRISPR laboratories within T2 refine crops so their traits match the demands of the rotating, artificial-gravity habitat. Trait optimisation strengthens root systems for semi-aerated hydroponics, adjusts photoreceptors to the station's LED spectra, and enhances metabolic pathways for nutrient density. Genes influencing auxin transport, cytoskeletal structure, and stem rigidity are modified to maintain proper growth under the 0.89-1.10 g gravity gradient across T2's cross-section. Faster growth-cycle variants, critical for Zone Page 8 B's grain rotation, are incorporated into selectable lines. All engineering loops through the AI-driven phenotyping system: multispectral imaging and metabolic sensors track growth with high precision, allowing the AI to evaluate which edits succeed and which require refinement, creating a continuous improvement cycle where each generation is more suited to the habitat than the last.

Biosynthesis and Bioprocessing Hub

The Biosynthesis and Bioprocessing Hub is housed within the central spine at the approximate height of T2, occupying a 150 m tall annular section between radii of 50 m (inner structural core) and 280 m (near the spine's 300 m outer wall). This placement at the settlement's centre of gravity minimises rotational stress on large fluid-filled bioreactors and positions the hub adjacent to the agricultural torus for efficient material transport via the side-panel conveyor network. The total enclosed volume is approximately 35.8 million m3 , of which roughly 60% (~21.5 million m3) is allocated to operational bioreactor arrays, processing equipment, and support infrastructure.

The gravity gradient within the hub ranges from 0.027 g at the inner boundary (R = 50 m) to 0.153 g at the outer boundary (R = 280 m). This low-gravity environment reduces mechanical stress on large fluid-filled tanks, helps keep algal cultures evenly suspended with minimal energy expenditure for mixing, and enables smoother bioreactor operations compared to full-gravity alternatives. Convection, drainage, and equipment handling remain practical at these gravity levels while keeping structural loads low, allowing large bioreactors to be maintained efficiently.

Algal Photobioreactor Array: Oxygen and Biomass Engine

Dense photobioreactors cultivate strains of Spirulina and Chlorella, illuminated by both fibre-optically routed light and high-efficacy artificial LED panels. Fed with CO2 -rich air drawn from the habitat's atmospheric circulation, these reactors produce steady oxygen output while generating edible, protein-rich biomass. At a production rate of 10-15 g dry algae per m2 per day, a single hectare of reactor surface can produce over 50 kg of dry biomass daily, supporting thousands of inhabitants with supplemental protein, omega-3 fatty acids, and essential micronutrients.

The agricultural crops in T2 serve as the primary oxygen source, generating approximately 516,000 kg of O2 daily from their combined ~20.6 million m2 of photosynthetically active growing surface, which alone exceeds the settlement's total daily O2 requirement of ~151,200 kg. The algal photobioreactor array therefore functions as a critical redundancy layer and supplementary system rather than the sole oxygen source. In the event of partial agricultural system failure, the biosynthesis hub can be rapidly scaled to compensate, providing atmospheric resilience independent of food production status. Emergency O2 tanks and chemical scrubbers remain on standby as additional failsafes.

Beyond direct nutrition, algae serve as biochemical workhorses. Their biomass can be processed into flours, supplements, omega-3-enriched products, pigments, or engineered metabolites. CRISPR-engineered strains boost oxygen output, enhance metabolite production rates, and are optimised for the specific LED spectra and low-gravity fluid dynamics of the spine environment.

Microbial Fermenters

Microbial fermenters within the biosynthesis hub cultivate engineered bacteria and yeast to produce essential nutrients and materials that cannot be efficiently derived from plant agriculture alone. These organisms generate vitamins (notably B12, which is absent from plant-based diets), create single-cell protein from waste gases such as CO2 or hydrogen, and synthesise useful biopolymers including exopolysaccharides (EPS), bacterial cellulose, and mycelium-based structural materials. The outputs of the microbial fermentation system serve multiple downstream applications:

Output Category	Products	Settlement Application
Nutritional supplements	Vitamin B12, riboflavin, folic acid, essential amino acids	Dietary supplementation; fortification of algal and plant-based foods
Single-cell protein	Bacterial and yeast biomass (40-70% protein by dry weight)	Protein source for direct consumption, aquaculture feed, and food processing
Biopolymers	EPS, bacterial cellulose, PHA (polyhydroxy- alkanooates)	Bioplastics, binders, packaging, and structural composites
Industrial precursors	Mycelium, bioadhesives, pigments	Textile production, radiation-shielding composites (when mixed

		with regolith)
--	--	----------------

Table 7. Microbial fermenter outputs and their settlement applications

All strains are CRISPR-engineered for safety, efficiency, and built-in genetic kill switches that prevent proliferation outside their designated containment. The fermenters feed on recycled waste gases (CO2 , H2), treated wastewater, and residual biomass from the agricultural system, transforming low-value inputs into high-value outputs. Operating as a closed-loop biofactory, the microbial system converts CO2 , recycled nitrogen, water, and energy into oxygen, edible biomass, and versatile organic materials. Non-pathogenic strain selection and strict compartmentalisation ensure biosafety throughout. In emergencies, individual bioreactor sectors can be sealed off to isolate contaminated cultures without disrupting the remainder of the system.

Exopolysaccharide Production and Extraction

Certain bacteria dramatically increase exopolysaccharide (EPS) production under controlled stress conditions (elevated temperature, 5% salinity, controlled drought), making strain selection and precise stress management key to high yields. In the biosynthesis hub, EPS extraction operates as a compact biorefinery with a defined workflow:

- Primary separation: centrifuges and tangential-flow filters separate biomass from culture broth.
- Contaminant removal: enzymatic treatment and activated-carbon adsorption eliminate residual proteins, nucleic acids, and pigments.
- EPS isolation: precipitation (typically ethanol-based) and ultrafiltration concentrate the polysaccharide fraction.
- Purification: anion-exchange chromatography produces high-purity fractions suitable for food-grade and biomedical applications; this method offers clean purification of charged EPS but requires careful pH control and higher operating costs.
- Final processing: spray-drying or lyophilisation converts purified EPS into storable powders for downstream use in food thickening, bioplastic formulation, wound dressings, and composite binding agents.

Optional pigment and secondary metabolite extraction occurs in parallel, capturing carotenoids, phycocyanins, and other high-value compounds before the final drying stage. The EPS production line integrates tightly with the microbial fermenter infrastructure, sharing sterilisation, fluid handling, and quality control systems to maximise capital efficiency.

Waste Management and Resource Recovery

In order to achieve maximum efficiency, the concept of "waste" as an undesirable byproduct that ought to be discarded should be abolished, as it is fundamentally incompatible with the concept of "self-sustenance". Consequently, the waste management system is engineered as a closed-loop, resource recovery network, tailored for extracting maximal yield: a Closed-Loop Waste Metabolism System (CWMS) that reconceptualises all material outputs as resource streams, achieving 85-90% mass recovery for organic and metallic streams, while hazardous and complex electronic materials maintain lower recovery efficiencies of 60-75%, reflecting thermodynamic and material-separation constraints, with the remaining waste representing truly irrecoverable materials, immobilised in stable mineral form to eradicate environmental risk. The CWMS manages four

primary waste streams: organic waste (food scraps, agricultural residues, sewage), inorganic recyclables (plastics, metals, glass), hazardous materials (medical waste, batteries, electronics), and construction debris, each routed through optimised processing pathways. Inter-stream integration allows for additional resource recovery, such as nutrient extraction from sewage and metal recovery from electronic waste.

The system is designed for scalability, being capable of processing up to 200,000 tonnes yearly, including industrial, construction, and agricultural waste, incorporating a 25-40% contingency margin over projected generation rates. Liquid waste streams, including urine, hygiene water, and atmospheric condensate, are processed through multistage distillation, membrane filtration, and catalytic oxidation systems, attaining water recovery efficiencies surpassing 95%. Solid organic waste, such as food remnants, inedible biomass, and biodegradable packaging, is routed towards aerobic and anaerobic bioreactors where microbial consortia convert complex organics into stabilised compost, nutrient salts, and recoverable water.

Syngas for energy storage or propulsion applications, alongside mineral residues, will be produced via high-temperature pyrolysis or plasma gasification of residual non-organic waste. Plasma-based processing is deployed selectively due to its high energy demand and is reserved for complex or hazardous materials unsuitable for biological treatment. Synthesised gases may serve as supplementary chemical feedstock or be stored for station-keeping thrusters used in orbital corrections. Prior to propulsion use, the gas mixture undergoes purification and compositional adjustment to meet specific propellant performance and combustion stability requirements. Infrastructure is spread through three hierarchical processing levels, in order to minimise transport energy and maximise resilience. At residential and commercial nodes, local preprocessing takes place, while aggregation and biological or AI-assisted sorting are handled by district-level facilities, as settlement-wide plants conduct final material valorisation and stabilisation.

This architecture ensures that around 90% of waste is processed before reaching the highest level. With a professional workforce accounting for 2.5% (including AI oversight, maintenance, agricultural nutrient management, etc.) of the habitat population to support technical operations and quality control, considerable automation lowers human exposure to hazardous procedures. Overall, CWMS serves as a critical metabolic subsystem, providing the long-term material circularity required for a self-sufficient extraterrestrial human habitat.

Air Quality and Atmospheric Regulation

Air quality within the settlement's parameters is a critical criterion for both short-term crew performance and long-term human health, given the closed-loop environment must continuously remove carbon dioxide, trace contaminants, and particulate matter, while maintaining optimal oxygen levels. Due to limited possibilities to resupply and the immediate risks carried by system failure, the station's air management strategy utilises redundant life-support technologies (backup systems that ensure continuous availability of vital environmental conditions), real-time monitoring, and biologically inspired regeneration systems to ensure a stable, breathable atmosphere under all operating conditions.

The Saturn space habitat will use a fully closed-loop life-support system. Oxygen is regenerated through the electrolysis of water and Sabatier reactors combining H₂ and CO₂, while being supplemented from stored or in-situ resources, as the CO₂ exhaled by the inhabitants is constantly drawn into the air revitalisation loop.

Methane generated through the Sabatier reaction is not vented, as on the ISS, but redirected into a methane-cracking unit where carbon is recovered as solid graphite and hydrogen is recycled back into the system. This enables near-complete carbon loop closure. On ISS, NASA removes CO₂ and trace gases with solid sorbents and catalytic reactions; a similar but scaled and more autonomous system will be implemented.

For instance, amine or zeolite-based scrubbers could capture CO₂, with Sabatier reactors recycling H₂ into water and methane. Humidity is managed by condensers and dehumidifiers, whose recovered water feeds the potable-water system. In addition, bioregenerative elements (controlled plant growth modules) can assimilate CO₂ and produce fresh O₂ and food, as in ESA's MELiSSA closed-loop experiments.

Beyond CO₂ /O₂ control, trace contaminants (VOCs from materials, solvents, human metabolism) must be removed to below safe limits. Ammonia, acetaldehyde, formaldehyde, and other organics are adsorbed on activated-carbon/zeolite filters (Trace Contaminant Control Subassembly) or oxidized on catalytic beds. The ISS even uses onboard FTIR spectrometers to monitor key gases in real-time. Particulates and microbes are captured by HEPA filters: in partial or artificial gravity environments, aerosol behaviour may differ from Earth norms, necessitating continuous HEPA and UV recirculation. Oxygen/nitrogen balance and cabin pressure (typically ~1 atmosphere with ~20-21% O₂, corresponding to ~21 kPa oxygen partial pressure. Reduced-pressure habitats operating at 0.7-0.8 atm require an increased oxygen fraction to maintain equivalent oxygen partial pressure; however, the settlement operates at approximately 1 atmosphere to minimise decompression risk and maintain long-term cardiopulmonary stability) will be actively regulated.

In summary, the habitat's ECLSS will recycle air with life-support hardware analogous to (and more autonomous than) the ISS systems, ensuring carbon dioxide is removed and oxygen replenished while scrubbing all harmful gases and particulates.

Crucially, the physicochemical air-handling infrastructure is augmented by bioregenerative plant modules, which provide passive CO₂ assimilation, oxygen production, and humidity regulation while simultaneously enhancing crew psychological well-being. This hybrid architecture, combining engineered reliability with biological adaptability, ensures atmospheric resilience suitable for decades-long habitation in the Saturnian system.

The settlement's atmospheric balance is maintained jointly by two biological systems: the robotic vertical farming network housed in T2 (detailed in the Agricultural Production System section) and the algal photobioreactor array within the Spine Biosynthesis Hub (detailed in the Biosynthesis and Bioprocessing section). Together, these systems absorb approximately 180,000 kg of CO₂ daily and regenerate over 151,000 kg of O₂, providing both primary atmospheric regulation and redundancy against physicochemical system degradation.

Death Protocol and Mortality Management

A feasible long-term space settlement must confront human mortality with the same robustness applied to life support, habitat integrity, or governance. Therefore, mortality management is enacted as an integrated medical, ethical, psychological, and engineering framework, planned for preserving crew safety, social stability, as well as environmental sustainability. The management of human mortality presents unique challenges that transcend terrestrial practices: biological hazard occurrence in a closed environment and psychological effects

within an isolated community. This framework is arranged under the Comprehensive Interstellar Mortality Protocol (CIMP), which systematises procedures, while concomitantly respecting individual dignity, supporting community grieving, and contributing to outpost sustainability. All mortality procedures are overseen by a Settlement Ethics Council operating under a codified legal charter ratified by the habitat's governing body. Death certification, consent verification, and material reintegration are subject to audit and independent oversight.

Upon confirmation of death by the onboard medical personnel, the body is immediately isolated within a sealed containment unit in order to prevent microbial proliferation and atmospheric contamination. Short-term preservation occurs within a cryogenic chamber integrated into the settlement's thermal control scheme, allowing respectful stabilisation with legal documentation, family notification, and ceremonial preparations.

The mortality management procedure consists of four coordinated phases: immediate response, memorial services, the processing of remains, and lastly long-term memorialisation. The immediate response phase prioritises biosafety, procedural clarity, and psychological reinforcement for kith and kin. Funeral services take place inside a dedicated Celestial Memorial Facility, designated for supporting both private and collective grieving and remembrance. The space appointed for ceremonial practice is adaptable, accommodating diverse cultural and spiritual practices, with options for Earth-link participation to alleviate isolation from distant family members. To reinforce social cohesion and shared identity, community rituals, annual remembrance ceremonies, and archival documentation of the deceased's contribution shall be embedded into the settlement's governance framework.

Long-term disposition of remains is overseen by mass efficiency, biohazard prevention, and planetary protection constraints. As both traditional burial and controlled ejection of remains into space are infeasible options due to hazard regulation, the remains undergo a different approach, that being an automated, multi-phase processing system that renders all biological matter chemically stable and sterile. Furthermore, the matter undergoes high temperature pyrolysis and plasma refinement that decompose organic matter while enabling subsequent recovery of mineral and metallic residues. Dignity ought to be ensured; therefore, automated handling bestows procedural invisibility, diminishing distress to the community.

Recovered materials are reintegrated into settlement systems in a manner which preserves symbolic and ethical meaning. Mineral residues are chemically processed into plant-available nutrients that shall be incorporated into horticulture memorial areas, where living plants serve as durable memorials, as well as contribute to food production and air filtration. Metallic materials, such as titanium from medical implants, will be purified and fabricated into representative keepsake objects for friends and family, serving as tangible remembrance without affecting resource efficiency. These practices ensure the transformation of resource recovery as a technical necessity into an emotionally resonant contribution to spiritual viability.

Certain ceremonial dispositions, such as the incorporation of neutral remains into radiation shielding for additional structural application, are allowed, however, under strict regulations, reinforcing the connection between individual sacrifice and the protection of numerous future generations. The incorporation of mineralised remains into radiation shielding serves a symbolic and memorial function rather than a structural necessity, given the negligible contribution to total shielding mass. This option requires informed consent

documented well in advance. The settlement acknowledges that survival in space depends on collective responsibility, framing death as part of the long-standing continuity of human presence. Moreover, for further ethical depth, consent is subject to annual renewal in order to respect evolving personal beliefs, seeing as the decision takes place long before eternal silence.

Psychological support protocols accompany all mortality events. Trained grief counsellors, ritual facilitators and medical staff provide structured, comprehensive support, as well as biometric and behavioural monitoring. By openly embracing death as an inevitable component of interstellar life, the settlement avoids denial-based frailty, fostering resilience, continuity, and meaning.

Altogether, through the integration of medical containment, ethical governance, ceremonial practice, and closed-loop resource management, the mortality protocol ensures that death, while unavoidable, does not threaten the safety, stability, or moral integrity of the settlement. Instead, it metamorphoses into a deeper meaning that honours individual lives while sustaining the communal future.

Nutrition and Meal Planning

The sustainment of human health in an extraterrestrial habitat is paramount. To certify peak human functioning, the settlement employs a methodical nutrition system optimised for metabolic efficiency and long-term disease prevention, as well as cognitive clarity and psychological resilience. Therefore, the dietary system is engineered to ensure both maximal resource yield and meeting the adult Recommended Dietary Allowance (RDA), while adhering to evidence-based astronaut nutrition standards.

Caloric intake is calculated based on an amalgam of reasons: individual body mass, height, body fat percentage, activity level, gender, and age. The settlement maintains 0.9-1.05 g artificial gravity to counteract long-term bone demineralisation, modestly increasing baseline metabolic expenditure. Under slightly elevated artificial gravity (if maintained above 1g), mechanical load modestly increases, with muscles having to work harder for fundamental motor functions, or simply supporting one's bodyweight, maintaining posture, or stabilising joints. To facilitate those needs, caloric intake must proportionally increase to mechanical demand. To briefly explain the mechanism behind increased mechanical exertion, muscle fibre recruitment is increased (if gravity exceeds 1g), especially slow-twitch postural fibres, higher ATP (adenosine triphosphate) turnover, greater bone loading, and elevated cardiovascular workload.

In contrast to a healthy adult's daily caloric intake on Earth, that being around 2000-2500 calories, the settlement's plan ranges between 2500-3000 calories, with a slight increase in calcium, vitamin D, and magnesium, as well as emphasis on omega-3 fatty acids for anti-inflammatory and cardiovascular benefits, and antioxidants. Macronutrient distribution prioritises high-quality protein to mitigate muscle atrophy, complex carbohydrates for metabolic stability, and unsaturated fats for cardiovascular and neurological function.

The production of food relies on a hybrid system that combines shelf-stable reserves with continuous bioregenerative agriculture. Vertical hydroponic modules cultivate leafy greens, legumes, and fruiting crops grown in orchards, while algal bioreactors and fungal cultivars provide additional protein and micronutrients. Nutrient solutions are derived from reclaimed waste streams, closing the biochemical loop.

Meal planning incorporates sensory and gustatory diversity, cultural variation, and periodic novelty to prevent flavour fatigue, a notorious risk factor for the underconsumption of calories in remote environments. Food transcends the barrier of mere sustenance, becoming a social and psychological anchor within the habitat. Microalgal supplementation is cycled to prevent micronutrient excess and flavour fatigue, ensuring metabolic balance and dietary compliance.

This one-day menu delivers roughly 2050–2150 kcal, ~90-100 g protein, ~290 g carbohydrates (including ~44 g fiber), and ~63 g of healthy plant-derived fats. Thanks to biofortified crops and algae-based micronutrients, it comfortably meets all essential vitamin and mineral requirements for an adult in a moderate-activity lifestyle.

Dish Name (Meal)	Ingredients (all sourced from settlement cultivation)	Nutritional Values (per serving)
Titan’s Garden Scramble (Breakfast)	Chlorella-enriched “egg” scramble (made from chickpea flour & algal protein emulating eggs); diced tomatoes, bell peppers, and onions (fresh from hydroponics); herbs (basil, chives).	Calories: ~200 kcal Protein: 12 g Carbs: 18 g (fiber 5 g total: 2 g soluble, 3 g insoluble) Fat: 8 g Vitamins: Rich in vitamin B ₂ and B ₆ , vitamin C Minerals: Iron, Potassium 300 mg.
Sunrise Spirulina Smoothie (Mid-morning Snack)	Hydroponic kale, spinach, and banana; almond milk (from hydroponic almonds); Spirulina powder; flaxseed (oilseed crop); a dash of honey (from colony apiary or syrup from beets).	Calories: ~350 kcal Protein: 15 g Carbs: 45 g (of which ~8 g fiber: 4 g soluble, 4 g insoluble) Fat: 12 g Vitamins: High in vitamin A and K from greens; vitamin C from kale/banana; vitamin B ₁₂ (added via fortified Spirulina) Minerals: Calcium, Iron , Magnesium.
Green Moon Power Stew (Lunch)	Lentils and quinoa; Lab-grown mycoprotein “meat” chunks (fermented fungus akin to Quorn, fed on crop waste); carrots, potatoes, and celery (hydroponic root veggies); garlic and thyme; Spirulina sauce (umami-rich pesto with algae and basil).	Calories: ~600 kcal Protein: 30 g Carbs: 85 g (fiber 15 g: 6 g soluble, 9 g insoluble) Fat: 15 g Vitamins: Excellent in vitamin A, vitamin K, B ₉ and B ₁₂ (added in mycoprotein) Minerals: Iron, Zinc, Calcium, Selenium.
Crunchy Algae Crackers with Hummus (Afternoon Snack)	Algae-infused crackers (wheat, ground spirulina, olive oil from hydroponic olives, salt); hummus made from chickpeas, tahini (sesame), lemon, and garlic.	Calories: ~250 kcal Protein: 8 g Carbs: 30 g (fiber 6 g: mostly insoluble from wheat bran) Fat: 10 g (mostly unsaturated) Vitamins: Vitamin E, B ₁ (Thiamin); Minerals: Iron, Copper, Manganese.

Dish Name (Meal)	Ingredients (all sourced from settlement cultivation)	Nutritional Values (per serving)
Titan's Garden Scramble (Breakfast)	Chlorella-enriched "egg" scramble (made from chickpea flour & algal protein emulating eggs); diced tomatoes, bell peppers, and onions (fresh from hydroponics); herbs (basil, chives).	Calories: ~200 kcal Protein: 12 g Carbs: 18 g (fiber 5 g total: 2 g soluble, 3 g insoluble) Fat: 8 g Vitamins: Rich in vitamin B ₂ and B ₆ , vitamin C Minerals: Iron, Potassium 300 mg.
Saturn Stir-Fry (Dinner)	Stir-fried Asian greens (bok choy, napa cabbage, broccoli, and edamame) and fresh fish fillet seasoned with ginger-soy sauce, served over golden rice (CRISPR-enriched, high in β -carotene) and topped with roasted peanuts.	Calories: ~650 kcal Protein: 34 g Carbs: 80 g (fiber 10 g: 4 g soluble, 6 g insoluble) Fat: 18 g Vitamins: High in vitamin C, vitamin A (from Golden rice β -carotene), vitamin K, and a range of B vitamins from fermentation; Minerals: Magnesium, Iron, Calcium, Omega-3

Microalgal and supplemental vitamins are cycled and monitored to prevent excess intake of vitamin D and omega-3 fatty acids, ensuring all nutrients remain within safe and evidence-based ranges. Automated meal assembly with ingredient-level tracking prevents allergic reactions; parallel production lines with dedicated equipment also satisfy religious requirements (kosher, halal); AI-driven nutritional monitoring provides real-time deficiency flagging.

Artificial Hibernation and Torpor Systems

Artificial hibernation is a cornerstone technology for the settlement, enabling extensive metabolic suppression with all-encompassing physiological recovery. In contrast to speculative cryogenic preservation, despite not having been officially clinically validated yet, controlled metabolic suppression in the 32-34 degrees C range has been demonstrated in therapeutic contexts for short-term clinical applications, though long-term human validation remains experimental. Torpor is incorporated through a multi-modal protocol that combines:

- Pharmacological modulation - sustained low-dose melatonin with targeted adenosine and opioid pathway regulation in order to suppress sympathetic activity and reduce thermogenesis.
- Gradual thermal reduction - the reduction of core temperature from 37 degrees C to approximately 32 degrees C in the span of 4-6 hours to prevent arrhythmias and shivering. It is currently limited to short-duration critical applications (in ICU conditions for 24-72 hours).
- AI-regulated monitoring - continuous real-time tracking of cardiovascular stability, metabolic rate, oxygen consumption, and arousal readiness.

A metabolic decrease to approximately 25-30% of the baseline is derived from comparative mammalian torpor models; not yet validated in long-term human trials - resulting in an average of around 70-75% reduction in oxygen consumption, caloric demand, CO₂ production, water use, and thermal control load.

The primary challenge of prolonged immobility, such as muscular atrophy, bone demineralisation, and cardiovascular conditioning, is mitigated through full body electrical muscle stimulation (EMS) performed multiple times throughout the day, pharmacological bone preservation protocols, and closed-loop glucose and nutrient infusion. Animal studies have demonstrated extended torpor periods with high survival rates and neurological recovery; however, long-duration human application remains experimental. The torpor system serves four major roles:

- Resource optimisation - discretionary cyclic torpor reduces life-support demand, allowing a 180,000-person settlement to temporarily function at the equivalent load of ~41,400 active inhabitants, if up to 75% of the population enters staggered torpor cycles. While metabolic suppression drastically reduces consumable demand, baseline infrastructural loads, thermal regulation, computational systems, and structural support, remain constant, moderating total energy savings.

- Emergency Survival Mode - extends survivability during life-support degradation by significantly lowering metabolic requirements.

- Medical Stabilisation - protects organs during trauma, surgery, or critical illness.

- Exploration and Transit - reduces consumables mass and radiation exposure during long-term expeditions.

Additionally, reduced metabolic activity may offer limited intrinsic radioprotective effects, as lower cellular division rates and decreased free-radical production may modestly reduce oxidative damage, though it does not eliminate ionising radiation effects, especially relevant due to Saturn's high-radiation environment. Crew members enter torpor in staggered cycles, ensuring continuous operational oversight of the settlement

Medical System and Healthcare Infrastructure

Medical autonomy constitutes a non-negotiable criterion within a Saturn-orbit settlement. Due to communication latency of 65-90 minutes each way, real-time terrestrial intervention during critical events, and evacuation to Earth is impossible, healthcare is engineered as a fully independent, AI-augmented, crew-operable system designed to transform medicine from a logistical vulnerability into a fundamental pillar of long-term habitation.

The Saturn Medical Network (SMN) serves a population of 180,000 inhabitants through a distributed, prevention-centred framework that rejects the traditional terrestrial model of hospital-centric care. Rather than concentrating resources in a few overloaded facilities, SMN lodges diagnostic and health monitoring in day-to-day life, enabling pre-emptive intervention in an environment where delayed interference can be lethal. SMN operates across five incorporated tiers:

- ★ Tier 1 - AI Diagnostic Kiosks (1,800 units): Each kiosk serves approximately 100 inhabitants as the first point of contact, providing symptom assessment, vital sign acquisition (heart rate, blood pressure, body

temperature, respiratory rate, oxygen saturation), point-of-care testing (blood glucose, urinalysis, infectious disease tests, cholesterol/electrolyte checks), and telemedical consultation initiation. The high kiosk density reflects a prevention-centred model prioritising continuous biosurveillance.

- ★ Tier 2 - Community Health Centres (90 centres): Delivering primary care (routine check-ups, vaccinations), chronic disease management, minor procedures (wound care, suturing, injections), and psychological care (counselling, stress management, crisis intervention) for roughly 2,000 residents each.
- ★ Tier 3 - District Medical Centres (18 centres): Serving ~10,000 residents each, providing emergency care, imaging (X-rays, CT scans, ultrasounds), laboratory services (blood panels), and specialty consultation (cardiology, neurology, dermatology).
- ★ Tier 4 - Central Hospital (1 facility): The biomedical core housing advanced surgery (robotic-assisted, neurosurgery, cardiac), intensive care (ICU, ECMO, ventilation), complex diagnostics (MRI, PET scans with on-site radioisotope production), and clinical trials under strict regulatory oversight.
- ★ Tier 5 - Earth Link: Telemedical specialist consultation (telecardiology, remote neurosurgery planning, rare disease), second opinions (oncology, complex surgical review), and training (procedural demonstrations, asynchronous case study, remote robotic surgery training).

All residents wear integrated biosensors synchronised with environmental monitoring systems. Detected physiological deviations trigger early-warning scores and automated recommendations (medication adjustment, activity modification, hydration protocols). Predictive applications include early cardiovascular risk recognition, prevention of metabolic decompensation, pre-symptomatic outbreak detection, mental health crisis mitigation, and musculoskeletal injury prevention. Escalation to human providers occurs automatically upon exceeding thresholds, shifting medicine from reactive care to proactive, resilience-focused approaches.

Despite the emphasis on prevention, SMN maintains advanced tertiary capabilities. The Central Hospital houses twelve operating rooms, reinforced with modified robotic surgical platforms that can withstand both microgravity and variable artificial gravity. Earth-based specialists provide asynchronous advisory input, with local robotic systems fully controlled by on-site surgeons. Autonomous subroutines perform standardised tasks such as suturing, cauterisation, and instrument exchange under physician oversight. Capabilities include minimally invasive general surgery, cardiac procedures with ECMO support, image-guided neurosurgery, orthopaedic fixation adapted to altered bone density, and emergency trauma care.

Closed-circuit anaesthesia systems recycle volatile agents, reducing consumable use by up to 95%. Stable drug concentrations with real-time depth monitoring are maintained by target-controlled infusion. Emergency management includes video laryngoscopy, surgical airway capability, and extracorporeal membrane Page 19 oxygenation for refractory cases. Radiation-hardened electronics and redundant power systems ensure operational continuity during solar events and magnetospheric radiation spikes.

Notwithstanding the operational autonomy, the settlement remains intellectually connected to Earth's medical ecosystem at all times. High-gain communication arrays enable clinical-grade consultation, though latency is unsuitable for real-time intervention; however, it enables asynchronous reviews for complex case planning. AI-assisted preprocessing summarises diagnostic data before transmission, enhancing bandwidth efficiency. Advanced telemedicine platforms ensure both physiological and psychological welfare, contributing to mental health support through immersive therapy addressing isolation stress, confinement anxiety, and Earth nostalgia.

As a consequence of the settlement's isolation, pharmaceutical inventories concentrate on radiation stability and prolonged shelf life. Compact, modular production units enable on-site preparation and customisation of essential medicines, guaranteeing uninterrupted treatment even in case of prolonged communication disruption.

Through distributed AI diagnostics, predictive biosurveillance, robotic surgical precision, Earth-linked expertise, and holistic wellness integration, the Saturn Medical Network ensures that even in extreme isolation, a population of 180,000 remains medically resilient. Healthcare becomes not merely an emergency response system, but an infrastructural backbone of civilization in orbit.

Beyond managing diseases, SMN integrates wellness efficiency through coordinated nutrition planning, gravity-adapted exercise prescription, circadian lighting regulation, social-connection algorithms, and comprehensive educational engagement. By integrating physiological, psychological, as well as social determinants of health, the system aims to exceed terrestrial health-adjusted life expectancy benchmarks.

Employment and work sectors

Within the ship's ecosystem, all adults aged 19–64 will work in domains essential to the functioning of both the vessel and the city it contains. Their work will be supported by advanced automation and a comprehensive robotics system; nevertheless, humans will remain the primary drivers of onboard operations. In total, there will be 121460 adults working, distributed across 15 main domains:

1. 14429 adults (12%) in infrastructure, maintenance, and inspections

A high degree of automation and robotics requires rigorous maintenance and repair capacity. Any malfunction must be addressed with precision to avoid disrupting the functioning of the entire city. Personnel in this domain require substantial backgrounds in engineering and applied research.

2. 9619 adults (8%) in life support (water & air)

A significant share of adults will be dedicated to maintaining and continuously verifying critical life-support resources generated onboard. These resources are essential for human survival, making robust systems and constant oversight indispensable.

3. 6012 adults (5%) in energy production

Energy production is non-negotiable in any human settlement. While automation will handle many routine tasks, human supervision and inspection remain necessary to ensure stable power delivery across all sectors.

4. 9619 adults (8%) in food systems

Food production in space, within an autonomous spaceship, is highly complex. This domain therefore requires specialists in agriculture, food safety, and nutrition, covering the entire chain from production through processing and distribution to consumption.

5. 8417 adults (7%) in production & manufacturing

Although automation dominates manufacturing, human expertise remains essential for design, quality control, and continuous optimization. This includes both everyday goods for residents and critical materials and components required for ship upkeep.

6. 9620 adults (8%) in information technology

High onboard automation demands a strong cadre of specialists in control systems, cybersecurity, and data analysis. They will develop and maintain operational software and ensure cyber-integrity across critical infrastructure.

7. 4810 adults (4%) in logistics & management

Even if internal transport is largely robotized, humans are required to ensure traceability, planning, and exception handling. Any logistical bottleneck can slow critical sectors or reduce quality of life for residents.

8. 10822 adults (9%) in healthcare

This domain requires heightened attention, as a closed artificial habitat can accelerate the spread of disease and amplify stress. Particular emphasis must be placed on paediatrics, to support children's physiological adaptation to space conditions, and on mental health, to prevent outcomes that could reduce wellbeing and performance.

9. 9619 adults (8%) in education & mentorship

The onboard education system will be carefully developed. Specialists will build children's foundational competencies, while mentors support each professional domain within the city. Roles may be full-time, such as teachers, or part-time, such as domain-specific mentors.

10. 12040 adults (10%) in services & hospitality

While this sector can be heavily automated and robotics will provide substantial support, human interaction is invaluable for residents. Maintaining a strong hospitality component is therefore vital to creating an experience as comparable as possible to life on Earth.

11. 4810 adults (4%) in governance & administration

In a context of limited resources, clear rules and a well-structured administration are essential. We allocate a limited number of positions to avoid excessive bureaucracy, while ensuring transparency and robust administrative and legal mechanisms.

12. 4810 adults (4%) safety & emergencies

A dedicated segment of the population will serve in security and emergency response, both to detect irregularities and to respond to emergencies such as fires or depressurization events.

13. 6012 adults (5%) in research & development

Because our mission is long-duration, we have to also plan for future innovation. We therefore envisage a research team to assess potential resources in our operational region of space and to drive technological upgrades to onboard systems, keeping pace with progress and addressing emerging challenges.

14. 7214 adults (6%) in culture & sport

Leisure is essential to human wellbeing regardless of environment, reflecting the inherently social nature of humanity. A moderate number of people will work in this sector to provide cultural and athletic events aligned with residents' interests.

15. 3607 adults (3%) in cross-sector management


While this function has no direct equivalent on Earth at the same scale, it is crucial for life in space. In a limited environment, coordination between sectors is essential; therefore, dedicated personnel will ensure competent operational management and smooth inter-sector collaboration. These 15 domains cover the majority of the ship's and residents' needs, ensuring not only functional survival but also a supportive environment for long-term development. Although the percentages are estimates, they provide a clear reference point for planning and recruitment.

Housing

No matter where you are, on Earth or in space, the human need for a place to stay, to play, even to create is among the most basic. For this reason, we really did not want to neglect the aspect of designing comfortable, sustainable homes for our population, so we came up with two blueprints for the two different types of homes available. The high population density of our settlement (16.000 /km²) does not allow for low residential zoning. To fit everyone, (both habitable tori taken into consideration) we calculated a plan for roughly 50000 units of 2 or 3 bedroom apartments, with an average of 3.6 people per apartment. This will translate to about 1660 five story buildings, with 6 apartments on every floor.

Being the ones giving out the homes, we took the liberty of designing them however we saw fit. This does not mean, however, that our residents will not be able to reshape and add their own personalities to their places, once everything settles down and society begins thriving on our space utopia.

2 bedroom apartment sketch 102 m² built area, 76 m² usable area, 2.9 m² balcony



3 bedroom apartment sketch: 07 m² built area, 80.5 m² usable area, 2.9 m² balcony



Self produced using SketchUp

Government

No society can exist without a form of government. To enhance operational efficiency aboard the vessel, we will develop an optimized governance framework that safeguards order and institutional coherence without becoming excessively bureaucratic. Accordingly, the system will be organized around two principal governing bodies: the Executive Council and the Citizens' Chamber.

a) Executive Council

The Executive Council constitutes the highest decision-making authority on the ship and is composed of seven members, each serving a four-year term. Its responsibilities include drafting quarterly development plans, submitting for vote the proposals originating from the Citizens' Chamber, and reviewing activity reports in order to identify opportunities to improve the ship's vital systems and overall performance.

Each member is assigned a field, as follows:

1. Life Support
2. Energy and Infrastructure
3. Food Systems and Biosecurity
4. Health and Wellbeing
5. IT and Automation
6. Logistics and Production
7. Education and Social Cohesion

Members of the Executive Council are elected within the Citizens' Chamber by an absolute majority of votes. Eligibility requirements include: holding a recognized certification in the targeted field, a minimum of five years of professional experience in that field, and at least two terms served in the Citizens' Chamber within the previous ten years (with the inaugural Executive Council being exempt from this requirement).

Candidates must sit an examination designed to assess both domain knowledge and leadership capacity. A minimum score of 75% is required to advance to the next stage. The subsequent stage consists of formally submitting a candidacy package that includes a Development Strategy and a four-year Action Plan for the chosen sector. These documents are voted on sequentially in the Citizens' Chamber. To advance to the final round, candidates must obtain at least 50% plus one vote, with a maximum of five candidates per sector permitted to proceed.

At this point, finalists participate in an electoral session in the Citizens' Chamber, during which they may deliver a speech of up to ten minutes and answer up to ten questions from delegates. Voting then takes place, and one person per sector assumes office based on the number of votes received.

After completing a four-year mandate, members may stand for immediate re-election. After a second consecutive term, however, they may not run again until the next electoral cycle following an additional four-year interval, in order to ensure meaningful rotation in office. No individual may serve more than three terms in total. Members may be removed from office at any time if a motion to that effect is approved by more than two-thirds of the ship's adult population.

The Executive Council serves as the central command point for governance decisions. Each member is empowered to submit directly, for vote in the Citizens' Chamber, projects designed to modify or improve elements within their own sector. For proposals that concern two or more sectors, deliberation and voting take

place within the Executive Council, and the proposal may advance only if it secures at least four votes. In emergency situations, the Executive Council is authorized to take immediate decisions and directly coordinate the Safety and Emergency Response function.

b) Citizens' Chamber

The Citizens' Chamber is an executive-consultative body that operates primarily "in the field" and collects suggestions and feedback from the ship's residents. It consists of 120 delegates who are likewise distributed across the 15 work sectors, with the purpose of inspecting activity and producing reports on what does not function properly and what could be improved.

These reports are transmitted to the Executive Council, which returns with implementation proposals that are then voted on within the Citizens' Chamber. The Citizens' Chamber also serves as the decision-making forum for electing members of the Executive Council, whose mandates are staggered, ensuring that the team changes gradually over time.

Members of the Citizens' Chamber are elected every six months within the sector they wish to represent. They must have at least two years of experience in the relevant field and must be nominated by their professional peers. After each six-month term, members return to their original work sector to help implement and operationalize the strategies and improvements identified during their mandate. They may subsequently run again after every two terms, with a maximum of ten terms in total.

The role of this body is to remain closely connected to day-to-day operations across all sectors. Frequent rotation brings a wider diversity of perspectives into the Chamber's reports, thereby increasing representativeness within each sector. The structured opportunity for members to return to their original positions after each mandate enables them to re-enter the workforce with a refreshed perspective and to introduce practical governance insights into operational environments. Moreover, the high degree of rotation allows a larger share of the adult population to participate in ship governance, thereby strengthening the democratic legitimacy of decisions of highest importance.

Conclusion

This interdependent governance system, while seemingly complex, substantially reduces the risk of power consolidation, since modifying or advancing a project requires multiple procedural steps and distinct approvals. Furthermore, the frequent turnover within the Citizens' Chamber generates a valuable surplus of perspectives and sector-specific feedback, increasing representativeness and improving problem detection. This dynamic is balanced by the stability provided by the Executive Council's four-year terms, which allow sufficient time to implement strategy while systematically integrating the diverse inputs produced through the Citizens' Chamber into increasingly well-calibrated proposals.

Education

As noted in the recruitment strategy, our initial objective is to embark highly qualified specialists across every critical domain in order to ensure the ship's reliable performance during its formative years. However, sustaining, and ultimately elevating, this level of professionalism requires the implementation of a robust

educational system capable of shaping disciplined future citizens equipped with practical competencies tailored to the space-based ecosystem in which we live.

The educational system will be organized into three core cycles, followed by a specialized final cycle for students pursuing the Academic Track:

a) Primary Cycle (ages 5–9)

Children encounter formal schooling for the first time and, through a predominantly playful and exploratory pedagogy, acquire foundational concepts in mathematics, science, culture, and, importantly, life aboard the ship. Learning will be strongly practice-oriented and game-based. The curriculum will also include frequent events centered on the cultural heritage of human civilization, helping children remain anchored to their roots despite the unprecedented environment.

b) Secondary Cycle (ages 9–13)

As students mature, they begin to grasp the ship's operational logic and deepen their knowledge through a more technical and information-rich approach. On the theoretical side, they study the physical principles underpinning life in space, the functioning of the ship-city, and the fundamentals of all key domains described above. On the practical side, they acquire emergency-response techniques, participate in governance simulations, and continue building competencies across essential sectors.

Physical activity becomes compulsory and is formally embedded in the curriculum, with at least one hour per day dedicated to the sport chosen by the student. At the end of this cycle, students sit a comprehensive examination covering all subjects studied thus far. Based on their results and personal preferences, they are assigned to the tertiary cycle.

c) Tertiary Cycle (ages 13–16)

This cycle branches into two pathways, determined by the student's secondary-cycle results and individual choice:

- Academic Track (for fields such as medicine, engineering, computer science, education, governance)

Students select five sectors in which they wish to specialize, with priority granted to those who achieved higher examination scores. During this period, they pursue advanced knowledge in each chosen sector and complete a practical module for each, enabling them to experience real working environments, engage directly with domain experts, and develop a clearer sense of their future professional direction.

Students may choose to replace one or more selected sectors by sitting an equivalency examination, provided that corresponding transfers occur in both directions so that capacity constraints remain balanced. At the end of the cycle, students select two sectors for final assessment, consisting of an advanced examination for the first option and a foundational examination for the second. The minimum passing threshold is 75 percent for both. If the threshold is not met, the student completes an additional year within the same cycle and may retake the examinations at the end of that year.

- Operational Track (for fields such as maintenance, manufacturing, agriculture, logistics, hospitality)

Students enter directly into an apprenticeship-centered pathway complemented by technical instruction specific to operational domains. Each student is assigned a mentor who provides continuous guidance. At the end of the cycle, students sit a dual assessment comprising both theoretical and practical components. Based on these results, they select the specific role they intend to pursue. To pass, a minimum score of 60 percent is required. Students who do not meet the threshold complete an additional apprenticeship year under close supervision and may retake the examination.

d) Final Cycle (ages 16–19, Academic Track only)

This cycle consists of an intensive, highly structured practicum. Each student is assigned an individual mentor and works in a one-to-one format to acquire the full set of competencies required for professional practice in the chosen field. The program focuses exclusively on that sector and closely related subjects. Completion requires both a theoretical final examination and a research paper. The minimum passing grade is 65 percent, while the final score directly determines the student's initial career placement and progression level within the sector. During this period, students may switch between options; however, the final examination will be conducted solely in the selected domain.

In parallel, students who followed the Operational Track begin a paid apprenticeship placement, serving as assistants within their selected field. By the age of 19, regardless of pathway, all individuals enter standard employment status, contributing directly to the ship's economy and ensuring that generational turnover occurs organically and continuously.

Although demanding, this educational framework ensures coherent child development and close monitoring of student progress across all stages. Moreover, at each cycle, learners will have access to advanced technological resources, including robotics and artificial intelligence, which will support balanced development and enable the acquisition of knowledge and practical skills as efficiently as possible.

Entertainment

To strengthen social cohesion, any city must include dedicated entertainment hubs where residents can step outside the routine of daily life and engage meaningfully with fellow citizens. Onboard, these hubs will be organized into two main categories.

1) Sports-oriented hubs

Although artificial gravity constrains certain everyday activities familiar from Earth, we will adapt traditional sports to the ship's conditions in order to provide residents with consistent opportunities to maintain healthy, active lifestyles. The settlement will therefore include facilities for football, basketball, volleyball, padel, futsal, and athletics, all of which remain largely compatible with the vessel's artificial-gravity environment. Every resident will be able to participate in leisure sport and friendly competitions, while students will engage in structured physical activity as part of the compulsory curriculum.

Innovation, however, lies in a flagship athletic concept that treats artificial gravity not as a limitation, but as a competitive advantage. We will develop an “Exatlon-style” tournament in which the arena is segmented into multiple decks, each calibrated to a distinct gravity level, and interconnected by dedicated corridors. Our proposed configuration is as follows:

- 0.7g: Parkour
- 0.8g: Volleyball
- 0.9g: Futsal
- 1.0g: Gymnastics

By staging disciplines under gravity conditions slightly lower or higher than Earth-standard gravity and the ship’s nominal living areas, the tournament will substantially amplify motivation, novelty, and athletic engagement. The competition will be held in a structured format and organized monthly, with teams of 10 to 12 participants competing in the order of registration for that month. It will constitute an intriguing contest of coordination, balance, speed, and endurance, in which adaptability becomes paramount and participants are tested in less conventional human capabilities. In doing so, we believe the program will elevate interest in sport and foster a healthier onboard environment overall.

2) Cultural hubs

On the cultural front, our aim is to replicate as faithfully as possible the civic life of an Earth-based city. We will host weekly theatre performances, maintain a cinema, establish a museum, and support a wide range of social clubs. In addition, we will introduce a Gastronomy Week, during which any interested residents may contribute signature dishes representative of their cultural heritage. This initiative will help preserve a substantial portion of Earth’s cultural diversity, particularly given that the mission will begin with individuals drawn from many nationalities.

Innovation will be most visible in the musical sphere, where we intend to organize concerts and festivals with a distinctly unique character. While we will actively promote local ensembles and emerging talent, particularly in opening acts, major events will also feature holographic artistic segments that recreate iconic musical performances by artists from Earth. In this way, we will offer something singular aboard the ship while enabling residents to maintain an emotional and cultural connection with the music that has shaped humanity on its home planet.

Special Scenarios

No matter how rigorously we engineer the ship’s safety, we must acknowledge that we are operating in space, within a region never before explored by humankind. Consequently, we must adopt comprehensive precautionary measures to ensure that, should an unforeseen emergency arise, the ship’s residents remain protected. To this end, we will implement an extremely intuitive emergency code through which citizens, regardless of age, will immediately understand how to respond in any critical situation. This code will be taught from the earliest years, both within families and throughout the primary cycle of school.

The code will consist of three colour levels, followed, when relevant, by a symbol:

a) RED: major emergency

All individuals must immediately cease their current activity and follow the emergency signals.

1. FIRE symbol + Zone: A fire has occurred either across the ship or within a specified area, which will be clearly indicated. All citizens must proceed to the nearest Refuge Room, a compartment specifically designed to provide protection against fire and smoke.
2. PRESSURE symbol: A depressurisation event has occurred. All citizens must take a mask from a mask box if one is located within seven metres, and then move promptly to the nearest Safe Room, a compartment maintained at emergency pressure standards.
3. GAS symbol: A toxic gas release has occurred. All citizens must take a mask from the nearest mask box and proceed rapidly to the nearest Refuge Room.
4. BIO symbol: A microbiological incident has occurred, involving contamination of a vital substance. All citizens must lock themselves inside their own room, provided it is not within the contaminated area, and await further instructions.
5. POWER symbol: A major blackout has occurred. All citizens must activate the flashlight function on their personal device and await further instructions.
6. SPIN symbol: An anomaly has occurred in the ship's normal rotation, potentially affecting artificial gravity and overall onboard stability. All citizens must sit down and hold on to the nearest stable point of support.

b) AMBER: moderate emergency

All individuals must stop non-essential activities and proceed to the designated assembly point, where a director from the Emergency Department will provide additional instructions. During this period, citizens must remain prepared to execute major emergency procedures if the situation escalates.

c) GREEN: emergency successfully concluded

This signal is displayed only after a RED or AMBER emergency, informing citizens that normal activity may safely resume. Until GREEN is issued, all individuals must continue to comply with the emergency regime.

This code is designed to prevent onboard tragedies by ensuring efficient communication through messages that are comprehensible to all age groups. In addition, periodic emergency simulations will be conducted in order to test citizens' capacity to respond effectively under conditions of risk.

Economy

More than an ordinary city, our spaceship requires a well-functioning economic system capable of ensuring its long-term sustainable development. Our objective is to guarantee not only the survival of all citizens, but also the existence of a free market that preserves a regulated and responsibly managed private sector.

To eliminate the economic instability that any existing terrestrial currency may experience, we will establish our own digital currency to support the ship's internal economic ecosystem. This currency will operate dynamically, adjusting citizens' purchasing power in accordance with the vessel's needs. For example, in a context where the settlement is resource-abundant and stable, the currency will hold greater value, enabling the acquisition of luxury goods and leisure services. Conversely, in times of crisis, purchasing power allocated to non-essential goods will decrease and be redirected toward essential goods vital to survival. This dynamic taxation and monetary adjustment mechanism will prevent inflation, the principal threat to a healthy economy, while fostering collective responsibility for maintaining the vessel's safety and ensuring that earned income retains and even increases its value.

Every adult citizen will also receive a salary, with a guaranteed minimum income sufficient to ensure a decent standard of living and to cover vital resources. Additional compensation will reflect the complexity of the profession performed, the level of education attained, years of professional experience, and any roles held within the ship's governance or management structures. All such contributions will be appropriately rewarded, allowing citizens to improve their standard of living in proportion to their efforts and achievements. Individuals operating within the private sector will likewise receive the minimum guaranteed income, with the opportunity to increase their earnings through the sale of goods or services. In this way, we ensure that no citizen experiences poverty while simultaneously fostering a meritocratic free market in which individuals are compensated proportionally to demonstrated skills and may allocate their income toward cultural, sporting, or recreational pursuits.

Through this mechanism, we will lay the foundations of an emergent economic system capable of generating stability from the vessel's earliest years. Over time, its inherent dynamism will allow for the necessary adjustments in response to the evolving needs of both the ship and its citizens.

Appendix

Github repo with C++ code written for calculating general info about the ship as well as a surface analyser to compliment our asteroid mining project:

https://github.com/rramond/NSS-26/tree/main/NSS26_COMP_CODE

Bibliography

Works Cited

1. NASA. Environmental Control and Life Support System (ECLSS) Overview. NASA, <https://www.nasa.gov/reference/environmental-control-and-life-support-system-eclss/>.
2. NASA. International Space Station Environmental Control and Life Support System. NASA Technical Reports Server (NTRS), <https://ntrs.nasa.gov/>.
3. European Space Agency. MELiSSA – Micro-Ecological Life Support System Alternative. ESA, https://www.esa.int/Enabling_Support/Space_Engineering_Technology/MELiSSA.
4. NASA. Sabatier Reactor Technology for CO₂ Reduction. NASA, https://www.nasa.gov/mission_pages/station/research/experiments/explorer/Investigation.html?#id=788.
5. NASA. Trace Contaminant Control Subassembly (TCCS). NASA, https://www.nasa.gov/mission_pages/station/research/experiments/explorer/Facility.html?#id=682.
6. World Health Organization. Vitamin and Mineral Requirements in Human Nutrition. 2nd ed., WHO Press, 2004, <https://www.who.int/publications/i/item/9241546123>.
7. National Academies of Sciences, Engineering, and Medicine. Dietary Reference Intakes for Calcium and Vitamin D. National Academies Press, 2011, <https://doi.org/10.17226/13050>.
8. NASA. Human Integration Design Handbook (HIDH). NASA, 2014, <https://www.nasa.gov/human-integration-design-handbook/>.
9. Putcha, Lakshmi, et al. "Pharmacology and Therapeutics in Space." *Journal of Clinical Pharmacology*, vol. 44, no. 8, 2004, <https://doi.org/10.1177/0091270004268038>.
10. Cerri, Matteo, et al. "Induction of a Torpor-Like State by Central Adenosine A1 Receptor Activation." *Journal of Neuroscience*, vol. 33, no. 36, 2013, <https://www.jneurosci.org/content/33/36/14512>.
11. National Institutes of Health. Therapeutic Hypothermia After Cardiac Arrest. NIH, <https://www.ncbi.nlm.nih.gov/books/>.
12. NASA. Artificial Gravity as a Countermeasure in Human Spaceflight. NASA Technical Reports Server, <https://ntrs.nasa.gov/>.
13. Centers for Disease Control and Prevention. Healthcare Infection Control Practices Advisory Committee Guidelines. CDC, <https://www.cdc.gov/infectioncontrol/>.
14. NASA. Closed-Loop Waste Management and Water Recovery Systems on ISS. NASA, https://www.nasa.gov/mission_pages/station/research/technology/.
15. Extracorporeal Life Support Organization. ELSO Guidelines for Adult Respiratory Failure. ELSO, <https://www.else.org/resources/guidelines.aspx>.
16. https://ajsr.org/wp-content/uploads/journal/published_paper/volume-3/issue-5/ajsr2025_NgbwpREz.pdf
17. Comparative Table: Traditional vs. Vertical Farming—Resource Use and Yields (Estimated, 2026)." *Farmonaut*, 7 Jan. 2026, <https://farmonaut.com/blogs/vertical-farming-uses-90-less-water-in-2026>.
18. AutoStore. "10 AutoStore Robots Use the Same Amount of Energy as 1 Vacuum Cleaner." AutoStore Technology Documentation, <https://www.autostoresystem.com>.
19. Crocker, Sara. "Avondale Vertical Farm Grows Greens in High-Tech Warehouse." *Phoenix New Times*, 19 May 2025,

<https://www.phoenixnewtimes.com/food-drink/avondale-vertical-farm-grows-greens-inside-wa-rehouse-21750103/>.

20. AutoStore. "Router: The Brain of the AutoStore System." AutoStore Product Documentation, AutoStore.
21. "Vertical Farming Energy 2026: The Race for Grid Parity." Energy Solutions, 10 Jan. 2026, <https://energy-solutions.co/articles/sub/vertical-farming-energy-optimization-market-intelligence-2027>.
22. Zhu, Xin-Guang, and Leo Marcelis. "Vertical farming for crop production." WUR eDepot, <https://edepot.wur.nl/639319>.
23. NASA Jet Propulsion Laboratory. (n.d.). Cassini–Huygens Mission to Saturn and Titan.
24. <https://solarsystem.nasa.gov/missions/cassini/overview/> — Primary data source for Titan's lakes, atmosphere, and composition.
25. ESA. (2005). Huygens Probe Results: Titan Surface and Atmosphere.
26. <https://www.esa.in> — Surface composition and methane cycle information.
27. Lorenz, R. D., & Mitton, J. (2010). Titan Unveiled: Saturn's Mysterious Moon Explored. Princeton University Press.— Detailed scientific background on Titan's geography and hydrocarbons.
28. NASA Planetary Data System (PDS). <https://pds.nasa.gov> — Technical planetary composition datasets.
29. NASA. (2023). Deep Space Optical Communications (DSOC). <https://www.nasa.gov>
30. NASA. (2013). Lunar Laser Communication Demonstration (LLCD).— First high-rate laser comm demonstration.
31. NASA. (2021). Laser Communications Relay Demonstration (LCRD).— Optical relay architecture.
32. NASA Space Communications and Navigation (SCaN). <https://www.nasa.gov/scan>
33. NASA. (n.d.). Radiation Protection for Human Spaceflight. <https://www.nasa.gov>