

Booking API Documentation - Complete Reference

Base URL

/api/bookings/

Authentication

All endpoints require JWT authentication. Include the token in the Authorization header:

Authorization: Bearer <your_jwt_token>

Role-Based Access Control

Regular User (Role: USER)

- Can create bookings
- Can view own bookings only
- Can cancel own pending bookings
- Can view statistics for own bookings

Company Owner (Role: OWNER)

- Cannot create bookings
- Can view all bookings belonging to their company's trips
- Can cancel any pending booking from their company
- Can view statistics for their company's bookings

Blocked Operations

- Direct updates via PUT/PATCH are forbidden for all roles
- DELETE operations are forbidden for all roles
- Use the cancel endpoint instead for status changes

Endpoint 1: Create Booking

POST /api/bookings/

Allowed Roles: Regular User only

Request Body:

```
json
{
  "trip": 12,
  "seat_ids": [1, 3],
  "passengers": [
    {
      "first_name": "Ali",
      "last_name": "Ahmadi",
      "national_code": "1234567890",
      "phone": "09123456789"
    },
    {
      "first_name": "Reza",
      "last_name": "Ahmadi",
      "national_code": "1234567891",
      "phone": "09123456788"
    }
  ]
}
```

Field Descriptions:

- trip (integer, required): ID of the trip to book
- seat_ids (array of integers, required): List of seat IDs to reserve
- passengers (array of objects, required): Passenger information for each seat
 - first_name (string, required): Passenger's first name
 - last_name (string, required): Passenger's last name
 - national_code (string, required): Valid national identification code

- phone (string, required): Contact phone number

Validation Rules:

- Number of seats must match number of passengers
- Each seat must be available (not already booked or pending)
- Each passenger must include all required fields
- Seats must belong to the specified trip's bus

Response (201 Created):

json

```
{  
  "id": 55,  
  "user": 5,  
  "expires_at": "2026-05-30T08:10:00Z",  
  "status": "pending_payment",  
  "total_price": "900000.00",  
  "trip": 12  
}
```

Response Fields:

- id: Unique booking identifier
- user: ID of the user who created the booking
- expires_at: ISO 8601 timestamp when booking expires (10 minutes from creation)
- status: Always "pending_payment" for new bookings
- total_price: Calculated total based on trip price × number of passengers
- trip: ID of the booked trip

Error Responses:

- **400 Bad Request:** Validation error (seat unavailable, missing fields, count mismatch)

- **401 Unauthorized:** Missing or invalid JWT token
 - **403 Forbidden:** User is not a regular user (company owner trying to create)
-

Endpoint 2: List Bookings

GET /api/bookings/

Allowed Roles: Regular User (own bookings) OR Company Owner (company bookings)

Query Parameters (all optional):

- `status` (string): Filter by booking status (pending_payment, paid, canceled, expired)
- `from_date` (date): Filter bookings created on or after this date (YYYY-MM-DD)
- `to_date` (date): Filter bookings created on or before this date (YYYY-MM-DD)
- `page` (integer): Page number for pagination
- `page_size` (integer): Number of items per page (default: 100)

Response (200 OK):

json

```
{
  "count": 10,
  "next": "http://api.example.com/api/bookings/?page=2",
  "previous": null,
  "results": [
    {
      "id": 55,
      "user": 5,
      "expires_at": "2026-05-30T08:10:00Z",
      "status": "pending_payment",
      "total_price": "900000.00",
      "trip": 12
    }
  ]
}
```

```
    },  
    {  
      "id": 56,  
      "user": 5,  
      "expires_at": "2026-05-29T15:30:00Z",  
      "status": "paid",  
      "total_price": "450000.00",  
      "trip": 13  
    }  
  ]  
}
```

Behavior by Role:

- **Regular User:** Returns only bookings belonging to the authenticated user
- **Company Owner:** Returns only bookings for trips belonging to the owner's company

Endpoint 3: Retrieve Single Booking

GET /api/bookings/{id}/

Allowed Roles: Regular User (own bookings) OR Company Owner (company bookings)

URL Parameters:

- id (integer, required): Booking ID

Response (200 OK):

```
json  
  
{  
  "id": 55,  
  "user": 5,  
  "expires_at": "2026-05-30T08:10:00Z",
```

```
"status": "pending_payment",  
"total_price": "900000.00",  
"price_at_booking": "450000.00",  
"created_at": "2026-05-30T08:00:00Z",  
"trip": 12  
}
```

Additional Response Fields (compared to list):

- **price_at_booking:** Price per seat at time of booking
- **created_at:** ISO 8601 timestamp when booking was created

Error Responses:

- **401 Unauthorized:** Missing or invalid JWT token
- **403 Forbidden:** User does not have permission to view this booking
- **404 Not Found:** Booking does not exist

Endpoint 4: Cancel Booking

PATCH /api/bookings/{id}/cancel/

Allowed Roles: Regular User (own bookings) OR Company Owner (company bookings)

URL Parameters:

- **id** (integer, required): Booking ID

Request Body: (empty - no data required)

Cancellation Conditions:

- Booking must be in "pending_payment" status
- Booking must not be expired
- Booking must not already be cancelled
- Paid bookings cannot be cancelled

Response (200 OK):

```
json
{
  "message": "Booking cancelled successfully",
  "booking_id": 55,
  "status": "canceled",
  "cancelled_by": "user"
}
```

Cancelled_by Values:

- "user": Regular user cancelled their own booking
- "company_owner": Company owner cancelled a booking for their company

Error Responses:

- **400 Bad Request:**
 - "Cannot cancel a paid booking. Please contact support."
 - "Cannot cancel an expired booking"
 - "Booking is already cancelled"
 - **401 Unauthorized:** Missing or invalid JWT token
 - **403 Forbidden:** User does not have permission to cancel this booking
 - **404 Not Found:** Booking does not exist
-

Endpoint 5: Get Booking Statistics

GET /api/bookings/stats/

Allowed Roles: Regular User (own statistics) OR Company Owner (company statistics)

Response (200 OK):

```
json
{
  "total_bookings": 15,
```

```
"paid_bookings": 8,  
"pending_bookings": 3,  
"cancelled_bookings": 2,  
"expired_bookings": 2,  
"total_revenue": "3600000.00"  
}
```

Statistics Fields:

- **total_bookings** (integer): Total number of bookings
- **paid_bookings** (integer): Count of bookings with PAID status
- **pending_bookings** (integer): Count of bookings awaiting payment
- **cancelled_bookings** (integer): Count of cancelled bookings
- **expired_bookings** (integer): Count of expired bookings
- **total_revenue** (decimal): Sum of total_price for all paid bookings

Behavior by Role:

- **Regular User:** Statistics based on user's own bookings only
- **Company Owner:** Statistics based on all bookings for the owner's company

Error Responses:

- **401 Unauthorized:** Missing or invalid JWT token

Endpoint 6: Payment Processing (External)

Note: This endpoint is not part of the booking API. Payment processing is handled separately through your payment gateway.

Automatic Status Update:

When payment is successfully processed via your payment gateway, the system will automatically:

1. Update booking status from "pending_payment" to "paid"
2. Keep booking as paid (no further changes allowed)

Booking Expiration:

- Bookings automatically expire 10 minutes after creation
- Expired bookings cannot be paid or cancelled
- The system checks expiration before any operation

Blocked Endpoints

The following HTTP methods return **403 Forbidden** for all roles:

Method	Endpoint	Error Message
PUT	/api/bookings/{id}/	"Direct updates not allowed. Use /cancel/ endpoints to change status only"
PATCH	/api/bookings/{id}/	"Direct updates not allowed. Use /cancel/ endpoints to change status only"
DELETE	/api/bookings/{id}/	"Direct updates not allowed. Use /cancel/ endpoints to change status only"

HTTP Status Codes Summary

Status Code	Meaning	When Used
200 OK	Success	GET requests, cancel operation, statistics
201 Created	Resource created	Successful booking creation
400 Bad Request	Client error	Validation failure, invalid cancellation conditions
401 Unauthorized	Authentication required	Missing or invalid JWT token

Status Code	Meaning	When Used
403 Forbidden	Permission denied	Wrong user role, blocked operation
404 Not Found	Resource not found	Booking ID doesn't exist or no permission

Booking Status Flow

* After 10 mins if in PENDING_PAYMENT , will go to EXPIRED

* payment after reached to PAID status will auto convert Booking to status PAID

*booking can reach to status=Canceled by normal-user or owner

Status Descriptions:

- pending_payment: Booking created, awaiting payment (expires in 10 minutes)
- paid: Payment confirmed, booking is final
- canceled: User or company owner cancelled before payment
- expired: 10 minutes passed without payment

Example API Calls (cURL)

Create Booking

bash

```
curl -X POST http://localhost:8000/api/bookings/ \
-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..." \
-H "Content-Type: application/json" \
-d '{
  "trip": 12,
  "seat_ids": [1, 3],
```

```
"passengers": [  
  {  
    "first_name": "Ali",  
    "last_name": "Ahmadi",  
    "national_code": "1234567890",  
    "phone": "09123456789"  
  }  
]  
'
```

List Bookings with Filters

bash

curl -X GET

"http://localhost:8000/api/bookings/?status=pending_payment&from_date=2026-05-01" \

-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..."

Get Single Booking

bash

curl -X GET http://localhost:8000/api/bookings/55/ \

-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..."

Cancel Booking

bash

curl -X PATCH http://localhost:8000/api/bookings/55/cancel/ \

-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..."

Get Statistics

bash

curl -X GET http://localhost:8000/api/bookings/stats/ \

-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..."