

Trips App API Documentation - Complete Reference

Base URL

/api/trips/company/trips/

Authentication Notes

- **Public Access:** Listing trips, retrieving single trips, and search endpoints are public (no authentication required)
 - **Authenticated Access:** Create, update, delete operations require authentication and company owner role
 - **Role Required for Write Operations:** Company Owner only
-

Endpoint 1: List Trips

GET /api/trips/company/trips/

Allowed Access: Public (no authentication required)

Query Parameters (pagination):

- `page` (integer): Page number (default: 1)
- `page_size` (integer): Items per page (default: 10)

Response (200 OK):

json

```
{
  "count": 25,
  "next": "http://api.example.com/api/trips/company/trips/?page=2",
  "previous": null,
  "results": [
    {
      "id": 12,
      "bus": 5,
      "origin_city": 1,
```

```
"destination_city": 2,  
"departure": "2026-06-15T08:00:00Z",  
"arrival": "2026-06-15T12:00:00Z",  
"price": "450000.00",  
"status": "scheduled",  
"company": 3,  
"bus_type": "VIP",  
"available_seats": 42  
}  
]  
}
```

Response Fields:

- **id:** Unique trip identifier
- **bus:** ID of the bus assigned to this trip
- **origin_city:** ID of departure city
- **destination_city:** ID of arrival city
- **departure:** ISO 8601 timestamp of departure time
- **arrival:** ISO 8601 timestamp of arrival time
- **price:** Ticket price per seat
- **status:** Current trip status (scheduled, cancelled, completed)
- **company:** ID of the company operating this trip
- **bus_type:** Type of bus (e.g., "VIP", "Standard", "Economy")
- **available_seats:** Number of seats still available for booking

Special Behavior by Role:

- **Public/Regular Users:** Returns all trips from all companies
- **Company Owner (Authenticated):** Returns only trips belonging to their company

Endpoint 2: Create Trip

POST /api/trips/company/trips/

Allowed Access: Company Owner only (authenticated + owner role)

Request Body:

json

```
{  
  "bus": 5,  
  "origin_city": 1,  
  "destination_city": 2,  
  "departure": "2026-06-15T08:00:00Z",  
  "arrival": "2026-06-15T12:00:00Z",  
  "price": 450000  
}
```

Field Descriptions:

- bus (integer, required): ID of the bus (must belong to owner's company)
- origin_city (integer, required): ID of departure city
- destination_city (integer, required): ID of arrival city
- departure (datetime, required): Departure date and time (ISO 8601)
- arrival (datetime, required): Arrival date and time (ISO 8601)
- price (decimal, required): Price per seat (must be positive)

Validation Rules:

- Origin and destination cities cannot be the same
- Arrival time must be after departure time
- Price must be greater than zero
- Bus must have at least 10 seats

- Bus must belong to the authenticated owner's company (auto-assigned)

Automatic Fields:

- company: Automatically set to the authenticated owner's company
- status: Defaults to "scheduled"

Response (201 Created):

json

```
{
  "id": 12,
  "bus": 5,
  "origin_city": 1,
  "destination_city": 2,
  "departure": "2026-06-15T08:00:00Z",
  "arrival": "2026-06-15T12:00:00Z",
  "price": "450000.00",
  "status": "scheduled",
  "company": 3,
  "bus_type": "VIP",
  "available_seats": 42
}
```

Error Responses:

- **400 Bad Request:**
 - "Origin city and destination city cannot be the same."
 - "Arrival time must be after departure time."
 - "Price must be positive."
 - "Bus {id} does not have enough seats, must have 10 seats at least"
- **401 Unauthorized:** Missing or invalid JWT token

- **403 Forbidden:** User is not a company owner
-

Endpoint 3: Retrieve Single Trip

GET /api/trips/company/trips/{id}/

Allowed Access: Public (no authentication required)

URL Parameters:

- id (integer, required): Trip ID

Response (200 OK):

json

```
{
  "id": 12,
  "bus": 5,
  "origin_city": 1,
  "destination_city": 2,
  "departure": "2026-06-15T08:00:00Z",
  "arrival": "2026-06-15T12:00:00Z",
  "price": "450000.00",
  "status": "scheduled",
  "company": 3,
  "bus_type": "VIP",
  "available_seats": 42
}
```

Error Responses:

- **404 Not Found:** Trip does not exist

Special Behavior:

- Regular users can view any trip

- Company owners can view their own trips (same as public)

Endpoint 4: Update Trip (Full Update)

PUT /api/trips/company/trips/{id}/

Allowed Access: Company Owner only (must own the trip's company)

Request Body: (all fields required)

json

```
{  
  "bus": 5,  
  "origin_city": 1,  
  "destination_city": 3,  
  "departure": "2026-06-15T09:00:00Z",  
  "arrival": "2026-06-15T13:00:00Z",  
  "price": 480000  
}
```

Response (200 OK): Same as retrieve response with updated data

Error Responses:

- **400 Bad Request:** Same validation as create
- **401 Unauthorized:** Missing authentication
- **403 Forbidden:** Not a company owner or doesn't own this trip
- **404 Not Found:** Trip does not exist

Endpoint 5: Partial Update Trip

PATCH /api/trips/company/trips/{id}/

Allowed Access: Company Owner only (must own the trip's company)

Request Body: (partial fields only)

```
json
{
  "price": 500000,
  "departure": "2026-06-15T10:00:00Z"
}
```

Response (200 OK): Same as retrieve response with updated fields

Error Responses: Same as PUT

Endpoint 6: Delete Trip

DELETE /api/trips/company/trips/{id}/

Allowed Access: Company Owner only (must own the trip's company)

Response (204 No Content): (empty body)

Important Note:

- Trips with existing bookings cannot be deleted (database constraint)
- Consider cancelling instead of deleting

Error Responses:

- **401 Unauthorized:** Missing authentication
 - **403 Forbidden:** Not a company owner or doesn't own this trip
 - **404 Not Found:** Trip does not exist
 - **405 Method Not Allowed:** If trip has associated bookings
-

Endpoint 7: Search Trips

GET /api/trips/company/trips/search/

Allowed Access: Public (no authentication required)

Query Parameters (all optional):

- origin (string): Origin city name or ID

- destination (string): Destination city name or ID
- date (date): Departure date (YYYY-MM-DD)

Request Example:

text

GET /api/trips/company/trips/search/?origin=Tehran&destination=Shiraz&date=2026-06-15

Response (200 OK):

json

```
[  
  {  
    "id": 12,  
    "bus": 5,  
    "origin_city": 1,  
    "destination_city": 2,  
    "departure": "2026-06-15T08:00:00Z",  
    "arrival": "2026-06-15T12:00:00Z",  
    "price": "450000.00",  
    "status": "scheduled",  
    "company": 3,  
    "bus_type": "VIP",  
    "available_seats": 42  
  },  
  {  
    "id": 15,  
    "bus": 7,  
    "origin_city": 1,  
    "destination_city": 2,
```



```
"departure": "2026-06-15T14:00:00Z",
"arrival": "2026-06-15T18:00:00Z",
"price": "450000.00",
"status": "scheduled",
"company": 4,
"bus_type": "Standard",
"available_seats": 38
}
]
```

Error Response (404 Not Found):

```
json
{
  "message": "No Trip Found"
}
```

Search Logic:

- Filters are applied with AND logic
- If no filters provided, returns all trips
- Date filter matches exact departure date (ignores time)
- Origin and destination can be city names or IDs

Trip Status Values

Status	Description	Can Book?
scheduled	Trip is planned and active	 Yes

Status	Description	Can Book?
cancelled	Trip has been cancelled	 No
completed	Trip has already departed	 No

Status Management:

- Company owners can update status via PUT/PATCH
- Completed/cancelled trips should not accept new bookings

Available Seats Calculation

Formula:

text

Available Seats = Bus Seat Count - Number of Paid Bookings

Important Notes:

- Only PAID bookings reduce available seats
- PENDING_PAYMENT bookings do NOT reserve seats
- Real-time calculation via get_available_seats() method

Example:

- Bus has 50 seats total
- 30 seats have PAID bookings
- Available seats = 20

Pagination Information

Default Settings:

- Page size: 10 items per page
- Page parameter: ?page=2

- Custom page size: ?page_size=25

Response Headers:

- count: Total number of items
- next: URL to next page (or null)
- previous: URL to previous page (or null)
- results: Array of trip objects

Complete API Endpoints Summary

Method	Endpoint	Authentication	Role	Description
GET	/api/trips/company/trips/	None	Public	List all trips
POST	/api/trips/company/trips/	JWT + Owner	Owner	Create new trip
GET	/api/trips/company/trips/{id}/	None	Public	Get single trip
PUT	/api/trips/company/trips/{id}/	JWT + Owner	Owner	Full update trip
PATCH	/api/trips/company/trips/{id}/	JWT + Owner	Owner	Partial update
DELETE	/api/trips/company/trips/{id}/	JWT + Owner	Owner	Delete trip
GET	/api/trips/company/trips/search/	None	Public	Search trips

HTTP Status Codes Summary

Status Code	Meaning	When Used
200 OK	Success	GET, PUT, PATCH operations
201 Created	Resource created	Successful trip creation
204 No Content	Success (no body)	Successful deletion
400 Bad Request	Client error	Validation failure
401 Unauthorized	Authentication required	Missing/invalid JWT
403 Forbidden	Permission denied	Not a company owner
404 Not Found	Resource not found	Trip doesn't exist

Example API Calls (cURL)

List All Trips (Public)

bash

```
curl -X GET "http://localhost:8000/api/trips/company/trips/?page=1&page_size=20"
```

Search Trips (Public)

bash

```
curl -X GET
```

```
"http://localhost:8000/api/trips/company/trips/search/?origin=Tehran&destination=Isfahan&date=2026-06-15"
```

Create Trip (Company Owner)

bash

```
curl -X POST http://localhost:8000/api/trips/company/trips/ \
-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..." \
-H "Content-Type: application/json" \
-d '{
  "bus": 5,
  "origin_city": 1,
  "destination_city": 2,
  "departure": "2026-06-15T08:00:00Z",
  "arrival": "2026-06-15T12:00:00Z",
  "price": 450000
}'
```

Get Single Trip (Public)

bash

```
curl -X GET http://localhost:8000/api/trips/company/trips/12/
```

Update Trip Price (Company Owner)

bash

```
curl -X PATCH http://localhost:8000/api/trips/company/trips/12/ \
-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..." \
-H "Content-Type: application/json" \
-d '{"price": 500000}'
```

Delete Trip (Company Owner)

bash

```
curl -X DELETE http://localhost:8000/api/trips/company/trips/12/ \
-H "Authorization: Bearer eyJhbGciOiJIUzI1NiIs..."
```

Important Notes

1. **Company Ownership:**

- When creating a trip, the company is automatically set from the authenticated owner
- Company owners can only manage trips for their own company
- The company field is read-only in serializer

2. **Bus Validation:**

- Buses must have at least 10 seats
- Bus must exist and be available
- Bus company is validated against owner's company

3. **City Management:**

- Cities are managed separately (assumed to be pre-populated)
- Origin and destination cannot be the same

4. **Available Seats:**

- Calculated in real-time based on PAID bookings
- Does not include PENDING_PAYMENT bookings
- Used for booking validation

5. **Search Optimization:**

- Search endpoint uses exact matches
- Date filter matches calendar date (ignores time)
- Returns 404 if no trips found (not empty array)

6. **Public Access:**

- Anyone can view trips (no authentication needed)
- Only company owners can modify trips

Data Model Relationships

text

Company (Owner)

↓

└ Bus

↓

└ Trip

↓

└ Booking

↓

└ Passenger

Key Constraints:

- One company can have multiple buses
- One bus can have multiple trips
- One trip can have multiple bookings
- Trip belongs to exactly one company (via bus)

Version Information

- **API Version:** 1.0
- **Last Updated:** May 2026
- **Authentication:** JWT for write operations only
- **Pagination:** Enabled (10 items per page default)