

1 .

//request:

GET /api/trips/company/trips/{id}/seats/

//response:

```
[  
  {  
    "id": 1,  
    "number": 1,  
    "status": "available"  
  },  
  {  
    "id": 2,  
    "number": 2,  
    "status": "reserved"  
  },  
  ...  
]
```

2.

if user A selects seat 5 , the seat will be locked , till request gets over like atomic action (booking is created by status of Pending_payment and passengers are generated and related to that booking)

in this time if user B selects seat 5 will receive error in db and no user with same seat in a trip is possible

3.

GET /api/accounts/me/

Authorization: Bearer <jwt_token>

Response (Regular User):

json

```
{  
  "id": 5,  
  "first_name": "Ali",  
  "last_name": "Ahmadi",  
  "phone": "09123456789",  
  "email": "ali@example.com",  
  "role": "user",  
  "company_name": null  
}
```

Response (Company Owner):

json

```
{  
  "id": 3,  
  "first_name": "Mohammad",  
  "last_name": "Rezaei",  
  "phone": "09987654321",  
  "email": "mohammad@travelco.com",  
  "role": "owner",  
  "company_name": "Pars Travel Co."  
}
```

4.

output of trip origin/destination id and name will return

```
{  
  "id": 12,  
  "origin_city": 1
```

```
"origin_city_name": "Tehran",  
"destination_city": 2,  
"destination_city_name": "Shiraz",  
...  
}
```