R65 Computer System

Memory Mapped IO Address Space

Address	Bytes	Name (W/R)	Description
1400			
1420	1	CRT_CRTADR	CRT Controller address
1421	1	R8_CRTDAT	CRT Controler Data
1430	1	R8_EMUCOM	Emulator command register 1: Export file 2: Import file 3: External editor 4: Change floppy disk 5: Obsolete (stack overflow) 6: Wait 10 ms, process events 7: Synchronize screen (30 ms) 8: Start listing 9: End listing 10: Execute shell command 11: Check Tektronix terminal 12: Not implemented 13: Flush listing file 14: Close listing, reopen printout.txt
1431	1	R8_EMURES	Emulator Result
1432	8	RS8_LED	8-character LED display buffer
144D	1	KIM_IFR1	IRQ1 flag
144E	1	KIM_IER1	IRQ1 enable
1451	1	KIM_PORTA2	Keyboard
145D	1	KIM_IFR2	IRQ2 flag
145E	1	KIM_IER2	IRQ2 enable
146D	1	KIM_IFR3	IRQ3 flag
146E	1	KIM_IER3	IRQ3 enable
14C0	1	R8_FDCOM / R8_FDSTAT	FDC ommand/status
14C1	1	R8_FDPARA / R8_FDRES	FDC parameter/result
14C2	1	R8_FDTSTM	FDC test mode
14C4	1	R8_FTDAT	FDCFDC Data register (R/W)
14E0	1	R8_MULTX	Multiplier X
14E1	1	R8_MULTY	Multiplier Y
14E2	2	R16_MULTR	Multiplier result
1700	1	KIM_HOSTOUT	Output to stdout
1702	1	D8_USPBD	$1702 — USPBD: LED display registerbit 2 indicates floppy disk operation (original hardware, not emulated).
1706	1	EMU_RAND	8-bit random number generator (0–255)
1707	1	EMU_FLAGS	Emulator flags (bit 0, key down)
1708	1	KIM_MOUSEMODE	Mouse event: 0=none, 1=text, 2=graphics

Address	Bytes	Name (W/R)	Description
1709	1	KIM1_MOUSEX	Mouse x coordinate
170A	1	KIM1_MOUSEY	Mouse y coordinate
170B	1	KIM_MOUSEDRAGX	Mouse drag X coordinate
170C	1	KIM_MOUSEDRAGY	Mouse drag Y coordinate
1747	1	R8_TMSEC	Timer count down (ms)
1780	1	M8_VFLAG	Video flag register Bit 7: Inverse video Bit 6: Graphics displayed Bit 5: Graphics initialized Bit 4: Display control character Bit 3: Autoprint on Bit 2: Auto line feed on Bit 1: Printing quiet Bit 0: No video key execution
1781	1	M8_SFLAG	System flag register Bit 7: Escape flag Bit 0: Pascal runtime active, changes text color
1782	1	M8_OFFSET	Display memory offset in lines
1785	1	M8_CHAR	Keyboard input character; cleared by writing 0.
1789	1	ANUMLIN	Number of text lines - 1;value 15 enables split video memory
178A	1	ANUMCHAR	Chars per line - 1
17B5	4	M8_TIME	Host time in BCD: hundredths, seconds, minutes, hours
17B9	1	M8_DATE	Host date; read initiates time/date update