

# BigQuery: Qwik Start - Command Line

GSP071



Google Cloud Self-Paced Labs

# Overview

Storing and querying massive datasets can be time consuming and expensive without the right hardware and infrastructure. BigQuery is a serverless, highly scalable [cloud data warehouse](#) that solves this problem by enabling super-fast SQL queries using the processing power of Google's infrastructure. Simply move your data into BigQuery and let us handle the hard work. You can control access to both the project and your data based on your business needs, such as giving others the ability to view or query your data. You can access BigQuery by using the [Console](#), [Web UI](#) or a [command-line tool](#) using a variety of [client libraries](#) such as Java, .NET, or Python. There are also a variety of [solution providers](#) that you can use to interact with BigQuery.

This hands-on lab shows you how to use `bq`, the python-based command line tool for BigQuery, to query public tables and load sample data into BigQuery.

## Setup and Requirements

### Before you click the Start Lab button

Read these instructions. Labs are timed and you cannot pause them. The timer, which starts when you click **Start Lab**, shows how long Google Cloud resources will be made available to you.

This Qwiklabs hands-on lab lets you do the lab activities yourself in a real cloud environment, not in a simulation or demo environment. It does so by giving you new, temporary credentials that you use to sign in and access Google Cloud for the duration of the lab.

### What you need

To complete this lab, you need:


- Access to a standard internet browser (Chrome browser recommended).
- Time to complete the lab.

**Note:** If you already have your own personal Google Cloud account or project, do not use it for this lab.

**Note:** If you are using a Pixelbook, open an Incognito window to run this lab.


### How to start your lab and sign in to the Google Cloud Console


1. Click the **Start Lab** button. If you need to pay for the lab, a pop-up opens for you to select your payment method. On the left is a panel populated with the temporary credentials that you must use for this lab.




Open Google Console

Caution: When you are in the console, do not deviate from the lab instructions. Doing so may cause your account to be blocked. [Learn more.](#)


Username  
google2727032\_student@qwiklabs.n 

Password  
k68CZXsxMZ 

GCP Project ID  
qwiklabs-gcp-4fbfecac8667e457 

[New to labs? View our introductory video!](#)

2. Copy the username, and then click **Open Google Console**. The lab spins up resources, and then opens another tab that shows the **Sign in** page.



Google

Sign in

Use your Google Account

Email or phone

[Forgot email?](#)

**Tip:** Open the tabs in separate windows, side-by-side.

If you see the **Choose an account** page, click **Use Another**



**Account.**

3. In the **Sign in** page, paste the username that you copied from the Connection Details panel. Then copy and paste the password.

**Important:** You must use the credentials from the Connection Details panel. Do not use your Qwiklabs credentials. If you have your own Google Cloud account, do not use it for this lab (avoids incurring charges).

4. Click through the subsequent pages:

- Accept the terms and conditions.
- Do not add recovery options or two-factor authentication (because this is a temporary account).
- Do not sign up for free trials.

After a few moments, the Cloud Console opens in this tab.


**Note:** You can view the menu with a list of Google Cloud Products and Services by clicking the **Navigation menu** at the top-left.




## Activate Cloud Shell

Cloud Shell is a virtual machine that is loaded with development tools. It offers a persistent 5GB home directory and runs on the Google Cloud. Cloud Shell provides command-line access to your Google Cloud resources.


In the Cloud Console, in the top right toolbar, click the **Activate Cloud Shell** button.



Click **Continue**.



It takes a few moments to provision and connect to the environment. When you are connected, you are already authenticated, and the project is set to your *PROJECT\_ID*. For example:



`gcloud` is the command-line tool for Google Cloud. It comes pre-installed on Cloud Shell and supports tab-completion.

You can list the active account name with this command:

```
gcloud auth list
```

(Output)

```
Credentialed accounts:
- <myaccount>@<mydomain>.com (active)
```

(Example output)

```
Credentialed accounts:
```

```
- google1623327 student@gwiklabs.net
```

You can list the project ID with this command:

```
gcloud config list project
```

(Output)

```
[core]  
project = <project ID>
```

(Example output)

```
[core]  
project = qwiklabs-gcp-44776a13dea667a6
```

For full documentation of `gcloud` see the [gcloud command-line tool overview](#).

## Examine a table

BigQuery offers a number of [sample tables](#) that you can run queries against. In this lab, you'll run queries against the `shakespeare` table, which contains an entry for every word in every play.

To examine the schema of the Shakespeare table in the samples dataset, run:

```
bq show bigquery-public-data:samples.shakespeare
```

In this command you're doing the following:

- `bq` to invoke the BigQuery command line tool
- `show` is the action
- then you're listing the name of the `project:public dataset.table` in BigQuery that you want to see.

Output:

| Last modified                | Schema   | Total Rows | Total Bytes |
|------------------------------|--|------------|-------------|
| Expiration Time Partitioning | Clustered Fields Labels  |            |             |
| 14 Mar 13:16:45              | <ul style="list-style-type: none"><li>word: string (required)</li><li>word_count: integer (required)</li><li>corpus: string (required)</li><li>corpus_date: integer (required)</li></ul> | 164656     | 6432064     |

# Run the help command

When you include a command name with the help commands, you get information about that specific command. For example, the following call to `bq help` retrieves information about the `query` command.

```
bq help query
```

To see a list of all of the commands `bq` uses, run just `bq help`.

## Run a query

Now you'll run a query to see how many times the substring "raisin" appears in Shakespeare's works.

To run a query, run the command `bq query "[SQL_STATEMENT]"`.

- Escape any quotation marks inside the `[SQL_STATEMENT]` with a `\` mark, or
- Use a different quotation mark type than the surrounding marks ("versus").

Run the following standard SQL query in Cloud Shell to count the number of times that the substring "raisin" appears in all of Shakespeare's works:

```
bq query --use_legacy_sql=false \  
'SELECT  
  word,  
  SUM(word_count) AS count  
FROM  
  `bigquery-public-data`.samples.shakespeare  
WHERE  
  word LIKE "%raisin%"  
GROUP BY  
  word'
```

In this command:

- `--use_legacy_sql=false` makes standard SQL the default query syntax

Output:

```
Waiting on job_e19 ... (0s) Current status: DONE  
+-----+-----+  
|      word      | count |  
+-----+-----+
```

|               |   |
|---------------|---|
| praising      | 8 |
| Praising      | 4 |
| raising       | 5 |
| dispraising   | 2 |
| dispraisingly | 1 |
| raisins       | 1 |

The table demonstrates that although the actual word **raisin** doesn't appear, the letters appear in order in several of Shakespeare's works.

### Test Completed Task

Click **Check my progress** to verify your performed task. If you have successfully run query against public dataset, you will see an assessment score.

Run a query (dataset: samples, table: shakespeare, substring: raisin)

Check my progress

If you search for a word that isn't in Shakespeare's works, no results are returned.

Run following search for "huzzah", returns no matches:

```
bq query --use_legacy_sql=false \
'SELECT
  word
FROM
  `bigquery-public-data`.samples.shakespeare
WHERE
  word = "huzzah"'
```

### Test Completed Task

Click **Check my progress** to verify your performed task. If you have successfully run query against public dataset, you will see an assessment score.

Run a query (dataset: samples, table: shakespeare, substring: huzzah)

Check my progress



# Create a new table

Now create your own table. Every table is stored inside a dataset. A *dataset* is a group of resources, such as tables and views.

## Create a new dataset

Use the `bq ls` command to list any existing datasets in your project:

```
bq ls
```

You will be brought back to the command line since there aren't any datasets in your project yet.

Run `bq ls` and the `bigquery-public-data` Project ID to list the datasets in that specific project, followed by a colon (:).

```
bq ls bigquery-public-data:
```

Output:

```
datasetId
-----
austin_311
austin_bikeshare
austin_crime
austin_incidents
austin_waste
baseball
bitcoin_blockchain
bls
census_bureau_construction
census_bureau_international
census_bureau_usa
census_utility
chicago_crime
...
```

Now create a dataset. A dataset name can be up to 1,024 characters long, and consist of A-Z, a-z, 0-9, and the underscore, but it cannot start with a number or underscore, or have spaces.

Use the `bq mk` command to create a new dataset named `babynames` in your Qwiklabs project:

```
bq mk babynames
```

Sample output:

```
Dataset 'qwiklabs-gcp-ba3466847fe3cec0:babynames' successfully created.
```

**Test Completed Task**

Click **Check my progress** to verify your performed task. If you have successfully created BigQuery dataset with name as babynames, you will see an assessment score.

Create a new dataset (name: babynames)

Check my progress

Run `bq ls` to confirm that the dataset now appears as part of your project:

```
bq ls
```

Sample output:

```
datasetId
-----
babynames
```

## Upload the dataset

Before you can build the table, you need to add the dataset to your project. The custom data file you'll use contains approximately 7 MB of data about popular baby names, provided by the US Social Security Administration.

Run this command to add the [baby names zip file](http://www.ssa.gov/OACT/babynames/names.zip) to your project, using the URL for the data file:

```
wget http://www.ssa.gov/OACT/babynames/names.zip
```

List the file:

```
ls
```

You can see the name of the file added to your project.

Now unzip the file:

```
unzip names.zip
```

That's a pretty big list of text files! List the files again:

```
ls
```

The `bq load` command creates or updates a table and loads data in a single step.

You will use the `bq load` command to load your source file into a new table called `names2010` in the `babynames` dataset you just created. By default, this runs synchronously, and will take a few seconds to complete.

The `bq load` arguments you'll be running are:

```
datasetID: babynames
tableID: names2010
```

```
source: yob2010.txt
schema: name:string,gender:string,count:integer
```

Create your table:

```
bq load babynames.names2010 yob2010.txt name:string,gender:string,count:integer
```

Sample output:

```
Waiting on job 4f0c0878f6184119abfdae05f5194e65 ... (35s) Current status: DONE
```

## Test Completed Task

Click **Check my progress** to verify your performed task. If you have successfully load data into dataset table, you will see an assessment score.

Load the data into a new table

Check my progress

Run `bq ls` and `babynames` to confirm that the table now appears in your dataset:

```
bq ls babynames
```

Output:

```
tableId      Type
-----
names2010    TABLE
```

Run `bq show` and your `dataset.table` to see the schema:

```
bq show babynames.names2010
```

Output:

| Last modified<br>Time Partitioning | Schema<br>Clustered Fields                               | Total Rows<br>Labels | Total Bytes | Expiration      |
|------------------------------------|--|----------------------|-------------|-----------------|
| 13 Aug 14:37:34                    | - name: string<br> - gender: string<br> - count: integer | 34073                | 654482      | 12 Oct 14:37:34 |

By default, when you load data, BigQuery expects UTF-8 encoded data. If you have data that is in ISO-8859-1 (or Latin-1) encoding and are having problems with your loaded data, you can tell BigQuery to treat your data as Latin-1 explicitly, using the `-E` flag. For more information, see [Character Encodings](#).

# Run queries

Now you're ready to query the data and return some interesting results.

Run the following command to return the top 5 most popular girls names:

```
bq query "SELECT name,count FROM babynames.names2010 WHERE gender = 'F' ORDER BY count DESC LIMIT 5"
```

Output:

```
Waiting on job_58c0f5ca52764ef1902eba611b71c651 ... (0s) Current status: DONE
+-----+-----+
|  name  | count |
+-----+-----+
| Isabella | 22913 |
| Sophia  | 20643 |
| Emma    | 17345 |
| Olivia  | 17028 |
| Ava     | 15433 |
+-----+-----+
```

Run the following command to see the top 5 most unusual boys names.

```
bq query "SELECT name,count FROM babynames.names2010 WHERE gender = 'M' ORDER BY count ASC LIMIT 5"
```

**Note:** The minimum count is 5 because the source data omits names with fewer than 5 occurrences.

Output:

```
Waiting on job_556ba2e5aad340a7b2818c3e3280b7a3 ... (1s) Current status: DONE
+-----+-----+
|  name  | count |
+-----+-----+
| Aaqib  |     5 |
| Aidan  |     5 |
| Aadhavan |     5 |
| Aarian |     5 |
| Aamarion |     5 |
+-----+-----+
```

## Test Completed Task

Click **Check my progress** to verify your performed task. If you have successfully run query against custom dataset, you will see an assessment score.

Run queries against your dataset table

Check my progress

# Test your Understanding

Below are multiple choice questions to reinforce your understanding of this lab's concepts. Answer them to the best of your abilities.

☐ can access BigQuery using:

☐ `gsutil`

☐ `gsutil` UI

☐ `gcloud` reamer

☐ `gcloud` command line tool

BigQuery REST API

Submit

Which CLI tool is used to interact with BigQuery service?

☒ `gsutil`

☐ `compute`

☐ `bq`

☐ `gcloud`

Submit

## Clean up

Run the `bq rm` command to remove the `babynames` dataset with the `-r` flag to delete all tables in the dataset.

```
bq rm -r babynames
```

Confirm the delete command by typing "y".

### Test Completed Task

Click **Check my progress** to verify your performed task. If you have successfully removed `babynames` dataset, you will see an assessment score.

Remove the babynames dataset

Check my progress

# Congratulations!

Now you can use the command line with BigQuery to manipulate data.



## Finish Your Quest

This self-paced lab is part of the Qwiklabs [BigQuery for Data Warehousing](#), [NCAA® March Madness®: Bracketology with Google Cloud](#), [BigQuery Basics for Data Analysts](#), and [Using the Cloud SDK Command Line](#) Quests. A Quest is a series of related labs that form a learning path. Completing a Quest earns you a badge to recognize your achievement. You can make your badge (or badges) public and link to them in your online resume or social media account. Enroll in a Quest and get immediate completion credit if you've taken this lab. See other available [Qwiklabs Quests](#).

## Next Steps / Learn More

This lab is also part of a series of labs called Qwik Starts. These labs are designed to give you a little taste of the many features available with Google Cloud. Search for "Qwik Starts" in the [lab catalog](#) to find the next lab you'd like to take!

## Google Cloud Training & Certification

...helps you make the most of Google Cloud technologies. [Our classes](#) include technical skills and best practices to help you get up to speed quickly and continue your learning journey. We offer fundamental to advanced level training, with on-demand, live, and virtual options to suit your busy schedule. [Certifications](#) help you validate and prove your skill and expertise in Google Cloud technologies.

Manual Last Updated April 28, 2021

Lab Last Tested April 28, 2021

Copyright 2021 Google LLC All rights reserved. Google and the Google logo are trademarks of Google LLC. All other company and product names may be trademarks of the respective companies with which they are associated.