

Airport

A Schema.org Type

[Thing](#) › [Place](#) › [CivicStructure](#) › **Airport**

[\[more...\]](#)

An airport.

Property	Expected Type	Description
Properties from Airport		
iataCode	Text	IATA identifier for an airline or airport.
icaoCode	Text	ICAO identifier for an airport.
Properties from CivicStructure		
openingHours	Text	The general opening hours for a business. Opening hours can be specified as a weekly time range, starting with days, then times per day. Multiple days can be listed with commas ',' separating each day. Day or time ranges are specified using a hyphen '- '.

Property	Expected Type	Description
		- Days are specified using the following two-letter combinations: Mo, Tu, We, Th, Fr, Sa, Su. - Times are specified using 24:00 format. For example, 3pm is specified as 15:00, 10am as 10:00. - Here is an example: <code><time itemprop="openingHours" datetime="Tu,Th 16:00-20:00">Tuesdays and Thursdays 4-8pm</time></code>. - If a business is open 7 days a week, then it can be specified as <code><time itemprop="openingHours" datetime="Mo-Su">Monday through Sunday, all day</time></code>.
Properties from Place	PropertyValue	A property-value pair representing an additional characteristic of the entity, e.g. a product feature or another characteristic for which there is no matching property in schema.org.
additionalProperty		Note: Publishers should be aware that applications designed to use specific schema.org properties (e.g. https://schema.org/width , https://schema.org/color , https://schema.org/gtin13 , ...) will typically expect such data to be provided using those properties, rather than using the generic property/value mechanism.

Property	Expected Type	Description
address	PostalAddress or Text	Physical address of the item.
aggregateRating	AggregateRating	The overall rating, based on a collection of reviews or ratings, of the item.
amenityFeature	LocationFeatureSpecification	An amenity feature (e.g. a characteristic or service) of the Accommodation. This generic property does not make a statement about whether the feature is included in an offer for the main accommodation or available at extra costs.
branchCode	Text	A short textual code (also called "store code") that uniquely identifies a place of business. The code is typically assigned by the parentOrganization and used in structured URLs. For example, in the URL <code>http://www.starbucks.co.uk/store-locator/etc/detail/3047</code> the code "3047" is a branchCode for a particular branch.
containedInPlace	Place	The basic containment relation between a place and one that contains it. Supersedes containedIn. Inverse property: containsPlace
containsPlace	Place	The basic containment relation between a place and another that it contains. Inverse property: containedInPlace

Property	Expected Type	Description
event	Event	Upcoming or past event associated with this place, organization, or action. Supersedes events .
faxNumber	Text	The fax number.
geo	GeoCoordinates or GeoShape	The geo coordinates of the place.
geoContains	GeospatialGeometry or Place	Represents a relationship between two geometries (or the places they represent), relating a containing geometry to a contained geometry. "a contains b iff no points of b lie in the exterior of a, and at least one point of the interior of b lies in the interior of a". As defined in DE-9IM .
geoCoveredBy	GeospatialGeometry or Place	Represents a relationship between two geometries (or the places they represent), relating a geometry to another that covers it. As defined in DE-9IM .
geoCovers	GeospatialGeometry or Place	Represents a relationship between two geometries (or the places they represent), relating a covering geometry to a covered geometry. "Every point of b is a point of (the interior or boundary of) a". As defined in DE-9IM .
geoCrosses	GeospatialGeometry or Place	Represents a relationship between two geometries (or the places they represent), relating a geometry to another that crosses it: "a crosses b: they have some but not all interior points in common, and the dimension of the intersection is less than that of at least one of them". As defined in DE-9IM .

Property	Expected Type	Description
geoDisjoint	GeospatialGeometry or Place	Represents spatial relations in which two geometries (or the places they represent) are topologically disjoint: "they have no point in common. They form a set of disconnected geometries." (A symmetric relationship, as defined in DE-9IM .)
geoEquals	GeospatialGeometry or Place	Represents spatial relations in which two geometries (or the places they represent) are topologically equal, as defined in DE-9IM . "Two geometries are topologically equal if their interiors intersect and no part of the interior or boundary of one geometry intersects the exterior of the other" (a symmetric relationship).
geoIntersects	GeospatialGeometry or Place	Represents spatial relations in which two geometries (or the places they represent) have at least one point in common. As defined in DE-9IM .
geoOverlaps	GeospatialGeometry or Place	Represents a relationship between two geometries (or the places they represent), relating a geometry to another that geospatially overlaps it, i.e. they have some but not all points in common. As defined in DE-9IM .
geoTouches	GeospatialGeometry or Place	Represents spatial relations in which two geometries (or the places they represent) touch: "they have at least one boundary point in common, but no interior points." (A symmetric relationship, as defined in DE-9IM .)
geoWithin	GeospatialGeometry or Place	Represents a relationship between two geometries (or the places they represent), relating a geometry to one

Property	Expected Type	Description
		that contains it, i.e. it is inside (i.e. within) its interior. As defined in DE-9IM .
globalLocationNumber	Text	The Global Location Number (GLN, sometimes also referred to as International Location Number or ILN) of the respective organization, person, or place. The GLN is a 13-digit number used to identify parties and physical locations.
hasCertification	Certification	Certification information about a product, organization, service, place, or person.
hasDriveThroughService	Boolean	Indicates whether some facility (e.g. FoodEstablishment , CovidTestingFacility) offers a service that can be used by driving through in a car. In the case of CovidTestingFacility such facilities could potentially help with social distancing from other potentially-infected users.
hasGS1DigitalLink	URL	The GS1 digital link associated with the object. This URL should conform to the particular requirements of digital links. The link should only contain the Application Identifiers (AIs) that are relevant for the entity being annotated, for instance a Product or an Organization, and for the correct granularity. In particular, for products: • A Digital Link that contains a serial number (AI 21) should only be present on instances of IndividualProduct • A Digital Link that contains a lot number (AI 10) should be annotated as SomeProduct if only

Property	Expected Type	Description
		products from that lot are sold, or IndividualProduct if there is only a specific product. A Digital Link that contains a global model number (AI 8013) should be attached to a Product or a ProductModel. Other item types should be adapted similarly.
hasMap	Map or URL	A URL to a map of the place. Supersedes maps , map .
isAccessibleForFree	Boolean	A flag to signal that the item, event, or place is accessible for free. Supersedes free .
isicV4	Text	The International Standard of Industrial Classification of All Economic Activities (ISIC), Revision 4 code for a particular organization, business person, or place.
keywords	DefinedTerm or Text or URL	Keywords or tags used to describe some item. Multiple textual entries in a keywords list are typically delimited by commas, or by repeating the property.
latitude	Number or Text	The latitude of a location. For example 37.42242 (WGS 84).
logo	ImageObject or URL	An associated logo.
longitude	Number or Text	The longitude of a location. For example -122.08585 (WGS 84).

Property	Expected Type	Description
maximumAttendeeCapacity	Integer	The total number of individuals that may attend an event or venue.
openingHoursSpecification	OpeningHoursSpecification	The opening hours of a certain place.
photo	ImageObject or Photograph	A photograph of this place. Supersedes photos .
publicAccess	Boolean	A flag to signal that the Place is open to public visitors. If this property is omitted there is no assumed default boolean value.
review	Review	A review of the item. Supersedes reviews .
slogan	Text	A slogan or motto associated with the item.
smokingAllowed	Boolean	Indicates whether it is allowed to smoke in the place, e.g. in the restaurant, hotel or hotel room.
specialOpeningHoursSpecification	OpeningHoursSpecification	The special opening hours of a certain place. Use this to explicitly override general opening hours brought in scope by openingHoursSpecification or openingHours.
telephone	Text	The telephone number.

Property	Expected Type	Description
tourBookingPage	URL	A page providing information on how to book a tour of some Place , such as an Accommodation or ApartmentComplex in a real estate setting, as well as other kinds of tours as appropriate.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.

Property	Expected Type	Description
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **Airport** may appear as a value for the following properties

Property	On Types	Description
arrivalAirport	Flight	The airport where the flight terminates.
departureAirport	Flight	The airport where the flight originates.

Examples

📄 Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "Airport",
  "iataCode": "JFK",
  "icaoCode": "KJFK",
  "name": "John F Kennedy International Airport",
  "openingHours": "Mo-Su",
  "address": {
    "@type": "PostalAddress",
    "addressCountry": "US",
    "addressLocality": "New York",
    "addressRegion": "NY",
```

```
        "postalCode": "11430"
    },
    "latitude": 40.639801,
    "longitude": -73.7789002,
    "maximumAttendeeCapacity": 100000,
    "telephone": "+1-718-244-4444",
    "url": "https://www.jfkairport.com/"
}
</script>
```