

BreadcrumbList

A Schema.org Type

Thing › **Intangible** › **ItemList** › **BreadcrumbList**

[\[more...\]](#)

A BreadcrumbList is an ItemList consisting of a chain of linked Web pages, typically described using at least their URL and their name, and typically ending with the current page.

The **position** property is used to reconstruct the order of the items in a BreadcrumbList. The convention is that a breadcrumb list has an **itemListOrder** of **ItemListOrderAscending** (lower values listed first), and that the first items in this list correspond to the "top" or beginning of the breadcrumb trail, e.g. with a site or section homepage. The specific values of 'position' are not assigned meaning for a BreadcrumbList, but they should be integers, e.g. beginning with '1' for the first item in the list.

Property	Expected Type	Description
Properties from ItemList		
itemListElement	ListItem or Text or Thing	For itemListElement values, you can use simple strings (e.g. "Peter", "Paul", "Mary"), existing entities, or use ListItem. Text values are best if the elements in the list are plain strings. Existing entities are best for a simple, unordered list of existing things in your data. ListItem is used with ordered lists when you want to provide additional context about the

Property	Expected Type	Description
		element in that list or when the same item might be in different places in different lists. Note: The order of elements in your mark-up is not sufficient for indicating the order or elements. Use ListItem with a 'position' property in such cases.
itemListOrder	ItemListOrderType or Text	Type of ordering (e.g. Ascending, Descending, Unordered).
numberOfItems	Integer	The number of items in an ItemList. Note that some descriptions might not fully describe all items in a list (e.g., multi-page pagination); in such cases, the numberOfItems would be for the entire list.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in

Property	Expected Type	Description
		particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **BreadcrumbList** may appear as a value for the following properties

Property	On Types	Description
breadcrumb	WebPage	A set of links that can help a user understand and navigate a website hierarchy.

Examples

📄 Example 1

No Markup	Microdata	RDFa	JSON-LD	Structure
-----------	-----------	------	----------------	-----------

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "BreadcrumbList",
  "itemListElement":
  [
    {
      "@type": "ListItem",
      "position": 1,
      "item":
      {
        "@id": "https://example.com/dresses",
        "name": "Dresses"
      }
    },
    {
```

```
"@type": "ListItem",
"position": 2,
"item":
{
  "@id": "https://example.com/dresses/real",
  "name": "Real Dresses"
}
]
}
</script>
```