

BroadcastService

A Schema.org Type

Thing › **Intangible** › **Service** › **BroadcastService**

[\[more...\]](#)

A delivery service through which content is provided via broadcast over the air or online.

Property	Expected Type	Description
Properties from BroadcastService		
broadcastAffiliateOf	Organization	The media network(s) whose content is broadcast on this station.
broadcastDisplayName	Text	The name displayed in the channel guide. For many US affiliates, it is the network name.
broadcastFrequency	BroadcastFrequencySpecification or Text	The frequency used for over-the-air broadcasts. Numeric values or simple ranges, e.g. 87-99. In addition a shortcut idiom is supported for frequencies of AM and FM radio channels, e.g. "87 FM".
broadcastTimezone	Text	The timezone in ISO 8601 format for which the service bases its broadcasts.

Property	Expected Type	Description
broadcaster	Organization	The organization owning or operating the broadcast service.
callSign	Text	A callsign , as used in broadcasting and radio communications to identify people, radio and TV stations, or vehicles.
hasBroadcastChannel	BroadcastChannel	A broadcast channel of a broadcast service. Inverse property: providesBroadcastService
inLanguage	Language or Text	The language of the content or performance or used in an action. Please use one of the language codes from the IETF BCP 47 standard . See also availableLanguage . Supersedes language .
parentService	BroadcastService	A broadcast service to which the broadcast service may belong to such as regional variations of a national channel.
videoFormat	Text	The type of screening or video broadcast used (e.g. IMAX, 3D, SD, HD, etc.).
Properties from Service		
aggregateRating	AggregateRating	The overall rating, based on a collection of reviews or ratings, of the item.
areaServed	AdministrativeArea or GeoShape or Place or Text	The geographic area where a service or offered item is provided. Supersedes serviceArea .

Property	Expected Type	Description
audience	Audience	An intended audience, i.e. a group for whom something was created. Supersedes serviceAudience .
availableChannel	ServiceChannel	A means of accessing the service (e.g. a phone bank, a web site, a location, etc.).
award	Text	An award won by or for this item. Supersedes awards .
brand	Brand or Organization	The brand(s) associated with a product or service, or the brand(s) maintained by an organization or business person.
broker	Organization or Person	An entity that arranges for an exchange between a buyer and a seller. In most cases a broker never acquires or releases ownership of a product or service involved in an exchange. If it is not clear whether an entity is a broker, seller, or buyer, the latter two terms are preferred. Supersedes bookingAgent .
category	CategoryCode or PhysicalActivityCategory or Text or Thing or URL	A category for the item. Greater signs or slashes can be used to informally indicate a category hierarchy.
hasCertification	Certification	Certification information about a product, organization, service, place, or person.
hasOfferCatalog	OfferCatalog	Indicates an OfferCatalog listing for this Organization, Person, or Service.
hoursAvailable	OpeningHoursSpecification	The hours during which this service or contact is available.

Property	Expected Type	Description
isRelatedTo	Product or Service	A pointer to another, somehow related product (or multiple products).
isSimilarTo	Product or Service	A pointer to another, functionally similar product (or multiple products).
logo	ImageObject or URL	An associated logo.
offers	Demand or Offer	An offer to provide this item—for example, an offer to sell a product, rent the DVD of a movie, perform a service, or give away tickets to an event. Use businessFunction to indicate the kind of transaction offered, i.e. sell, lease, etc. This property can also be used to describe a Demand. While this property is listed as expected on a number of common types, it can be used in others. In that case, using a second type, such as Product or a subtype of Product, can clarify the nature of the offer. Inverse property: itemOffered
provider	Organization or Person	The service provider, service operator, or service performer; the goods producer. Another party (a seller) may offer those services or goods on behalf of the provider. A provider may also serve as the seller. Supersedes carrier .
providerMobility	Text	Indicates the mobility of a provided service (e.g. 'static', 'dynamic').
review	Review	A review of the item. Supersedes reviews .

Property	Expected Type	Description
serviceOutput	Thing	The tangible thing generated by the service, e.g. a passport, permit, etc. Supersedes produces .
serviceType	GovernmentBenefitsType or Text	The type of service being offered, e.g. veterans' benefits, emergency relief, etc.
slogan	Text	A slogan or motto associated with the item.
termsOfService	Text or URL	Human-readable terms of service documentation.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information

Property	Expected Type	Description
		from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **BroadcastService** may appear as a value for the following properties

Property	On Types	Description
parentService	BroadcastService	A broadcast service to which the broadcast service may belong to such as regional variations of a national channel.
providesBroadcastService	BroadcastChannel	The BroadcastService offered on this channel.
publishedOn	PublicationEvent	A broadcast service associated with the publication event.

More specific Types

- **RadioBroadcastService**

Examples

Example 1

No Markup

Microdata

RDFa

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "TVSeries",
  "containsSeason": {
```

```
"@type": "TVSeason",
"episode": {
  "@type": "TVEpisode",
  "position": "8",
  "publication": [
    {
      "@type": "BroadcastEvent",
      "publishedOn": {
        "@type": "BroadcastService",
        "url": "http://www.bbc.co.uk/bbcone"
      },
      "startDate": "2010-05-22T18:15:00+01:00"
    },
    {
      "@type": "OnDemandEvent",
      "endDate": "2012-06-09T19:44:00+01:00",
      "startDate": "2012-06-02T19:45:00+01:00"
    }
  ],
  "url": "http://www.bbc.co.uk/programmes/b00sj9sq",
  "video": {
    "@type": "VideoObject",
    "url": "http://www.bbc.co.uk/iplayer/episode/b00sj9sq"
  }
},
"url": "http://www.bbc.co.uk/programmes/b00rs69w"
},
"url": "http://www.bbc.co.uk/programmes/b006q2x0"
```



```
}  
</script>
```

📄 Example 2

No Markup

Microdata

RDFa

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">  
{  
  "@context": "https://schema.org",  
  "@type": "RadioSeries",  
  "episode": {  
    "@type": "RadioEpisode",  
    "position": "604",  
    "publication": [  
      {  
        "@type": "BroadcastEvent",  
        "publishedOn": {  
          "@type": "BroadcastService",  
          "url": "http://www.bbc.co.uk/radio4"  
        },  
        "startDate": "2013-11-07T09:00:00+01:00"  
      },  
      {  
        "@type": "OnDemandEvent",  
        "startDate": "2013-11-07T09:45:00+01:00"  
      }  
    ]  
  }  
}
```

```

        }
    ],
    "url": "http://www.bbc.co.uk/programmes/b03ggc19"
},
    "url": "http://www.bbc.co.uk/programmes/b006qyk1"
}
</script>

```

📄 Example 3

No Markup	Microdata	RDFa	JSON-LD	Structure
-----------	-----------	------	----------------	-----------

Example encoded as JSON-LD in a HTML script tag.

```

<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "BroadcastService",
  "name": "WXKS-FM",
  "broadcastDisplayName": "Kiss 108",
  "broadcastFrequency": {
    "@type": "BroadcastFrequencySpecification",
    "broadcastFrequencyValue": 107.9,
    "broadcastSignalModulation": "FM"
  }
}

```

</script>

Example 4

No Markup

Microdata

RDFa

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "BroadcastService",
  "name": "WBZ-AM",
  "broadcastDisplayName": "WBZ NewsRadio",
  "broadcastFrequency": {
    "@type": "BroadcastFrequencySpecification",
    "broadcastFrequencyValue": 1030,
    "broadcastSignalModulation": "AM"
  }
}
</script>
```

Example 5

No Markup

Microdata

RDFa

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "BroadcastService",
  "name": "WAAY-TV",
  "broadcastDisplayName": "ABC",
  "videoFormat": "SD",
  "broadcastTimezone": "-8:00",
  "broadcastAffiliateOf": {
    "@type": "Organization",
    "name": "ABC"
  }
}
</script>
```

📄 Example 6

No Markup	Microdata	RDFa	JSON-LD	Structure
-----------	-----------	------	----------------	-----------

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "TelevisionChannel",
```

```

"name": "WAAY 7",
"broadcastChannelId": "7",
"broadcastServiceTier": "Premium",
"inBroadcastLineup": {
  "@type": "CableOrSatelliteService",
  "name": "Comcast"
},
"providesBroadcastService": {
  "@type": "BroadcastService",
  "name": "WAAY-TV",
  "broadcastDisplayName": "ABC",
  "broadcastAffiliateOf": {
    "@type": "Organization",
    "name": "ABC"
  }
}
}
</script>

```

Example 7

No Markup

Microdata

RDFa

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```

<script type="application/ld+json">
{
  "@context": "https://schema.org",

```

```
"@type": "BroadcastEvent",
"startDate": "2014-10-12T21:00",
"endDate": "2014-10-12T21:30",
"publishedOn": {
  "@type": "BroadcastService",
  "name": "WAAY-TV"
},
"workPerformed": {
  "@type": "CreativeWork",
  "name": "Modern Family: Three Turkeys"
},
"inLanguage": "en",
"subtitleLanguage": "es",
"videoFormat": "HD",
"isLiveBroadcast": false,
"name": "Modern Family - S6E8 - Three Turkeys",
"description": "Phil and Luke take over Thanksgiving duties."
}
</script>
```

