

BusTrip

A Schema.org Type

Thing › **Intangible** › **Trip** › **BusTrip**

[\[more...\]](#)

A trip on a commercial bus line.

Property	Expected Type	Description
Properties from BusTrip		
arrivalBusStop	BusStation or BusStop	The stop or station from which the bus arrives.
busName	Text	The name of the bus (e.g. Bolt Express).
busNumber	Text	The unique identifier for the bus.
departureBusStop	BusStation or BusStop	The stop or station from which the bus departs.
Properties from Trip		

Property	Expected Type	Description
arrivalTime	DateTime or Time	The expected arrival time.
departureTime	DateTime or Time	The expected departure time.
itinerary	ItemList or Place	Destination(s) (Place) that make up a trip. For a trip where destination order is important use ItemList to specify that order (see examples).
offers	Demand or Offer	An offer to provide this item—for example, an offer to sell a product, rent the DVD of a movie, perform a service, or give away tickets to an event. Use businessFunction to indicate the kind of transaction offered, i.e. sell, lease, etc. This property can also be used to describe a Demand . While this property is listed as expected on a number of common types, it can be used in others. In that case, using a second type, such as Product or a subtype of Product, can clarify the nature of the offer. Inverse property: itemOffered
partOfTrip	Trip	Identifies that this Trip is a subTrip of another Trip. For example Day 1, Day 2, etc. of a multi-day trip. Inverse property: subTrip
provider	Organization or Person	The service provider, service operator, or service performer; the goods producer. Another party (a seller) may offer those services or goods on behalf of the provider. A provider may also serve as the seller. Supersedes carrier .
subTrip	Trip	Identifies a Trip that is a subTrip of this Trip. For example Day 1, Day 2, etc. of a multi-day trip. Inverse property: partOfTrip
tripOrigin	Place	The location of origin of the trip, prior to any destination(s).

Property	Expected Type	Description
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity

Property	Expected Type	Description
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Examples

Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "BusReservation",
  "reservationId": "123456",
  "underName": {
```

```
    "@type": "Person",
    "name": "John Smith"
  },
  "reservationStatus": "https://schema.org/ReservationConfirmed",
  "reservationFor": {
    "@type": "BusTrip",
    "provider": {
      "@type": "Organization",
      "name": "Bolt NYC"
    },
    "departureBusStop": {
      "@type": "BusStop",
      "name": "Port Authority, NYC"
    },
    "departureTime": "2017-01-04T12:30:00-05:00",
    "arrivalBusStop": {
      "@type": "BusStop",
      "name": "Boston South Station"
    },
    "arrivalTime": "2017-01-04T17:10:00-05:00"
  }
}
</script>
```

