

CompoundPriceSpecification

A Schema.org Type

Thing › **Intangible** › **StructuredValue** › **PriceSpecification** › **CompoundPriceSpecification**

[\[more...\]](#)

A compound price specification is one that bundles multiple prices that all apply in combination for different dimensions of consumption. Use the name property of the attached unit price specification for indicating the dimension of a price component (e.g. "electricity" or "final cleaning").

Property	Expected Type	Description
Properties from CompoundPriceSpecification		
priceComponent	UnitPriceSpecification	This property links to all UnitPriceSpecification nodes that apply in parallel for the CompoundPriceSpecification node.
priceType	PriceTypeEnumeration or Text	Defines the type of a price specified for an offered product, for example a list price, a (temporary) sale price or a manufacturer suggested retail price. If multiple prices are specified for an offer the priceType property can be used to identify the type of each such specified price. The value of priceType can be specified as a value from enumeration PriceTypeEnumeration or as a free form text string for price types that are not already predefined in PriceTypeEnumeration.

Property	Expected Type	Description
Properties from PriceSpecification		
eligibleQuantity	QuantitativeValue	The interval and unit of measurement of ordering quantities for which the offer or price specification is valid. This allows e.g. specifying that a certain freight charge is valid only for a certain quantity.
eligibleTransactionVolume	PriceSpecification	The transaction volume, in a monetary unit, for which the offer or price specification is valid, e.g. for indicating a minimal purchasing volume, to express free shipping above a certain order volume, or to limit the acceptance of credit cards to purchases to a certain minimal amount.
maxPrice	Number	The highest price if the price is a range.
membershipPointsEarned	Number or QuantitativeValue	The number of membership points earned by the member. If necessary, the unitText can be used to express the units the points are issued in. (E.g. stars, miles, etc.)
minPrice	Number	The lowest price if the price is a range.
price	Number or Text	The offer price of a product, or of a price component when attached to PriceSpecification and its subtypes. Usage guidelines: Use the priceCurrency property (with standard formats: ISO 4217 currency format, e.g. "USD"; Ticker symbol for cryptocurrencies, e.g. "BTC"; well known names for Local Exchange Trading Systems (LETS) and other currency types, e.g. "Ithaca HOUR") instead of including ambiguous symbols such as '\$' in the value.

Property	Expected Type	Description
		- Use '.' (Unicode 'FULL STOP' (U+002E)) rather than ',' to indicate a decimal point. Avoid using these symbols as a readability separator. - Note that both RDFa and Microdata syntax allow the use of a "content=" attribute for publishing simple machine-readable values alongside more human-friendly formatting. - Use values from 0123456789 (Unicode 'DIGIT ZERO' (U+0030) to 'DIGIT NINE' (U+0039)) rather than superficially similar Unicode symbols.
priceCurrency	Text	The currency of the price, or a price component when attached to PriceSpecification and its subtypes. Use standard formats: ISO 4217 currency format, e.g. "USD"; Ticker symbol for cryptocurrencies, e.g. "BTC"; well known names for Local Exchange Trading Systems (LETS) and other currency types, e.g. "Ithaca HOUR".
validForMemberTier	MemberProgramTier	The membership program tier an Offer (or a PriceSpecification, OfferShippingDetails, or MerchantReturnPolicy under an Offer) is valid for.
validFrom	Date or DateTime	The date when the item becomes valid.
validThrough	Date or DateTime	The date after when the item is not valid. For example the end of an offer, salary period, or a period of opening hours.

Property	Expected Type	Description
valueAddedTaxIncluded	Boolean	Specifies whether the applicable value-added tax (VAT) is included in the price specification or not.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.

Property	Expected Type	Description
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Acknowledgements

GoodRelations Vocabulary Classes

This class is derived from the GoodRelations Vocabulary for E-Commerce, created by Martin Hepp. GoodRelations is a data model for sharing e-commerce data on the Web that can be expressed in a variety of syntaxes, including RDFa and HTML5 Microdata. More information about GoodRelations can be found at <http://purl.org/goodrelations/>.

[Terms and conditions](#) • [Schema.org](#) • V28.1 | 2024-11-22