

ContactPoint

A Schema.org Type

[Thing](#) > [Intangible](#) > [StructuredValue](#) > **ContactPoint**

[\[more...\]](#)

A contact point—for example, a Customer Complaints department.

Property	Expected Type	Description
Properties from ContactPoint		
areaServed	AdministrativeArea or GeoShape or Place or Text	The geographic area where a service or offered item is provided. Supersedes serviceArea .
availableLanguage	Language or Text	A language someone may use with or at the item, service or place. Please use one of the language codes from the IETF BCP 47 standard . See also inLanguage .
contactOption	ContactPointOption	An option available on this contact point (e.g. a toll-free number or support for hearing-impaired callers).

Property	Expected Type	Description
contactType	Text	A person or organization can have different contact points, for different purposes. For example, a sales contact point, a PR contact point and so on. This property is used to specify the kind of contact point.
email	Text	Email address.
faxNumber	Text	The fax number.
hoursAvailable	OpeningHoursSpecification	The hours during which this service or contact is available.
productSupported	Product or Text	The product or service this support contact point is related to (such as product support for a particular product line). This can be a specific product or product line (e.g. "iPhone") or a general category of products or services (e.g. "smartphones").
telephone	Text	The telephone number.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.

Property	Expected Type	Description
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.

Property	Expected Type	Description
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **ContactPoint** may appear as a value for the following properties

Property	On Types	Description
applicationContact	JobPosting	Contact details for further information relevant to this job posting.
bccRecipient	Message	A sub property of recipient. The recipient blind copied on a message.
ccRecipient	Message	A sub property of recipient. The recipient copied on a message.
contactPoint	HealthInsurancePlan or Organization or Person	A contact point for a person or organization.
contactPoints	Organization or Person	A contact point for a person or organization.
grantee	DigitalDocumentPermission	The person, organization, contact point, or audience that has been granted this permission.
homeLocation	Person	A contact location for a person's residence.
recipient	AuthorizeAction or CommunicateAction or DonateAction or	A sub property of participant. The participant who is at the receiving end of the action.

Property	On Types	Description
	GiveAction or Message or PayAction or ReturnAction or SendAction or TipAction	
servicePhone	ServiceChannel	The phone number to use to access the service.
serviceSmsNumber	ServiceChannel	The number to access the service by text message.
toRecipient	Message	A sub property of recipient. The recipient who was directly sent the message.
workLocation	Person	A contact location for a person's place of work.

More specific Types

- PostalAddress

Examples

📄 Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
```

```
{
  "@context": "https://schema.org",
  "@type": "GovernmentService",
  "name": "Veterans Affairs Emergency Mental Health",
  "serviceType": "Psychiatric Emergency Services",
  "serviceOperator": {
    "@type": "GovernmentOrganization",
    "name": "US Department of Veterans Affairs"
  },
  "areaServed": {
    "@type": "AdministrativeArea",
    "name": "Massachusetts"
  },
  "audience": {
    "@type": "Audience",
    "name": "Veterans"
  },
  "availableChannel": {
    "@type": "ServiceChannel",
    "name": "Urgent Care Clinic",
    "availableLanguage": {
      "@type": "Language",
      "name": "Spanish",
      "alternateName": "es"
    },
  },
  "serviceLocation": {
    "@type": "Hospital",
    "name": "VA Boston -- West Roxbury",
```

```
"address": {
  "@type": "PostalAddress",
  "streetAddress": "1400 VFW Parkway",
  "addressLocality": "West Roxbury",
  "addressRegion": "MA",
  "postalCode": "02132"
}
}
}
}
</script>
```

📄 Example 2

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{ "@context" : "https://schema.org",
  "@type" : "Organization",
  "url" : "http://www.your-company-site.com",
  "contactPoint" : [
    { "@type" : "ContactPoint",
      "telephone" : "+1-401-555-1212",
      "contactType" : "customer service"
    } ] }
}
```

</script>

📄 Example 3

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{ "@context" : "https://schema.org",
  "@type" : "Organization",
  "url" : "http://www.t-mobile.com",
  "contactPoint" : [
    { "@type" : "ContactPoint",
      "telephone" : "+1-877-746-0909",
      "contactType" : "customer service",
      "contactOption" : "TollFree",
      "areaServed" : "US"
    } , {
      "@type" : "ContactPoint",
      "telephone" : "+1-505-998-3793",
      "contactType" : "customer service"
    } , {
      "@type" : "ContactPoint",
      "telephone" : "+1-877-296-1018",
      "contactType" : "customer service",
      "contactOption" : ["HearingImpairedSupported","TollFree"] ,
      "areaServed" : "US"
    }
  ]
}
```



```
    } , {  
      "@type" : "ContactPoint",  
      "telephone" : "+1-877-453-1304",  
      "contactType" : "technical support",  
      "contactOption" : "TollFree",  
      "areaServed" : ["US","CA"],  
      "availableLanguage" : ["English","French"]  
    } , {  
      "@type" : "ContactPoint",  
      "telephone" : "+1-877-453-1304",  
      "contactType" : "bill payment",  
      "contactOption" : "TollFree",  
      "areaServed" : ["US","CA"]  
    } ] }  
</script>
```