

DefinedRegion

A Schema.org Type

Thing > **Intangible** > **StructuredValue** > **DefinedRegion**

[\[more...\]](#)

A DefinedRegion is a geographic area defined by potentially arbitrary (rather than political, administrative or natural geographical) criteria. Properties are provided for defining a region by reference to sets of postal codes.

Examples: a delivery destination when shopping. Region where regional pricing is configured.

Requirement 1: Country: US States: "NY", "CA"

Requirement 2: Country: US PostalCode Set: { [94000-94585], [97000, 97999], [13000, 13599] } { [12345, 12345], [78945, 78945], } Region = state, canton, prefecture, autonomous community...

Property	Expected Type	Description
Properties from DefinedRegion		
addressCountry	Country or Text	The country. Recommended to be in 2-letter ISO 3166-1 alpha-2 format, for example "US". For backward compatibility, a 3-letter ISO 3166-1 alpha-3 country code such as "SGP" or a full country name such as "Singapore" can also be used.

Property	Expected Type	Description
addressRegion	Text	The region in which the locality is, and which is in the country. For example, California or another appropriate first-level Administrative division .
postalCode	Text	The postal code. For example, 94043.
postalCodePrefix	Text	A defined range of postal codes indicated by a common textual prefix. Used for non-numeric systems such as UK.
postalCodeRange	PostalCodeRangeSpecification	A defined range of postal codes.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from

Property	Expected Type	Description
		other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **DefinedRegion** may appear as a value for the following properties

Property	On Types	Description
shippingDestination	DeliveryTimeSettings or	indicates (possibly multiple) shipping destinations. These can be defined in several ways, e.g. postalCode ranges.
	OfferShippingDetails or ShippingRateSettings	
shippingOrigin	OfferShippingDetails	Indicates the origin of a shipment, i.e. where it should be coming from.

Source

<https://github.com/schemaorg/schemaorg/issues/2506>

Examples

Example 1

No Markup

JSON-LD

Structure

Example encoded as *JSON-LD* in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
```

```
"@type": "DefinedRegion",  
"addressCountry": "US",  
"addressRegion": "CA",  
"postalCodeRange": {  
  "@type": "PostalCodeRangeSpecification",  
  "postalCodeBegin": "90001",  
  "postalCodeEnd": "96162"  
}  
}  
</script>
```