

Flight

A Schema.org Type

Thing › **Intangible** › **Trip** › **Flight**

[\[more...\]](#)

An airline flight.

Property	Expected Type	Description
Properties from Flight		
aircraft	Text or Vehicle	The kind of aircraft (e.g., "Boeing 747").
arrivalAirport	Airport	The airport where the flight terminates.
arrivalGate	Text	Identifier of the flight's arrival gate.
arrivalTerminal	Text	Identifier of the flight's arrival terminal.
boardingPolicy	BoardingPolicyType	The type of boarding policy used by the airline (e.g. zone-based or group-based).
departureAirport	Airport	The airport where the flight originates.

Property	Expected Type	Description
departureGate	Text	Identifier of the flight's departure gate.
departureTerminal	Text	Identifier of the flight's departure terminal.
estimatedFlightDuration	Duration or Text	The estimated time the flight will take.
flightDistance	Distance or Text	The distance of the flight.
flightNumber	Text	The unique identifier for a flight including the airline IATA code. For example, if describing United flight 110, where the IATA code for United is 'UA', the flightNumber is 'UA110'.
mealService	Text	Description of the meals that will be provided or available for purchase.
seller	Organization or Person	An entity which offers (sells / leases / lends / loans) the services / goods. A seller may also be a provider. Supersedes vendor , merchant .
webCheckinTime	DateTime	The time when a passenger can check into the flight online.
Properties from Trip		
arrivalTime	DateTime or Time	The expected arrival time.
departureTime	DateTime or Time	The expected departure time.
itinerary	ItemList or Place	Destination(s) (Place) that make up a trip. For a trip where destination order is important use ItemList to specify that order (see examples).

Property	Expected Type	Description
offers	Demand or Offer	An offer to provide this item—for example, an offer to sell a product, rent the DVD of a movie, perform a service, or give away tickets to an event. Use businessFunction to indicate the kind of transaction offered, i.e. sell, lease, etc. This property can also be used to describe a Demand . While this property is listed as expected on a number of common types, it can be used in others. In that case, using a second type, such as Product or a subtype of Product, can clarify the nature of the offer. Inverse property: itemOffered
partOfTrip	Trip	Identifies that this Trip is a subTrip of another Trip. For example Day 1, Day 2, etc. of a multi-day trip. Inverse property: subTrip
provider	Organization or Person	The service provider, service operator, or service performer; the goods producer. Another party (a seller) may offer those services or goods on behalf of the provider. A provider may also serve as the seller. Supersedes carrier .
subTrip	Trip	Identifies a Trip that is a subTrip of this Trip. For example Day 1, Day 2, etc. of a multi-day trip. Inverse property: partOfTrip
tripOrigin	Place	The location of origin of the trip, prior to any destination(s).
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added

Property	Expected Type	Description
		without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.

Property	Expected Type	Description
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Examples

📄 Example 1

No Markup

JSON-LD

Structure

Example encoded as *JSON-LD* in a *HTML script tag*.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "FlightReservation",
  "reservationId": "RXJ34P",
  "reservationStatus": "https://schema.org/ReservationConfirmed",
  "passengerPriorityStatus": "Fast Track",
  "passengerSequenceNumber": "ABC123",
  "securityScreening": "TSA PreCheck",
  "underName": {
    "@type": "Person",
```

```
    "name": "Eva Green"
  },
  "reservationFor": {
    "@type": "Flight",
    "flightNumber": "UA110",
    "provider": {
      "@type": "Airline",
      "name": "Continental",
      "iataCode": "CO",
      "boardingPolicy": "https://schema.org/ZoneBoardingPolicy"
    },
    "seller": {
      "@type": "Airline",
      "name": "United",
      "iataCode": "UA"
    },
    "departureAirport": {
      "@type": "Airport",
      "name": "San Francisco Airport",
      "iataCode": "SFO"
    },
    "departureTime": "2017-03-04T20:15:00-08:00",
    "arrivalAirport": {
      "@type": "Airport",
      "name": "John F. Kennedy International Airport",
      "iataCode": "JFK"
    },
    "arrivalTime": "2017-03-05T06:30:00-05:00"
```

```
}  
}  
</script>
```