

FlightReservation

A Schema.org Type

Thing > **Intangible** > **Reservation** > **FlightReservation**

[\[more...\]](#)

A reservation for air travel.

Note: This type is for information about actual reservations, e.g. in confirmation emails or HTML pages with individual confirmations of reservations. For offers of tickets, use **Offer**.

Property	Expected Type	Description
Properties from FlightReservation		
boardingGroup	Text	The airline-specific indicator of boarding order / preference.
passengerPriorityStatus	QualitativeValue or Text	The priority status assigned to a passenger for security or boarding (e.g. FastTrack or Priority).
passengerSequenceNumber	Text	The passenger's sequence number as assigned by the airline.
securityScreening	Text	The type of security screening the passenger is subject to.
Properties from Reservation		

Property	Expected Type	Description
bookingTime	DateTime	The date and time the reservation was booked.
broker	Organization or Person	An entity that arranges for an exchange between a buyer and a seller. In most cases a broker never acquires or releases ownership of a product or service involved in an exchange. If it is not clear whether an entity is a broker, seller, or buyer, the latter two terms are preferred. Supersedes bookingAgent .
modifiedTime	DateTime	The date and time the reservation was modified.
priceCurrency	Text	The currency of the price, or a price component when attached to PriceSpecification and its subtypes. Use standard formats: ISO 4217 currency format , e.g. "USD"; Ticker symbol for cryptocurrencies, e.g. "BTC"; well known names for Local Exchange Trading Systems (LETS) and other currency types, e.g. "Ithaca HOUR".
programMembershipUsed	ProgramMembership	Any membership in a frequent flyer, hotel loyalty program, etc. being applied to the reservation.
provider	Organization or Person	The service provider, service operator, or service performer; the goods producer. Another party (a seller) may offer those services or goods on behalf of the provider. A provider may also serve as the seller. Supersedes carrier .
reservationFor	Thing	The thing -- flight, event, restaurant, etc. being reserved.
reservationId	Text	A unique identifier for the reservation.
reservationStatus	ReservationStatusType	The current status of the reservation.

Property	Expected Type	Description
reservedTicket	Ticket	A ticket associated with the reservation.
totalPrice	Number or PriceSpecification or Text	The total price for the reservation or ticket, including applicable taxes, shipping, etc. Usage guidelines: - Use values from 0123456789 (Unicode 'DIGIT ZERO' (U+0030) to 'DIGIT NINE' (U+0039)) rather than superficially similar Unicode symbols. - Use '.' (Unicode 'FULL STOP' (U+002E)) rather than ',' to indicate a decimal point. Avoid using these symbols as a readability separator.
underName	Organization or Person	The person or organization the reservation or ticket is for.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.

Property	Expected Type	Description
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.

Property	Expected Type	Description
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Examples

Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "FlightReservation",
  "reservationId": "RXJ34P",
  "reservationStatus": "https://schema.org/ReservationConfirmed",
  "passengerPriorityStatus": "Fast Track",
  "passengerSequenceNumber": "ABC123",
  "securityScreening": "TSA PreCheck",
  "underName": {
    "@type": "Person",
    "name": "Eva Green"
  },
  "reservationFor": {
```

```
"@type": "Flight",
"flightNumber": "UA110",
"provider": {
  "@type": "Airline",
  "name": "Continental",
  "iataCode": "CO",
  "boardingPolicy": "https://schema.org/ZoneBoardingPolicy"
},
"seller": {
  "@type": "Airline",
  "name": "United",
  "iataCode": "UA"
},
"departureAirport": {
  "@type": "Airport",
  "name": "San Francisco Airport",
  "iataCode": "SFO"
},
"departureTime": "2017-03-04T20:15:00-08:00",
"arrivalAirport": {
  "@type": "Airport",
  "name": "John F. Kennedy International Airport",
  "iataCode": "JFK"
},
"arrivalTime": "2017-03-05T06:30:00-05:00"
}
}
</script>
```

