

GeoCircle

A Schema.org Type

Thing > **Intangible** > **StructuredValue** > **GeoShape** > **GeoCircle**

[\[more...\]](#)

A GeoCircle is a GeoShape representing a circular geographic area. As it is a GeoShape it provides the simple textual property 'circle', but also allows the combination of postalCode alongside geoRadius. The center of the circle can be indicated via the 'geoMidpoint' property, or more approximately using 'address', 'postalCode'.

Property	Expected Type	Description
Properties from GeoCircle		
geoMidpoint	GeoCoordinates	Indicates the GeoCoordinates at the centre of a GeoShape, e.g. GeoCircle.
geoRadius	Distance or Number or Text	Indicates the approximate radius of a GeoCircle (metres unless indicated otherwise via Distance notation).
Properties from GeoShape		
address	PostalAddress or Text	Physical address of the item.

Property	Expected Type	Description
addressCountry	Country or Text	The country. Recommended to be in 2-letter ISO 3166-1 alpha-2 format, for example "US". For backward compatibility, a 3-letter ISO 3166-1 alpha-3 country code such as "SGP" or a full country name such as "Singapore" can also be used.
box	Text	A box is the area enclosed by the rectangle formed by two points. The first point is the lower corner, the second point is the upper corner. A box is expressed as two points separated by a space character.
circle	Text	A circle is the circular region of a specified radius centered at a specified latitude and longitude. A circle is expressed as a pair followed by a radius in meters.
elevation	Number or Text	The elevation of a location (WGS 84). Values may be of the form 'NUMBER UNIT_OF_MEASUREMENT' (e.g., '1,000 m', '3,200 ft') while numbers alone should be assumed to be a value in meters.
line	Text	A line is a point-to-point path consisting of two or more points. A line is expressed as a series of two or more point objects separated by space.
polygon	Text	A polygon is the area enclosed by a point-to-point path for which the starting and ending points are the same. A polygon is expressed as a series of four or more space delimited points where the first and final points are identical.
postalCode	Text	The postal code. For example, 94043.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an

Property	Expected Type	Description
		appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.

Property	Expected Type	Description
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Examples

📄 Example 1

No Markup Microdata RDFa **JSON-LD** Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org/",
  "@type": "FoodEstablishment",
  "name": "Joe's Pizza",
  "location": {
    "@type": "PostalAddress",
    "@id": "http://example.com/address",
    "streetAddress": "123 Main Street",
    "addressLocality": "Cambridge",
    "addressRegion": "MA",
    "postalCode": "02142"
  },

```

```
"makesOffer": {
  "@type": "Offer",
  "priceSpecification": {
    "@type": "DeliveryChargeSpecification",
    "appliesToDeliveryMethod": "http://purl.org/goodrelations/v1#DeliveryModeOwnFleet",
    "eligibleTransactionVolume": {
      "@type": "PriceSpecification",
      "price": "20.00",
      "priceCurrency": "USD"
    },
    "eligibleRegion": {
      "@type": "GeoCircle",
      "address": {
        "@id": "http://www.example.com/address"
      },
      "geoRadius": "5000"
    }
  }
}
</script>
```

Example 2

No Markup

Microdata

RDFa

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org/",
  "@type": "TaxiService",
  "provider": {
    "@type": "LocalBusiness",
    "name": "driver #123",
    "location": {
      "@type": "Place",
      "geo": {
        "@type": "GeoCircle",
        "geoMidpoint": {
          "@type": "GeoCoordinates",
          "latitude": "42.362757",
          "longitude": "-71.087109"
        },
        "geoRadius": "50"
      }
    }
  },
  "providerMobility": "dynamic"
}
</script>
```

