

GeoCoordinates

A Schema.org Type

Thing > **Intangible** > **StructuredValue** > **GeoCoordinates**

[\[more...\]](#)

The geographic coordinates of a place or event.

Property	Expected Type	Description
Properties from GeoCoordinates		
address	PostalAddress or Text	Physical address of the item.
addressCountry	Country or Text	The country. Recommended to be in 2-letter ISO 3166-1 alpha-2 format, for example "US". For backward compatibility, a 3-letter ISO 3166-1 alpha-3 country code such as "SGP" or a full country name such as "Singapore" can also be used.
elevation	Number or Text	The elevation of a location (WGS 84). Values may be of the form 'NUMBER UNIT_OF_MEASUREMENT' (e.g., '1,000 m', '3,200 ft') while numbers alone should be assumed to be a value in meters.

Property	Expected Type	Description
latitude	Number or Text	The latitude of a location. For example 37 . 42242 (WGS 84).
longitude	Number or Text	The longitude of a location. For example - 122 . 08585 (WGS 84).
postalCode	Text	The postal code. For example, 94043.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.

Property	Expected Type	Description
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **GeoCoordinates** may appear as a value for the following properties

Property	On Types	Description
geo	Place	The geo coordinates of the place.
geoMidpoint	GeoCircle	Indicates the GeoCoordinates at the centre of a GeoShape, e.g. GeoCircle.

Examples

📄 Example 1

No Markup	Microdata	RDFa	JSON-LD	Structure
-----------	-----------	------	----------------	-----------

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "Place",
  "geo": {
    "@type": "GeoCoordinates",
    "latitude": "40.75",
    "longitude": "-73.98"
  },
  "name": "Empire State Building"
}
</script>
```

Example 2

No Markup

Microdata

Example notes or example HTML without markup.

This example is in microdata only.