

LinkRole

A Schema.org Type

This term is in the "new" area - implementation feedback and adoption from applications and websites can help improve our definitions.

Thing › **Intangible** › **Role** › **LinkRole**

[\[more...\]](#)

A Role that represents a Web link, e.g. as expressed via the 'url' property. Its linkRelationship property can indicate URL-based and plain textual link types, e.g. those in IANA link registry or others such as 'amphtml'. This structure provides a placeholder where details from HTML's link element can be represented outside of HTML, e.g. in JSON-LD feeds.

Property	Expected Type	Description
Properties from LinkRole		
inLanguage	Language or Text	The language of the content or performance or used in an action. Please use one of the language codes from the IETF BCP 47 standard . See also availableLanguage . Supersedes language .
linkRelationship	Text	Indicates the relationship type of a Web link.
Properties from Role		

Property	Expected Type	Description
endDate	Date or DateTime	The end date and time of the item (in ISO 8601 date format).
roleName	Text or URL	A role played, performed or filled by a person or organization. For example, the team of creators for a comic book might fill the roles named 'inker', 'penciller', and 'letterer'; or an athlete in a SportsTeam might play in the position named 'Quarterback'. Supersedes namedPosition .
startDate	Date or DateTime	The start date and time of the item (in ISO 8601 date format).
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.

Property	Expected Type	Description
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Source

<https://github.com/schemaorg/schemaorg/issues/1045>

Examples

📄 Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org/",
  "@type": "Restaurant",
  "potentialAction": {
    "@type": "ReserveAction",
    "target": [
      "http://www.example.com/Reserve",
      {
        "@type": "LinkRole",
        "target": "http://www.example.com/Reserve-JP",
        "inLanguage": "jp",
        "linkRelationship": "alternate"
      }
    ]
  }
}
```

</script>

📄 Example 2

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org/",
  "@type": "Article",
  "url": "http://www.example.com/article",
  "url": {
    "@type": "LinkRole",
    "url": "http://www.example.com/article-amp",
    "linkRelationship": "amphtml"
  }
}
</script>
```

