

PerformanceRole

A Schema.org Type

Thing > **Intangible** > **Role** > **PerformanceRole**

[\[more...\]](#)

A PerformanceRole is a Role that some entity places with regard to a theatrical performance, e.g. in a Movie, TVSeries etc.

Property	Expected Type	Description
Properties from PerformanceRole		
characterName	Text	The name of a character played in some acting or performing role, i.e. in a PerformanceRole.
Properties from Role		
endDate	Date or DateTime	The end date and time of the item (in ISO 8601 date format).
roleName	Text or URL	A role played, performed or filled by a person or organization. For example, the team of creators for a comic book might fill the roles named 'inker', 'penciller', and 'letterer'; or an athlete in a SportsTeam might play in the position named 'Quarterback'. Supersedes namedPosition .

Property	Expected Type	Description
startDate	Date or DateTime	The start date and time of the item (in ISO 8601 date format).
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of <code>rdf:type</code> in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .

Property	Expected Type	Description
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Examples

📄 Example 1

No Markup

Microdata

RDFa

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
```

```
"@type": "Movie",
"name": "Ghostbusters",
"sameAs": "http://en.wikipedia.org/wiki/Ghostbusters",
"actor": {
  "@type": "PerformanceRole",
  "actor": {
    "@type": "Person",
    "name": "Bill Murray"
  },
  "characterName": "Dr. Peter Venkman"
}
}
</script>
```