

PronounceableText

A Schema.org Type

This term is in the "new" area - implementation feedback and adoption from applications and websites can help improve our definitions.

DataType > **Text** > **PronounceableText**

[more...]

Data type: PronounceableText.

Property	Expected Type	Description
Properties from PronounceableText		
inLanguage	Language or Text	The language of the content or performance or used in an action. Please use one of the language codes from the IETF BCP 47 standard . See also availableLanguage . Supersedes language .
phoneticText	Text	Representation of a text textValue using the specified speechToTextMarkup . For example the city name of Houston in IPA: /'hju:stən/.
speechToTextMarkup	Text	Form of markup used. eg. SSML or IPA .

Property	Expected Type	Description
<code>textValue</code>	<code>Text</code>	Text value being annotated.

Source

<https://github.com/schemaorg/schemaorg/issues/2108>

Examples

Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org/",
  "@type": "City",
  "name": {
    "@type": "PronounceableText",
    "inLanguage": "en-US",
    "textValue": "Worcester",
    "speechToTextMarkup": "IPA",
    "phoneticText": "'wɔstə/'
  }
}
```

```
}  
}  
</script>
```

📄 Example 2

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">  
{  
  "@context": "https://schema.org/",  
  "@type": "RadioStation",  
  "name": ["WKRP",  
    {  
      "@type": "PronounceableText",  
      "textValue": "WKRP",  
      "speechToTextMarkup": "SSML",  
      "phoneticText": "<speak><say-as interpret-as=\"characters\">WKRP</say-as>"  
    }  
  ]  
}  
</script>
```

