

PropertyValueSpecification

A Schema.org Type

Thing › **Intangible** › **PropertyValueSpecification**

[\[more...\]](#)

A Property value specification.

Property	Expected Type	Description
Properties from PropertyValueSpecification		
defaultValue	Text or Thing	The default value of the input. For properties that expect a literal, the default is a literal value, for properties that expect an object, it's an ID reference to one of the current values.
maxValue	Number	The upper value of some characteristic or property.
minValue	Number	The lower value of some characteristic or property.
multipleValues	Boolean	Whether multiple values are allowed for the property. Default is false.
readonlyValue	Boolean	Whether or not a property is mutable. Default is false. Specifying this for a property that also has a value makes it act similar to a "hidden" input in an HTML form.

Property	Expected Type	Description
stepValue	Number	The stepValue attribute indicates the granularity that is expected (and required) of the value in a PropertyValueSpecification.
valueMaxLength	Number	Specifies the allowed range for number of characters in a literal value.
valueMinLength	Number	Specifies the minimum allowed range for number of characters in a literal value.
valueName	Text	Indicates the name of the PropertyValueSpecification to be used in URL templates and form encoding in a manner analogous to HTML's input@name.
valuePattern	Text	Specifies a regular expression for testing literal values according to the HTML spec.
valueRequired	Boolean	Whether the property must be filled in to complete the action. Default is false.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may

Property	Expected Type	Description
		be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Acknowledgements

Hydra project

The schema.org Actions mechanism benefited from extensive discussions across the Web standards community around W3C, in particular from the [Hydra project](#)'s community group.