

QuantitativeValue

A Schema.org Type

[Thing](#) > [Intangible](#) > [StructuredValue](#) > **QuantitativeValue**

[\[more...\]](#)

A point value or interval for product characteristics and other purposes.

Property	Expected Type	Description
Properties from QuantitativeValue		
additionalProperty	PropertyValue	A property-value pair representing an additional characteristic of the entity, e.g. a product feature or another characteristic for which there is no matching property in schema.org. Note: Publishers should be aware that applications designed to use specific schema.org properties (e.g. https://schema.org/width , https://schema.org/color , https://schema.org/gtin13 , ...) will typically expect such data to be provided using those properties, rather than using the generic property/value mechanism.
maxValue	Number	The upper value of some characteristic or property.
minValue	Number	The lower value of some characteristic or property.

Property	Expected Type	Description
unitCode	Text or URL	The unit of measurement given using the UN/CEFACT Common Code (3 characters) or a URL. Other codes than the UN/CEFACT Common Code may be used with a prefix followed by a colon.
unitText	Text	A string or text indicating the unit of measurement. Useful if you cannot provide a standard unit code for unitCode .
value	Boolean or Number or StructuredValue or Text	The value of a QuantitativeValue (including Observation) or property value node. - For QuantitativeValue and MonetaryAmount, the recommended type for values is 'Number'. - For PropertyValue, it can be 'Text', 'Number', 'Boolean', or 'StructuredValue'. - Use values from 0123456789 (Unicode 'DIGIT ZERO' (U+0030) to 'DIGIT NINE' (U+0039)) rather than superficially similar Unicode symbols. - Use '.' (Unicode 'FULL STOP' (U+002E)) rather than ',' to indicate a decimal point. Avoid using these symbols as a readability separator.
valueReference	DefinedTerm or Enumeration or MeasurementTypeEnumeration or PropertyValue or QualitativeValue or QuantitativeValue or	A secondary value that provides additional information on the original value, e.g. a reference temperature or a type of measurement.

Property	Expected Type	Description
	StructuredValue or Text	
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.

Property	Expected Type	Description
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **QuantitativeValue** may appear as a value for the following properties

Property	On Types	Description
accelerationTime	Vehicle	The time needed to accelerate the vehicle from a given target velocity. Typical unit code(s): SEC for seconds

Property	On Types	Description
		Note: There are unfortunately no standard units for speed, so you can use seconds/0..100 km/h or seconds/0..60 mph or seconds and indicate the velocities in the QuantitativeValue, or use valueReference and QuantitativeValue of 0..60 mph or 0..100 km/h as reference speeds.
activityDuration	ExercisePlan	Length of time to engage in the activity.
activityFrequency	ExercisePlan	How often one should engage in the activity.
advanceBookingRequirement	Demand or Offer	The amount of time that is required between acceptance and actual usage of the resource or service.
annualPercentageRate	FinancialProduct	The annual rate that is charged for borrowing (or making a loan), expressed as a single percentage number that represents the cost of funds over the term of a loan. This includes any fees or charges associated with the transaction.
billingDuration	UnitPriceSpecification	Specifies for how long this price (or price component) is used, for example, to model the contractual duration of a payment plan. Type can be either a Duration or a Quantity. Unit of measurement, for example month, is specified by the unitCode property).
broadcastFrequencyValue	BroadcastFrequencySpecification	The frequency in MHz for a particular broadcast.
cargoVolume	Vehicle	The available volume for cargo or luggage. For automobiles, this is the trunk volume. Typical unit code(s): LTR for liters, FTQ for cubic foot

Property	On Types	Description
		Note: You can use minValue and maxValue to indicate ranges.
deliveryLeadTime	Demand or Offer	The typical delay between the receipt of the order and the item leaving the warehouse or being prepared for pickup. The pickup method is on site pickup.
depth	OfferShippingDetails or Product or VisualArtwork	The depth of the item.
durationOfWarranty	WarrantyPromise	The duration of the warranty promise. Common units are year, MON for months, or DAY for days.
eligibleDuration	Demand or Offer	The duration for which the given offer is valid.
eligibleQuantity	Demand or Offer or PriceSpecification	The interval and unit of measurement of ordering quantity for which the offer or price specification is valid. This allows e.g. a freight charge is valid only for a certain quantity.
engineDisplacement	EngineSpecification	The volume swept by all of the pistons inside the cylinder of a combustion engine in a single movement. Typical unit code(s) : CMQ for cubic centimeter, LTR for liter, inches * Note 1: You can link to information about how the value has been determined using the valueReference property. You can use minValue and maxValue to indicate ranges.
enginePower	EngineSpecification	The power of the vehicle's engine. Typical unit code(s) : CV for brake horsepower, N12 for metric horsepower (P

Property	On Types	Description
		W) - Note 1: There are many different ways of measuring power. For an overview, see http://en.wikipedia.org/wiki/Horsepower#Etymology. - Note 2: You can link to information about how to determine the value using the valueReference property. - Note 3: You can use minValue and maxValue to indicate the range of values.
floorSize	Accommodation or FloorPlan	The size of the accommodation, e.g. in square meters. Typical unit code(s): MTK for square meter, FTK for square foot.
fuelCapacity	Vehicle	The capacity of the fuel tank or in the case of electric vehicles, the capacity of the battery. If there are multiple components for storage, this should indicate the total capacity of all components of the same type. Typical unit code(s): LTR for liters, GLL of US gallons, GUK of UK gallons, AMH for ampere-hours (for electrical vehicles).
fuelConsumption	Vehicle	The amount of fuel consumed for traveling a particular distance or duration with the given vehicle (e.g. liters per 100 km). - Note 1: There are unfortunately no standard unit codes for fuel consumption. Use unitText to indicate the unit code (e.g. "liters per 100 km"). - Note 2: There are two ways of indicating the fuel consumption (e.g. 8 liters per 100 km) or efficiency (e.g. 30 miles per gallon). They are reciprocal values.

Property	On Types	Description
fuelEfficiency		Note 3: Often, the absolute value is useful o speed ("at 80 km/h") or usage pattern ("city valueReference to link the value for the fu value.
	Vehicle	The distance traveled per unit of fuel used; most co (mpg) or kilometers per liter (km/L). - Note 1: There are unfortunately no standard gallon or kilometers per liter. Use unitText measurement, e.g. mpg or km/L. - Note 2: There are two ways of indicating the fuelConsumption (e.g. 8 liters per 100 km) (e.g. 30 miles per gallon). They are reciprocal. - Note 3: Often, the absolute value is useful o speed ("at 80 km/h") or usage pattern ("city valueReference to link the value for the fu value.
	ShippingDeliveryTime	The typical delay between the receipt of the order a leaving the warehouse or being prepared for pickup method is on site pickup. Typical properties: minVal for DAY). This is by common convention assumed to unitCode is used, coded as "d"), i.e. only counting c normally operates.
handlingTime		
hasMeasurement	Certification or Offer or	A measurement of an item, For example, the insear a bicycle, the gauge of a screw, or the carbon footp certification by an authority. Usually an exact meas

Property	On Types	Description
height	Product or SizeSpecification	range of measurements for adjustable products, for example, book bindings.
	MediaObject or OfferShippingDetails or Person or Product or VisualArtwork	The height of the item.
	ExercisePlan	Quantitative measure gauging the degree of force exerted, for example, heartbeats per minute. May include the velocity of movement.
interestRate	FinancialProduct	The interest rate, charged or paid, applicable to the loan or credit agreement. This is different from the calculated annualPercentageRate.
inventoryLevel	Demand or Offer or SomeProducts	The current approximate inventory level for the item.
leaseLength	Accommodation or Offer or RealEstateListing	Length of the lease for some Accommodation , either for some Offer or in some cases intrinsic to the property.
loanTerm	LoanOrCredit	The duration of the loan or credit agreement.
marginOfError	Observation	A marginOfError for an Observation .
materialExtent	CreativeWork	The quantity of the materials being described or an estimate of the space they occupy.

Property	On Types	Description
membershipPointsEarned	MemberProgramTier or PriceSpecification or ProgramMembership	The number of membership points earned by the member. (The unitText can be used to express the units the points are measured in, e.g. miles, etc.)
mileageFromOdometer	Vehicle	The total distance travelled by the particular vehicle since its production, as read from its odometer. Typical unit code(s): KMT for kilometers, SMI for statute miles
molecularWeight	MolecularEntity	This is the molecular weight of the entity being described. Units should be included in the form '<Number> <unit>', for example '100 g/mol' or as '<QuantitativeValue>'. The molecular weight is the sum of the atomic weights of the constituent atoms.
monoisotopicMolecularWeight	MolecularEntity	The monoisotopic mass is the sum of the masses of the constituent atoms using the unbound, ground-state, rest mass of the most abundant isotope for each element instead of the isotopic average. Units should be included in the form '<Number> <unit>', for example '100.0443546 g/mol' or as '<QuantitativeValue>'. The monoisotopic mass is the sum of the masses of the constituent atoms using the unbound, ground-state, rest mass of the most abundant isotope for each element instead of the isotopic average.
numAdults	LodgingReservation	The number of adults staying in the unit.
numChildren	LodgingReservation	The number of children staying in the unit.
numberOfAccommodationUnits	ApartmentComplex or FloorPlan	Indicates the total (available plus unavailable) number of accommodation units in an ApartmentComplex , or the number of accommodation units for a specific FloorPlan (within its specific ApartmentComplex). Indicates the total (available plus unavailable) number of accommodation units in an ApartmentComplex , or the number of accommodation units for a specific FloorPlan (within its specific ApartmentComplex).
numberOfAvailableAccommodationUnits	ApartmentComplex or FloorPlan	Indicates the number of available accommodation units in an ApartmentComplex , or the number of available accommodation units for a specific FloorPlan (within its specific ApartmentComplex).

Property	On Types	Description
numberOfAxles		FloorPlan (within its specific ApartmentComplex : numberOfAccommodationUnits .
	Vehicle	The number of axles. Typical unit code(s): C62.
numberOfBedrooms	Accommodation or ApartmentComplex or FloorPlan	The total integer number of bedrooms in a some Ac ApartmentComplex or FloorPlan .
numberOfDoors	Vehicle	The number of doors. Typical unit code(s): C62.
numberOfEmployees	BusinessAudience or Organization	The number of employees in an organization, e.g. b
numberOfForwardGears	Vehicle	The total number of forward gears available for the vehicle. Typical unit code(s): C62.
numberOfPlayers	Game or VideoGameSeries	Indicate how many people can play this game (mini
numberOfPreviousOwners	Vehicle	The number of owners of the vehicle, including the Typical unit code(s): C62.

Property	On Types	Description
numberOfRooms	Accommodation or Apartment or FloorPlan or House or LodgingBusiness or SingleFamilyResidence or Suite	The number of rooms (excluding bathrooms and closets) available for accommodation or lodging business. Typical unit code is C62 for no unit. The type of room can be put in the QuantitativeValue .
occupancy	Accommodation or Apartment or HotelRoom or SingleFamilyResidence or Suite	The allowed total occupancy for the accommodation (including adults, infants etc). For individual accommodations, this is the maximum but defines the permitted usage as per the reservation (e.g. a double room used by a single person). Typical unit code is C62 for no unit.
orderQuantity	OrderItem	The number of the item ordered. If the property is not applicable, the quantity is one.
partySize	FoodEstablishmentReservation or TaxiReservation	Number of people the reservation should accommodate.
payload	Vehicle	The permitted weight of passengers and cargo, EXCEPT for empty vehicle. Typical unit code(s): KGM for kilogram, LBR for pound. - Note 1: Many databases specify the permitted weight, which is the sum of weight and payload. - Note 2: You can indicate additional information in the QuantitativeValue node.

Property	On Types	Description
recipeYield referenceQuantity repetitions requiredQuantity restPeriods		- Note 3: You may also link to a Qualitative additional information using valueReference. - Note 4: Note that you can use minValue and maxValue to define ranges.
	Recipe	The quantity produced by the recipe (for example, number of servings, etc).
	UnitPriceSpecification	The reference quantity for which a certain price applies, e.g. price of electricity. This property is a replacement for unit price in advanced cases where the price does not relate to a specific quantity.
	ExercisePlan	Number of times one should repeat the activity.
	HowToItem	The required quantity of the item(s).
	ExercisePlan	How often one should break from the activity.

Property	On Types	Description
roofLoad	BusOrCoach or Car	The permitted total weight of cargo and installation of the vehicle. Typical unit code(s) : KGM for kilogram, LBR for pound - Note 1: You can indicate additional information using QuantitativeValue node. - Note 2: You may also link to a Qualitative additional information using valueReference property. - Note 3: Note that you can use minValue and maxValue for ranges.
	Vehicle	The number of persons that can be seated (e.g. in a vehicle, the physical space available, and in terms of limitation). Typical unit code(s) : C62 for persons.
seatingCapacity		
size	CreativeWork or Product	A standardized size of a product or creative work, such as a simple textual string (for example 'XL', '32Wx34L'), a unitCode, or a comprehensive and structured Size object. In some cases, the width, height, depth and weight properties are applicable.
speed	Vehicle	The speed range of the vehicle. If the vehicle is powered, the upper limit of the speed range (indicated by maxValue). The maximum speed achievable under regular conditions. Typical unit code(s) : KMH for km/h, HM for mile per hour, KT for knot

Property	On Types	Description
		*Note 1: Use minValue and maxValue to indicate the minimal value is zero. * Note 2: There are many different speed range. You can link to information about how determined using the valueReference property.
stupidProperty	<u>StupidType</u> or Vehicle	This is a StupidProperty! - for testing only.
suggestedAge	PeopleAudience or SizeSpecification	The age or age range for the intended audience or person. months for infants, 1-5 years for toddlers.
suggestedMeasurement	PeopleAudience or SizeSpecification	A suggested range of body measurements for the intended person, for example inseam between 32 and 34 inches and 190 cm. Typically found on a size chart for wear.
	Vehicle	The permitted vertical load (TWR) of a trailer attachment referred to as Tongue Load Rating (TLR) or Vertical Typical unit code(s): KGM for kilogram, LBR for pound
tongueWeight		- Note 1: You can indicate additional information using QuantitativeValue node. - Note 2: You may also link to a Qualitative additional information using valueReference property. - Note 3: Note that you can use minValue and maxValue ranges.

Property	On Types	Description
torque	EngineSpecification	The torque (turning force) of the vehicle's engine. Typical unit code(s): NU for newton metre (N m), F1 or F48 for pound-force per inch - Note 1: You can link to information about how determined (e.g. reference RPM) using the valueReference property. - Note 2: You can use minValue and maxValue to indicate ranges.
	Vehicle	The permitted weight of a trailer attached to the vehicle. Typical unit code(s): KGM for kilogram, LBR for pound. For additional information in the name of the QuantitativeValue node. You may also link to a QualitativeValue node that provides information using valueReference. * Note 3: Note minValue and maxValue to indicate ranges.
trailerWeight		
transitTime	ShippingDeliveryTime	The typical delay the order has been sent for delivery to the final customer. Typical properties: minValue, maxValue
valueReference	PropertyValue or QualitativeValue or QuantitativeValue	A secondary value that provides additional information, e.g. a reference temperature or a type of measurement.
vehicleSeatingCapacity	Vehicle	The number of passengers that can be seated in the vehicle, in the physical space available, and in terms of limitations. Typical unit code(s): C62 for persons.

Property	On Types	Description
weight	OfferShippingDetails or Person or Product or VisualArtwork	The weight of the product or person.
	Vehicle	The permitted total weight of the loaded vehicle, in cargo and the weight of the empty vehicle. Typical unit code(s): KGM for kilogram, LBR for pound - Note 1: You can indicate additional information using QuantitativeValue node. - Note 2: You may also link to a Qualitative additional information using valueReference. - Note 3: Note that you can use minValue and maxValue to indicate ranges.
weightTotal		
wheelbase	Vehicle	The distance between the centers of the front and rear wheels. Typical unit code(s): CMT for centimeters, MTR for meter, FT for foot/feet.
width	MediaObject or OfferShippingDetails or Product or VisualArtwork	The width of the item.

Property	On Types	Description
workload	ExercisePlan	Quantitative measure of the physiologic output of to as energy expenditure.
yearlyRevenue	BusinessAudience	The size of the business in annual revenue.
yearsInOperation	BusinessAudience	The age of the business.
yield	HowTo	The quantity that results by performing instruction airplane, 10 personalized candles.

More specific Types

- **Observation**

Acknowledgements

GoodRelations Vocabulary Classes

This class is derived from the GoodRelations Vocabulary for E-Commerce, created by Martin Hepp. GoodRelations is a data model for sharing e-commerce data on the Web that can be expressed in a variety of syntaxes, including RDFa and HTML5 Microdata. More information about GoodRelations can be found at <http://purl.org/goodrelations/>.

