

Schedule

A Schema.org Type

This term is in the "new" area - implementation feedback and adoption from applications and websites can help improve our definitions.

Thing > **Intangible** > **Schedule**

[\[more...\]](#)

A schedule defines a repeating time period used to describe a regularly occurring **Event**. At a minimum a schedule will specify **repeatFrequency** which describes the interval between occurrences of the event. Additional information can be provided to specify the schedule more precisely. This includes identifying the day(s) of the week or month when the recurring event will take place, in addition to its start and end time. Schedules may also have start and end dates to indicate when they are active, e.g. to define a limited calendar of events.

Property	Expected Type	Description
Properties from Schedule		
byDay	DayOfWeek or Text	Defines the day(s) of the week on which a recurring Event takes place. May be specified using either DayOfWeek , or alternatively Text conforming to iCal's syntax for byDay recurrence rules.

Property	Expected Type	Description
byMonth	Integer	Defines the month(s) of the year on which a recurring Event takes place. Specified as an Integer between 1-12. January is 1.
byMonthDay	Integer	Defines the day(s) of the month on which a recurring Event takes place. Specified as an Integer between 1-31.
byMonthWeek	Integer	Defines the week(s) of the month on which a recurring Event takes place. Specified as an Integer between 1-5. For clarity, byMonthWeek is best used in conjunction with byDay to indicate concepts like the first and third Mondays of a month.
duration	Duration	The duration of the item (movie, audio recording, event, etc.) in ISO 8601 duration format .
endDate	Date or DateTime	The end date and time of the item (in ISO 8601 date format).
endTime	DateTime or Time	The endTime of something. For a reserved event or service (e.g. FoodEstablishmentReservation), the time that it is expected to end. For actions that span a period of time, when the action was performed. E.g. John wrote a book from January to <i>December</i>. For media, including audio and video, it's the time offset of the end of a clip within a larger file. Note that Event uses startDate/endDate instead of startTime/endTime, even when describing dates with times. This situation may be clarified in future revisions.
exceptDate	Date or DateTime	Defines a Date or DateTime during which a scheduled Event will not take place. The property allows exceptions to a Schedule to be specified. If an exception is specified as a DateTime then only the event that would have started at that specific date and time should be excluded from the schedule. If an exception is specified as a Date then any event that is scheduled for that 24 hour period should be excluded

Property	Expected Type	Description
		from the schedule. This allows a whole day to be excluded from the schedule without having to itemise every scheduled event.
repeatCount	Integer	Defines the number of times a recurring Event will take place.
repeatFrequency	Duration or Text	Defines the frequency at which Events will occur according to a schedule Schedule . The intervals between events should be defined as a Duration of time.
scheduleTimezone	Text	Indicates the timezone for which the time(s) indicated in the Schedule are given. The value provided should be among those listed in the IANA Time Zone Database.
startDate	Date or DateTime	The start date and time of the item (in ISO 8601 date format).
startTime	DateTime or Time	The startTime of something. For a reserved event or service (e.g. FoodEstablishmentReservation), the time that it is expected to start. For actions that span a period of time, when the action was performed. E.g. John wrote a book from <i>January</i> to December. For media, including audio and video, it's the time offset of the start of a clip within a larger file. Note that Event uses startDate/endDate instead of startTime/endTime, even when describing dates with times. This situation may be clarified in future revisions.
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an

Property	Expected Type	Description
		appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.

Property	Expected Type	Description
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **Schedule** may appear as a value for the following properties

Property	On Types	Description
courseSchedule	CourseInstance	Represents the length and pace of a course, expressed as a Schedule .
eventSchedule	Event	Associates an Event with a Schedule . There are circumstances where it is preferable to share a schedule for a series of repeating events rather than data on the individual events themselves. For example, a website or application might prefer to publish a schedule for a weekly gym class rather than provide data on every event. A schedule could be processed by applications to add forthcoming events to a calendar. An Event that is associated with a Schedule using this property should not have startDate or endDate properties. These are instead defined within the associated Schedule , this avoids any ambiguity for clients using the data. The property might have repeated values to specify different schedules, e.g. for different months or seasons.

Source

<https://github.com/schemaorg/schemaorg/issues/1457>

Examples

📄 Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org/",
  "@type": "Event",
  "url": "http://www.example.org/events/1",
  "name": "Tai chi Class",
  "description": "A weekly Tai-Chi class",
  "duration": "PT60M",
  "eventSchedule": {
    "@type": "Schedule",
    "startDate": "2017-01-01",
    "endDate": "2017-12-31",
    "repeatFrequency": "P1W",
    "byDay": "https://schema.org/Wednesday",
    "startTime": "19:00:00",
    "endTime": "20:00:00",
    "scheduleTimezone": "Europe/London"
  }
}
</script>
```

📄 Example 2

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org/",
  "@type": "Event",
  "name": "Example Meetup",
  "eventSchedule": {
    "@type": "Schedule",
    "repeatFrequency": "P1M",
    "byMonthDay": [1,15],
    "startTime": "09:00:00",
    "endTime": "10:00:00",
    "scheduleTimezone": "America/Glace_Bay"
  }
}
</script>
```

📄 Example 3

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```

<script type="application/ld+json">
  {
    "@context": "https://schema.org",
    "@type": "Event",
    "name": "Count Example",
    "eventSchedule":
      {
        "@type": "Schedule",
        "startDate": "2016-12-24",
        "repeatFrequency": "P1D",
        "repeatCount": 10,
        "startTime": "09:00:00",
        "endTime": "10:00:00",
        "scheduleTimezone": "Europe/London"
      }
  }
</script>

```

📄 Example 4

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```

<script type="application/ld+json">
  {
    "@context": "https://schema.org",

```

```
"@type": "Event",
"name": "Example",
"eventSchedule": [
  {
    "@type": "Schedule",
    "repeatFrequency": "P1D",
    "byDay": [
      "https://schema.org/Monday",
      "https://schema.org/Tuesday",
      "https://schema.org/Wednesday",
      "https://schema.org/Thursday",
      "https://schema.org/Friday"
    ],
    "startTime": "09:00:00",
    "endTime": "10:00:00",
    "scheduleTimezone": "America/Glace_Bay"
  },
  {
    "@type": "Schedule",
    "repeatFrequency": "P1D",
    "byDay": [
      "https://schema.org/Monday",
      "https://schema.org/Tuesday",
      "https://schema.org/Wednesday",
      "https://schema.org/Thursday",
      "https://schema.org/Friday"
    ],
    "startTime": "14:00:00",
```

```
        "endTime": "15:00:00",
        "scheduleTimezone": "America/Glace_Bay"
    }
]
}
</script>
```

📄 Example 5

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "Event",
  "name": "Example",
  "eventSchedule": [
    {
      "@type": "Schedule",
      "repeatFrequency": "P1M",
      "byDay": "2MO",
      "startTime": "18:00:00",
      "endTime": "19:30:00",
      "scheduleTimezone": "Asia/Shanghai"
    }
  ]
}
```

```
}  
</script>
```

📄 Example 6

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">  
{  
  "@context": "https://schema.org",  
  "@type": "LiteraryEvent",  
  "name": "Local Bookseller Author Night",  
  "description": "Join us the first and third Wednesdays of each month for readings by local authors.",  
  "eventSchedule": {  
    "@type": "Schedule",  
    "byDay": "https://schema.org/Wednesday",  
    "byMonthWeek": [1, 3],  
    "startTime": "20:00:00",  
    "endTime": "22:00:00"  
  }  
}  
</script>
```

