

Seat

A Schema.org Type

Thing › **Intangible** › **Seat**

[\[more...\]](#)

Used to describe a seat, such as a reserved seat in an event reservation.

Property	Expected Type	Description
Properties from Seat		
seatNumber	Text	The location of the reserved seat (e.g., 27).
seatRow	Text	The row location of the reserved seat (e.g., B).
seatSection	Text	The section location of the reserved seat (e.g. Orchestra).
seatingType	QualitativeValue or Text	The type/class of the seat.
Properties from Thing		

Property	Expected Type	Description
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of <code>rdf:type</code> in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity

Property	Expected Type	Description
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **Seat** may appear as a value for the following properties

Property	On Types	Description
ticketedSeat	Ticket	The seat associated with the ticket.

Examples

Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
```

```
{
  "@context": "https://schema.org",
  "@type": "EventReservation",
  "reservationId": "E123456789",
  "reservationStatus": "https://schema.org/ReservationConfirmed",
  "underName": {
    "@type": "Person",
    "name": "John Smith"
  },
  "reservationFor": {
    "@type": "Event",
    "name": "Foo Fighters Concert",
    "startDate": "2017-03-06T19:30:00-08:00",
    "location": {
      "@type": "Place",
      "name": "AT&T Park",
      "address": {
        "@type": "PostalAddress",
        "streetAddress": "24 Willie Mays Plaza",
        "addressLocality": "San Francisco",
        "addressRegion": "CA",
        "postalCode": "94107",
        "addressCountry": "US"
      }
    }
  },
  "reservedTicket": {
    "@type": "Ticket",
```

```
"ticketNumber": "abc123",  
"ticketToken": "qrCode:AB34",  
"ticketedSeat": {  
  "@type": "Seat",  
  "seatRow": "A",  
  "seatNumber": "12",  
  "seatSection": "101"  
}  
}  
}  
</script>
```