

ShippingDeliveryTime

A Schema.org Type

[Thing](#) > [Intangible](#) > [StructuredValue](#) > **ShippingDeliveryTime**

[\[more...\]](#)

ShippingDeliveryTime provides various pieces of information about delivery times for shipping.

Property	Expected Type	Description
Properties from ShippingDeliveryTime		
businessDays	OpeningHoursSpecification	Days of the week when the merchant typically operates, indicated via opening hours markup.
cutoffTime	Time	Order cutoff time allows merchants to describe the time after which they will no longer process orders received on that day. For orders processed after cutoff time, one day gets added to the delivery time estimate. This property is expected to be most typically used via the ShippingRateSettings publication pattern. The time is indicated using the ISO-8601 Time format, e.g. "23:30:00-05:00" would represent 6:30 pm Eastern Standard Time (EST) which is 5 hours behind Coordinated Universal Time (UTC).

Property	Expected Type	Description
handlingTime	QuantitativeValue	The typical delay between the receipt of the order and the goods either leaving the warehouse or being prepared for pickup, in case the delivery method is on site pickup. Typical properties: minValue, maxValue, unitCode (d for DAY). This is by common convention assumed to mean business days (if a unitCode is used, coded as "d"), i.e. only counting days when the business normally operates.
transitTime	QuantitativeValue	The typical delay the order has been sent for delivery and the goods reach the final customer. Typical properties: minValue, maxValue, unitCode (d for DAY).
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other

Property	Expected Type	Description
		properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **ShippingDeliveryTime** may appear as a value for the following properties

Property	On Types	Description
deliveryTime	DeliveryTimeSettings or OfferShippingDetails	The total delay between the receipt of the order and the goods reaching the final customer.

Source

<https://github.com/schemaorg/schemaorg/issues/2506>

Examples

Example 1

No Markup

JSON-LD

Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
  "@context": "https://schema.org",
  "@type": "OfferShippingDetails",
  "deliveryTime": {
    "@type": "ShippingDeliveryTime",
    "businessDays": {
      "@type": "OpeningHoursSpecification",
```

```
    "dayOfWeek": [
      "https://schema.org/Monday",
      "https://schema.org/Tuesday",
      "https://schema.org/Wednesday",
      "https://schema.org/Thursday",
      "https://schema.org/Friday"
    ],
    "cutoffTime": "12:00:15Z",
    "handlingTime": {
      "@type": "QuantitativeValue",
      "minValue": 1,
      "maxValue": 2,
      "unitCode": "d"
    },
    "transitTime": {
      "@type": "QuantitativeValue",
      "minValue": 1,
      "maxValue": 10,
      "unitCode": "d"
    }
  },
  "shippingRate": {
    "@type": "MonetaryAmount",
    "value": 4.95,
    "currency": "USD"
  }
}
```

</script>

[Terms and conditions](#) • [Schema.org](#) • V28.1 | 2024-11-22