

SpeakableSpecification

A Schema.org Type

Thing › **Intangible** › **SpeakableSpecification**

[\[more...\]](#)

A **SpeakableSpecification** indicates (typically via **xpath** or **cssSelector**) sections of a document that are highlighted as particularly **speakable**. Instances of this type are expected to be used primarily as values of the **speakable** property.

Property	Expected Type	Description
Properties from SpeakableSpecification		
cssSelector	CssSelectorType	A CSS selector, e.g. of a SpeakableSpecification or WebPageElement . In the latter case, multiple matches within a page can constitute a single conceptual "Web page element".
xpath	XPathType	An XPath, e.g. of a SpeakableSpecification or WebPageElement . In the latter case, multiple matches within a page can constitute a single conceptual "Web page element".
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between

Property	Expected Type	Description
		something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of <code>rdf:type</code> in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.

Property	Expected Type	Description
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **SpeakableSpecification** may appear as a value for the following properties

Property	On Types	Description
speakable	Article or WebPage	Indicates sections of a Web page that are particularly 'speakable' in the sense of being highlighted as being especially appropriate for text-to-speech conversion. Other sections of a page may also be usefully spoken in particular circumstances; the 'speakable' property serves to indicate the parts most likely to be generally useful for speech. The <i>speakable</i> property can be repeated an arbitrary number of times, with three kinds of possible 'content-locator' values: 1.) <i>id-value</i> URL references - uses <i>id-value</i> of an element in the page being annotated. The simplest use of <i>speakable</i> has (potentially relative) URL values, referencing identified sections of the document concerned. 2.) CSS Selectors - addresses content in the annotated page, e.g. via class attribute. Use the cssSelector property.

Property	On Types	Description
		3.) XPaths - addresses content via XPaths (assuming an XML view of the content). Use the xpath property.
		For more sophisticated markup of speakable sections beyond simple ID references, either CSS selectors or XPath expressions to pick out document section(s) as speakable. For this we define a supporting type, SpeakableSpecification which is defined to be a possible value of the <i>speakable</i> property.

Source

<https://github.com/schemaorg/schemaorg/issues/1389>

Examples

📄 Example 1

No Markup	JSON-LD	Structure
-----------	---------	-----------

Example encoded as JSON-LD in a HTML script tag.

```
{
  "@context": "https://schema.org/",
  "@type": "WebPage",
  "name": "Jane Doe's homepage",
  "speakable": {
    "@type": "SpeakableSpecification",
    "cssSelector": ["headline", "summary"]
  }
}
```

```
{,  
  "url": "http://www.janedoe.com"  
}
```

📄 Example 2

No Markup

Microdata

Example notes or example HTML without markup.

An example of speakable markup in Microdata in HTML head section.