

UnitPriceSpecification

A Schema.org Type

[Thing](#) › [Intangible](#) › [StructuredValue](#) › [PriceSpecification](#) › **UnitPriceSpecification**

[\[more...\]](#)

The price asked for a given offer by the respective organization or person.

Property	Expected Type	Description
Properties from UnitPriceSpecification		
billingDuration	Duration or Number or QuantitativeValue	Specifies for how long this price (or price component) will be billed. Can be used, for example, to model the contractual duration of a subscription or payment plan. Type can be either a Duration or a Number (in which case the unit of measurement, for example month, is specified by the unitCode property).
billingIncrement	Number	This property specifies the minimal quantity and rounding increment that will be the basis for the billing. The unit of measurement is specified by the unitCode property.
billingStart	Number	Specifies after how much time this price (or price component) becomes valid and billing starts. Can be used, for example, to

Property	Expected Type	Description
		model a price increase after the first year of a subscription. The unit of measurement is specified by the unitCode property.
priceComponentType	PriceComponentTypeEnumeration	Identifies a price component (for example, a line item on an invoice), part of the total price for an offer.
priceType	PriceTypeEnumeration or Text	Defines the type of a price specified for an offered product, for example a list price, a (temporary) sale price or a manufacturer suggested retail price. If multiple prices are specified for an offer the priceType property can be used to identify the type of each such specified price. The value of priceType can be specified as a value from enumeration PriceTypeEnumeration or as a free form text string for price types that are not already predefined in PriceTypeEnumeration.
referenceQuantity	QuantitativeValue	The reference quantity for which a certain price applies, e.g. 1 EUR per 4 kWh of electricity. This property is a replacement for unitOfMeasurement for the advanced cases where the price does not relate to a standard unit.
unitCode	Text or URL	The unit of measurement given using the UN/CEFACT Common Code (3 characters) or a URL. Other codes than the UN/CEFACT Common Code may be used with a prefix followed by a colon.
unitText	Text	A string or text indicating the unit of measurement. Useful if you cannot provide a standard unit code for unitCode .
Properties from PriceSpecification		
eligibleQuantity	QuantitativeValue	The interval and unit of measurement of ordering quantities for which the offer or price specification is valid. This allows e.g.

Property	Expected Type	Description
		specifying that a certain freight charge is valid only for a certain quantity.
eligibleTransactionVolume	PriceSpecification	The transaction volume, in a monetary unit, for which the offer or price specification is valid, e.g. for indicating a minimal purchasing volume, to express free shipping above a certain order volume, or to limit the acceptance of credit cards to purchases to a certain minimal amount.
maxPrice	Number	The highest price if the price is a range.
membershipPointsEarned	Number or QuantitativeValue	The number of membership points earned by the member. If necessary, the unitText can be used to express the units the points are issued in. (E.g. stars, miles, etc.)
minPrice	Number	The lowest price if the price is a range.
price	Number or Text	The offer price of a product, or of a price component when attached to PriceSpecification and its subtypes. Usage guidelines: - Use the priceCurrency property (with standard formats: ISO 4217 currency format, e.g. "USD"; Ticker symbol for cryptocurrencies, e.g. "BTC"; well known names for Local Exchange Trading Systems (LETS) and other currency types, e.g. "Ithaca HOUR") instead of including ambiguous symbols such as '\$' in the value. - Use '.' (Unicode 'FULL STOP' (U+002E)) rather than ',' to indicate a decimal point. Avoid using these symbols as a

Property	Expected Type	Description
		readability separator. - Note that both RDFa and Microdata syntax allow the use of a "content=" attribute for publishing simple machine-readable values alongside more human-friendly formatting. - Use values from 0123456789 (Unicode 'DIGIT ZERO' (U+0030) to 'DIGIT NINE' (U+0039)) rather than superficially similar Unicode symbols.
priceCurrency	Text	The currency of the price, or a price component when attached to PriceSpecification and its subtypes. Use standard formats: ISO 4217 currency format, e.g. "USD"; Ticker symbol for cryptocurrencies, e.g. "BTC"; well known names for Local Exchange Trading Systems (LETS) and other currency types, e.g. "Ithaca HOUR".
validForMemberTier	MemberProgramTier	The membership program tier an Offer (or a PriceSpecification, OfferShippingDetails, or MerchantReturnPolicy under an Offer) is valid for.
validFrom	Date or DateTime	The date when the item becomes valid.
validThrough	Date or DateTime	The date after when the item is not valid. For example the end of an offer, salary period, or a period of opening hours.
valueAddedTaxIncluded	Boolean	Specifies whether the applicable value-added tax (VAT) is included in the price specification or not.

Property	Expected Type	Description
Properties from Thing		
additionalType	Text or URL	An additional type for the item, typically used for adding more specific types from external vocabularies in microdata syntax. This is a relationship between something and a class that the thing is in. Typically the value is a URI-identified RDF class, and in this case corresponds to the use of rdf:type in RDF. Text values can be used sparingly, for cases where useful information can be added without their being an appropriate schema to reference. In the case of text values, the class label should follow the schema.org style guide .
alternateName	Text	An alias for the item.
description	Text or TextObject	A description of the item.
disambiguatingDescription	Text	A sub property of description. A short description of the item used to disambiguate from other, similar items. Information from other properties (in particular, name) may be necessary for the description to be useful for disambiguation.
identifier	PropertyValue or Text or URL	The identifier property represents any kind of identifier for any kind of Thing , such as ISBNs, GTIN codes, UUIDs etc. Schema.org provides dedicated properties for representing many of these, either as textual strings or as URL (URI) links. See background notes for more details.
image	ImageObject or URL	An image of the item. This can be a URL or a fully described ImageObject .

Property	Expected Type	Description
mainEntityOfPage	CreativeWork or URL	Indicates a page (or other CreativeWork) for which this thing is the main entity being described. See background notes for details. Inverse property: mainEntity
name	Text	The name of the item.
potentialAction	Action	Indicates a potential Action, which describes an idealized action in which this thing would play an 'object' role.
sameAs	URL	URL of a reference Web page that unambiguously indicates the item's identity. E.g. the URL of the item's Wikipedia page, Wikidata entry, or official website.
subjectOf	CreativeWork or Event	A CreativeWork or Event about this Thing. Inverse property: about
url	URL	URL of the item.

Instances of **UnitPriceSpecification** may appear as a value for the following properties

Property	On Types	Description
currentExchangeRate	ExchangeRateSpecification	The current price of a currency.

Property	On Types	Description
hasTierRequirement	MemberProgramTier	A requirement for a user to join a membership tier, for example: a CreditCard if the tier requires sign up for a credit card, A UnitPriceSpecification if the user is required to pay a (periodic) fee, or a MonetaryAmount if the user needs to spend a minimum amount to join the tier. If a tier is free to join then this property does not need to be specified.
priceComponent	CompoundPriceSpecification	This property links to all UnitPriceSpecification nodes that apply in parallel for the CompoundPriceSpecification node.

Acknowledgements

GoodRelations Vocabulary Classes

This class is derived from the GoodRelations Vocabulary for E-Commerce, created by Martin Hepp. GoodRelations is a data model for sharing e-commerce data on the Web that can be expressed in a variety of syntaxes, including RDFa and HTML5 Microdata. More information about GoodRelations can be found at <http://purl.org/goodrelations/>.

Examples

📄 Example 1

No Markup Microdata RDFa **JSON-LD** Structure

Example encoded as JSON-LD in a HTML script tag.

```
<script type="application/ld+json">
{
```

```
"@context": "https://schema.org",
"@type": "CreditCard",
"name": "Wells Fargo Secured Visa® Credit Card",
"requiredCollateral": "Requires a minimum $300 security deposit.",
"amount": {
  "@type": "MonetaryAmount",
  "minValue": "300",
  "maxValue": "10000",
  "currency": "USD"
},
"offers": {
  "@type": "Offer",
  "offeredBy": {
    "@type": "BankOrCreditUnion",
    "name": "Wells Fargo"
  },
  "priceSpecification": {
    "@type": "UnitPriceSpecification",
    "price": "25",
    "priceCurrency": "USD",
    "referenceQuantity": {
      "@type": "QuantitativeValue",
      "value": "1",
      "unitCode": "ANN"
    }
  }
},
"annualPercentageRate": "18.99",
```



```
"feesAndCommissionsSpecification": "https://www.wellsfargo.com/credit-cards/secured/terms/"  
}  
</script>
```

Terms and conditions • Schema.org • V28.1 | 2024-11-22