

CS 246 Fall 2013 - Tutorial 2

September 24, 2013

1 Summary

- Shell Scripting
- Testing
- C++ I/O

2 Shell Scripting

2.1 Basic Scripting

- The following is a simple shell script that you may have seen before

```
1  #!/bin/bash
2  date
3  whoami
4  echo "Hello World!"
```

- Suppose that this script is contained in the file “simple.script”. How do we run this script?
- Answer 1: Use chmod to set the user executable bit
- Answer 2: Invoke bash with the script as a parameter

2.2 Command Line Arguments

- To make more complex shell scripts, we likely want to accept arguments from the command line
- Recall the following special shell variables:
 - `${#}` provides the number of arguments, excluding `$0`
 - `${0}` **always** contains the name of the script
 - `${1}`, `${2}`, `${3}`, ... refer to the arguments by position (not name)
 - `@` all arguments supplied to the currently running script (except `$0`), as separate strings
- Let's very quickly see these in action - see paramExample.script

2.3 More Complex Scripting

- Recall from lecture that bash shell scripts can have if-statements, routines, for-loops, while loops, variables, and possibly other things
- Let's write a shell script that determines the factorial of a given argument (> 0).
- Let's start by writing the main body of the program

```
1  #!/bin/bash
2  i=$(( ${1} - 1 ))
3  total=$1
4  while [ "${i}" -gt 1 ]; do
5      total=$(( ${total} * ${i} ))
```

```

6     i=$(( ${i}-1 ))
7 done
8 echo "${1} factorial is ${total}"

```

- But what if `${1}` isn't `> 0`? We should check this.

```

1  #!/bin/bash
2
3  if [ "${1}" -lt 1 ] # line *
4  then
5      echo "${1} is not > 0" 1>&2
6      exit 1
7  fi
8  # Insert body of function here

```

- Why do we encapsulate `${1}` in quotes on line `*`?
- What else should we check?
 - That we have a single parameter? Yes.
 - That the single parameter is a number? Yes. But that's more complicated so we won't

```

1  #!/bin/bash
2  if [ $# -ne 1 ]
3  then
4      echo "Incorrect number of parameters" 1>&2
5      echo "Usage: ${0} n, where n > 0"
6      exit 1
7  elif [ "${1}" -lt 1 ]
8  then
9      echo "${1} is not > 0" 1>&2
10     echo "Usage: ${0} n, where n > 0"
11     exit 1
12 fi
13 # Include body here

```

- But now we're duplicating lines of code. How to solve? Create a usage routine and call that!

```

1  #!/bin/bash
2  usage(){
3      echo "Usage: ${0} n, where n > 0" 1>&2
4      exit 1
5  }
6  if [ $# -ne 1 ]
7  then
8      echo "Incorrect number of parameters" 1>&2
9      usage
10 elif [ "${1}" -lt 1 ]
11 then
12     echo "${1} is not > 0" 1>&2
13     usage
14 fi
15 # Include body here

```

- Note that we could make this more robust and let our usage routine take a parameter but that's for you to figure out.

3 Testing

We're going to perform a miniature case study of testing and determine some possible test cases for a problem.

Problem: Given a program that reads from stdin a list of integers with the goal of determining if some combination of a list of integers can sum to the last integer given, where integers are ≥ 0 , e.g. input is of the form

```

n
x_1
x_2
..
x_n
y

```

where n specifies the number of possible summands, x_i is a possible summand in ascending order, and y is the target value. If no combination of integers can sum to the target value then “Impossible!” should be printed.

What are some possible test cases?

- Test containing 0 as target and no 0 summand should print “Impossible!”
- Test containing 0 as both, should print “Impossible!”
- Test which fails if you start from low and go to high
- Test which contains even integers and an odd target should print “Impossible!”
- Target smaller than all integers should print “Impossible!”
- Target less than largest integer but target still attainable

4 C++ I/O

- C++ I/O is radically different than the C I/O you may be used to
- For this course, you should not use C I/O unless told otherwise
- Recall, that C++ has three default input and output streams:
 - **cout** - standard output
 - **cerr** - standard error (unbuffered - prints immediately)¹
 - **cin** - standard input
- Let’s see an example that will take in a number and output a phrase. (phrases.cpp)

```

1  #include <iostream>
2  #include <string>
3  using namespace std;
4
5  int main() {
6      int choice;
7      int numChoices = 5;
8      string phrases[] = {"More Vespeene Gas required.", "The sun is shining. But the ice is slippery.",
9                          "Gotta go fast!", "Autobots, roll out!", "Do or do not. There is no try."};
10     cout << "Please choose a number from 1-5: ";
11     while(cin >> choice) { // cin needs to be read at least once before it can hit eof or fail
12         if(choice > numChoices)
13             cerr << "Invalid number" << endl;
14         else
15             cout << phrases[choice-1] << endl;
16         cout << "Please choose a number from 1-5: ";
17     }
18 }

```

- This program will end when either eof is reached or invalid input is given (e.g. non-integer input).
- Accordingly, this program is not very robust. How could we make it more so?
 - Explicitly checking for failure/eof by using `cin.fail()` and `cin.eof()` and not using the implicit conversion to boolean value

¹Technically, there are four. The fourth is `clog` and is basically buffered `cerr`

- If we are in a failure case then we could use `cin.ignore()` to ignore the next character of input and then `cin.clear()` to reset the failure flag
 - Why do we reset the failure flag?
- Recall that `cin` ignores any and all whitespace (unless you use an I/O manipulator to tell it otherwise).
- Suppose we wanted to get an entire line. How could we do this?
 - By using **`getline`**, e.g. `string s; getline(cin, s)`
 - Thus we take a line from `cin` and store it in the string `s`.
 - But how do we process this line now? Using **`stringstreams`**! But that's next week.