

retrigger.cmd - notes
=====

retrigger.cmd itself must stay comment-free: MAME's debugger command language is a separate thing from 6809 assembly, and it doesn't understand a leading ";" (or any other) comment syntax. Passing a commented file via -debugscript makes MAME try to interpret each comment line as a command in its own right, and it reports an error for every single one - harmless (the actual "go" command still runs correctly), but noisy. Hence this file lives here instead.

Why the file is just "go":

With -debug, MAME starts paused at the reset vector before any code runs at all - confirmed directly from MAME's own docs ("MAME also breaks into the debugger after the initial soft reset on startup if the debugger is active"). The serial connection is already established by this point too: mame_listener.py binds and starts listening before MAME is even launched, and "-bitb socket.HOST:PORT" makes MAME connect straight into it as part of its own startup. So there's nothing to wait for - "go" just resumes execution from the reset vector, which runs the normal cold-boot path (COLDSTRT -> ... -> JSR TSTRUNNER, since UNITTESTS=1 was baked into this specific ROM build) and all test output goes straight down the already-open socket.

If a future need arises to retrigger INITCODE specifically (rather than a full reset-vector boot - e.g. re-running tests without relauching MAME), that's a different command: "do pc=\$FFA6", per Section 6 of the ClaudeForth documentation. That's a manual debugger-window command for interactive use, not something this script currently automates.