OPEN ITEMS CHECKLIST — part 5 (16 October 2026)

Changes since part 4 (15 October 2026). Every stage was assembled in all four builds (`SERIALPOLL` 0/1 by `UNITTESTS` 0/1) and with test selectors 0, 10, 11 and 17, and the assembler unit tests and ANS tests were run by the user in MAME after each stage.

Page-zero scratch removed (stages 5k to 5m)

`GLOBALS` now uses **69 of 256 bytes** (127 before stage 5k). Polled `BASECODE` is 7963 bytes (was 8273), ending at `$FBDE` ; interrupt-driven is 8282, ending at `$FD1D` . `BASEDICT` is unchanged (`$D498` - `$DCC3`).

- ☑ **Stage 5k.** `WORD` (S frame: delimiter and start), `PARSE` and `PARSE-NAME` (start address is the result c-addr, length is the pointer difference), `-TRAILING` , `HEADER` (S frame), `SNAME` , `ENVIRONMENT?` , `ELSE` / `ENDOF` (orig1 parked on S), `UNTIL` / `AGAIN` / `LOOP` / `+LOOP` (the parked dest is already under the operand address, so `PATCH` is called directly), `REPEAT` (S frame) and `EXIT` (Y counts the DO frames). The `S"` family: `PARSEQUOTE` leaves `c-addr u` on the data stack and one helper, `CSTRCOMP` , compiles the call and the counted string for `S"` , `."` , `ABORT"` and `SLITERAL` . `DOABORTQUOTE` no longer pushes a stray register before its `THROW` . `CURXT` had shared a cell with `NEWHDR` ; it now has its own. Shadow entry `WORDW.7` .
- ☑ **Stage 5l.** `FIND` keeps the counted string on the data stack for the whole search and replaces it with the result; `SETDOES` reads the length byte into B. Shadow entry `FINDW.1` .
- ☑ **Stage 5m.** `>NUMBER` / `NUMLOOP` / `UDMULADD` work in place on the `( ud c-addr u )` frame, which `NUMBER?` now builds itself (with a 3-byte S frame for the original c-addr and the negate flag, and an in-place 32-bit negate). `#` and `#S` divide the double in place (`UDDIGIT` returns the remainder in A). `.` , `.R` , `D.` and `D.R` hold their sign cell on S. Shadow entry `NUMBERQ.6` .
- ☑ **Decision: stop here.** What is left is the shared multiply/divide convention (`PRODHI` / `PRODLO` , `DIVNUM` / `DIVDEN` / `DIVREM` , `MAHI` - `MBLO` , the sign flags) and the four `MSCR` cells, about 45 bytes. Those words

share the cells deliberately, and moving them to the stack would rewrite about 800 lines, make them larger and slower, and free space nothing needs.

- ☑ **Idea considered and rejected:** using the `DP` register as a byte-save location. `TFR` to or from `DP` takes 6 cycles against 4 for a direct-page `STA` / `LDA` and 4-5 for a stack-frame access, it would break direct addressing of `GLOBALS` while active, and `IRQH` could fire with the wrong direct page. No loop in the source saves and restores a byte on every pass.

Documentation

- ☑ `ClaudeForth.docx` and preview PDF dated 16 October 2026: memory map table and ROM sizes (padding 965 / 646 bytes; unused ROM 5985 / 5666 bytes), Section 5 items, regenerated source appendix (stage 5m), rebuilt index and page numbers. Memory-map SVG and PDF regenerated.
- □ **Timeline** on the title page not updated.