OPEN ITEMS CHECKLIST — part 11 (5 November 2026)

Changes since part 10. Stage 6o adds chained interrupt handlers and redirectable character I/O. Source: `forth6809_stage_6o.asm`; documentation: `ClaudeForth 20261105` (rebuilt, new Section 4.9); shadow file: `forth6809 20261105.shd` (IOVEC.1, IRQH.1, MEMMAP.22).

Done in stage 6o (tested in my emulator, polled build)

- ☑ **Redirectable `EMIT`, `KEY` and `KEY?`.** They are now `JMP [EMITV]`, `JMP [KEYV]` and `JMP [KEYQV]` (page-zero cells). The serial routines are renamed `EMITACIA`, `KEYACIA`, `KEYQACIA`. New words `(EMIT)`, `(KEY)`, `(KEY?)` return the cell addresses: `' MYEMIT (EMIT) !`, `(EMIT) @`. `IOVINIT` resets the cells at cold start, warm start and in `QUIT` after a caught error (before `ERROR n` is printed). `PUTXON` and `PUTXOFF` bypass the vectors. `ACCEPT` 's echo goes through `EMIT`.
- ☑ **Chained interrupt handlers.** When `IRQH` finds the interrupt is not from the ACIA it does `JMP [IRQCHAIN]`; the cell starts at an RTI (`IRQRTI`). The polled build's `IRQH` is the same jump, so chaining works in both builds. New word `IRQ-CHAIN ( -- addr )`. The cell is set by cold start only. FIRQ and NMI are not chained.
- ☑ **Space:** 4 headers (+46 bytes), +68 bytes of code, +8 page-zero bytes (`GLOBALS_USED` 139+19*DISASM+21*DECOMP). The init code had 1 byte spare, so `INITCODE` moved from `$FFA4` to `$FF9C` (INITSIZE 81). `BASECODE` / `BASEDICT`: `$D876/$CE99`, `$D180/$C792`, `$CE00/$C40A` (DISASM/DECOMP 0 0, 1 0, 1 1). Default build: 269 headers, 12305 bytes of code polled (395 spare), 12624 interrupt (**76 spare**), dictionary 2550.
- ☑ **Unit-test region shrank** (778 bytes with both options on, 1682 with `DECOMP=0`, 3225 with `DISASM=0`). Effects: group 10 (Memory) no longer fitted even with `DISASM=0` (3485 bytes), so it is **split into groups 10 and 21** (`TSTCMOVE`, `TSTCMOVEGT`, `TSTMOVE1-3` moved to 21). Both scripts now run 22 groups. With `DISASM=1 DECOMP=0` groups 0, 2, 13, 14, 15, 17 fit (5 dropped, 10 bytes over); with both on **none** fit (13 is 18 bytes over, 15 is 152). `FIT_DISASM` and `FIT_DECOMP` updated in both scripts.

- ☑ **Tests (emulator):** new `38_io_vectors.tests.fs` (18 tests: cells in page zero and distinct; `IRQ-CHAIN @ C@` is `$3B`; output captured through `EMIT`, `TYPE`, `.`, `SPACE`, `CR`; restore; `KEY` and `KEY?` redirected; `ACCEPT` fed from a string with its echo captured). Checked by hand: the vectors are reset after an undefined word, after `ABORT` and after a division error. Regression: ANS 33 (78), 34 (23), 27 (50), 36 (14), 37 (64), 8 (71), 12 (73), `see_check.py` 19/0. Unit-test groups 0-21 pass with `DISASM=0` (group 0 `TSTKEYQ FAIL` is the known emulator artifact); 0, 2, 13, 14, 15, 17 pass with `DISASM=1 DECOMP=0`.
- ☑ **Documentation:** four glossary entries; `KEY`, `KEY?`, `EMIT`, `ACCEPT` and `QUIT` entries mention the vectors; new Section 4.9; memory map, size figures, BASECODE/BASEDICT and unit-test tables, group 21, counts 265 → 269; Section 5 item; index.

Open items

- □ **Please run in lwasm and MAME:** all combinations of `SERIALPOLL`, `DISASM` and `DECOMP` assemble; `38_io_vectors.tests.fs` (add `38` to `--sections`); the unit-test scripts (22 groups; some groups are SKIPPED with `DISASM=1`). My emulator cannot run the interrupt-driven build (`SERIALPOLL=0`), so I checked that build only by assembling it and reading the bytes (`JMP [IRQCHAIN]` is `6E 9F 00 83`).
- □ **A test of a real chained interrupt is missing.** `IRQ-CHAIN` is tested only for its initial value. A proper test needs an interrupt source other than the ACIA (in MAME, a timer) to hit a chained handler.
- □ Decide whether the lost unit-test coverage matters: with the disassembler on, groups 5, 13 and 15 (and 16 since 6n) can no longer be built. To get 13 and 15 back with both options on, about 150 bytes would have to be found.
- □ Timeline entry for the 6o work (hours) — needs your figures.
- □ `CASE` is not rebuilt by `SEE` and other `SEE` limits (part 9) still apply.
- □ A unit test group for the Search-Order words is still missing.
- □ README_ANS.md: add `38` to the `--sections` list and list `38_io_vectors.tests.fs`; README.md Plans: "Vectored I/O" and "Interrupt chaining" can be ticked (see `README_review_6o.md`).