meeami-tts

Time-aligned US-English text-to-speech on the word timing of a non-US reference

Project report · Chaganti Raja Ravi Teja · November 2026

Code: https://github.com/rrtchaganti/meeami-tts (frozen at git tag `freeze-v1`, commit 5889ecf)
Models and all test outputs: https://huggingface.co/Raviteja546/meeami-tts

23.9 ms	0 samples	2.9%	4.20
word-boundary error (V0, original VITS: 40.5 ms)	length error on all 1,248 test references	WER of the output (L2 references: 6.3%)	UTMOS naturalness (LJSpeech recordings: 4.36)

Held-out test accents (Arabic, Korean, Vietnamese; 12 speakers × 104 sentences), evaluated once after the code freeze.

Abstract

Given an English text and a recording of it by a non-US speaker, the system speaks the text in the LJSpeech US voice and accent while following the recording's timing: the output is exactly as long as the reference and every word starts and ends where the speaker said it, pauses included. The reference contributes timing only. The approach makes durations an *input*: VITS is fine-tuned from the official LJSpeech checkpoint with monotonic alignment search (MAS) replaced by Montreal Forced Aligner (MFA) phone durations. At inference, MFA finds the reference's word boundaries, and each word's span is filled with the model's own native phone rhythm (one elastic factor per word, a 2.5× stretch cap, exact cumulative rounding). On 1,248 held-out test references, word boundaries land 23.9 ms from the human annotation (MFA's own error on accented speech is 19.4 ms), against 40.5 ms for the original VITS given the same timing and 31.9 ms for FastSpeech2. Two diagnosed defects were fixed with minimal, controlled changes (a position-in-phone embedding and a two-token diphthong); two pace-augmentation ablations are reported as negative results. All decisions were fixed on dev accents before the test accents were read.

Contents

1. Introduction **3**

1.1 Task . . . 3

1.2 Contributions . . . 3

1.3 Constraints . . . 3

2. Data and the accent-disjoint split **3**

3. Method **4**

3.1 Design principle: one source per output property . . . 4

3.2 Text front end . . . 4

3.3 Forced alignment and its error on accented speech . . . 5

3.4 Models . . . 5

3.5 Inference: transferring word timing . . . 6

4. Evaluation methodology **7**

5. Experiments and ablations **8**

5.1 Inference tuning (dev) . . . 8

5.2 Phase 1: M1 vs M0 (dev) . . . 8

5.3 Phase 2a: "words end sharply" → position-in-phone embedding . . . 8

5.4 Phase 2b: pace augmentation, Ablations A and B (negative result) . . . 9

5.5 Phase 2c: "cry" heard as "cra" → two-token diphthong . . . 9

5.6 The immediate baseline V0 and duration fidelity . . . 9

6. Results on the held-out test accents **10**

7. Efficiency **14**

8. Robustness and live testing **14**

9. Limitations and future work **15**

10. Reproducibility and deliverables **15**

Appendix A. Deviations from the plan **16**

Appendix B. Claim → evidence **16**

How to read this report. Tables and figures are generated from the committed result files by `scripts/build_report_pdf.py` (`make report-pdf`). `D-n` / `E-n` refer to entries of the decision and error log `docs/DECISIONS.md`; `docs/REPORT.md` holds the same material with a link to the exact line of code behind every claim. Audio for every claim is in `samples/` (byte-exact copies of the evaluated files).

1. Introduction

1.1 Task

Inputs: an English text and a recording of that text read by a **non-US** speaker (the *reference*). **Output:** speech that (1) says exactly the input words with a US accent, (2) is in the LJSpeech voice (one US female speaker) and (3) follows the reference's timing: the same total length, every word starting and ending at about the reference time, pauses included. Voice, accent and pronunciation of the reference must not leak.

Why it is hard. Part of an accent lives in timing: L2 speakers lengthen, shorten and pause differently. The system must copy *word-level* timing from the reference while keeping *phone-level* timing inside each word native, and it must stay natural when a word is forced to be much slower or faster than the voice would say it.

1.2 Contributions

- **Durations as an input.** VITS fine-tuned with MFA durations instead of MAS (VITS-MFA), so a reference can dictate timing; measured against the unmodified VITS (V0) given the same timing: 40.5 → 23.9 ms word-boundary error.
- **Word-timing transfer with native rhythm** (elastic fit, stretch cap, exact-length quantization): output length is exact for every reference by construction.
- **Two diagnosed fixes** from listening reports, each with a pre-stated success rule and a one-key control: a position-in-phone embedding (US probability +0.09 on dev) and a two-token diphthong ("cry" heard as "cra"; test WER 4.4% → 2.9%).
- **Two pace-augmentation ablations** (target-agnostic A, target-aware B) reported as negative results.
- **An accent-disjoint evaluation** with a test lock enforced in code, a paired-statistics protocol, and probes that separate the model's rendering error from the aligner's error.

1.3 Constraints

Constraint	Consequence for the design
Train on LJSpeech only	Voice and accent come from one US speaker; L2 data is used only for evaluation, tuning and Ablation B's statistics.
Generalise to unseen accents	L2-ARCTIC split by accent; test accents locked in code until git tag freeze-v1 exists.
One rented L40S GPU for ~8 h, an 8 GB laptop GPU	M1 trained once on the full budget; every later experiment branches from it for 20k steps.
A live demo on unseen files	Edge-case suite, CTC aligner fallback, exact output length by construction, typed-text pre-pass.

2. Data and the accent-disjoint split

Dataset	Use
LJSpeech 1.1: 13,100 clips, one US female speaker, 22.05 kHz	Training, with the original VITS filelists (12,500 / 100 / 500), so the pretrained checkpoint never saw val or test. MFA kept 13,073 (99.79%).
L2-ARCTIC v5: 24 speakers, 6 L1s × 4	References for dev and test; its hand-corrected word tiers are the timing ground truth.
Dev accents: Hindi, Mandarin, Spanish	Tuning, phase-2 decisions, Ablation B's pace statistics. 100 sentences × 12 speakers = 1,200 references.
Test accents: Arabic, Korean, Vietnamese	Read once, after freeze-v1. 104 sentences × 12 speakers = 1,248 references.

Table 1. Data. Evaluation uses the utterances that have a manual annotation for every speaker of the split.

Why split by accent. The claim to support is "works for accents the system was never tuned on"; a sentence-level split would let tuning see every accent. **The lock is code, not convention:** reading a test speaker's audio raises `SplitLockedError` unless `git rev-parse`

`refs/tags/freeze-v1` succeeds, and a unit test fills fake test WAVs with junk bytes so any premature read fails.

3. Method

3.1 Design principle: one source per output property

Output property	Its only source	Deliberately not taken from
Words	input text → normalizer	the reference audio or an ASR transcript
Pronunciation	data/lexicon/lexicon.txt (first CMUdict entry; g2p_en for OOV)	the reference's pronunciation
Voice, accent, intonation	the model, trained on LJSpeech only	the reference (no accented audio in training)
Word start/end times, pauses, length	the reference, aligned with MFA	the model's own durations
Phone timing inside a word	the model's native durations, fitted to the word span	the reference's phone timing, which carries accent

Table 2. Nothing is averaged between reference and model, so each failure has one place to look. Evidence for the last row: copying the reference's phone durations gave the worst WER of the tuning grid (10.6% vs 2.5%; §5.1).




Figure 1. Inference pipeline. Timing enters only through the reference's word boundaries; inside each word the model's native phone rhythm is stretched with LJ's own elasticity.

3.2 Text front end

- **One normalizer** for training text, MFA transcripts and inference input (currency → symbols → unidecode → dates → times → abbreviations → numbers); any digit left over raises instead of being dropped.
- **Lexicon:** 14,912 words, one pronunciation each: 13,640 from CMUdict, 1,168 from g2p_en, 104 from a possessive rule (g2p_en mangled *x's* when *x* is in CMUdict). Unseen words at inference are G2P'd and appended to the same file, so it stays the only pronunciation source.
- **Symbols:** pad, sil, sp + 69 ARPAbet phones = 72, exactly MFA's english_us_arpa phone set (asserted by a test), so every model token has an MFA duration.
- **Typed-text pre-pass** (added after the freeze for live input): money, times, dates, ratios, units, URLs, e-mails, Roman numerals, CamelCase, initialisms and vowel-less letter strings, plus refusals for non-Latin script. 119 of 121 stress cases pass; a test asserts that every L2-ARCTIC transcript gives the same words as before.

3.3 Forced alignment and its error on accented speech

MFA 3.4.3 with the pretrained english_us_arpa model and our lexicon aligns LJSpeech (training durations), the L2 references (the timing to copy) and the model outputs (the measured timing), with one set of parsing rules, so alignment conventions cancel in comparisons. Wide beam (100 / retry 400); MFA silently drops unknown flags, so the wrapper validates every flag. Boundaries are rounded on cumulative times (no drift), internal silences ≥ 3 frames become `sp`, and every speech phone gets ≥ 1 frame (382 phones had 0 frames otherwise).

Dev accent	Word MAE	Word ≤ 20 ms	Phone MAE	Phone ≤ 20 ms
Hindi	18.2 ms	76.8%	12.3 ms	89.0%
Mandarin	20.2 ms	74.2%	14.0 ms	86.7%
Spanish	19.9 ms	74.0%	13.2 ms	87.6%
All (1,800 utterances)	**19.4 ms**	**75.0%**	**13.1 ms**	**87.7%**

Table 3. MFA against L2-ARCTIC's hand-corrected tiers (reports/mfa_l2_dev.md). The system metric aligns the output with MFA and compares with the manual reference annotation, so about 19 ms of MFA error is part of every system's score: 23.9 ms is close to that measurement floor. Fallback aligner: MMS_FA CTC (~53 ms MAE).




Figure 2. MFA's word and phone boundary error on the dev accents against the manual annotation.

3.4 Models

V0, the immediate baseline (inference only): the official pretrained LJSpeech VITS exactly as released (MAS-learned alignment, stochastic duration predictor, blank tokens, IPA characters). It is the checkpoint M1 is fine-tuned from, so V0 vs M1 measures the MAS → MFA swap. Lexicon phones are written in espeak-style IPA; its predicted per-character durations give each phone's native rhythm, and the same word-timing fit drives it. Its one adapter choice (which phone owns a blank) was made on dev (blank → next character: 40.7 vs 50.8 ms).

M0, the second baseline (inference only): ming024's pretrained FastSpeech2 + HiFi-GAN; reference durations enter as d_targets through the variance adaptor's training path.

M1, VITS-MFA: jaywalnut310/vits fine-tuned from the official checkpoint (553 matching tensors loaded) with six changes:

#	Change	Reason
1	Remove MAS; alignment = one-hot expansion of MFA durations	Durations must be controllable at inference; MAS learns its own alignment, which a reference cannot override.
2	No blank tokens	Blanks have no MFA duration.
3	72 ARPAbet symbols; text embedding re-initialized	The pretrained model read 178 IPA characters.
4	Deterministic duration predictor on the detached encoder, MSE on log frames, masked on sil	Only native relative durations inside a word are needed; sampling would add random rhythm.
5	Optional position-in-phone embedding (16 bins)	Lets the prior change inside a phone (phase 2a).
6	Data loader on the project manifests	One manifest format for all data.

Table 4. PLAN changes from VITS to VITS-MFA. Posterior encoder, flow, HiFi-GAN decoder and the VITS losses are unchanged.

$$L_G = 45 \cdot L_{mel} + L_{KL} + L_{dur} + L_{adv} + 2 \cdot L_{fm},\ L_{dur} = mean_i\ (\log \hat{d}_i - \log d_i)^2$$

Error on the log scale is relative (2× off costs the same for a 3-frame stop and a 20-frame vowel) and its minimizer is the geometric-mean duration, the natural centre for the multiplicative fit of §3.5. **Training:** 114,000 steps at batch 32 on one L40S (~8 h; bf16 networks, fp32 losses). val/dur fell throughout (0.134 → 0.094); val mel-L1 reached its minimum at 12k and rose slightly, the GAN trade-off rather than overfitting (train and val drifted together, discriminator balanced). Phase-2 variants branch from M1 for 20,000 steps each with a fresh optimizer; new parameters start so that every variant *is* M1 at step 0.




Figure 3. M1 training curves (phase 1, 114k steps).

System	Difference from M1 (one key each, asserted by tests)
m1_cont	+20k steps, no change: the control for "more training"
m1_pos	use_pos: true (position-in-phone embedding, zero-initialized)
abl_a_pos	m1_pos + 40% Ablation A clips (target-agnostic pace augmentation)
abl_b_pos	m1_pos + 40% Ablation B clips (pace statistics of the dev accents)
m1_pos_diph (main)	**m1_pos + diph_split: each diphthong X becomes X + X+ (87 symbols)**

Table 5. Phase-2 variants: one start point, one step count, one optimizer reset; each pair differs in one setting.

What a fixed external alignment takes away. MAS re-chooses the alignment every step from the model's own prior and flow output; MFA's alignment is fixed by an HMM-GMM that never sees the latent space. The gradients through the KL term are unchanged (MAS is not differentiable), but the feedback from latent space to alignment is lost: boundary errors stay in the KL for all of training, and with no blanks each phone has one constant prior over all its frames. Measured: every MFA-trained model moves 14-16% less inside phones than the LJ recordings (Figure 4). What it buys is control: the fine-tuned systems render given durations about on time (§5.6).




Figure 4. Phone dynamics on 100 LJ val clips resynthesized with ground-truth durations: mean log-mel movement inside phones relative to the LJ recordings, and how much movement is piled up at phone onsets.

3.5 Inference: transferring word timing

For a word of D reference frames, the duration predictor gives native durations $\hat{d}_i$ for its phones, and every phone is scaled with one z per word, found by bisection:

$$d_i = exp(log\ \hat{d}_i + z{\cdot}\sigma_i),\ \Sigma_i\, d_i = D$$

σ_i is the phone's standard deviation of log duration in LJ train, so phones LJ naturally stretches (vowels) absorb most of the change and stops barely move: the word fills the reference's slot the way the LJ speaker would say it slower or faster. *Example*, "cry" at twice its native length: proportional scaling gives K/R/AY ×2.0 each; elastic gives ×1.75 / ×2.4 / ×2.0.

- **Stretch cap.** Beyond 2.5× native length a word is not stretched further; the excess becomes a pause and the next word still starts on time. It acts on 148 words in 128 of 1,248 test references.
- **Exact length.** Cumulative rounding to exactly round(N_{ref}·22050/sr_{ref}/256) frames (each word boundary within half a frame), then pad/trim to the exact sample count. Length error is an asserted invariant, not a statistic.
- **Diphthong split at the model boundary only.** m1_pos_diph splits each diphthong right before the model and merges the two predicted durations afterwards; lexicon, MFA and pipeline keep 72 symbols.

4. Evaluation methodology

Requirement	Metric	Definition
Exact length	Length error	output samples − round(N_ref·22050/sr_ref); must be 0
Word timing	Word-boundary MAE; % within 20 / 50 ms	every word's start and end; reference times from the **manual** annotation, output times from MFA on the output; words matched by sequence alignment
Pauses	Pause F1	pause = silence ≥ 100 ms between two matched words; F1 over word boundaries
Exact words	WER, CER	faster-whisper large-v3 vs input text, both through Whisper's EnglishTextNormalizer; also run on the references and LJ
US accent	US probability	CommonAccent ECAPA accent-ID, softmax(30·cosine)
LJ voice	Speaker similarity	ECAPA cosine to the mean of 100 LJ test clips (high) and to the reference speaker (low)
Naturalness	UTMOS	SpeechMOS utmos22_strong; LJ recordings are the ceiling
Robustness	Stretch ratio	speech frames ÷ the model's native frames, for binning

Table 6. Metrics. All evaluation models are pinned by version and sha256 and loaded offline.

- **Statistics.** 95% percentile bootstrap CIs over utterances (1,000 resamples). Paired Wilcoxon signed-rank tests of each system against its own control, overall, per accent and per stretch tercile; Holm-adjusted within each family of 8 metrics. Every system speaks the same references, so paired differences remove between-sentence variance.
- **Decision rules before results.** The tuning rule, the phase-2a winner rule and the diphthong success criteria were written in DECISIONS.md before each run.
- **Probes.** Duration fidelity (where a word lands in the output vs where the pipeline put it: separates the model's rendering error from the shared reference-alignment error), aligner calibration on natural dev speech, phone dynamics, an LPC formant probe for diphthong glides, and the reference pace ρ.

Caveats, stated rather than hidden.

- Accent-ID US probability is near-binary per utterance (softmax ×30); it flips on inaudible changes, so it is read only as a population mean.
- MFA judges systems trained on MFA durations, which may favour them. CTC, the second judge, has a +38 ms start bias on natural speech (calibration: MFA bias 0.0 ms, CTC +38.2 ms), so CTC numbers are read against CTC's own zero point, never as a ranking.
- UTMOS chose the augmentation stretcher's parameters (on LJ only) and is also an evaluation metric.

- M1's dev numbers are slightly optimistic: 120 of 1,200 dev references were used for tuning. Test has no such bias.

5. Experiments and ablations

Each phase-2 round started from a listening observation, checked the input first, measured the defect with a targeted probe, found the design cause, made a minimal opt-in fix with a one-key control, and re-measured with the same probe plus the full metric set. All decisions below were made on dev.

5.1 Inference tuning (dev)

21 settings on a fixed 120-utterance dev subset: transfer variant (elastic, proportional, phone_copy), stretch cap, prior noise scale and aligner. Rule, fixed before running: among elastic settings within 5 ms of the best MAE, take the highest UTMOS. Chosen: elastic, cap 2.5, noise 0.333, MFA (21.9 ms; best 21.5 ms; UTMOS 4.21; WER 2.5%).




Figure 5. Tuning grid. The noise scale drives WER (0.333: 2.5-3.5%; 0.667: 4.6-6.7%), a looser cap lowers MAE at no UTMOS cost, and copying the reference's phone durations (phone_copy) has by far the worst WER: the reference's phone timing carries accent, so only word boundaries are copied.

5.2 Phase 1: M1 vs M0 (dev)

Dev, 1,200 references	M0 (FastSpeech2)	M1 (VITS-MFA)
Word-boundary MAE	31.3 ms	**23.7 ms** (p ≈ 1e-140)
Within 20 ms	55.4%	**68.5%**
Pause F1	0.75	**0.84**
WER	10.0%	**3.5%**
UTMOS	3.94	**4.20**
US probability	0.73	0.72 (n.s.)

Table 7. Both systems receive the same durations; M1 renders them more crisply. US probability did not improve, which set up phase 2.

5.3 Phase 2a: "words end sharply" → position-in-phone embedding

Probes ruled out energy, pitch and the duration predictor at word ends; what differed was spectral movement *inside* phones (14% below LJ, 20% in the middle third). Cause: without blanks every frame of a phone shares one constant prior mean. Fix: frame k of a d-frame phone gets bin ⌊16(k + 0.5)/d⌋ and a learned vector is added before the prior projection. **Result vs m1_cont** (the same 20k steps without the change): within-phone movement did not move (0.856× vs 0.858× LJ; the learned effect sits at phone edges, which the probe excludes), but US probability rose 0.680 → 0.769 (p = 5e-31, higher in all three accents) with no significant change elsewhere. m1_pos became the base for the next rounds.

5.4 Phase 2b: pace augmentation, Ablations A and B (negative result)

Hypothesis: training on time-stretched LJ teaches the model to stay natural at high stretch ratios. **A (target-agnostic):** utterance pace $z_u \sim U(-1.5, 1.5)$, word pace $z_w = z_u + N(0, 0.5^2)$, the same elastic factors as inference, longer and inserted pauses from room tone. **B (target-aware):** word paces and pauses sampled from dev-accent statistics (AR(1) residuals, P(pause) = 0.223); word-level ratios only. 2 copies per LJ clip mixed 60/40; the duration loss is masked on augmented rows; the 5% worst clips by UTMOS drop removed.

A forced deviation: the planned Rubber Band R3 stretcher degraded every clip (UTMOS 4.38 → 2.92, ~1.2 even for < 5% stretch), so a time-varying WSOLA stretcher with the same time map was written in numpy (mean UTMOS drop 1.336 → 0.321; re-alignment matched the planned boundaries to a median ~7 ms).

Dev, paired vs m1_pos	m1_pos	abl_a_pos	abl_b_pos
Word-boundary MAE	24.16 ms	24.04 (n.s.)	24.21 (n.s.)
WER	3.9%	3.4% (n.s.)	3.9% (n.s.)
US probability	0.769	**0.642** (p < 1e-10)	0.747 (n.s.)
UTMOS	4.18	**4.07** (p < 1e-10)	**4.10** (p < 1e-5)

Table 8. Neither ablation improved timing or WER in any stretch tercile, both cost UTMOS, and B shows no gain even on the accents its statistics came from. Likely cause: residual stretch artifacts in 40% of batches. A's pace range is far wider than real L2 pace, hence its US-probability loss.

5.5 Phase 2c: "cry" heard as "cra" → two-token diphthong

The lexicon gives cry → K R AY1, so the error was the model's. An LPC probe showed the reference gliding to /ɪ/ (F2 +285 Hz, F1 737 → 554) while M1, m1_cont and m1_pos held an /a/; across LJ val every model flattened diphthongs (mean |ΔF2| 307-321 Hz vs 396 for LJ). **Cause: token design.** The pretrained VITS read "cry" as k _ ɹ _ ˈ _ a _ ɪː a diphthong was two targets and a transition; ARPAbet made it one token with one constant prior. **Fix:** AW, AY, EY, OW, OY (× 3 stresses) become X + X+ (72 → 87 symbols); MFA's duration is split 50/50 and merged back as $\log(e^a + e^b)$ for timing; each X+ embedding starts as a copy of X.

Dev, paired vs m1_pos	m1_pos	m1_pos_diph	p (Holm)
Word-boundary MAE	24.16 ms	**23.48 ms**	< 1e-6
WER	3.9%	**2.7%**	< 1e-6
CER	2.0%	**1.2%**	< 1e-6
UTMOS	4.18	**4.20**	2e-4
US probability	**0.769**	0.738	1e-4
Mean |ΔF2| of diphthongs (LJ 396 Hz)	321 Hz	**389 Hz**	

Table 9. "cry" now glides (F1 864 → 528 Hz, F2 +215 Hz). The one unmet criterion, US probability, was investigated: it does not correlate with the number of diphthongs, sentences without any dropped too, the classifier flips both ways (91 large drops vs 58 rises), and the four largest drops sounded identical to the listener. Decision (D-85): m1_pos_diph is the main system; then the code was frozen and the test split read once.

5.6 The immediate baseline V0 and duration fidelity

V0 is the same pretrained VITS before the MAS → MFA swap, given the same word timing through the same pipeline. To see *why* it misses the timing, the fidelity probe compares where MFA finds each word in the output with where the pipeline placed it, which removes the shared error of aligning the reference.




Figure 6. Duration fidelity on test (MFA on the outputs vs the planned word times). V0 renders its given durations ~20 ms early and scattered; the fine-tuned systems render them about on time. CTC, an independent judge read against its own zero point, finds the same early shift for V0.

Two judges agree on the direction and size of V0's shift; CTC's own scatter is too large to rank the scatter, so that part rests on MFA. **The trade-off, stated plainly:** V0 is the stronger system on WER and UTMOS; fine-tuning on MFA durations without blanks bought controllable timing and a more US-like accent, at a cost the diphthong split already halved (M1 − V0: +1.7 WER points; main − V0: +0.8).




Figure 7. Every paired comparison of the project, as mean difference (system − control) per utterance.

6. Results on the held-out test accents

Arabic, Korean and Vietnamese, 12 speakers, 1,248 references; read once after freeze-v1. All 1,248 references were aligned by MFA (no CTC fallback). Length error is 0 for every output of every system.

System	Word MAE (ms) [95% CI]	≤ 20 ms	Pause F1	WER	US prob	UTMOS	Spk sim LJ
L2 references				6.3%	0.486		
LJSpeech recordings				1.9%		4.36	
V0 (VITS + MAS)	40.5 [39.7, 41.2]	41.2%	0.815	2.1%	0.649	4.31	0.802

System	Word MAE (ms) [95% CI]	≤ 20 ms	Pause F1	WER	US prob	UTMOS	Spk sim LJ
M0 (FastSpeech2)	31.9 [31.1, 32.7]	55.3%	0.726	9.3%	0.746	3.96	0.766
M1 (VITS-MFA)	24.2 [23.5, 24.9]	69.3%	0.822	3.8%	0.734	4.19	0.805
m1_pos	24.6 [24.0, 25.4]	68.3%	0.826	4.4%	0.781	4.17	0.806
m1_pos_diph (main)	**23.9 [23.3, 24.7]**	**69.6%**	**0.835**	**2.9%**	**0.762**	**4.20**	**0.800**
abl_a_pos	24.7 [24.0, 25.5]	68.3%	0.825	3.9%	0.665	4.06	0.801
abl_b_pos	24.7 [24.1, 25.4]	68.3%	0.826	4.5%	0.767	4.08	0.796

Table 10. Main results (results/<system>/test/summary.json). Speaker similarity to the reference speaker stays low (0.11 for the main system): the reference's voice does not leak.

Paired comparison (test)	Δ MAE (ms)	Δ ≤ 20 ms (pt)	Δ WER (pt)	Δ UTMOS	Δ US prob
m1_pos_diph − m1_pos	-0.7 (p 1e-8)	+1.2 (p 1e-4)	-1.5 (p 1e-8)	+0.03 (p 1e-5)	-0.019 (p 0.017)
abl_a_pos − m1_pos	+0.0 (n.s.)	-0.1 (n.s.)	-0.5 (n.s.)	-0.11 (p 4e-38)	-0.116 (p 8e-45)
abl_b_pos − m1_pos	+0.1 (n.s.)	-0.1 (n.s.)	+0.1 (n.s.)	-0.09 (p 4e-23)	-0.014 (n.s.)
m1_pos_diph − M1	-0.3 (n.s.)	+0.3 (n.s.)	-0.9 (p 2e-5)	+0.01 (n.s.)	+0.027 (n.s.)
M1 − V0	-16.3 (p 4e-189)	+28.1 (p 2e-184)	+1.7 (p 3e-11)	-0.12 (p 8e-33)	+0.086 (p 3e-12)
m1_pos_diph − V0	-16.5 (p 5e-192)	+28.4 (p 1e-185)	+0.8 (p 0.004)	-0.12 (p 3e-28)	+0.113 (p 8e-20)

Table 11. Paired Wilcoxon tests on the 1,248 test references, Holm-adjusted (results/paired/test_*.csv).

Findings.

- **Replacing MAS with MFA durations is what makes the output follow the reference timing:** main vs V0, −16.5 ms MAE and +28 points within 20 ms, in every accent and every stretch range; the cost is +0.8 WER points and −0.12 UTMOS.
- **VITS-MFA beats FastSpeech2 on every axis but accent** (M1 vs M0: −8 ms MAE, WER 9.3% → 3.8%, UTMOS +0.23).
- **The diphthong split replicated on test** against its control: WER −1.5 points, MAE −0.7 ms, UTMOS +0.03.
- **Pace augmentation is a negative result on test too:** no timing or WER gain; UTMOS −0.11 (A), −0.09 (B).
- **Dev conclusions replicated on the unseen accents,** and the reference pace on dev (1.12× LJ) matched test (1.16×).




Figure 8. The headline sample, YBAA_arctic_a0003 ("For the twentieth time that evening the two men shook hands"). Top: the L2 reference with its human word annotation; below: the main system and V0, each with word times found by MFA on the output. Same length by construction; the main system's words sit on the reference's word starts, V0's drift early. Audio: samples/demo/arabic/YBAA_arctic_a0003/.




Figure 9. Distribution of per-reference word-boundary MAE on test. The main system's whole distribution is shifted left of V0 and M0, not just its mean; 90th percentiles: V0 56.8 ms, M0 45.6 ms, M1 36.3 ms, m1_pos_diph 35.5 ms.




Figure 10. Per test accent, with 95% bootstrap CIs. The timing gain over V0 and M0 holds in every accent; Korean speakers are easiest for every system.

Accent	Reference US prob	V0 MAE / WER	M1 MAE / WER	m1_pos_diph MAE / WER	main US prob
Arabic	0.455	40.5 ms / 2.6%	24.9 ms / 4.3%	24.6 ms / 3.4%	0.721
Korean	0.595	39.2 ms / 1.5%	22.2 ms / 3.3%	21.8 ms / 2.2%	0.793
Vietnamese	0.406	41.6 ms / 2.2%	25.4 ms / 4.0%	25.4 ms / 3.2%	0.771

Table 12. Per accent, test. US probability rises from 0.41-0.60 for the references to 0.72-0.79 for the outputs.




Figure 11. Word-boundary MAE by stretch ratio (references binned by the main system's stretch ratio; 1,132 references have one). Every system's error rises when the reference is far slower or faster than LJ; the gap to V0 holds in every bin.




Figure 12. Reference pace relative to LJ on dev and test: dev was a fair stand-in for test.

Failures are shown, not hidden. The worst reference per accent is in samples/demo/ (e.g. THV_arctic_a0067: 148 ms for the main system and for V0 alike). The second-aligner cross-check

(CTC on the outputs) gives 45.6-52.0 ms for all systems; its +38 ms start bias on real speech makes it unusable as a ranking (V0's early shift cancels part of that bias), which is why it is reported only against its own zero point (§5.6).

7. Efficiency

Quantity	Value (main checkpoint)
Inference parameters	28.1 M: decoder 14.3 M, flow 7.1 M, text encoder 6.3 M, duration predictor 0.35 M
Training-only parameters	54.0 M: discriminators 46.7 M, posterior encoder 7.2 M
Compute	27.2 GMACs per second of audio; 99.7% in flow + decoder (hand-checked: dec.conv_pre = 59.2 MMACs/s)
RTX 4060 laptop latency (p50, 3.7 s output)	text encoder + durations 5.4 ms; flow + decoder 39.4 ms; MFA align_one 3.3 s
RTX 4060 real-time factor	model only 0.012 (80× faster than real time); end to end 0.90 (MFA dominates)
CPU, 12 threads / 1 thread	flow + decoder 0.78 s / 1.78 s (model RTF 0.21 / 0.48)
Training (L40S)	0.229 s/step at batch 32; 114k steps ≈ 7.3 h

Table 13. results/profile_*.json (10 warm-up + 50 timed runs, CUDA-synchronized; MFA 1 + 5 runs). MACs counted with ptflops' aten backend (the module-hook backend reported ~0).




Figure 13. Latency and compute breakdown. End-to-end latency is aligner-bound, not model-bound.

8. Robustness and live testing

- **Edge-case suite** (21 cases, 21/21 on GPU and CPU): digits, currency, dates, abbreviations, an OOV name; MP3, 8 / 48 kHz, stereo, clipped, noisy and reverberant audio; > 20 s, a 1.8 s pause, 1.6× tempo, a one-word cut; an unspoken word, a false start and a forced CTC path. Pass = exact length or a clean fallback.
- **Typed text:** 121-case stress set (119 pass; the 2 failures are G2P guesses for unknown names) and a 12-case end-to-end rehearsal including refusals.
- **Unit tests:** 308 pass on the author's machine; 300 pass, 9 skipped on a clean clone without datasets.
- **Browser demo:** visitors record or upload a sentence and get all seven systems side by side; 50 recorded sessions are kept in samples/browser_tests/.

Live testing of the browser demo exposed failures that read-speech corpora never contain:

Input	What happened	Cause	Status
abc, chaganti (words first seen at inference)	MFA returned spn; the demo fell back to CTC	MFA reused a stale parsed copy of the lexicon	**Fixed:** MFA's temp dir is keyed by the lexicon's hash
bcd, xyz	G2P invented a word (bcd → "bed")	nothing marks a letter string	**Fixed:** unknown vowel-less 3-5 letter tokens are spelled out
letter "a" in a, b, c	aligned to 30-80 ms; output says "uh"	one pronunciation for "a": AH0, the article	**Open:** needs a letter-name reading (EY1 gave 220-330 ms)

Input	What happened	Cause	Status
"I" in may I know you	"I" got 30 ms (MFA's minimum)	vowel-to-vowel junction EY → AY	**Open:** fine after a pause or sentence-initially
ijk; brrr, grr; pq	G2P word; wrongly spelled; not spelled	limits of the regex heuristic	**Open:** needs a learned normaliser

Table 14. Live-testing findings (E-35). The test results are unaffected: every evaluation word was in the lexicon when MFA's cache was first built.

9. Limitations and future work

- **Accent-ID is a weak judge;** a MUSHRA-style listening test with accent ratings is the right next measurement.
- **Part of the accent lives in timing:** forcing LJ's voice onto L2 word timing caps how American it can sound.
- **Fixed alignments flatten phones** (14-16% less movement inside phones); V0 keeps better WER and UTMOS.
- **No word-boundary token** ("a name" = "an aim" at the encoder input); the 50/50 diphthong split is fixed.
- **The ablations were branched late** (20k steps from M1), so they test late-stage augmentation only.
- **V0 needs an adapter** (IPA from the lexicon, a blank-ownership rule); a learned adapter could narrow its gap.
- **End-to-end latency is MFA-bound** (3.3 s per reference vs 45 ms for the model).

Future work, by expected value: (1) learn the alignment again with MAS *inside* MFA's word spans, restoring the alignment-latent feedback while keeping timing control; (2) a word-boundary flag on the encoder input; (3) learned diphthong split points; (4) splitting CH, JH, ER the same way; (5) a listening test as the accent judge; (6) a resident or faster aligner for live use; (7) letter names and vowel-only words for live input.

Takeaway. Make durations an input, copy word timing (not phone timing), and check the tokens before adding data: replacing MAS cut word error from 40.5 to 24 ms, and the largest later gain came from a two-token diphthong, not from more training data.

10. Reproducibility and deliverables

Step	Command	Result
Environments	make env	conda envs tts and mfa from pinned envs/*.yml (lock files in envs/lock/)
Models	make models	frozen inference checkpoints and baselines from the HF Hub, pinned revision, sha256-checked
Synthesize	make infer / make live-demo	out.wav (exact length), timings.json, timing.png
Test outputs	make outputs	all 1,248 evaluated outputs per system into results/<system>/test/
Tests	make test; make text-stress; make rehearse	300 pass on a clean clone; 119/121; 12/12
Browser demo	make web-demo (+ make web-tunnel)	record / upload, all seven systems side by side
This report	make report-pdf	docs/meeami-tts_report.pdf from the committed results

Table 15. Checked from a fresh clone with no login and an empty download cache (D-104).

Deliverable	Where
Code (frozen at freeze-v1)	https://github.com/rrtchaganti/meeami-tts
Detailed report with a code link for every claim	docs/REPORT.md; decision and error log docs/DECISIONS.md
Exact audio evidence: reference, annotation, all 7 outputs, word timings, ≥ 2 accents	samples/demo/ (21 samples, 3 accents; MAE recomputed and checked, 147/147)

Deliverable	Where
Listening sets behind phase-2 decisions; browser recordings	samples/listening/, samples/browser_tests/
Checkpoints and every test output	https://huggingface.co/Raviteja546/meeami-tts
Slides	slides/meeami-tts_v3.pptx

Table 16. Where each deliverable lives.

Appendix A. Deviations from the plan

Plan said	Done instead	Why
Rubber Band R3 time-stretching	time-varying WSOLA (numpy), same time map	R3 cost ~1.2-1.5 UTMOS on every clip; WSOLA 0.32
torchaudio forced_align	numpy CTC Viterbi, same MMS_FA model	conda-forge torchaudio 2.8 lacks the extension
OOV from g2p_en	+ possessive rule	g2p_en mangled 104 possessives
Three GPU instances	one L40S: M1, then 20k-step branches	availability
Data-center GPU profile	laptop GPU and CPU only	not runnable on the instance
n_vocab = 72	87 for m1_pos_diph only (opt-in)	diagnosed diphthong flattening
UTMOS via torch.hub defaults	sha256-pinned weights, weights_only=True	hub did a full pickle load of unhashed weights
Baseline M0 only	+ V0, the original VITS with MAS (after the freeze, inference only)	the immediate baseline for the MAS → MFA swap
Normalizer as specified	+ typed-text pre-pass (after the freeze)	live input; corpus words unchanged (tested)
MFA align_one with a fixed temp dir	temp dir keyed by the lexicon hash	stale parsed lexicon made new words unknown

Appendix B. Claim → evidence

Claim	Evidence (committed files)
Output length exact for every output	length_error = 0 in every results/*/test/per_utt.csv
MFA error on accented speech ≈ 19 ms	reports/mfa_l2_dev.md
MAS → MFA makes timing follow the reference	results/paired/test_m1_pos_diph_vs_v0.csv; samples/demo/
V0 renders durations early and scattered	results/fidelity/test.json, calibration_dev.json
Fixed alignments flatten phones	results/phone_dynamics/*.json
Cap 2.5 and noise 0.333 chosen by a pre-stated rule	results/tune/grid.json, choice.json
Ablations give no gain	results/paired/{dev,test}_abl_*_vs_m1_pos.csv
Diphthong split improves timing, WER, UTMOS; "cry" glides	results/paired/*_m1_pos_diph_vs_m1_pos.csv; samples/listening/p2c_diphthongs/
Test split not read before the freeze	git tag freeze-v1 → 5889ecf; tts/guard.py
Hosted checkpoints are the frozen ones	MANIFEST.sha256 on the Hub; scripts/export_infer.py --verify