

Figure 1: Decoder.

$$F^{[D],[\ell]} = \text{feed\_forward\_nn}(j^{[D],[\ell]})$$
(1a)

$$I^{[L],[\ell]} = W^{[L],[D]}Y^{[D],[\ell]}$$
 (1b)

$$K^{[D],[\ell]} = W_k^{[D],[d]} e^{[d],[\ell]}$$
 (1c)

$$O^{[D],[\ell]} = \text{multi\_head\_attention}(Q^{[D],[\ell]}, K^{[D],[\ell]}, V^{[D],[\ell]})$$

$$\tag{1d}$$

$$P^{[L],[\ell]} = \operatorname{softmax}(I^{[L],[\ell]}) \ (\sum_{\alpha \in [\ell]} P^{[L],\alpha} = 1)$$
 (1e)

$$Q^{[D],[\ell]} = W_{\underline{q}}^{[D],[d]} e^{[d],[\ell]}$$
(1f)

$$V^{[D],[\ell]} = W_v^{[D],[d]} e^{[d],[\ell]}$$
(1g)

$$Y^{[D],[\ell]} = \text{normalize}(F^{[D],[\ell]} + a^{[D],[\ell]})$$
 (1h)

$$a^{[D],[\ell]} = \text{normalize}(O^{[D],[\ell]} + e^{[d],[\ell]})$$
 (1i)

$$e^{[d],[\ell]} = E^{[d],[L]} x^{[L],[\ell]}$$
 (1j)

$$j^{[D],[\ell]} = \text{normalize}(o^{[D],[\ell]} + a^{[D],[\ell]})$$
 (1k)

$$k^{[D],[\ell]} = \text{prior, obtained from encoder.}$$
 (11)

$$o^{[D],[\ell]} = \text{multi\_head\_attention}(q^{[D],[\ell]}, k^{[D],[\ell]}, v^{[D],[\ell]}) \tag{1m}$$

$$q^{[D],[\ell]} = \text{prior, obtained from encoder.}$$
 (1n)

$$v^{[D],[\ell]} = a^{[D],[\ell]} \tag{10}$$

$$x^{[L],[\ell]} = \text{prior}$$
 (1p)