QRecord Class



WiX managed SDK

WixToolset.Dtf.WindowsInstaller.Linq namespace

QRecord Class

Generic record entity for queryable databases, and base for strongly-typed entity subclasses.

Methods

Method	Description
Assign()	Not yet implemented.
Delete()	Deletes the record from the table if it exists.
I(index)	Used by subclasses to get a field as an integer.
Insert()	Inserts the record in the database.
Insert(temporary)	Inserts the record into the table.
Merge()	Not yet implemented.
NI(index)	Used by subclasses to get a field as a nullable integer.

Method	Description	
Refresh()	Not yet implemented.	
ToString()	Dumps all record fields to a string.	
Validate()	Not yet implemented.	
ValidateDelete()	Not yet implemented.	
ValidateFields()	Not yet implemented.	
ValidateNew()	Not yet implemented.	

Properties

Property	Description
FieldCount	Gets the number of fields in the record.
Item	Gets or sets a record field.
Item	Gets or sets a record field.

Remarks

Several predefined specialized subclasses are provided for common standard tables. Subclasses for additional standard tables or custom tables are not necessary, but they are easy to create and make the coding experience much nicer. When creating subclasses, the following attributes may be useful: «see T:WixToolset.Dtf.WindowsInstaller.Linq.DatabaseTableAttribute» , «see T:WixToolset.Dtf.WindowsInstaller.Linq.DatabaseColumnAttribute»

```
WixToolset.Dtf.WindowsInstaller.Linq.dll version 4.0.2+644ed0118bae1aa885bb6cc906dc6c0b904de4d9
```

Assign() Method

Not yet implemented.

Declaration

public void Assign()

Delete() Method

Deletes the record from the table if it exists.

Declaration

```
public void Delete()
```

Used by subclasses to get a field as an integer.

Declaration

```
protected int I(
  int index
)
```

Parameters

Parameter	Туре	Description
index	int	zero-based column index of the field

Insert() Method

Inserts the record in the database.

Declaration

```
public void Insert()
```

Remarks

The record (primary keys) may not already exist in the table. Use «see M:WixToolset.Dtf.WindowsInstaller.Linq.QTable`1.NewRecord» to get a new record. Prmary keys and all required fields must be filled in before insertion.

Insert(temporary) Method

Inserts the record into the table.

Declaration

```
public void Insert(
  bool temporary
)
```

Parameters

Parameter	Туре	Description
temporary	bool	true if the record is temporarily inserted, to be visible only as long as the database is open

Remarks

The record (primary keys) may not already exist in the table.Use «see M:WixToolset.Dtf.WindowsInstaller.Linq.QTable`1.NewRecord»

to get a new record. Prmary keys and all required fields must be filled in before insertion.

Merge() Method

Not yet implemented.

Declaration

```
public bool Merge()
```

NI(index) Method

Used by subclasses to get a field as a nullable integer.

Declaration

```
protected System.Nullable<System.Int32> NI(
  int index
)
```

Parameters

Parameter	Туре	Description
index	int	zero-based column index of the field

Refresh() Method

Not yet implemented.

Declaration

public void Refresh()

ToString() Method

Dumps all record fields to a string.

Declaration

public string ToString()

Validate() Method

Not yet implemented.

Declaration

```
public System.Collections.Generic.ICollection<WixToolset.Dtf.WindowsInstaller.ValidationErrorInfo>
Validate()
```

ValidateDelete() Method

Not yet implemented.

Declaration

```
public System.Collections.Generic.ICollection<WixToolset.Dtf.WindowsInstaller.ValidationErrorInfo>
ValidateDelete()
```

ValidateFields() Method

Not yet implemented.

Declaration

public System.Collections.Generic.ICollection<WixToolset.Dtf.WindowsInstaller.ValidationErrorInfo>

```
ValidateFields()
```

ValidateNew() Method

Not yet implemented.

Declaration

```
public System.Collections.Generic.ICollection<WixToolset.Dtf.WindowsInstaller.ValidationErrorInfo>
ValidateNew()
```

FieldCount Property

Gets the number of fields in the record.

Declaration

```
public int FieldCount { get; set; }
```

Item Property

Gets or sets a record field.

Declaration

```
public string Item[
  string field
] { get; set; }
```

Parameters

Parameter	Туре	Description
field	string	column name of the field

Remarks

Setting a field value will automatically update the database.

Item Property

Gets or sets a record field.

Declaration

```
public string Item[
  int index
```

```
] { get; set; }
```

Parameters

Parameter	Туре	Description
index	int	zero-based column index of the field

Remarks

Setting a field value will automatically update the database.