



CustomActionTypes Enumeration

Defines flags for the Type column of the CustomAction table.

Members

Member	Description
Async	Run asynchronously
ClientRepeat	Run on client only if UI already run on client
Commit	In conjunction with InScript: run Commit ops from script on success
Continue	Ignore action return status, continue running
Directory	Source = Directory.Directory, folder containing existing file
Dll	Target = entry point name
Exe	Target = command line args

Member	Description
FirstSequence	Skip if UI sequence already run
HideTarget	Don't record the contents of the Target field in the log file
InScript	Queue for execution within script
Install	Target = property list for nested engine initialization
JScript	Target = entry point name, null if none to call
NoImpersonate	No impersonation, run in system context
None	Unspecified custom action type.
OncePerProcess	Skip if UI sequence already run in same process
PatchUninstall	The custom action runs only when a patch is being uninstalled
Property	Source = Property.Property, full path to executable
Rollback	In conjunction with InScript: queue in Rollback script
SixtyFourBitScript	Script requires 64bit process
SourceFile	Source = File.File, file part of installation

Member	Description
TextData	Target = text string to be formatted and set into property
TSAware	Impersonate for per-machine installs on TS machines
VBScript	Target = entry point name, null if none to call

WixToolset.Dtf.WindowsInstaller.dll version 4.0.2+644ed0118bae1aa885bb6cc906dc6c0b904de4d9