



Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics

Neural Network



Ratchainant Thammasudjarit, Ph.D.



Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics

Prerequisite Mathematics




Recall your linear algebra

Linear Algebra


- A function of univariate is defined as

$$x \mapsto f(x)$$


Function



Each input must have only one output




This is a function



This is NOT a function

Linear Algebra


sigmoid



- Properties
 - $f(x) \in [0, 1]$
 - $x \in [-\infty, \infty]$
 - $x \rightarrow 0$, $f(x)$ becomes linear
 - $\text{abs}(x) > 4$, $f(x)$ changes slowly

Linear Algebra


tanh



- Properties
 - $f(x) \in [-1, 1]$
 - $x \in [-\infty, \infty]$
 - $x \rightarrow 0$, $f(x)$ becomes linear
 - $\text{abs}(x) > 2$, $f(x)$ changes slowly

Linear Algebra

ReLU (Rectifier Linear Unit)




```
def relu(x):  
    y = np.maximum(0, x)  
    return y
```

- Properties
 - $f(x) \in [0, \infty]$
 - $x \in [-\infty, \infty]$
 - $x \leq 0, f(x) = 0$
 - $x > 0, f(x) = x$


Linear Algebra

Vector



$$\|\vec{u}\| = \sqrt{3^2 + 4^2} = 5$$

- Dot product



$$\vec{u} \cdot \vec{v} = (3 \times 4) + (4 \times 3) = 24$$

- Transpose

if

$$\mathbf{u} = \begin{bmatrix} 3 & 4 \end{bmatrix}$$

then

$$\mathbf{u}^T = \begin{bmatrix} 3 \\ 4 \end{bmatrix}$$

Linear Algebra

Matrix

A stack of vectors

- Pairwise multiplication

$$A = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \end{bmatrix} \quad B = \begin{bmatrix} 2 & 2 & 2 \\ 2 & 2 & 2 \end{bmatrix}$$

$$A \odot B = \begin{bmatrix} 1 \times 2 & 2 \times 2 & 3 \times 2 \\ 4 \times 2 & 5 \times 2 & 6 \times 2 \end{bmatrix} = \begin{bmatrix} 2 & 4 & 6 \\ 8 & 10 & 12 \end{bmatrix}$$

- Transpose


$$A^T = \begin{bmatrix} 1 & 4 \\ 2 & 5 \\ 3 & 6 \end{bmatrix}$$

Linear Algebra

Calculus (Derivative)

- Derivative

$$f'(x) = \lim_{\Delta x \rightarrow 0} \frac{f(x + \Delta x) - f(x)}{\Delta x}$$



$\Delta x = 1$	
if $x = 2$	then $f(x) = 4$
if $x = 3$	then $f(x) = 9$

$\Delta x = 0.001$	
if $x = 2$	then $f(x) = 4$
if $x = 2.001$	then $f(x) \approx 4.004$

$$\text{if } x = 2 \text{ then slope} = \frac{\Delta f(x)}{\Delta x} = \frac{0.004}{0.001} = 4$$

$$\text{Mathematically, } \frac{d}{dx} f(x) = 2x = 2(2) = 4$$

Linear Algebra

Derivative of sigmoid

$$g(z) = \frac{1}{1 + e^{-z}}$$

$$\begin{aligned}\frac{d}{dz} g(z) &= \frac{d}{dz} \left[\frac{1}{1 + e^{-z}} \right] \\ &= \frac{d}{dz} (1 + e^{-z})^{-1} \\ &= -(1 + e^{-z})^{-2} \frac{d}{dz} (1 + e^{-z}) \\ &= -(1 + e^{-z})^{-2} \frac{d}{dz} (e^{-z})\end{aligned}$$

$$\begin{aligned}&= -(1 + e^{-z})^{-2} (-e^{-z}) \\ &= \frac{e^{-z}}{(1 + e^{-z})^2} \\ &= \frac{1}{1 + e^{-z}} \cdot \frac{e^{-z}}{1 + e^{-z}} \\ &= \frac{1}{1 + e^{-z}} \cdot \frac{(1 + e^{-z}) - 1}{1 + e^{-z}} \\ &= \frac{1}{1 + e^{-z}} \left[\frac{1 + e^{-z}}{1 + e^{-z}} - \frac{1}{1 + e^{-z}} \right] \\ &= \frac{1}{1 + e^{-z}} \left[1 - \frac{1}{1 + e^{-z}} \right]\end{aligned}$$

$$\therefore \frac{d}{dz} g(z) = g(z)(1 - g(z))$$

Linear Algebra

Derivative of tanh

$$g(z) = \tanh(z)$$

$$= \frac{e^z - e^{-z}}{e^z + e^{-z}}$$

$$\frac{d}{dz} g(z) = \frac{(e^z + e^{-z})d(e^z - e^{-z}) - (e^z - e^{-z})d(e^z + e^{-z})}{(e^z + e^{-z})^2}$$

$$= \frac{(e^z + e^{-z})(e^z + e^{-z}) - (e^z - e^{-z})(e^z - e^{-z})}{(e^z + e^{-z})^2}$$

$$= 1 - \left(\frac{e^z - e^{-z}}{e^z + e^{-z}} \right)^2$$

$$\therefore \frac{d}{dz} g(z) = 1 - \tanh^2(z)$$

Linear Algebra

Derivative of relu

$$g(z) = \max(0, z)$$

$$\frac{d}{dz}g(z) = \begin{cases} 0 & \text{if } z < 0 \\ 1 & \text{if } z > 0 \\ \text{undefined} & \text{if } z = 0 \end{cases}$$

In neural network practice, z can get close to zero but never be zero, e.g. 0.00000 ...

$$\therefore \frac{d}{dz}g(z) = \begin{cases} 0 & \text{if } z < 0 \\ 1 & \text{if } z > 0 \end{cases}$$



Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics


Perceptron

A smallest unit in neural network


Training Sample VS Training Data

Training sample is a pair of feature vector \mathbf{x} and its class label

$$(\mathbf{x}, y), \mathbf{x} \in \mathbb{R}^{n_x}, y \in \{0,1\}$$



Training data is m pair of feature vector \mathbf{x} and its class label




$$\mathbf{x} \in \mathbb{R}^{n_x \times 1}$$

$$\mathbf{X} \in \mathbb{R}^{n_x \times m}$$

$$\mathbf{y} \in \mathbb{R}^{1 \times m}$$

A Perceptron

The smallest unit of neural network




$$\hat{y} = P(y = 1 | \mathbf{x}^{(i)}) = \frac{1}{1 + e^{-(\mathbf{w}^T \cdot \mathbf{x}^{(i)} + b)}}$$

- Given $\mathbf{x}^{(i)} \in \mathbb{R}^{n_x \times 1}$, determine
 - $\hat{y} = P(y = 1 | \mathbf{x}^{(i)})$
- Parameters
 - $\mathbf{w} \in \mathbb{R}^{1 \times n_x}$
 - $b \in \mathbb{R}$
- Output
 - $\hat{y} = g(z) = g(\mathbf{w}^T \cdot \mathbf{x}^{(i)} + b)$

A Perceptron

The smallest unit of neural network




$$g(z) = \frac{1}{1 + e^{-z}}$$

- If $z \gg 0, g(z) \rightarrow 1$
- if $z \ll 0, g(z) \rightarrow 0$

Loss Function

Error of a training sample

The loss function $\mathcal{L}(\hat{y}, y)$ determines how close of \hat{y} to the ground-truth y



$$\mathcal{L}(\hat{y}, y) = -(y \log \hat{y} - (1 - y) \log(1 - \hat{y}))$$

$$\text{Goal: } \mathcal{L}(\hat{y}, y) \rightarrow 0$$

if $y = 1$,

$$\therefore z = w^T \cdot x + b, \quad \rightarrow \infty$$

$$\hat{y} = \frac{1}{1 + e^{-z}}, \quad \rightarrow 1$$

$$\mathcal{L}(\hat{y}, y) = -\log \hat{y}, \quad \rightarrow 0$$

if $y = 0$,

$$\therefore z = w^T \cdot x + b, \quad \rightarrow -\infty$$

$$\hat{y} = \frac{1}{1 + e^{-z}}, \quad \rightarrow 0$$

$$\mathcal{L}(\hat{y}, y) = -\log(1 - \hat{y}), \quad \rightarrow 0$$

Cost Function

Error of training data


The cost function $J(\mathbf{w}, b)$ indicates how well the model does in entire training samples

$$\begin{aligned} J(\mathbf{w}, b) &= \frac{1}{m} \sum_{i=1}^m \mathcal{L}(\hat{y}^{(i)}, y^{(i)}) \\ &= -\frac{1}{m} \sum_{i=1}^m [y^{(i)} \log \hat{y}^{(i)} + (1 - y^{(i)}) \log(1 - \hat{y}^{(i)})] \end{aligned}$$

- Training Goal
 - Find \mathbf{w}, b that minimize $J(\mathbf{w}, b)$

Gradient Descent


Searching for minimum point in hyperplane



- Goal
 - Determine \mathbf{w} , b that minimize $J(\mathbf{w}, b)$

Gradient Descent

Initialize weight and adjust until the cost function approach to minimum



- Procedure

Repeat {

$$w := w - \alpha \frac{d}{dw} J(w)$$

Until $J(w) \rightarrow \min(J(w))$
}

where α represents the learning rate (a small positive value)

On the right

$$\frac{d}{dw} J(w) > 0, \quad \rightarrow w \text{ is adjusted by decreasing } \frac{d}{dw} J(w)$$

On the left

$$\frac{d}{dw} J(w) < 0, \quad \rightarrow w \text{ is adjusted by increasing } \frac{d}{dw} J(w)$$

Gradient Descent

Summary


- Minimizing $J(\mathbf{w}, b)$
 - $w := w - \alpha \frac{d}{dw} J(w, b), \quad \text{where } w \in \mathbf{w}$
 - $b := b - \alpha \frac{d}{db} J(w, b)$
- In each training iteration, we need to determine

$$\frac{d}{dw} J(w, b) \quad \text{and} \quad \frac{d}{db} J(w, b)$$

Computational Graph

Forward path

Given a function $J(a, b, c) = 3(a + bc)$




- Forward path
 - $J(a, b, c)$ can be determined
- Backward path
 - Derivative of $J(a, b, c)$ w.r.t. a or b or c can be determined

Computational Graph

Backward path

Given a function $J(a, b, c) = 3(a + bc)$



- Finding $\frac{dJ}{dv}$

- $v = 11$ $\xrightarrow{\text{Nudge its value}}$ $v = 11.001$

- $J = 33$ $\xrightarrow{\text{Changed by } v}$ $J = 33.003$


Therefore

$$\frac{dJ}{dv} = \frac{0.003}{0.001} = 3$$

Computational Graph

Backward path

Given a function $J(a, b, c) = 3(a + bc)$



- Finding $\frac{dJ}{da}$

- $a = 5$ $\xrightarrow{\text{Nudge its value}}$ $a = 5.001$
- $v = 11$ $\xrightarrow{\text{Changed by } a}$ $v = 11.001$
- $J = 33$ $\xrightarrow{\text{Changed by } a, v}$ $J = 33.003$

Therefore


$$\frac{dJ}{da} = \frac{dJ}{dv} \cdot \frac{dv}{da} = \frac{0.003}{0.001} \cdot \frac{0.001}{0.001} = 3$$

Chain rule

Perceptron with Gradient Descent

For a training sample

Given $\mathbf{w} = [w_1 \ w_2]$ and b



- Recap

$$z = \mathbf{w}^T \cdot \mathbf{x}^{(i)} + b$$

$$\hat{y} = a = g(z)$$

$$g(z) = \frac{1}{1 + e^{-z}}$$


$$\mathcal{L}(a, y) = -(y \log a + (1 - y) \log(1 - a))$$

- Goal

- To adjust $\mathbf{w} = [w_1 \ w_2]$ and b to minimize $\mathcal{L}(a, y)$

Perceptron with Gradient Descent

Backward Propagation



$$\begin{aligned}\Delta z &= \frac{d}{dz} \mathcal{L}(a, y) \\ &= \frac{d}{da} \mathcal{L}(a, y) \cdot \frac{da}{dz}\end{aligned}$$

$$\text{since } \frac{d}{da} \mathcal{L}(a, y) = \frac{d}{da} [-y \log a - (1 - y) \log(1 - a)]$$

$$= -\frac{y}{a} + \frac{1 - y}{1 - a}$$

$$\text{and } \frac{da}{dz} = a(1 - a)$$

$$\begin{aligned}\therefore \Delta z &= \left(-\frac{y}{a} + \frac{1 - y}{1 - a} \right) \cdot a(1 - a) \\ &= a - y\end{aligned}$$

In other words, Δz is the difference between obtained output and desired output



Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics



Implementation

Vectorization

Applying a perceptron to m samples

Broadcasting property enable implementation without looping over training data

$$\mathbf{y} = g(\mathbf{z}) = g(\mathbf{w}^T \cdot \mathbf{X} + b)$$



Naïve Implementation

Loop and Loop and Loop

This is NOT an efficient method

Note: Python programming does not have the Δ character. For simplicity, let's change

$$\Delta w_1 \rightarrow dw_1$$

$$\Delta w_2 \rightarrow dw_2$$

$$\Delta b \rightarrow db$$

Initialize

$$\mathcal{J} = 0, dw_1 = 0, dw_2 = 0, db = 0$$

for epoch = 1 to max_epoch:

for i = 1 to m:

compute $z^{(i)}, a^{(i)}$

$$\mathcal{J} += -[y^{(i)} \log a^{(i)} + (1 - y^{(i)}) \log(1 - a^{(i)})]$$

compute $dz^{(i)}$

update db

for j = 1 to n_x :

update dw_j

$$\mathcal{J} /= \frac{\mathcal{J}}{m}$$

Implement with Vectorization

The efficient method

Initialize

$$J = 0, dw_1 = 0, dw_2 = 0, db = 0$$

for epoch = 1 to max_epoch:

$$\mathbf{Z} = \mathbf{w}^T \cdot \mathbf{X} + b$$

$$\mathbf{A} = g(\mathbf{Z})$$

$$J = -\frac{1}{m} \sum (\mathbf{y} \log \mathbf{A} - (1 - \mathbf{y}) \log(1 - \mathbf{A}))$$

$$\mathbf{dz} = \mathbf{A} - \mathbf{Y}$$

$$d\mathbf{w} = \frac{1}{m} \mathbf{X} \cdot \mathbf{dz}^T$$

$$db = \frac{1}{m} \cdot \text{np.sum}(\mathbf{dz})$$

$$\mathbf{w} -= \alpha \cdot d\mathbf{w}$$

$$b -= \alpha \cdot db$$

Implement with Vectorization

The efficient method

Only loop over training iteration

for epoch = 1 to max_epoch:

$$\mathbf{Z}_{1 \times m} = \underbrace{(\mathbf{w}_{1 \times n_x})^T}_{1 \times m} \cdot \mathbf{X}_{n_x \times m} + b$$

$$\mathbf{A}_{1 \times m} = g(\mathbf{Z}_{1 \times m})$$

$$\mathcal{J} = -\frac{1}{m} \sum_{i=1}^m \underbrace{(\mathbf{y}_{1 \times m} \log \mathbf{A}_{1 \times m})}_{1 \times m} - \underbrace{(1 - \mathbf{y}_{1 \times m}) \log(1 - \mathbf{A}_{1 \times m})}_{1 \times m}$$

$$\mathbf{dz}_{1 \times m} = \mathbf{A}_{1 \times m} - \mathbf{y}_{1 \times m} \quad 1 \times 1$$

$$\mathbf{dw}_{1 \times n_x} = \frac{1}{m} \mathbf{X}_{n_x \times m} \cdot (\mathbf{dz}_{1 \times m})^T$$

$$db = \frac{1}{m} \sum_{i=1}^m \mathbf{dz}_{1 \times m}$$

$$\mathbf{w}_{1 \times n_x} \leftarrow \mathbf{w}_{1 \times n_x} + \alpha \cdot \mathbf{dw}_{1 \times n_x}$$

$$b \leftarrow b + \alpha \cdot db$$



Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics


Neural Network




A collection of perceptrons

Shallow Neural Network


None or a few hidden layers



1-Layer Network
(0 Hidden Layer)
(perceptron or logistic regression)




2-Layer Network
(1 Hidden Layer)



3-Layer Network
(2 Hidden Layer)

Deep Neural Network

More hidden layers



- Notations

L represents the number of layers (exclude the input layer)

$n^{[l]}$ represents the number of units in the l^{th} layer

Examples:

$$n^{[1]} = 5, \quad n^{[2]} = 4, \quad n^{[3]} = 3, \quad n^{[4]} = 1$$

$g^{[l]}(\cdot)$ represents the activation function in the l^{th} layer

$\mathbf{z}^{[l]}$ represents the linear combination in the l^{th} layer

$\mathbf{a}^{[l]}$ represents the activated values in the l^{th} layer

$\mathbf{W}^{[l]}$ represents the weights matrix in the l^{th} layer

$\mathbf{b}^{[l]}$ represents the bias in the l^{th} layer


\mathbb{W} represents the collection of weights matrix of all layers

$w_{i,j}$ represents the weights connecting between the i^{th} unit in the l^{th} layer to the j^{th} unit in the $(l-1)^{th}$ layer

\mathbb{b} represents the collection of bias vectors of all layers

Deep Neural Network

Weights



- Weights $\mathbb{W} = \begin{bmatrix} \mathbf{W}^{[1]} \\ \mathbf{W}^{[2]} \\ \mathbf{W}^{[3]} \\ \mathbf{W}^{[4]} \end{bmatrix}$

$$\mathbf{W}^{[l]} = \begin{bmatrix} \mathbf{w}_1^{[l]} \\ \dots \\ \mathbf{w}_{n^{[l]}}^{[l]} \end{bmatrix}_{n^{[l]}, n^{[l-1]}}$$


- Example

$$\mathbf{W}^{[3]} = \begin{bmatrix} w_{1,1} & \dots & w_{1,4} \\ \vdots & \ddots & \vdots \\ w_{3,1} & \dots & w_{3,4} \end{bmatrix}$$

Dimension of $\mathbf{W}^{[l]}$ is $(n^{[l]}, n^{[l-1]})$

Deep Neural Network

Biases



- Biases


$$\mathbb{b} = [\mathbf{b}^{[1]} \quad \dots \quad \mathbf{b}^{[4]}] = \begin{bmatrix} b_1^{[1]} & \dots & b_1^{[4]} \\ \vdots & \dots & \vdots \\ b_5^{[1]} & \dots & b_3^{[4]} \end{bmatrix}$$

$$\therefore \mathbf{b}^{[l]} = \begin{bmatrix} b_1^{[l]} \\ \vdots \\ b_{n^{[l]}}^{[l]} \end{bmatrix}$$


Dimension of $\mathbf{b}^{[l]}$ is $(n^{[l]}, 1)$

Implementation with Vectorization

The L layers neural network




- At the layer l : $\mathbf{W}^{[l]}, \mathbf{b}^{[l]}$



Implementation with Vectorization

The L layers neural network



- At the layer l : $\mathbf{W}^{[l]}, \mathbf{b}^{[l]}$

- Forward Propagation

$$\mathbf{z}^{[l]} = \mathbf{W}^{[l]} \cdot \mathbf{a}^{[l-1]} + \mathbf{b}^{[l]}$$

$$\mathbf{a}^{[l]} = g^{[l]}(\mathbf{z}^{[l]})$$

- Backward Propagation

$$d\mathbf{z}^{[l]} = d\mathbf{a}^{[l]} * g'^{[l]}(\mathbf{z}^{[l]})$$

$$d\mathbf{W}^{[l]} = \frac{1}{m} d\mathbf{z}^{[l]} \cdot \mathbf{a}^{[l-1]T}$$

$$d\mathbf{b}^{[l]} = \frac{1}{m} \sum_{i=1}^m d\mathbf{z}^{[l]}$$

$np.sum(d\mathbf{z}^{[l]}, axis = 1, keepdims = True)$

$$d\mathbf{a}^{[l-1]} = \mathbf{W}^{[l]T} \cdot d\mathbf{z}^{[l]}$$



Mahidol University

Faculty of Medicine Ramathibodi Hospital


Section for Clinical Epidemiology and Biostatistics

Model Tuning


Bias and Variance Problem

Easy to learn but difficult to master


- Unable to visualize in high dimensional data



High Bias
(Underfitting)



Just right



High Variance
(Overfitting)



Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics

Regularization

L1 and L2

L1 and L2 Regularization

Recall the cost function of perceptron

Goal:

$$\min_{\mathbf{w}, b} \mathcal{J}(\mathbf{w}, b), \quad \mathbf{w} \in \mathbb{R}^{n_x}, b \in \mathbb{R}$$

- L1 regularization (Lasso)

$$\mathcal{J}(\mathbf{w}, b) = \frac{1}{m} \sum_{i=1}^m \mathcal{L}(\hat{y}^{(i)}, y^{(i)}) + \frac{\lambda}{2m} \|\mathbf{w}\|_1 \quad \text{Regularization term}$$

$$\text{where } \|\mathbf{w}\|_1 = \sum_{j=1}^{n_x} |w_j|$$

λ represents the regularization parameter

- L1 makes many weights become zeros
- Good for compacting the model
- L1 is not often used

L1 and L2 Regularization

Recall the cost function of perceptron

Goal:

$$\min_{\mathbf{w}, b} \mathcal{J}(\mathbf{w}, b), \quad \mathbf{w} \in \mathbb{R}^{n_x}, b \in \mathbb{R}$$

- L2 regularization (Ridge)

$$\mathcal{J}(\mathbf{w}, b) = \frac{1}{m} \sum_{i=1}^m \mathcal{L}(\hat{y}^{(i)}, y^{(i)}) + \frac{\lambda}{2m} \|\mathbf{w}\|_2^2$$

Regularization term

where $\|\mathbf{w}\|_2^2 = \sum_{j=1}^{n_x} w_j^2 = \mathbf{w}^T \cdot \mathbf{w}$

λ represents the regularization parameter

- L2 is much more often used compared to L1

L2 Regularization

L2 of Deep Neural Network

The cost function

$$\mathcal{J}(\mathbf{w}^{[1]}, \mathbf{b}^{[1]}, \dots, \mathbf{w}^{[L]}, \mathbf{b}^{[L]}) = \frac{1}{m} \sum_{i=1}^m \mathcal{L}(\hat{y}^{(i)}, y^{(i)}) + \frac{\lambda}{2m} \sum_{l=1}^L \|\mathbf{w}^{[l]}\|_F^2$$

where

Frobenious norm $\|\mathbf{w}\|_F^2 = \sum_{i=1}^{n^{[l-1]}} \sum_{j=1}^{n^{[l]}} (w_{ij}^{[l]})^2$

$$\mathbf{w}^{[l]}: (n^{[l]}, n^{[l-1]})$$

- Modifying back propagation

$$d\mathbf{w}^{[l]} = (\cdot) + \frac{\lambda}{m} \mathbf{w}^{[l]}$$

$$\mathbf{w}^{[l]} = \mathbf{w}^{[l]} - \alpha d\mathbf{w}^{[l]}$$

$$= \mathbf{w}^{[l]} - \alpha \left[(\cdot) + \frac{\lambda}{m} \mathbf{w}^{[l]} \right]$$

$$= \mathbf{w}^{[l]} - \frac{\alpha\lambda}{m} \mathbf{w}^{[l]} - \alpha(\cdot)$$


$$= \left(1 - \frac{\alpha\lambda}{m}\right) \mathbf{w}^{[l]} - \alpha(\cdot)$$

Weight Decay

where (\cdot) represents the term obtained from original back propagation



L2 Regularization

Why does L2 prevent overfitting?





L2 Regularization

Why does L2 prevent overfitting?



$\lambda \uparrow$
 $\mathbf{w}^{[l]} \downarrow$
 $\mathbf{z}^{[l]} \downarrow$

$$\because \mathbf{z}^{[l]} = \mathbf{w}^{[l]} \mathbf{a}^{[l-1]} + \mathbf{b}^{[l]}$$




Decision boundary is stretched out

L2 Regularization


Smoother cost function

$$\mathcal{J}(\mathbf{w}^{[1]}, \mathbf{b}^{[1]}, \dots, \mathbf{w}^{[L]}, \mathbf{b}^{[L]}) = \frac{1}{m} \sum_{i=1}^m \mathcal{L}(\hat{y}^{(i)}, y^{(i)}) + \frac{\lambda}{2m} \sum_{l=1}^L \|\mathbf{w}^{[l]}\|_F^2$$

Without regularization



With regularization





Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics

Regularization





DropOut & DropConnect

DropOut

Ensemble Neural Network


- Set the probability of enable hidden units in each hidden layer
- The edges connected to any disable hidden unit will be removed
- DropOut is applied ONLY training but NOT testing
- DropOut produces many possible combination of neuron network
- DropOut is very popular in computer vision



DropConnect


Generalization of DropOut

- Set the Boolean mask to randomly disable connections
- Rescale output on active connections
- DropConnect is applied ONLY for training but NOT testing
- DropConnect makes even more possible combination than dropout
- DropConnect is very popular in computer vision



Implementation

Illustration of DropConnect at the layer 3




- Define theoretical variable to Python variable
 - P as keepprob
- Create a Boolean mask to randomly disable weights

```
keepprob = 0.8  
d3 = np.random.rand(a3.shape[0], a3.shape[1]) < keepprob
```

```
In [43]: d3  
Out[43]:  
array([[ True,  True,  True],  
       [False,  True,  True],  
       [ True, False,  True]])
```

Implementation

Illustration of DropConnect at the layer 3



- Rescale the $\mathbf{a}^{[3]}$

```
a3 /= keepprob
```

- Example: If $\mathbf{a}^{[3]}$ is

```
array([[1., 2., 3.],  
       [4., 5., 6.],  
       [7., 8., 9.]])
```

- Rescale $\mathbf{a}^{[3]}$ after drop connect will be


```
array([[ 1.25,  2.5 ,  3.75],  
       [ 0.   ,  6.25,  7.5 ],  
       [ 8.75,  0.   , 11.25]])
```

- In practice $\mathbf{a}^{[3]}$ is obtained from

$$\mathbf{a}^{[3]} = g^{[3]}(\mathbf{z}^{[3]}) = g^{[3]}(\mathbf{W}^{[3]} \cdot \mathbf{a}^{[2]} + \mathbf{b}^{[3]})$$

Recommended Settings

Some idea to set your keepprob




- The keepprob can be different value in different layer
- The lower $n^{[l]}$ (number of hidden units in the layer l) the higher keepprob
- Input layer has keepprob equal to 1

Other Regularizations

Early stopping

$J(W, \mathbf{b})$



- Stop training based on the cost convergence



Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics

Gradient

Normalized Input




Speed up your training

- Subtract mean

$$\mu = \frac{1}{m} \sum_{i=1}^m \mathbf{x}^{(i)}$$


$$\mathbf{X} := \mathbf{X} - \mu$$

- Data will have zero mean



Normalized Input

Speed up your training




- Normalized variance

$$\sigma^2 = \frac{1}{m} \sum_{i=1}^m (\mathbf{x}^{(i)})^2$$

$$\mathbf{X} = \frac{\mathbf{X}}{\sigma^2}$$

- Data will have zero mean and normalized variance





- μ and σ^2 from training set will be used in test set

Normalized Input

- Given a contour of the cost function

Speed up your training





Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics

Minibatch Gradient Descent

Batch VS Mini-batch

Dividing training data into minibatch

Notations

$\mathbf{X}^{(t)}$ and $\mathbf{y}^{(t)}$ for training samples of mini-batch t

- Vectorization enables effective computation over m samples

$$\mathbf{X}_{n_x \times m} = [\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \dots, \mathbf{x}^{(m)}]$$

$$\mathbf{y}_{1 \times m} = [y^{(1)}, y^{(2)}, \dots, y^{(m)}]$$

- What if m is extremely large, e.g. 5,000,000
 - Use mini-batch

$$\begin{aligned} \mathbf{X}_{n_x \times m} &= [\underbrace{\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \dots, \mathbf{x}^{(1000)}}_{\mathbf{X}^{(1)}} | \underbrace{\mathbf{x}^{(1001)}, \mathbf{x}^{(1002)}, \dots, \mathbf{x}^{(2000)}}_{\mathbf{X}^{(2)}} | \dots \dots | \dots \dots \underbrace{\mathbf{x}^{(5,000,000)}}_{\mathbf{X}^{(5000)}}] \\ \mathbf{y}_{1 \times m} &= [\underbrace{y^{(1)}, y^{(2)}, \dots, y^{(1000)}}_{\mathbf{y}^{(1)}} | \underbrace{y^{(1001)}, y^{(1002)}, \dots, y^{(2000)}}_{\mathbf{y}^{(2)}} | \dots \dots | \dots \dots \underbrace{y^{(5,000,000)}}_{\mathbf{y}^{(5000)}}] \end{aligned}$$

Mini-Batch Implementation

From the previous example

```
while {  
  for t in range(0, 5000):
```

```
    # Forward propagation on  $X^{(t)}$ 
```

$$\mathbf{z}^{[1]} = \mathbf{w}^{[1]} \cdot \mathbf{X}^{(t)} + \mathbf{b}^{[1]}$$

$$\mathbf{a}^{[1]} = g(\mathbf{z}^{[1]})$$

\vdots

$$\mathbf{z}^{[L]} = \mathbf{w}^{[L]} \cdot \mathbf{a}^{[L-1]} + \mathbf{b}^{[L]}$$

$$\mathbf{a}^{[L]} = g(\mathbf{z}^{[L]})$$

Use vectorization implementation

$$\mathcal{J}^{(t)} = \frac{1}{1000} \sum_{i=1}^{1000} \mathcal{L}(\hat{y}^{(i)}, y^{(i)}) + \frac{\lambda}{2 \times 1000} \sum_l \|\mathbf{w}^{[l]}\|_F^2$$

from $\mathbf{X}^{(t)}, \mathbf{y}^{(t)}$

Backward propagation w.r.t. $\mathcal{J}^{(t)}$ using $\mathbf{X}^{(t)}$ and $\mathbf{y}^{(t)}$

$$\mathbf{w}^{[l]} = \mathbf{w}^{[l]} - \alpha \mathbf{dw}^{[l]}$$


$$\mathbf{b}^{[l]} = \mathbf{b}^{[l]} - \alpha \mathbf{db}^{[l]}$$

```
} until converge
```

Mini-batch gradient descent

Cost function comparison

$J(W, \mathbf{b})$




- The cost function of mini-batch gradient descent could be oscillated
 - $\mathbf{X}^{\{1\}}, \mathbf{y}^{\{1\}}$ might be an easy gradient
 - $\mathbf{X}^{\{2\}}, \mathbf{y}^{\{2\}}$ might be a harder gradient
 - Overall should be downward

Choosing Mini-batch size

The extreme cases

Stochastic Gradient Descent



Batch Gradient Descent

- Mini-batch size = m
 - Batch gradient descent

$$(\mathbf{X}^{\{1\}}, \mathbf{y}^{\{1\}}) = (\mathbf{X}, \mathbf{y})$$

- Mini-batch size = 1
 - Stochastic gradient descent

$$(\mathbf{X}^{\{1\}}, \mathbf{y}^{\{1\}}) = (\mathbf{x}^{(1)}, y^{(1)})$$

Characteristics	Batch	Mini-batch	SGD
Speed	Very Slow	Fast	Slow <i>Does not leverage vectorization</i>
Convergence to minimum	Guarantee	Not Guarantee	Not Guarantee

Choosing Mini-batch size

Conclusion

- Small Training Set ($m \leq 2000$)
 - Use Batch gradient descent
- Otherwise
 - Use Mini-batch
- Suggested mini-batch size
 - 2^k to perfectly fit in CPU/GPU memory, e.g. 64, 128, 256, 512, etc



Mahidol University

Faculty of Medicine Ramathibodi Hospital


Section for Clinical Epidemiology and Biostatistics

Gradient Optimization

Momentum Gradient Descent, RMSprop, and ADAM

Momentum Gradient Descent

Idea



- Gradient Descent
- Momentum Gradient Descent
- Overshoot (too much learning rate)

- Desired movement directions
 - Fast to the minimum point

From our example, movement on this direction (→) should be fast


- Slow to others

From our example, movement on this direction (↕) should be slow

Momentum Gradient Descent

Velocity and Acceleration

Similar to a ball rolling in a bowl



- On iteration t:
Compute \mathbf{dW} , \mathbf{db} on a set of mini-batch

$$\begin{aligned} \mathbf{v}_{\mathbf{dW}} &= \beta \mathbf{v}_{\mathbf{dW}} + (1 - \beta) \mathbf{dW} \\ \mathbf{v}_{\mathbf{db}} &= \beta \mathbf{v}_{\mathbf{db}} + (1 - \beta) \mathbf{db} \end{aligned}$$

Diagram illustrating the momentum update equations. The equations are shown for $\mathbf{v}_{\mathbf{dW}}$ and $\mathbf{v}_{\mathbf{db}}$. The terms $\beta \mathbf{v}_{\mathbf{dW}}$ and $\beta \mathbf{v}_{\mathbf{db}}$ are highlighted in green, representing the previous velocity. The terms $(1 - \beta) \mathbf{dW}$ and $(1 - \beta) \mathbf{db}$ are highlighted in blue, representing the current acceleration. Arrows indicate the flow of information: a red arrow labeled 'friction' points from the previous velocity term to the current velocity term, a green arrow labeled 'velocity' points from the current velocity term to the current velocity term, and a blue arrow labeled 'acceleration' points from the current acceleration term to the current velocity term.

$$\mathbf{W} = \mathbf{W} - \alpha \mathbf{v}_{\mathbf{dW}}$$

$$\mathbf{b} = \mathbf{b} - \alpha \mathbf{v}_{\mathbf{db}}$$

Momentum Gradient Descent

Implementation

Initialize $\mathbf{v}_{d\mathbf{W}} = 0, \mathbf{v}_{d\mathbf{b}} = 0$

Note: dimension of $\mathbf{v}_{d\mathbf{W}} = d\mathbf{W}$
dimension of $\mathbf{v}_{d\mathbf{b}} = d\mathbf{b}$

Hyper-parameters are α, β

- On iteration t :
Compute $d\mathbf{W}, d\mathbf{b}$ on a set of mini-batch

$$\mathbf{v}_{d\mathbf{W}} = \beta \mathbf{v}_{d\mathbf{W}} + (1 - \beta) d\mathbf{W}$$

$$\mathbf{v}_{d\mathbf{b}} = \beta \mathbf{v}_{d\mathbf{b}} + (1 - \beta) d\mathbf{b}$$


$$\mathbf{W} = \mathbf{W} - \alpha \mathbf{v}_{d\mathbf{W}}$$

$$\mathbf{b} = \mathbf{b} - \alpha \mathbf{v}_{d\mathbf{b}}$$

- In practice, $\beta = 0.9$
- Some literature omitted $1 - \beta$

RMSprop

Speed up gradient descent



→ Gradient Descent
→ RMSprop

- On iteration t :
Compute \mathbf{dW} , \mathbf{db} on a set of mini-batch

$$s_{\mathbf{dW}} = \beta s_{\mathbf{dW}} + (1 - \beta) \mathbf{dW}^2$$

$$s_{\mathbf{db}} = \beta s_{\mathbf{db}} + (1 - \beta) \mathbf{db}^2$$

$$\mathbf{W} = \mathbf{W} - \frac{\alpha \mathbf{dW}}{\sqrt{s_{\mathbf{dW}} + \epsilon}}$$


$$\mathbf{b} = \mathbf{b} - \frac{\alpha \mathbf{db}}{\sqrt{s_{\mathbf{db}} + \epsilon}}$$

*a small positive number for numerical stabilization
(preventing divided by zero)*

- RMSprop enables to use the larger learning rate without overshoot movement

Bias Correction

Idea



- Bias correction of data point t is defined as

$$v_t = \beta v_{t-1} + (1 - \beta) \theta_t$$

data point t \nearrow

$$\text{set } \beta = 0.98, \quad v_0 = 0$$

$$v_1 = 0.98v_0 + 0.02\theta_1$$

$$v_2 = 0.98v_1 + 0.02\theta_2 = 0.0196\theta_1 + 0.02\theta_2$$

- Use $\frac{v_t}{1 - \beta^t}$ to estimate the ideal data point t
- Not accurate at the beginning of t but later will be much more accurate

Adaptive Moment Estimation (Adam)

Combining momentum and RMSprop

Initialize $\mathbf{v}_{dW} = 0, s_{dW} = 0, \mathbf{v}_{db} = 0, s_{db} = 0$

Note: Adam works well in wide range across deep learning applications

- On iteration t :

Compute \mathbf{dW}, \mathbf{db} on a set of mini-batch

$$\mathbf{v}_{dW} = \beta_1 \mathbf{v}_{dW} + (1 - \beta_1) \mathbf{dW}$$

$$\mathbf{v}_{db} = \beta_1 \mathbf{v}_{db} + (1 - \beta_1) \mathbf{db}$$

momentum

$$s_{dW} = \beta_2 s_{dW} + (1 - \beta_2) \mathbf{dW}^2$$

$$s_{db} = \beta_2 s_{db} + (1 - \beta_2) \mathbf{db}^2$$

RMSprop

$$\mathbf{v}_{dW}^{\text{correct}} = \frac{\mathbf{v}_{dW}}{1 - \beta_1^t}, \quad \mathbf{v}_{db}^{\text{correct}} = \frac{\mathbf{v}_{db}}{1 - \beta_1^t}$$

$$s_{dW}^{\text{correct}} = \frac{s_{dW}}{1 - \beta_2^t}, \quad s_{db}^{\text{correct}} = \frac{s_{db}}{1 - \beta_2^t}$$

bias correction

$$\mathbf{W}^{[l]} = \mathbf{W}^{[l]} - \alpha \frac{\mathbf{v}_{dW}^{\text{correct}}}{\sqrt{s_{dW}^{\text{correct}} + \epsilon}}$$


$$\mathbf{b}^{[l]} = \mathbf{b}^{[l]} - \alpha \frac{\mathbf{v}_{db}^{\text{correct}}}{\sqrt{s_{db}^{\text{correct}} + \epsilon}}$$

updating


Suggested Hyper-parameters

Fixed learning rate VS Decayed Learning rate

- α : Need to be tuned
- β_1 : 0.9
- β_2 : 0.999
- ε : 10^{-8}



Fixed learning rate



Decayed Learning rate



Mahidol University

Faculty of Medicine Ramathibodi Hospital

Section for Clinical Epidemiology and Biostatistics

Hyperparameter Tuning



Strategy to choose hyper-parameters


Deep learning hyperparameters

Ranked by importance

- 1st priority
 - α : Learning rate
- 2nd priority
 - β : Adam's parameters only ($\beta_1, \beta_2, \epsilon$) (Use default values)
 - Mini-batch size
 - $n^{[l]}$: Number of hidden units in the layer l
- 3rd priority
 - L : Number of layers
 - β : Momentum and RMSprop

Tuning Strategies


Grid approach



- Grid approach is acceptable for traditional ML
- Limitations
 - Important of some hyperparameters might not be fully address
 - Ex. Grid allows trial on 5 values of α and ε from 25 experiments

Tuning Strategies

For deep learning random grid is better




- Random grid allows trial on 25 values of α from 25 experiments
- Random grid gives us more richly to explore sets of possible hyperparameters

Tuning Strategies

- Start from randomly coarse
- Randomly fine later

Coarse to fine




Tuning Strategies

Use the appropriate scale to pitch hyperparameters


- Normal scale works for some hyperparameters

- $n^{[l]}$

- L



- Log-scale is good for learning rate



Spending 10% of resource to search between 0.0001 to 0.1 whereas 90% of resources to search between 0.1 to 1

