



UNIVERSITY OF
CAMBRIDGE

Department of Computer
Science and Technology

Accelerating Molecular Generation through Representation Alignment

Shreyas Ravishankar

Hughes Hall

June 2026

Submitted in partial fulfillment of the requirements for the
Master of Philosophy in Advanced Computer Science

Total page count: 67

Main chapters (excluding front-matter, references and appendix): 48 pages (pp 7–54)

Main chapters word count: 14904

Methodology used to generate that word count:

The count is produced with `texcount` over the $\text{\LaTeX}$ source, following `\input` files. It is scoped to the core chapters by `%TC:ignore` directives that exclude the front matter, bibliography, and appendix. The reported figure sums body text, section headings, and figure/table captions (i.e. narrative text); data listings are not counted, in keeping with the word-count rules outlined at <https://www.cst.cam.ac.uk/teaching/masters/projects/acs/guidelines>. Reproduce with:

```
$ make wordcount
```

```
perl tools/texcount.pl -inc -sum -total -1 report-draft.tex
```

Declaration

I, Shreyas Ravishankar of Hughes Hall, being a candidate for the Master of Philosophy in Advanced Computer Science, hereby declare that this report and the work described in it are my own work, unaided except as may be specified below, and that the report does not contain material that has already been used to any substantial extent for a comparable purpose. In preparation of this report, I adhered to the Department of Computer Science and Technology AI Policy. [The project required the approved use of {insert name of technology} and such use is acknowledged in the text at the relevant sections.] [I am content for my report to be made available to the students and staff of the University.]

Signed:

Date:

Abstract

The evolution of generative machine learning for de-novo molecular design has increasingly favoured prior-light models, trading hard structural symmetries for architectural simplicity and synthetic data scale. While this enables broader scaling, it dilutes the structural signal available to the model during training. This exacerbates the model’s representation bottleneck, as it must simultaneously learn how to represent complex geometry and generate samples using the same objective. In practice, this dual burden leads to slow convergence and expensive training budgets.

In this context, our report investigates Representation Alignment (REPA), a technique from the imaging domain that alleviates the representation bottleneck. REPA injects soft inductive biases by aligning a generator’s hidden states with the embeddings of a frozen, pre-trained encoder. We characterise when and why it succeeds in the molecular domain. Our findings highlight how REPA’s efficacy depends on two conditions. The first is headroom, a gap in what the baseline already represents or produces for the alignment to fill. The second is a usable teacher, an encoder that carries structural information the baseline does not already learn on its own, and that transfers to the generative task.

To determine teacher suitability, we first introduce a domain-agnostic profiling framework that evaluates candidate encoders across three dimensions: information content, relevance to the generative task, and embedding conditioning. We use these profiles to select alignment targets, then conduct empirical studies on two flow-matching transformer architectures: Tabasco for small molecules and Proteina for protein backbones.

On Tabasco, REPA yields no measurable improvements in generation quality or training efficiency, which we attribute to small molecules meeting neither condition. The baseline already saturates the relevant quality metrics, and candidate encoders carry no signal that transfers usefully to the 3D generative task. Conversely, protein backbones meet both conditions, and REPA accelerates Proteina’s convergence on key generation metrics. We also show that in the long run, the best performing teacher encoder is downstream of the data regime. Experimental and synthetic datasets leave headroom in different places, so the alignment target that pays off shifts between them.

Ultimately, we show that REPA is not a single mechanism in the molecular domain, but a family of encoder-mediated interventions. We also offer a principled, domain-agnostic framework for selecting alignment targets to guide REPA beyond molecules.

Acknowledgements

I am very grateful to Miruna Cretu, Vladimir Radenkovic, and Rishabh Anand for their vision and guidance through this project. I would also like to thank Professor Pietro Lio for all his support.

Contents

1	Introduction	7
1.1	A history of trade-offs	7
1.2	Representation alignment	8
1.3	Contributions	9
2	Background and Related Work	10
2.1	Flow matching	10
2.2	Representation alignment	11
2.2.1	What makes for a good REPA encoder?	13
2.3	A primer on molecular generation	13
2.4	Tabasco and Proteina	14
2.4.1	Small molecules and Tabasco	14
2.4.2	Protein backbones and Proteina	15
2.5	Open questions	16
3	Evaluating molecular generation	17
3.1	What makes for a “good” molecule?	17
3.2	Representation and generation are multi-factorial and multi-scale problems	17
3.3	The linear probe principle	18
3.4	Small-molecule metrics	19
3.5	Protein-backbone metrics	19
3.6	The designability–diversity trade-off	23
4	Encoder targets and profiling	25
4.1	A profiling protocol	25
4.2	Small molecule encoders	28
4.3	Protein backbone encoders	29
4.4	Informing our experiments	29
5	REPA on small molecules	30
5.1	Experimental setup	30
5.1.1	Dataset	30
5.1.2	Models	30

5.1.3	Metrics	31
5.2	Results: no measurable gain	32
5.3	Discussion	34
6	REPA on protein backbones	36
6.1	Experimental setup	37
6.1.1	Datasets	37
6.1.2	Models	38
6.1.3	Metrics	40
6.1.4	Evaluation protocol	40
6.2	Results	41
6.2.1	REPA improves representation quality asymptotically	41
6.2.2	A diagnostic check on alignment	43
6.2.3	In the short run, REPA accelerates generation quality in both ex- perimental and synthetic data regimes	44
6.2.4	In the long run, REPA gains are data-regime dependent	47
6.2.5	What we do not claim	49
6.3	Discussion	50
7	Conclusions	52
7.1	Does REPA work in the molecular domain?	52
7.2	When does REPA work?	53
7.3	Open questions	54
A	Technical details	60
A.1	Protein dataset composition and split overlap	60
A.2	Choice of CATH fold-probe level	60
A.3	Leakage-controlled probe evaluation	61
A.4	Full representation-quality ablation	62
A.5	Representation quality on AFDB	62
A.6	Representation-alignment matrix	63
A.7	Representation-generation coupling on AFDB	63
A.8	The ssJSD-2D secondary-structure metric	64
A.9	Secondary-structure composition of the designable subset	64
A.10	Deterministic (ODE) sampling across variants	65
A.11	Per-seed spread of the 1.3M results	66
A.12	Full encoder profiles	67

Chapter 1

Introduction

The evolution of generative machine learning in scientific domains is defined by the shifting tensions between data scale, data quality, and structural priors. Our report examines a recent addition to this story, *representation alignment*, in two regimes for de-novo molecular generation — small molecules and protein backbones — and characterises its behaviour. In this introduction, we trace the narrative arc of research trends in molecular generation, and highlight the motivation for our work: the emerging need for data-efficient modelling in a world of prior-light models.

1.1 A history of trade-offs

The dominant ideas in generative modelling are *denoising diffusion* and its offshoot *flow matching* [1, 2], which found breakthrough success in the realm of image generation. This paradigm has since been adapted for de-novo design challenges across scientific fields, such as generating drug-like small molecules [15], protein backbones [18, 19, 14], and inorganic materials [21]. Training these models is typically expensive in both data and compute, with state-of-the-art image generators routinely training on billions of examples [36]. However, the corpus of available high-quality molecular data sits orders of magnitude below this. Experimental determination is slow and expensive, which means datasets are correspondingly small. For example, protein structure generators have largely been trained on at most half a million structures [14], which may explain why they have not yet matched the maturity of their vision-domain counterparts.

Historically, researchers compensated for the small scale of high-quality molecular data by encoding structural priors directly into model architectures [42]. SE(3)-equivariant architectures, for example, enforce the rotational and translational symmetries expected of molecules by construction [44]. But hard structural priors come with a computational cost, and the operations required to encode geometry are a bottleneck to scaling models. A recent wave of research has moved entirely the other way: drop hard priors, use bare-bones non-equivariant transformer stacks, and rely on data scale and augmentation to teach the model what equivariance buys. This shift fits a broader trend in machine

learning on leveraging representation instead of model architecture to inject soft inductive biases for structured data. Vision Transformers [45] showed that the spatial-locality and translation-equivariance priors of convolutional neural nets (CNNs) can be learned rather than imposed, given sufficient scale. Graph Transformers like TokenGT [46] have made the same case for graphs. AlphaFold 3 [48] stripped many of the SE(3)-equivariant biases of AlphaFold 2 [47], replacing the structure module with a diffusion model operating on raw coordinates. Brehmer et al. [49] make the empirical scaling case directly: more data through a simpler model beats less data through a richer one. In our work, we examine Tabasco [15] and Proteina [14], which are flow-based generators built on largely vanilla transformers for small molecules and protein backbones respectively.

Given the difficulty of procuring data in scientific domains, data scale must necessarily come from non-experimental sources, which may be of lower quality. For example, recent efforts in protein generation have leaned on synthetic structures from folding-model predictions [14, 38] to expand training datasets into the tens of millions. However, even these enhanced corpora are arguably insufficient. Metagenomic databases catalogue over two billion natural protein sequences [40], and the theoretical sequence space at a median protein length [41] is hundreds of orders of magnitude greater still. Even at the frontier of the field’s data scale, we sample but a sliver of the distribution we wish to model.

In summary, the field has traded hard structural priors for architectural simplicity, and curated data for synthetic scale. However, this trade-off dilutes the structural signal available to a model. Furthermore, even if we accept lower data quality, our best attempts at creating large datasets may still not be large enough. These twin challenges amplify the need for techniques that make training still more efficient without sacrificing quality.

1.2 Representation alignment

But why is training diffusion-transformer architectures expensive in the first place? One answer comes from Yu et al. [5], who argue that these models suffer from a *representation bottleneck*. During training, a model is implicitly asked to learn two distinct tasks simultaneously. The first is representation: extracting semantically meaningful encodings from complex data. The second is generation: constructing data from these encodings. The standard denoising objective alone may not provide sufficient signal for representation learning, leading to slow convergence and the large training budgets these models require.

This burden falls harder on the prior-light models we study. In the absence of equivariant architectures, the training objective must now shoulder the additional responsibility of learning structural symmetries. Moreover, the scarcity of high-quality data compounds the problem. The model must learn complex geometry from data that only sparsely samples the true distribution, with no architectural scaffolding to fall back on.

One response to this problem is to supply representational structure from elsewhere. Instead of being entirely left to the training objective, it can be injected softly as an

auxiliary training signal. This is the idea behind Representation Alignment (REPA), which Yu et al. propose as a remedy. The technique adds a regularisation term that aligns a generator’s intermediate hidden states with the embeddings of a frozen pretrained encoder. On image diffusion, they report roughly a $17.5\times$ training speed-up against a strong baseline to achieve similar generation quality. REPA has since been extended beyond images to video [9], audio [10], and recently to molecular generation [7, 8], where it has been demonstrated but not systematically characterised.

1.3 Contributions

In this light, the core question we investigate in this report is: *can prior-light molecular generation models benefit from representation alignment with pre-trained models, in training efficiency and generation quality?* We aim to characterise when and why this works, including failure modes and limitations.

We document two lines of enquiry.

- (i) *Does REPA work in the molecular domain?*: We conduct empirical studies on training flow-based generators with REPA in two regimes: Tabasco [15] for small molecules, and Proteina [14] for protein backbones. We find that REPA does not measurably improve Tabasco, but it accelerates generation quality and improves training efficiency for Proteina.
- (ii) *When does REPA work?*: Following Singh et al. [6] in the realm of image generation, we develop a profiling framework to characterise the suitability of an encoder as a representation target. For every encoder, we measure its *information* content, the *relevance* of that content for the generation task, and the mathematical *conditioning* of its embeddings for the alignment objective.

We do not propose a new architecture or alignment loss, and our two studies are not a controlled experiment over the conditions that govern REPA’s effectiveness. Instead, they are best read as paired case studies in regimes where those conditions differ.

The remainder of this report is organised as follows. Chapter 2 sets out the background and context needed to read the rest: flow matching, REPA, and molecular generation. Chapter 3 discusses what it means for a generative model to be “good” in our domain, and the tensions that question hides. Chapter 4 develops the encoder-profiling framework and uses it to predict where REPA may and may not help. Chapters 5 and 6 present the two paired studies, small molecules first and protein backbones second. Finally, we conclude in Chapter 7 with a discussion of whether what we learn generalises beyond molecular generation.

Chapter 2

Background and Related Work

In this chapter, we introduce the machinery the rest of this thesis depends on: flow matching (§2.1), representation alignment (§2.2), the de-novo molecular design pipeline (§2.3), and the two domains and models we work with (§2.4). The treatment is cursory by design. We intend only to guide the reader through this report, and we provide citations for omitted details.

2.1 Flow matching

Generative modelling is the problem of *sampling* new artefacts from a complex data distribution accessible only through a finite training set. A common strategy here is to fix a simple distribution we can sample from cheaply — typically standard Gaussian noise $p_0 = \mathcal{N}(0, I)$ — and learn a mapping from it to the desired data distribution p_1 .

Flow matching (FM) [2] realises this mapping as a continuous-time transport. The model designer defines a *probability path* between a noise sample and a data sample — a continuous interpolation between them — and the model learns to carry the noise sample along this path. Concretely, it parameterises a time-dependent *velocity field* $v_\theta(x, t)$ that gives the instantaneous direction of motion at each location x and time $t \in [0, 1]$. At inference, integrating the learned ordinary differential equation (ODE) $\dot{x}_t = v_\theta(x_t, t)$ from $t = 0$ to $t = 1$ pushes a fresh noise sample forward into a fresh data sample.

A common choice of probability path is the linear interpolant, $x_t = (1 - t)x_0 + tx_1$ for $x_0 \sim p_0$ and $x_1 \sim p_1$. The model’s target is the *marginal* velocity field at (x, t) : the average direction of motion over all noise-data pairs whose paths pass through that point. Supervising this marginal directly is intractable, since the contributing pairs are not known in advance. However, the key observation [2] is that the *conditional* velocity along the path of any specific noise-data pair is tractable: for the linear interpolant, simply $\dot{x}_t = x_1 - x_0$. Regressing the model on these conditional velocities, averaged over many sampled pairs, recovers the marginal field in expectation, and gives the training loss as a




Figure 2.1: The REPA construction. The generator v_θ processes the noised sample x_t to produce the velocity field for the flow-matching loss $\mathcal{L}_{\text{FM}}$. In parallel, a frozen encoder f_{enc} (shaded) embeds the clean sample x_1 . A trainable projector h_ϕ maps the generator’s hidden state z_ℓ into the encoder’s space, and the REPA loss $\mathcal{L}_{\text{REPA}}$ is their token-averaged negated similarity. The total loss combines the two with weight λ .

mean-squared regression:

$$\mathcal{L}_{\text{FM}} = \mathbb{E}_{t, x_0, x_1} \|v_\theta(x_t, t) - (x_1 - x_0)\|^2.$$

In practice, every training step samples a time $t \in [0, 1]$ and a noise-data pair (x_0, x_1) , computes the interpolant x_t , and takes a gradient step on this squared error.

Flow matching with this linear interpolant generalises score-based diffusion: the variance-preserving Gaussian-path objective of denoising diffusion models [1] is a special case of the FM family [2, 4].

Generating samples from a trained flow-matching model amounts to integrating the learned velocity field, often with a standard ODE solver. The field also admits stochastic (SDE) samplers that inject noise during integration. The noise amount is a tunable knob that broadens diversity at some cost to per-sample quality, with the deterministic ODE its zero-noise limit. The models we work with, Tabasco and Proteina, support both.

Conditional generation augments v_θ with context tokens — such as a class label, a sequence length, or a structural motif — with conditioning supplied at both training and sampling time. In this report, we focus on unconditional generation only.

For fuller treatments, see Lipman et al. [2, 4].

2.2 Representation alignment

Chapter 1 introduced the argument made by Yu et al. [5] about the *representation bottleneck* in diffusion-transformer models. It applies to flow-matching models too, by the

equivalence above (§2.1). The flow-matching objective implicitly asks a model to learn two things at once: a useful representation of the data, and a velocity field that interprets this representation. This twin burden, they argue, leads to slow convergence and large training budgets.

Their proposed solution, Representation Alignment (REPA), addresses the first half of this burden by adding a regularisation term to the training loss. Figure 2.1 shows the construction. The regularisation pulls z_ℓ , the generator’s intermediate hidden state at a chosen *alignment layer* ℓ , towards the embeddings produced by a frozen pretrained encoder f_{enc} run on the clean data sample x_1 . The hidden state z_ℓ is a sequence of N token vectors. In the context of images, each token represents an image patch; in the molecular setting, each token represents an atom or residue that is part of the larger molecule (§2.3). A small trainable *projector head* h_ϕ — a three-layer multi-layer perceptron (MLP) in the original paper — maps z_ℓ into the encoder’s feature space, so that $h_\phi(z_\ell)$ and $f_{\text{enc}}(x_1)$ can be compared. This alignment is asymmetric. The encoder provides a fixed target throughout training, while the generator parameters θ and the projector ϕ are updated. The alignment loss is the negated similarity, averaged token-wise, between projected and target embeddings:

$$\mathcal{L}_{\text{REPA}} = -\mathbb{E}_{t, x_0, x_1} \left[\frac{1}{N} \sum_{n=1}^N \text{sim}(h_\phi(z_\ell)_n, f_{\text{enc}}(x_1)_n) \right],$$

where n indexes the N tokens within a sample. In images N is constant, so a token-wise average matches a per-sample-then-batch average; for molecules N varies per sample, and the two diverge.

The final training objective is the flow-matching loss from §2.1 plus this term, scaled by a weight λ :

$$\mathcal{L} = \mathcal{L}_{\text{FM}} + \lambda \mathcal{L}_{\text{REPA}}.$$

This construction exposes several design choices, some of whose effects we revisit in the ablations of Chapter 6:

- The encoder f_{enc} , since different encoders capture distinct aspects of the data.
- The alignment layer ℓ at which the projector attaches. Yu et al. found mid-network layers best for images, but this is only an empirical observation.
- The alignment-loss weight λ , which balances alignment against the generative objective. Yu et al. used 0.5 for images.
- The similarity metric sim . We adopt cosine similarity, which Yu et al. found more effective than mean-squared error.
- The averaging mode. Averaging within each sample weights every molecule equally, while pooling across the batch gives larger molecules proportionally more REPA signal.

We adopt the core REPA construction as in Yu et al. for this report. However, a small family of methodological variants on REPA has since emerged. Dispersive regularisers [12] replace the external encoder with an internal contrastive term, while flexible-target formulations [7] broaden which encoder features the loss attaches to. Separately, REPA-style alignment has been applied beyond the image setting, to video [9], audio [10], materials [11], and molecules [8]. We defer exploration of these variants to future work.

2.2.1 What makes for a good REPA encoder?

The encoder f_{enc} is among REPA’s largest design choices, but what makes a good alignment target? Yu et al. [5] observed that ImageNet linear-probe accuracy correlates positively with generation performance, suggesting global semantic representation is the driving factor. More recent work by Singh et al. [6] reports the opposite after profiling a wider range of encoders: linear-probe accuracy does not predict REPA gain, while a measure of the spatial structure of patch-token representations does. Generation performance may therefore be driven by *local* feature geometry rather than *global* semantic strength. Encoder characterisation for REPA remains open, particularly in the molecular setting, and we pick up the thread in Chapter 4.

2.3 A primer on molecular generation




Figure 2.2: The de-novo molecular design cycle. An upstream specification drives a generative model to produce a candidate pool, which is funnelled through in-silico filters and then synthesised (or expressed) and assayed in the wet lab. Results feed back into the next round.

We now turn to the molecular setting, and the role generative models play within the broader de-novo molecular design pipeline. In a real-world scenario, generative models are rarely intended to produce ready-to-use artefacts. Instead, they act as high-throughput in-silico proposal engines in an iterative process of refinement and selection. This process, often called a *design campaign* [57], is summarised in Figure 2.2.

An upstream specification, such as a drug-likeness profile or a fold class, conditions a generative model to produce a pool of candidate samples, which are then funnelled through in-silico filters. For small molecules, these typically include checks for structural validity and physical plausibility [58], drug-likeness [61], and target docking; for protein




Figure 2.3: The two molecular domains, at very different scales. (a) A small molecule, aspirin: 13 heavy atoms. (b) A protein backbone, ubiquitin: 76 residues, 602 atoms.

backbones, designability and structural diversity are the dominant considerations [14]. The select few survivors are produced in a laboratory, through chemical synthesis (small molecules) or expression in cell lines (proteins), and evaluated using in-vitro or in-vivo assays. Experimental results then feed back into the next round of generation.

This pipeline framing is relevant to our discussion of evaluation metrics in Chapter 3. Several metrics we adopt, such as structural validity and designability, are not measures of intrinsic molecular quality, but proxies for specific in-silico filter steps.

2.4 Tabasco and Proteina

The two models we study — Tabasco [15] for small molecules and Proteina [14] for protein backbones (Figure 2.3) — are both non-equivariant transformer flow-matching generators, designed to scale with data and model size rather than impose structural priors by construction.

Tabasco is motivated by the success of similar architectures in protein-structure generation, like Proteina, setting it apart from equivariant message-passing small-molecule generators such as EQGAT-diff [52], MiDi [53], and SemlaFlow [54]. In turn, Proteina is motivated by the pair-bias attention mechanism introduced in AlphaFold 3 [48], which distinguishes it from SE(3)-equivariant backbone generators such as RFdiffusion [18], FrameFlow [50], and Genie [51].

2.4.1 Small molecules and Tabasco

In medicinal chemistry, a *small molecule* is a drug-like compound at the sub-900-Dalton scale [55]. In-silico, its structure is typically represented using two coupled features: a discrete *molecular graph* of typed atoms connected by typed bonds, and a continuous

conformer placing those atoms in 3D Cartesian space. A flow-matching model must therefore handle both parameterisations jointly.

Tabasco [15] represents each molecule as a sequence of per-atom tokens, each carrying an atom-type embedding and a 3D coordinate, but with no explicit bond decoder. This treats the molecule as a point cloud of typed atoms rather than a graph, sidestepping edge modelling at the cost of having to recover bond structure post hoc from interatomic distances. Tabasco is trained on GEOM-drugs [39], a public dataset of drug-like conformers.

This point-cloud-of-atoms parameterisation is one of several, each with a different trade-off. *SMILES* and *SELFIES* string encodings discard the 3D conformer entirely. *3D voxel grids* preserve geometry but lose the graph and inflate the token count. *Equivariant point clouds*, used by EQGAT-diff [52], MiDi [53], and SemlaFlow [54], keep both but require SE(3)-equivariant layers. See Duval et al. [43] and Wang et al. [23] for broader surveys.

2.4.2 Protein backbones and Proteina

A *protein* is a chain of amino-acid residues, ranging from around 50 to several thousands in length [56]. Each amino-acid residue contributes four *backbone* atoms (N, C $_{\alpha}$, C, O) whose interactions determine the chain’s *fold* geometry, and a *side chain* that determines its amino-acid identity.

A protein’s *secondary structure* is its local pattern of α -helices and β -strands; its *tertiary structure* is the global three-dimensional fold those elements form when they pack together. A CATH code [65] (Class, Architecture, Topology, Homology) classifies this fold hierarchically. *Class* captures broad secondary-structure content (mostly- α , mostly- β , or mixed), *Architecture* the gross spatial arrangement of those elements, and *Topology* their specific connectivity.

For the structure-generation problem we study, it is customary to model only the backbone, with sequence identity recovered downstream by a separate *inverse-folding* model such as ProteinMPNN [25]. The *CA-trace* compresses this further, using only the C $_{\alpha}$ coordinate of each residue. It retains enough information to recover fold topology, at lower cost than the fuller *all-atom* representation. Proteina [14] adopts this C $_{\alpha}$ parameterisation, representing each backbone as a sequence of per-residue tokens carrying continuous C $_{\alpha}$ Cartesian coordinates. The models reported in the original presentation are largely trained on high-confidence synthetic structures from the AlphaFold Database (AFDB) [38].

Again, the CA-trace is one of several protein parameterisations. *Sequence-only* models such as the ESM lineage [24] operate on amino-acid strings, capturing rich functional priors but little 3D structure. *Full-atom* representations close the gap to physical realism at substantial compute cost. *Equivariant* parameterisations, such as torsion angles and oriented residue frames, encode SE(3) symmetries by construction and underlie the equivariant generators noted above, but have historically bottlenecked scaling. See Notin et al. [63] for a broader survey.

2.5 Open questions

This survey leaves open the two questions of §1.3. First, *does REPA work for molecules?* Existing molecular REPA work [7, 8] has not ablated over encoder choice, and protein backbone generation in particular remains unexplored. Second, *when does REPA work?* The encoder-characterisation work introduced in §2.2.1 has begun to ask which encoder properties predict REPA gain, but only for images, and we seek to explore this further. We take up both questions in Chapters 4–6.

Chapter 3

Evaluating molecular generation

What does it mean for a model to generate “good” artefacts? In this chapter, we outline a framework for evaluating molecular generation, and the tensions inherent to this endeavour. We argue that no single number suffices here, define the metric suites we use for small molecules (Table 3.1) and protein backbones (Table 3.2), and introduce the probe principle by which we measure a model’s internal representations. We also introduce the theme of a *trade-off frontier* with these metrics. A gain on one axis may imply a loss on another (Chapter 6), a tension we return to in §3.6.

3.1 What makes for a “good” molecule?

“Goodness” is usually task-specific, and a de-novo design pipeline (§2.3) asks several things of a generated candidate pool at once. A useful set must at least be *valid*: realistic enough to survive downstream filters; *diverse*: spread across the design space, not collapsed onto a few modes; and *designable*: amenable to synthesis. These axes trade off against each other. A model can buy validity by memorising a handful of safe scaffolds, at the cost of diversity; or buy diversity by spreading its mass thinly, at the cost of designability. No axis is dispensable, and maximising any one in isolation is uninformative, as these metrics are themselves proxies for the pipeline’s real-world filter steps.

3.2 Representation and generation are multi-factorial and multi-scale problems

Moreover, the need for a suite of evaluation metrics reflects how molecules are represented in-silico. Molecules present a stark contrast with images, which originated the generative machine learning methods we adopt (§2.1).

In a 2D image, *geometry* and *content* are coupled in one representation. The pixel grid is at once an object’s shape and its identity. There is a single contiguous feature space, so one self-supervised encoder can serve as a near-complete description of it. This coupling

is what lets image generation lean on a single strong encoder, and lets image quality be summarised, to a first approximation, by a single Fréchet distance in that encoder’s feature space [60].

However, molecules pull geometry and content apart, and into more than two pieces. A molecule is at once a discrete graph of typed atoms drawn from a periodic-table-sized alphabet, and a continuous 3D geometry. This is a discrete–continuous duality with no clean analogue in the pixel grid. The two concepts are only loosely tied: one bonding graph admits many conformers, and similar geometries can host different atom types. Geometry is itself organised hierarchically from local environments up to global shape. Indeed, the taxonomy used to describe protein structure makes this explicit, running from primary sequence through secondary-structure elements to the tertiary fold.

As a consequence, both representation and generation quality are *multi-factorial* and *multi-scale* in this domain. No single encoder captures every factor of content and geometry at every scale at once, as we see in Chapter 4. Moreover, no single metric can score a generated set along all those factors at once. A model can match the distribution of folds while getting local geometry subtly wrong; it can place atoms in valid positions while collapsing the diversity of shapes it produces. These are independent failures, so mode collapse is harder to reason about here than in the image domain.

The metric suite we propose in this chapter is an attempt at handling this complexity. We decompose quality along the factors the domain pulls apart, and interpret metrics holistically to understand the complete picture. For each domain we report two complementary families: *representation quality*, which scores what the model encodes internally, and *generation quality*, which scores its outputs. We present them in that order throughout the report, since representation is what REPA’s mechanism acts on (§2.2) and generation is the outcome we hope it improves.

3.3 The linear probe principle

One way to understand what a model represents internally is the *linear probe*. We freeze the model, extract its hidden states for clean inputs, and fit a linear regression to a known structural label. If the label is recoverable by this simple probe, that information is considered to be present and accessible in the representation; if not, it is considered absent or deeply entangled. This follows standard practice in image generation, where encoders are often characterised by ImageNet linear-probe accuracy [5]. We use this mechanism in two places: on the frozen encoders we might align to (Chapter 4), and on the generator trunk itself (Chapters 5 and 6).

The form of the read-out follows the label. For real-valued targets, we fit a regression and score recoverability by held-out R^2 . For categorical targets, we fit a logistic classifier and score top-1 accuracy.

We outline the small-molecule targets we regress against in §3.4, and the protein suite in

§3.5. Each probe maps to a necessary condition for a useful alignment target. The tasks span content and geometry from local to global scales, so we interpret a representation that scores well across the whole battery as genuinely carrying holistic information.

3.4 Small-molecule metrics

Table 3.1 collects every small-molecule metric we use, following the conventions of recent 3D molecular generators [15, 52, 54].

Representation quality. This asks what structural information the generator has learned to encode internally. We apply the probe principle of §3.3, regressing mean-pooled per-atom features onto four global RDKit descriptors [62] — molecular weight, LogP, ring count, and rotatable-bond count — and score recoverability by held-out R^2 .

Generation quality. This asks if the generator produces good artefacts. For small molecules, quality metrics fall into three groups: per-molecule *structural quality* (validity, connectivity, uniqueness), set-level *coverage* (diversity, novelty), and *distributional realism* (the Fréchet ChemNet Distance, FCD [59]). The first group guards against malformed or repeated molecules; the second against mode collapse and memorisation; FCD, the small-molecule analogue of the image-domain Fréchet Inception Distance [60], asks whether the generated set as a whole resembles real molecules. As we explore in Chapter 5, the structural-quality metrics are particularly amenable to saturation by a strong generator. This does not mean the problem is solved; rather, it is a limit of the yardstick itself.

3.5 Protein-backbone metrics

Protein backbones are larger and more variable than small molecules (Chapter 2), and evaluating them is correspondingly more involved. Table 3.2 collects all the protein metrics we use. We present representation first, then generation, and close by offering our own framework for how the generation metrics should be grouped and read together.

Representation quality. We apply the probe principle of §3.3 for three tasks adapted from the literature, spanning local to global structure: per-residue inverse-folding recovery [28] for the local chemical environment; backbone dihedral error [27] for low-level geometry; and CATH fold classification [27] for global fold. The first two are scored per residue (top-1 accuracy and mean absolute error), while the fold probe is a logistic classifier on mean-pooled per-chain features. Because the three are largely orthogonal, improving all of them at once is strong evidence of holistic representation quality.

Representation alignment. This asks not what the generator encodes, but how geometrically close it sits to a frozen encoder. We measure it with CKNNA [66], a mutual-nearest-neighbour kernel alignment, following the original REPA analysis [5] and a recent molecular extension [8]. We use it as a diagnostic lens on how REPA acts rather than a quantity we optimise.

Metric	Definition	Content	Score
Representation quality — probe recoverability of RDKit descriptors [62]			
MolWt $\uparrow$	Molecular weight	Global size	R^2
LogP $\uparrow$	Octanol–water partition coefficient	Lipophilicity	R^2
Rings $\uparrow$	Ring count	Topology	R^2
RotBonds $\uparrow$	Rotatable-bond count	Flexibility	R^2
Generation quality			
<i>Structural quality</i>			
Validity $\uparrow$	Fraction sanitising to a valid molecule once bonds are inferred	Malformed geometry	Fraction
Connectivity $\uparrow$	Fraction forming a single connected component	Fragmentation	Fraction
Uniqueness $\uparrow$	Fraction not duplicating another generation	Trivial repetition	Fraction
<i>Set coverage</i>			
Diversity $\uparrow$	Mean pairwise dissimilarity across the generated set	Mode collapse	Fraction
Novelty $\uparrow$	Fraction of the set absent from the training data	Memorisation	Fraction
<i>Distributional realism</i>			
FCD $\downarrow$ [59]	Fréchet ChemNet Distance: Fréchet distance over the whole set in a property-prediction network’s feature space	Distributional realism	Distance

Table 3.1: Small-molecule metrics (Chapter 5), following the conventions of recent 3D molecular generators [15, 52, 54]. Arrows give the good direction.

Generation quality. Measures of generation quality draw on two lineages. The *canonical* ones — designability, and various counts of novelty and diversity — score or tally individual generations, and predate modern generative models. The *model-based* ones, introduced to this domain by Proteina [14], borrow the idea from image generation of comparing a generated set against a reference in a learned feature space. We headline on one from each: designability as the canonical measure of per-sample quality, and the Fréchet Protein Structure Distance (FPSD) as the model-based measure of set-level distributional realism. We outline these two metrics, add a secondary-structure metric of our own, and then set out a framework that organises them all.

Designability. This metric estimates the fraction of generated backbones that are realisable as real proteins. It involves an in-silico round-trip through the protein design loop (§2.4.2). Each backbone is inverse-folded with ProteinMPNN [25], a model trained to predict an amino-acid sequence that would fold into a given backbone, to propose candidate sequences. These sequences are then re-folded with ESMFold, a model trained to predict 3D structure from sequence. A backbone is termed designable when the self-consistency root-mean-squared deviation (scRMSD) between the generated backbone and its re-folded prediction falls below 2 Å (Figure 3.1).

Metric	Definition	Content	Score
Representation quality			
IF top-1 $\uparrow$	Per-residue inverse-folding sequence recovery [28]	Local chemical env.	Top-1 acc.
Dihedral MAE $\downarrow$	Per-residue backbone dihedral-angle error [27]	Low-level geometry	MAE
CATH-A top-1 $\uparrow$	Per-chain fold-architecture classification [27] (Table A.2)	Global fold	Top-1 acc.
Representation alignment			
CKNNA $\uparrow$ [66]	Per-residue mutual-nearest-neighbour kernel alignment, trunk vs. encoder	Trunk–encoder similarity	Score
Generation quality			
<i>Quality</i>			
FPSD $\downarrow$	Fréchet Protein Structure Distance: distance over the whole set in a structural encoder’s (GearNet) feature space	Distributional realism	Distance
Des $\uparrow$	Fraction of generated backbones that are designable	Physical realisability	Fraction
<i>Tertiary structure — whole set (T-W)</i>			
fJSD-A $\downarrow$	Jensen–Shannon divergence vs. reference CATH-A distribution	Fold-distribution match	Divergence
fS-A $\uparrow$	Spread of generated folds across CATH-architecture classes	Whole-set fold diversity	Count
<i>Tertiary structure — designable subset (T-D)</i>			
#Clust $\uparrow$	Number of TM ≥ 0.5 structural clusters	Designable diversity	Count
pwTM $\downarrow$	Mean pairwise TM-score	Designable diversity	TM-score
<i>Secondary structure — whole set (S-W)</i>			
ssJSD-2D $\downarrow$	Jensen–Shannon divergence of the (helix-frac, strand-frac) distribution	Secondary-structure match	Divergence
<i>Secondary structure — designable subset (S-D)</i>			
ssJSD-2D $\downarrow$	As above, on the designable subset	SS match (designable)	Divergence
β -strand frac. $\uparrow$	Mean β -strand (E) fraction	β -content	Fraction

Table 3.2: Protein-backbone metrics (Chapter 6). Arrows give the good direction; full per-metric results appear in Tables 6.6 and 6.7.




Figure 3.1: Designable versus non-designable backbones. Designable ones (top, $\text{scRMSD} < 2 \text{ \AA}$) re-fold to their generated shape; non-designable ones (bottom, 16–20 $\text{\AA}$) do not. The two right-hand designable examples are β -rich, not easy helices. From our PDB models at 1.3M steps (§6.2.4).

One caveat affects interpretation: designability is an in-silico proxy, not ground-truth physical realism, so it inherits the biases of the folding models it relies on. The inverse-folding and folding steps share model lineage with AlphaFold2 [47], and hence with the synthetic AlphaFold Database (AFDB), whose structures are themselves AF2 predictions. Generators trained on AFDB therefore score systematically higher on designability by construction, as we explore in Chapter 6.

Designable β -strand fraction. A model can inflate designability by emitting easy, highly foldable all- α backbones, since idealised helical bundles re-fold with low scRMSD almost by construction. On the contrary, β -strand content is harder to render designable. As a guard-rail, we track the mean fraction of residues in β -strand (f_E) over the designable subset, and read it alongside designability. A designable set that retains β -rich folds is evidence that its designability is genuine, rather than bought with trivial helical artefacts. (We use the $\text{C}\alpha$ -only secondary-structure assignment of Appendix A.8.)

FPSD. The Fréchet Protein Structure Distance [14] is the protein analogue of the imaging FID. First, it embeds the generated and reference sets using an external encoder: in this case, a GearNet [26] model trained on a fold classification task. Then, it models each set of embeddings as a Gaussian, and reports the Fréchet distance between the two — a scalar that drops to zero as the generated distribution matches the reference in both mean and covariance. Because the encoder reads fold-level geometry, FPSD scores how well a generated set reproduces the reference distribution of folds. By matching covariance and not just the mean, it carries some diversity signal of its own, which is why it often moves together with our dedicated diversity metrics. This GearNet fold classifier is also

one of our two REPA alignment targets in our study of protein backbones (Chapter 6). A model aligned to it might then be expected to gain on FPSD mechanically, by being pulled toward the metric’s own feature space. We check this in §6.2.3 and find it does not hold.

ssJSD-2D. We introduce this secondary-structure metric in our report. Like FPSD and fJSD, it is a *distributional* metric, scoring the generated secondary-structure distribution against a real reference. Proteina already measures this, but only at the level of mean helix and strand content, which is blind to a model that matches the average composition while collapsing its spread. In contrast, ssJSD-2D is a Jensen–Shannon divergence over the full joint (helix-fraction, strand-fraction) distribution against the reference, so it rewards reproducing the whole spread of secondary-structure content, not just its centre. The per-residue helix, strand, and coil labels come from the P-SEA algorithm [67], run on $C\alpha$ coordinates alone, as implemented in Biotite [68] (Appendix A.8).

A two-axis taxonomy. We propose reading all these metrics through a framework that organises them by structural and distributional relevance. Two axes do the work: *tertiary* versus *secondary* structure, and the *whole set* versus the *designable subset*. The result is a grid of metric groups, which the result tables in Chapter 6 lay out as super-columns. *Tertiary-whole* (*T-W*) asks whether the distribution of global folds matches a reference over all backbones; its flagship is FPSD, alongside fJSD (a Jensen–Shannon divergence between the generated and reference fold-class distributions) and a fold-spread score (fS) [14]. Both fJSD and fS are defined at each level of the CATH hierarchy (§2.4.2); we headline on the architecture level (fJSD-A, fS-A). *Tertiary-designable* (*T-D*) asks the same diversity question, but only of backbones that pass designability. Its canonical measure in the protein-backbone literature is the cluster count, the number of distinct structural clusters the designable set falls into [14]. That count is sensitive to the number of designable backbones, however, which varies across our models — a model that simply passes more backbones forms more clusters without being any more diverse. We therefore use the pairwise TM-score (pwTM) throughout instead. As a pairwise average, pwTM stays robust at the small sizes of the designable subset, where a distributional measure like fS is unreliable. *Secondary-whole* (*S-W*) and *secondary-designable* (*S-D*) apply ssJSD-2D over the same two populations.

A caveat on noise. We also note that generative metrics are noisy, so a gap between two point estimates is not necessarily a finding. We report bootstrap intervals and seed sweeps where possible to guard against this.

3.6 The designability–diversity trade-off

A central dynamic in protein generation pits the designability number against the diversity of the designable subset (T-D). A model can trivially raise its designability number by collapsing onto a few reliable, highly foldable modes, but this shrinks the diversity of that

designable subset, and vice versa. This dynamic is noted regularly in the literature [14], and is typically modulated by a choice of sampler noise.

Ultimately, how does this trade-off help us compare models? In our studies, we distinguish between two phenomena. The first is whether a model merely occupies a different spot on the same envelope, in which case the optimal choice is use-case specific. The second is whether a model pushes the envelope itself — playing the same trade-off game, but at a higher level, winning on one axis without conceding the other. This makes a model canonically better.

These complex dynamics further motivate the question: *what makes an encoder a good teacher of representational information in this domain?* We examine this question in Chapter 4, which informs the experiments we present in Chapters 5 and 6.

Chapter 4

Encoder targets and profiling

What properties make an encoder a good target for representation alignment? This question is unsettled in the image domain, with global semantic quality and local spatial structure both proposed as the driver (§2.2.1).

In this chapter, we ask this question in the molecular domain. Earlier, we discussed how molecular representation is multi-factorial and multi-scale (§3.2), which means that no single pre-trained encoder is likely to capture all of it. An encoder is typically optimised for one task in isolation, and sees a molecule through that lens — local geometry, global shape, or chemical identity. The encoder we align to therefore selects which factor REPA is most likely to transfer.

Our profiling work in this chapter makes this concrete. We build a suite of diagnostics to assess what information an encoder contains, how much of it is relevant to the generative task, and how well conditioned its embeddings are. We use this to profile seven candidate encoders across small molecules and proteins, and then use the results to guide which encoders to align with in the studies of Chapters 5 and 6.

4.1 A profiling protocol

We profile every candidate encoder with the protocol summarised in Table 4.1. Each encoder is run frozen on a sample of structures from our training sets: 200–2,000 molecules (QM9 and GEOM) for the small molecule encoders, and 200 proteins (PDB) for the protein encoders. This yields one embedding vector per atom or residue — tens of thousands of vectors in each case — and every diagnostic is computed from these per-token embeddings.

We ask three things of each encoder, and a good target needs all three.

Information asks: *what does the encoder contain?* This estimates the upper bound on what REPA can add to a model. Alignment cannot teach anything the encoder does not itself hold. For a 3D generator, the axis that matters most is 3D geometry. We measure geometry-awareness by how far the embedding moves under a change in 3D

Diagnostic	What it captures	How we compute it
Information	<i>what the encoder encodes — an upper bound on REPA’s transfer</i>	
3D geometry	sensitivity to 3D pose	cosine self-similarity across conformers (molecules) or after a 1 Å coordinate perturbation (proteins)
Token identity	atom or residue type (high = a lookup the molecular generator already has; off-task for the protein generator, which is not given residue identity)	linear-probe accuracy
Relevance	<i>what the generator can match without improving its representation</i>	
Saturation	the embeddings barely vary, so a constant prediction already matches them	a high <i>floor</i> : the average cosine similarity of each token embedding to the dataset mean
Cheatability	the variation that exists is content the generator is already fed (for molecules; for proteins this identity variation is read as off-task, not cheatable)	a high <i>lift</i> from identity alone: the rise a REPA-form 3-layer MLP gains from a one-hot of the atom or residue type (cosine-similarity loss, 80/20 split)
Off-task risk	the remaining variation is some factor the generator does not need, rather than the 3D geometry it does	a low floor and low lift, read against the 3D-awareness probe
Conditioning	<i>whether the embedding is well-formed</i>	
Effective rank	dimensions actually used	RankMe [33] (Roy–Vetterli effective rank)
Sparsity, dead dims	inactive dimensions	fraction of exact zeros; permanently inactive dimensions
Norm scale	numerical conditioning	mean embedding ℓ_2 norm

Table 4.1: The profiling diagnostics, grouped by the three properties: information, relevance, and conditioning.

pose: across distinct conformers of the same molecule for the molecular encoders, and after a 1 Å coordinate perturbation for the protein encoders, where only a single structure is available. We also report token identity, since a high score there suggests that an encoder is performing an identity lookup that the generator may already be capable of.

Relevance asks: *how much of a REPA target can the generator match without improving the representation it is trying to learn?* A generator does not need to learn all the information contained in an encoder. Indeed, during training, it is fed most of the relevant *content* of the molecule directly: the normalised token index always, and, for molecules, a one-hot of the atom type (the protein generator is given position but not residue identity;

see §4.3). What it must acquire is the 3D *geometry*, which it sees only as noisy coordinates it is being trained to denoise. Hence, a REPA target is relevant only insofar as matching it forces the generator to improve that geometric representation.

A target can fail this in two ways:

- *cheatable*: the target is trivially reconstructible from inputs the generator already holds. So the model can saturate alignment loss without actually learning a better representation.
- *off-task*: matching the target does require representation learning, but what it requires is not what we need. For example, since the protein generator is not given residue identity, matching an identity-encoding target would force it to infer sequence from backbone. This is a genuine learning problem, but a different one from generating geometry, so the pressure may not assist the task we care about.

We estimate the cheatable fraction directly. We fit a three-layer MLP, the same projector that REPA uses (§2.2), to reconstruct embeddings from cheap features that withhold all 3D geometry: first *identity* alone (a one-hot of the atom or residue type), then *identity+position* (Table 4.1). Separately, with no projector fit, we also score the *constant* dataset mean, which is the optimal input-free prediction. We read this constant baseline as the *floor*, and the rise of the fitted rungs above it as the *lift*.

Read together, the floor and lift sort an encoder into one of three configurations:

- high floor suggests *saturation*. The embeddings barely vary, so a constant prediction already matches them. There is little signal to align to.
- low floor, high lift suggests *cheatable*. The embeddings vary, but the cheap inputs reconstruct that variation, so it is largely an identity lookup using data the generator is already fed.
- low floor, low lift is *promising*. However, a low lift only says the variation does not stem from the cheap identity we tested. It does not positively affirm that it comes from the geometry a generator needs. We interpret this against the information probes to tell a geometric encoder from one varying for some *off-task* reason.

Conditioning asks: *is the embedding mathematically well-formed enough to be a target?* For example, an embedding whose variance has collapsed onto a few directions (a low effective rank), or that is mostly zero, is a bottleneck. Too little structure passes through for the alignment to transmit anything, no matter the information or the relevance.

We apply this protocol to molecule encoders first (§4.2), then protein encoders (§4.3), and draw together what it implies in §4.4.

Encoder	Dim	token-ID	3D	Floor	Lift	Sparsity	Verdict
CheMeleon (2D graph)	2048	1.00	1.00	0.43	+0.04	93.8%	too sparse
MACE (3D potential)	192	1.00	0.998	0.86	+0.005	0%	saturated

Table 4.2: Molecule encoder profiles. Neither encoder shows promise. *token-ID*: atom-type linear-probe accuracy (trivially 1.00 for both; uninformative). *3D*: cosine self-similarity across conformers (lower = more 3D-sensitive). *Floor*: constant-prediction cosine (high = saturated). *Lift*: the rise a same-form MLP gains above the floor from cheap inputs. *Sparsity*: fraction of exact zeros.

Encoder	Dim	AA-probe	3D	Floor	Lift	RankMe	Verdict
GearNet	512	0.137	0.27	0.43	+0.009	256	usable
random-init	512	0.127	1.00	0.95	+0.003	100	saturated
ProteinMPNN	128	0.327	0.73	0.84	+0.014	85	weak but usable
ESM2-650M (L33)	1280	0.998	N/A	0.67	+0.053	1031	off-task [†]
PW-GearNet	3072	0.928	0.86	0.71	+0.013	208	poorly conditioned
MC-GearNet-Edge	3072	0.146	0.77	0.86	+0.002	12	collapsed

Table 4.3: Protein encoder profiles. GearNet and ProteinMPNN show promise. *AA-probe*: residue-identity linear-probe accuracy (high = an identity lookup the generator already has). *3D*: cosine self-similarity after a 1 Å perturbation (lower = more 3D-sensitive; N/A for sequence-only ESM2). *Floor*: constant-prediction cosine (high = saturated). *Lift*: the rise a same-form MLP gains above the floor from cheap inputs. *RankMe*: Roy–Vetterli effective rank out of *Dim* [33]. [†]ESM2’s lift is the largest here but is sequence context, not 3D: off-task.

4.2 Small molecule encoders

We profile two publicly available pre-trained encoders, summarised in Table 4.2 (full values in Appendix A.12). They bracket a useful contrast. One sees the 2D bonding graph, the other sees 3D geometry. Neither, the framework finds, is a clean alignment target.

CheMeleon [32] is a directed message-passing network (a ChemProp D-MPNN) that passes messages along the bonds of the 2D molecular graph; it never sees coordinates. Its embeddings are well spread (a low floor), but it fails on two other counts. First, it is 93.8% sparse, so alignment runs over a shifting, ill-conditioned subspace. Second, it is conformer-invariant by construction, so its lift is 2D bond-graph context, which may not aid a 3D generator.

MACE [30] is an equivariant message-passing network built on many-body atomic interactions, pretrained as an interatomic potential to predict energies from 3D structure. The model’s embeddings are mathematically well-formed. However, its energy pretraining captures local environments over global pose, so its 3D signal is weak, and a high floor of 0.86 suggests it is mean-saturated.

4.3 Protein backbone encoders

Proteins offer a wider choice of pre-trained encoders. We profile five candidates plus a random-initialised reference, summarised in Table 4.3 (full values in Appendix A.12).

GearNet [26], our lead candidate, is a message-passing network. It passes messages over a residue graph wired by spatial and sequential proximity. The checkpoint we profile is pre-trained for CATH fold classification and released with Proteina [14]. It is genuinely 3D-aware (a 1 Å perturbation drops the cosine self-similarity to 0.27) and barely a residue-identity lookup (AA-probe 0.137). The embeddings are spread, and the remaining headroom is likely geometric. The random-init row suggests that the architecture alone gives a near-constant, low-rank embedding, and the training significantly improves on this.

ESM2 [24] offers an instructive contrast, as a transformer-based protein language model trained by masked-residue prediction over sequence alone. It produces the largest lift in the field, yet that lift is sequence context. It ignores coordinates by construction, and its last layer flattens almost entirely to residue identity (AA-probe 0.998 against GearNet’s 0.137). This information is real but likely unhelpful to a backbone generator.

ProteinMPNN [25] is a message-passing network over a nearest-neighbour backbone graph, pretrained for inverse folding (predicting sequence from structure). It has the cleanest conditioning of any 3D-aware encoder we profile, but its geometric signal is significantly weaker than GearNet’s (a 1 Å perturbation leaves the cosine self-similarity at 0.73, against 0.27), and it has a relatively high floor. We characterise this encoder as weak but usable: its 3D signal is faint, but clean and genuinely geometric.

The remaining two are GearNet-Edge variants. PW-GearNet [26, 27], pretrained on backbone torsions, is only weakly 3D-sensitive and poorly conditioned: its effective rank uses just 208 of 3072 dimensions. MC-GearNet-Edge [26] is collapsed entirely, with 95% of its variance in a single dimension.

Of the five candidates, only GearNet clears all three diagnostics, with ProteinMPNN also showing promise. Each of the others fails a different gate.

4.4 Informing our experiments

Our profiles are measured before any alignment training, so the expectations they set are a-priori, not post-hoc rationalisations. We use them to guide which encoders our studies will showcase. For small molecules (Chapter 5), we expect no measurable REPA gain. For protein backbones (Chapter 6), we expect that GearNet and ProteinMPNN are most likely to help. The following two chapters put these ideas to the test.

Chapter 5

REPA on small molecules

Having profiled candidate encoders for their suitability as a representation alignment (REPA) target in Chapter 4, we now put that analysis to the test, beginning with small molecules. We ask: *can REPA accelerate or improve the training of Tabasco [15], a flow-matching transformer-based generator of 3D drug-like small molecules?*

Our headline finding is that no REPA variant measurably improves, or accelerates the training of, Tabasco’s small-molecule generation. On structural-quality metrics, the baseline is already at ceiling. On FCD, the one metric with headroom, the REPA variants perform no better than baseline. Nor do they reach any level of quality faster: the baseline leads from the beginning of training. We explore *why* in §5.3, where two properties of this regime — a saturated evaluation surface and the absence of a usable teacher — emerge as an explanation and seed the contrast with proteins (Chapter 6).

5.1 Experimental setup

5.1.1 Dataset

We train on GEOM-drugs [39], a dataset of drug-like molecular conformers at the sub-900-Dalton scale. It holds roughly 1.4M molecules, split $\sim 80/10/10$ into 1,142,099 training, 146,411 validation, and 146,798 test molecules. We model heavy atoms only, and augment each sample with eight random rotations. Each molecule is represented as a small point cloud of typed atoms, typically fewer than fifty, as outlined earlier (§2.4.1).

5.1.2 Models

The baseline is the unmodified Tabasco flow-matching transformer (§2.4.1): a 3.7M-parameter non-equivariant model that denoises 3D atom coordinates and atom types jointly. Our REPA variants add a trainable projector that aligns the trunk’s hidden states to a frozen encoder, evaluated on the clean ($t=1$) molecule (§2.2; Figure 5.1). The trunk carries two hidden-state streams, one for coordinates and one for atom types. We concatenate them and pass the pair through a single shared projector, so the alignment




Figure 5.1: The Tabasco REPA setup. The trunk is trained with flow matching ($\mathcal{L}_{\text{FM}}$, a mean-squared error on the velocity); its layer- ℓ hidden state is projected and aligned by cosine similarity to one frozen encoder per run, giving the REPA loss $\mathcal{L}_{\text{REPA}}$. The two combine into the training objective. Neither encoder transfers to generation.

acts on one combined representation. It enters the loss as a plain additive regulariser, leaving the flow-matching objective untouched.

Encoder ablations. The two encoders we study come from the profiling of Chapter 4, and span a useful contrast. *CheMeleon* [32] is a 2D molecular-graph encoder. It is conformer-invariant, so it sees only the bonding graph and not the 3D pose. Meanwhile, *MACE* [30, 31] is a 3D interatomic-potential encoder. It is geometry-aware, but, as the profiling showed, its output is a narrow descriptor of local atomic environments. Hence, the former carries rich 2D-graph information, while the latter encodes 3D geometry.

5.1.3 Metrics

Representation quality. We use the small-molecule probe battery of Chapter 3 (Table 3.1): a linear ridge regression from mean-pooled per-atom features to four RDKit descriptors [62], scored by held-out R^2 . We apply it to both the frozen encoders, to see what each REPA target carries on its own, and the generator trunk, to see what the model itself comes to encode, and rely on it in the diagnosis of §5.3.

The probe set comprises 1,000 molecules from the GEOM-drugs validation split. We fit the regression on 800 of these and report R^2 on the held-out 200.

Generation quality. We report the standard small-molecule generation metrics of Chapter 3 (Table 3.1): validity, connectivity, and uniqueness (structural quality); diversity and novelty (set coverage); and the Fréchet ChemNet Distance (FCD), the one distributional axis with headroom.

Property	Value
<i>Base architecture</i>	
Backbone (<i>trunk</i>)	Tabasco: 3.7M-param, 16-layer non-equivariant transformer (hidden dim 128, 8 heads, SiLU, cross-attention)
Inputs (what the trunk sees)	per-atom token index + atom-type one-hot + noisy 3D coordinates
<i>REPA alignment</i>	
Encoder targets	CheMeleon (2D, 2048-d) · MACE (3D, 192-d)
Injection depth ℓ	final (last) layer
Combination mode	additive $\mathcal{L}_{\text{gen}} + \lambda \mathcal{L}_{\text{REPA}}$ (default) · tradeoff (convex) $(1 - \lambda) \mathcal{L}_{\text{gen}} + \lambda \mathcal{L}_{\text{REPA}}$
Projector	single shared 3-layer MLP
Similarity metric sim	cosine similarity
Averaging mode	per atom
Alignment weight λ	0.8
<i>Training & sampling</i>	
Learning rate	2×10^{-3}
Batch size	256
Weight decay	none
EMA decay	0.999
Sampler	SDE (Langevin) interpolant, 100 integration steps
Prior noise scale	1.0 (unit Gaussian)
Langevin schedule	$1/(t+0.01)$, disabled for $t \geq 0.9$
White-noise scale	0.01

Table 5.1: Model and training configuration. This chapter presents two encoder targets; the tradeoff combination mode is examined in §5.3.

We compute every metric on a set of 1,000 molecules sampled from the trained model using the SDE interpolant described in Table 5.1. We mimic the molecular-size distribution of GEOM-drugs in this set, and use the training set as the reference for our FCD metric.

5.2 Results: no measurable gain

No REPA variant meaningfully improves on the baseline. As outlined in Table 5.2, the baseline pushes validity, connectivity, and uniqueness to their ceiling, and the REPA variants follow suit (Figure 5.2). This is perhaps to be expected, since these are largely properties of bond topology, which a strong generator reproduces almost perfectly. Essentially, there is no headroom on these metrics for improvement.

On FCD, the one metric with room to move, both tested variants are worse. The baseline records the lowest (best) FCD at 5.61; CheMeleon lands at 7.43 and MACE at 6.81 (Table 5.2). We caveat this by noting that each variant is a single run, not a multi-seed average, and we do not have per-set FCD intervals to bound the gaps. Nevertheless, both point estimates strongly favour the baseline.

There is no acceleration in generation quality. REPA’s headline result in the




Figure 5.2: Representative molecules generated by Tabasco’s baseline and two REPA variants (CheMeleon, MACE). All are valid, connected, and drug-like, illustrating the saturated structural-quality surface that leaves REPA no headroom (§5.3).

Model	Steps	Valid.	Conn.	Uniq.	Div.	Nov.	FCD ↓
Baseline	151k	0.980	0.998	1.000	0.886	0.966	5.61
REPA-CheMeleon	73k	0.972	0.999	1.000	0.882	0.961	7.43
REPA-MACE	69k	1.000	0.995	0.996	0.884	0.977	6.81
REPA-MACE (tradeoff)	69k	1.000	0.999	1.000	0.883	0.982	6.32

Table 5.2: **REPA brings no measurable generation quality gain over the baseline.** The quality metrics are saturated, sitting at or near their ceiling for baseline and variants alike. On FCD, the only metric with headroom, every REPA run is worse. The MACE *tradeoff* row replaces the additive REPA loss with a convex one (§5.3). (1,000 sampled molecules; higher-is-better except FCD (↓). *Steps* is the training step at evaluation; the baseline trained $\sim 2\times$ longer, but metrics plateau early, so this is fair (§5.2); $n=1$ seed, one run per variant.)

image domain is a training speed-up: the same generation quality reached in far fewer steps (§2.2) [5]. No such speed-up appears here. On every axis, the REPA variants and the baseline are indistinguishable from the first few thousand steps (Figure 5.3).

The unequal training does not make this comparison unfair. The baseline trained roughly twice as long as the REPA variants ($\sim 152k$ steps over 33 epochs, versus $\sim 69\text{--}73k$ for the two REPA runs) for our final point estimates. We stopped the REPA runs early on purpose. With the quality metrics saturated and FCD flat or worse, there was no evidence that further training would change the verdict. Nor did shorter runs cost the variants anything on the saturated axes, which always plateau within the first few thousand steps.




Figure 5.3: **REPA does not accelerate generation quality over the baseline.** Generation quality on GEOM-drugs (100 molecules sampled per epoch during training), plotted over training step across the range all three runs reach. The baseline and both REPA variants track together and reach near-ceiling on every axis within the first few thousand steps, leaving no headroom for alignment to fill. The metric is the in-training estimate, so values differ slightly from the final-checkpoint evaluation of Table 5.2. ($n=1$ seed, one run per variant.)

5.3 Discussion

The null result suggests this regime offers neither headroom nor usable teachers. Under the original hypothesis, REPA [5] alleviates a representation bottleneck and therefore accelerates improvements on generation quality. However, this needs two conditions. First, there must be *headroom*: a gap in what the generator represents or produces, for the alignment to fill. Second, there must be a *usable teacher*: an encoder that encodes representational information that differs from what the trunk already has and transfers to the generative task. In this regime, neither condition holds.

The first condition fails on the metric surface. The generation quality axes are saturated, as §5.2 showed. The representation side is saturated too — the trunk already encodes what our descriptors capture — so this regime happens to be closed on both.

The second condition fails on both encoders, for opposite reasons. From our linear probes in Table 5.3, we learn that CheMeleon decodes the descriptors almost perfectly in isolation (R^2 up to 0.99). But the baseline trunk *already decodes them well* (0.64–0.92), because they are 2D-graph quantities and the trunk sees the graph. CheMeleon’s signal therefore overlaps with what the model already has. Moreover, FCD ultimately scores the inferred 2D graph — the very information the trunk already holds — so even on the one metric with headroom, CheMeleon adds nothing new.

MACE presents the contrary problem. It is genuinely 3D, but it encodes only a narrow, energy-tuned slice of *local* atomic chemistry. The global descriptors we probe sit outside that slice, so they are largely undecodable from its mean-pooled embedding (R^2 near zero, save a weak 0.31 on LogP). Its signal differs from the trunk’s, but does not transfer. To calibrate the scale, note that an untrained random-weight encoder (Dummy) already decodes molecular weight at $R^2 = 0.82$, simply because weight tracks atom count. MACE

Source	MolWt	LogP	#Rings	#RotBonds
<i>Frozen encoders (the REPA targets in isolation)</i>				
CheMeleon (2D)	0.993	0.988	0.995	0.989
MACE (3D)	0.022	0.307	0.081	-0.014
Dummy	0.822	0.160	0.432	0.345
<i>Generator trunk (the model’s internal representation)</i>				
Baseline	0.920	0.713	0.742	0.636
REPA-CheMeleon	0.943	0.669	0.736	0.606
REPA-MACE	0.935	0.703	0.704	0.582
REPA-MACE (tradeoff)	0.955	0.730	0.732	0.666

Table 5.3: **Linear-probe R^2 reveals little representational difference between REPA and the baseline.** The baseline trunk already captures what CheMeleon learns, while MACE’s embedding is too narrow to decode these descriptors. Hence, neither makes for a usable REPA target. (R^2 for four RDKit descriptors, on held-out molecules; §5.1.3; $n=1$ seed.)

falls below even this floor on three of the four descriptors.

Forcing the signal in does not rescue it either. As a final test, we replaced the additive regulariser with a convex *trade-off* loss, $(1 - \lambda) \cdot \mathcal{L}_{\text{gen}} + \lambda \cdot \mathcal{L}_{\text{REPA}}$. This deliberately down-weights the flow-matching loss to force the model to adopt the encoder’s representation. Even so, the effect on generation is negligible. MACE under the trade-off loss still trails the baseline on FCD (6.32 versus 5.61; Table 5.2). Its only mark is on the representation, where it is the only variant to beat the baseline on a majority of the descriptor probes (Table 5.3), but only by a small margin. Even when forced into the architecture, MACE leaves only a tiny trace in representation, and nothing in generation.

When is REPA actually useful? Our results sharpen the question on REPA’s effectiveness rather than settling it. Under our setup, REPA does not help because the regime offers neither headroom nor a usable teacher. This is not evidence that REPA cannot help with molecular generation in principle. Indeed, we do not claim to have exhausted the REPA design space, and there may be other configurations that work well. But it does suggest the question has no single answer. Molecular generation is a broad domain of distinct regimes, and whether REPA helps may be decided within each, not across the whole. Read that way, REPA is not a single intervention, but a family of them.

Practically, we must look for a regime within the domain that satisfies these two conditions. Protein backbone generation presents an intriguing possibility on both fronts, and that is where we turn next.

Chapter 6

REPA on protein backbones

In this chapter, we expand the scope of our study on representation alignment from small molecules to much larger ones: proteins. In Chapter 5, our efforts using REPA to generate small molecules yielded little demonstrable improvement, because the Tabasco [15] baseline already saturated most measures of generation quality, and because the encoders used were likely unhelpful. However, de-novo backbone design represents a more challenging task, as the data distribution of proteins is significantly larger, and the geometry of these structures is correspondingly more complex. In this context, we ask: *can REPA accelerate or improve the training of Proteina [14], a flow-matching transformer-based protein backbone generator?*

Our headline finding is that REPA accelerates convergence on the two key measures of protein generation quality. This holds across both experimental and synthetic training-data regimes (Figure 6.1). The one exception is designability on synthetic data, which the baseline already saturates under standard sampling (§6.1.1). This chapter characterises *what* happens and attempts to understand *why*. We note that our objective here is to test whether the mechanism transfers at all, not to search for the optimal REPA configuration.

A caveat on unequal training and evaluation. Given resource constraints, not every variant was trained for the same number of steps, or evaluated with the same number of seeds. We prioritised training and evaluating promising candidates. We flag where this shapes a comparison and read trends rather than single points.

Reading figures and tables in this chapter. Unless otherwise specified, figures plot data from the PDB-trained $n \leq 256$ data-regime (§6.1.1) using 3 seeds; trajectories show the cross-seed mean, with shaded bands giving the min/max range. Every artefact notes its seed count in a trailing parenthetical. In tables, the baseline is usually an absolute value and each REPA row a Δ from it; **green** marks a change in the metric’s good direction and **red** a change against it; **darker green** signals the best entry in a column; small $|\Delta|$ are left uncoloured.




Figure 6.1: **REPA accelerates convergence on FPsD in both experimental and synthetic regimes, and designability in the former.** The strongest variant in each regime is shown, along with the random-encoder control. (Each point is a mean over 3 seeds, except a few single-seed checkpoints at the trajectory tails; 1,125 backbones/seed, 250 for designability.)

6.1 Experimental setup

We integrate REPA into Proteina [14], a 60M-parameter non-equivariant flow-matching generator of $\text{C}\alpha$ protein backbones (§2.4.2). Following §2.2, we attach a trainable projector at a chosen trunk layer, aligning the model’s hidden states to a frozen external encoder (Figure 6.2).

6.1.1 Datasets

We train in two data regimes that mirror the data-scarcity context motivating this report (Chapter 1). The Protein Data Bank (PDB) [37] is the high-quality experimental source, but it is relatively scarce, containing on the order of hundreds of thousands of structures. The AlphaFold Database (AFDB) [38] is the synthetic alternative containing hundreds of millions of AF2-predicted structures, but it is almost entirely unverified. We treat the datasets as two ends of a quality-scale axis. (We use the manually-curated Swiss-Prot subset of AFDB as a reproducible stand-in for the Foldseek-clustered TrEMBL subset on which Proteina was trained in the original presentation [14]. This corpus contained data that has since been pruned from AFDB, and is hence inaccessible.)




Figure 6.2: The Proteina REPA setup. The trunk is trained with flow matching ($\mathcal{L}_{\text{FM}}$, a mean-squared error on the velocity); its layer- ℓ hidden state ($\ell \in \{4, 9\}$) is projected and aligned by cosine similarity to one frozen encoder per run, giving the REPA loss $\mathcal{L}_{\text{REPA}}$. The two combine into the training objective. Each encoder routes its gain to a different generation factor.

Following Proteina [14], we train on the subset of chains with at most 256 residues; we represent this length-regime by $n \leq 256$. (We note that this represents only a property of the training datasets, not a bound on the length of the proteins that models trained on these datasets can generate.) Following this filter, the two training sets are comparable in size (PDB: 273,771 / 3,190 / 323 train/val/test chains; AFDB: 229,670 / 4,521 / 235). Appendix A.1 contains further details on dataset composition. During training, we augment each backbone with a single random global rotation per sample.

Different datasets in this domain carry different biases. Trends in designability offer a clear example, as training on AFDB raises the in-silico-designability floor well above PDB at every setting we tested (§6.2.3). This is the designability-proxy lineage effect of Chapter 3: the test re-folds with models sharing AlphaFold2’s lineage, so AlphaFold-like backbones are plausibly re-folded most confidently. We also note that both datasets feature some amount of structural similarity across training and evaluation subsets. We attempt to control for this in our evaluation protocol, as noted in §6.1.4.

6.1.2 Models

The base Proteina model comprises a stack of ten transformer layers (zero-indexed) that feeds a flow matching objective. Our experiments add a REPA loss to this design, as outlined in Table 6.1.

Property	Value
<i>Base architecture</i>	
Backbone (<i>trunk</i>)	Proteina (CAFlow): 60M-param, 10-layer non-equivariant C α transformer (token dim 512, 8 heads)
Inputs (what the trunk sees)	per-residue token index + noisy C α coordinates (no residue identity)
<i>REPA alignment</i>	
Encoder targets	GearNet (512-d) $\cdot$ ProteinMPNN (128-d) $\cdot$ random-GearNet (control)
Injection depth ℓ	layer 4 (middle) $\cdot$ layer 9 (last)
Projector	3-layer MLP, hidden dim 512
Similarity metric sim	cosine similarity
Averaging mode	per residue
Alignment weight λ	0.5
<i>Training & sampling</i>	
Learning rate	10^{-3}
Batch size	24 ($n \leq 256$)
Weight decay	none
EMA decay	0.999
Sampler	SDE, noise scale $\gamma = 0.45$
Integration steps	400 (step size $dt = 0.0025$)
Self-conditioning	on
Diffusion schedule	$g_t = 1/t$, log-spaced time steps

Table 6.1: Model and training configuration. This chapter presents two encoder targets and two injection depths. Other ablations are deferred to Appendix A.

Encoder and injection-depth ablations. Our narrative concentrates on the two encoders identified as most viable in Chapter 4: *GearNet* [26], a structure encoder pre-trained for CATH fold classification (checkpoint released with Proteina [14]); and *ProteinMPNN* [25], which encodes each residue’s local inverse-folding environment. Each encoder is attached at two depths: layer 4 (middle) and layer 9 (last). The remaining encoder and depth combinations are collected in Appendix A.4. Figures presented in this chapter will typically feature the best performing model to serve as an illustrative example.

Separating regularisation from mechanism. A random-weights GearNet attached at layer 4, identical in architecture but never trained, serves as a control architecture in this chapter. We use this model to separate whatever REPA achieves merely due to the regularisation effect of adding an auxiliary loss from what it achieves through the encoder’s *learned* structural knowledge. Crucially, a trained encoder at the same layer 4 still outperforms the random one, so the learned-versus-random gap is not an artefact of injection depth (Appendix A.4).

6.1.3 Metrics

The original hypothesis that motivated REPA for imaging [5] was that alleviating a *representation* bottleneck would improve *generation* quality. We seek to understand if the same mechanism applies in the molecular domain as well. Hence, along with estimating the quality of a model’s generated samples, we are also interested in what the model comes to represent internally. To this end, we measure three families of metrics, as outlined below: representation quality, representation alignment, and generation quality (Table 3.2).

Representation quality. We use the three-task protein battery of Chapter 3 (inverse folding, dihedral error, CATH fold classification; Table 3.2). Because the three probes target largely orthogonal capabilities — local chemical environment, local geometry, and global fold — improving all of them at once is strong evidence of holistic representation quality. Among the CATH levels we headline on architecture (CATH-A): Class is too easy (top-1 saturates) and Topology too sparse (too many buckets, too few chains). We report all three for completeness, the patterns holding across them, and motivate the choice in Appendix A.2 (Table A.2).

Representation alignment. This measures how close the trunk sits to a structural encoder, via CKNNA (§3.3). As in the original REPA analysis [5] and a recent molecular extension [8], we use it as a diagnostic — a mechanistic lens on how REPA might produce its representation gains — rather than a quantity we optimise or build claims on.

Generation quality. This is what ultimately matters, and we report it through the two-axis taxonomy of Chapter 3 — tertiary/secondary structure crossed with whole set/designable subset — laid out as supercolumns in our result tables: Quality, T-W, T-D, S-W, and S-D (Table 3.2). We report two headline metrics: designability and FPSD. We use this taxonomy to analyse REPA’s effect on both the whole generated distribution and the designable subset.

Most of these metrics follow Proteina [14]; the one we add, ssJSD-2D, is defined in Chapter 3. As we explore in §6.2.4, REPA improves distribution match and whole-set diversity together, but may trade off tertiary-structure diversity within the designable subset.

6.1.4 Evaluation protocol

Representation probing. Following the probe principle of §3.3, we fit probes to a frozen checkpoint’s hidden states on clean inputs ($t=1$): the inverse-folding (IF) and dihedral probes per residue, the CATH probe per chain on mean-pooled representations. IF is a 20-way classification, while CATH-A is a ~ 40 -way one.

Each probe is fit on 1,000 training chains. We evaluate the per-residue probes (inverse folding and dihedral) on a *blinded* set of ~ 325 proteins (~ 43 k residues) held to under 30% sequence identity to all training data, which removes both model- and probe-side leakage. The per-chain CATH probe needs many distinct chains spread across fold classes, which that small slice cannot supply, so we relax it to a *probe-clean* evaluation on a larger

validation set of $\sim 3,190$ chains. We detail this scheme, and the model/probe leakage distinction it controls for, in Appendix A.3, and read rank-order and Δ -from-baseline throughout this chapter.

Representation alignment. In §3.3, we outlined how CKNNA scores how closely two representations share their nearest-neighbour structure. We compute it on clean ($t=1$) data from a fixed held-out batch, between the hidden states at every trunk layer and three domain-relevant encoders: GearNet, ProteinMPNN, and ESM2 [24]. We use $k=10$ neighbours over 10,000 residues, and bracket each value with a subsample-without-replacement bootstrap (50 draws at 80%; sampling with replacement would inflate the score through duplicate neighbour pairs). The absolute CKNNA values we record are small, an order of magnitude below image-domain REPA [5], so we read the direction and layer structure of the effect, and its separation from the baseline, not its raw magnitude.

Generation sampling. Our generation evaluation follows the Proteina protocol [14], at a reduced sample budget. We record further details on the protocol in §3.5.

For whole-set evaluations, we sample 1,125 backbones per checkpoint — 125 at each length in $\{50, 75, \dots, 250\}$ — and compute metrics over all of them. Depending on the training regime, we use matching PDB or AFDB reference statistics.

For designability evaluations, 50 backbones at each length $\{50, 100, 150, 200, 250\}$ are inverse-folded with ProteinMPNN (8 sequences each), re-folded with ESMFold, and called designable when the self-consistency RMSD is below 2 Å. The designable-subset metrics (T-D, S-D) are then computed on the backbones that pass.

With this experimental testbed in place, the rest of the chapter investigates what the REPA construction changes with respect to baseline, and how that helps improve generation quality. We now turn to the results.

6.2 Results

6.2.1 REPA improves representation quality asymptotically

At baseline, the flow-matching objective helps the model encode some useful representational information. Figure 6.3 shows the results of probing our models along the three orthogonal axes of §6.1.3: local chemical environment (inverse folding), local geometry (backbone dihedrals), and global fold (CATH classification, with CATH-A as our headline metric). The trained baseline consistently does better than both random features and an untrained Proteina trunk. This suggests that the flow-matching objective does indeed learn to *represent* protein backbones as it learns to *generate* them.

Every trained-encoder REPA variant improves representational capacity, consistently and durably. Each lifts all three probes substantially above the baseline, from the very beginning of training, and the difference persists. This is an asymptotic




Figure 6.3: **REPA lifts the trunk’s representation quality asymptotically.** REPA variants open a quality gap over baseline that never closes; the random control gains least, evidence of genuine transfer rather than regularisation. (L9-GearNet and L9-MPNN shown; 3 probe seeds; protocol in Appendix A.3.)

Variant	IF top-1 $\uparrow$	dihedral MAE ($^{\circ}$) $\downarrow$	CATH top-1 acc. $\uparrow$		
			C	A	T
Baseline	0.129	31.5	0.724	0.408	0.332
REPA L4-random	−0.010	+3.9	+0.049	+0.011	−0.005
REPA L9-GearNet	+0.023	−6.4	+0.153	+0.267	+0.415
REPA L9-MPNN	+0.026	−5.6	+0.081	+0.063	+0.106

Table 6.2: **REPA’s representation advantage is encoder-routed.** REPA-GearNet wins the fold probes (CATH C/A/T) decisively, while REPA-MPNN edges the per-residue probe (IF). The random control gains least and does not help IF, evidence of genuine structural transfer rather than regularisation. (Means over $n=3$ seeds at 1.0M; best-layer linear probe (protocol in Appendix A.3). Per-seed ranges and remaining variants in Appendix Table A.3.)

gap that the baseline never closes across 1.8M steps, not just a head start or an accelerated convergence pattern. This gap confirms one of the hypotheses posited in the original REPA presentation [5]: an alignment target during training can fill the representational headroom left by the flow-matching objective.

Every encoder routes representation gain differently. REPA-GearNet consistently wins the fold probes, while REPA-MPNN edges the per-residue inverse-folding probe (Table 6.2). This pattern follows what we would expect a-priori, given the tasks that each encoder has been specifically trained for. This ties into our emerging theme on the multi-factorial nature of representation learning in the molecular domain (Chapter 3). No single encoder captures every factor, so the choice of alignment target is also a choice over the representational factor a model designer wishes to emphasise. We establish this routing on PDB-trained models and report the AFDB results in Appendix A.5.

REPA offers a mechanistic effect beyond just regularisation. Our random-weights control improves on the baseline for the fold probes (CATH), but not for the per-residue ones. Where it helps, this may be because *any* regularisation generically improves repre-

sensation capacity, or because even an untrained message-passing network imposes some geometric priors that aid the trunk. However, the trained encoders consistently perform far better. This sharpens the case for a genuine mechanistic effect, as regularisation alone is not the whole story.

The random control behaves as we expected a saturated target would. In §4.3 we characterised the random-init encoder as saturated, based on its high-floor signature. This makes the alignment loss cheatable, in that the trunk can optimise the loss without learning anything useful (§4.1). Our results bear this out. The random encoder’s cosine similarity saturates higher than every trained model’s — ≈ 0.89 against ≈ 0.80 for a trained GearNet at the same layer 4 on PDB. Yet this near-perfect alignment buys the least representation quality of any variant, and no FPSD or designability gain (§6.2.3).

6.2.2 A diagnostic check on alignment

Following Yu et al. [5] and recent in-domain work [8], we investigate the mechanism that may be driving REPA’s representation quality gains by quantifying the representation alignment it induces. Using CKNNA [66], we score how closely our models’ per-residue geometry matches that of three domain-specific encoders: GearNet and ProteinMPNN, our two alignment targets in this chapter; and ESM2 [24], which we align to only in our ablations, not in the models presented here. We note that we study alignment only as a diagnostic, and not to make claims about REPA’s utility.

REPA lifts alignment above the random floor, albeit at low magnitude. The baseline sits at the random floor at every layer (CKNNA ≈ 0), while REPA separates from it cleanly, suggesting that its hidden states do move towards the encoder’s (Figure 6.4a). This serves as a minimal check that the construction changes model behaviour. However, the magnitude of this signal is small. Peak per-residue CKNNA (bootstrap median) is ≈ 0.02 – 0.05 , on a scale where self-alignment is 1. We therefore read the pattern, not its size, and stake no strong claim on these numbers.

Aligning to one encoder nudges the trunk towards others as well. Every REPA variant we tested raises alignment to all three encoders, including those it was not aligned to (full model $\times$ encoder matrix in Appendix A.6). A GearNet-aligned trunk, for example, also moves closer to ProteinMPNN and ESM2 [24] (Figure 6.4b), suggesting that REPA-induced alignment is not merely circular self-alignment. One possible explanation for this phenomenon is the *Platonic representation hypothesis* [66]. This idea suggests that models trained on related data converge toward a shared representation. In this framework, REPA may be nudging the trunk toward a common structural representation that several encoders approximate, rather than toward any single encoder.




Figure 6.4: **REPA aligns the trunk with domain encoders, including those it was not trained with.** (a) Each REPA variant lifts per-residue alignment to its own target encoder above the baseline floor. (b) REPA induces cross-encoder alignment: for example, a GearNet-aligned trunk also moves toward ProteinMPNN and ESM2. Absolute alignment is small throughout, so we read the pattern, not its magnitude. (Step 1M, $t=1.0$; per-residue CKNNA, $k=10$; lines are bootstrap medians, shaded bands the 5–95% subsample bootstrap interval; $n=1$ seed.)

6.2.3 In the short run, REPA accelerates generation quality in both experimental and synthetic data regimes

Here, we outline our headline results using the *Quality* metrics of our suite, FPSD and designability (as in Table 3.2). A deeper analysis of generation quality along tertiary- and secondary-structure decomposition follows in §6.2.4.

Every REPA variant gives generation quality an early head start. Table 6.3 shows how at 400K steps, every variant already leads the baseline on PDB designability, by +48% to +149%. Most variants also lead on FPSD in both regimes, with the best at +28%. AFDB designability is the lone exception, for the proxy reason given in §6.1.1.

For the strongest variant per dataset, this early acceleration holds across the whole sampler-noise axis. The lead is not an artefact of one inference recipe. Taking the strongest variant per dataset (Table 6.3), it reaches a higher level of *both* FPSD and designability than the baseline at almost every sampler setting (Table 6.4). The lone exception is the degenerate $\gamma=0$ regime, where heavy noise correction inflates both models’ divergence. This shows the acceleration is built into the learned model, not merely recovered at inference.

FPSD does not merely reward alignment to its own encoder. FPSD reads generated sets through a GearNet fold classifier (§3.5), which is one of the encoders we align to. A GearNet-aligned trunk might then gain on FPSD for free, pulled toward the metric’s feature space. This does not bear out. On PDB, the best FPSD belongs to an MPNN-aligned model, not a GearNet-aligned one (Table 6.6). The metric is rewarding a real distributional improvement, not self-alignment, which also lends credence to the GearNet-led FPSD wins we report on AFDB.

Variant (last ckpt)	Accel. @400K (vs base)	Long run (abs. best)
<i>PDB FPSD</i> ↓		
baseline (to 2.0M)	472 (@400K)	288 (@1.8M)
Random control (1.2M)	−7% (506)	346 (@1.1M)
L4-GearNet (1.0M)	+7% (440)	432 (@1.0M)
L9-GearNet (1.6M)	+28% (341)	319 (@700K)
L4-MPNN (1.6M)	−8% (512)	329 (@1.6M)
L9-MPNN (2.0M)	+13% (410)	297 (@1.6M)
<i>PDB designability</i> ↑		
baseline (to 2.0M)	0.26 (@400K)	0.67 (@1.6M)
Random control (1.2M)	+48% (0.39)	0.49 (@900K)
L4-GearNet (1.0M)	+98% (0.52)	0.70 (@700K)
L9-GearNet (1.6M)	+97% (0.52)	0.63 (@800K)
L4-MPNN (1.6M)	+124% (0.59)	0.71 (@1.6M)
L9-MPNN (2.0M)	+149% (0.66)	0.82 (@1.8M)
<i>AFDB FPSD</i> ↓		
baseline (to 1.5M)	431 (@400K)	386 (@1.3M)
Random control (500K)	+16% (361)	361 (@400K)
L4-GearNet (1.3M)	+24% (328)	282 (@1.2M)
L9-GearNet (1.0M)	+28% (313)	293 (@1.0M)
L4-MPNN (1.1M)	−10% (477)	416 (@1.0M)
L9-MPNN (1.5M)	+18% (352)	352 (@400K)
<i>AFDB designability</i> ↑		
baseline (to 1.5M)	0.75 (@400K)	0.75 (@400K)
Random control (500K)	+5% (0.79)	0.85 (@500K)
L4-GearNet (1.3M)	+4% (0.78)	0.78 (@400K)
L9-GearNet (1.0M)	−4% (0.72)	0.77 (@800K)
L4-MPNN (1.1M)	−9% (0.68)	0.69 (@700K)
L9-MPNN (1.5M)	−6% (0.71)	0.77 (@700K)

Table 6.3: **Most REPA variants accelerate generation quality over the baseline.** In some regimes they also win the long run. Acceleration is the %-delta vs the baseline at 400K (the anchor of Figure 6.5), with the absolute score in parentheses; the long run is each variant’s absolute best, with the baseline capped at the furthest trained variant per regime (2.0M PDB, 1.5M AFDB), coloured against the baseline-best row. ($n=1-3$ seeds, seed-mean; 1,125 backbones/seed, 250 for designability.)

This acceleration is consistent with the representation-bottleneck hypothesis. Yu et al. [5] hypothesise that a model’s representation quality and its generation quality are coupled, because it is learning both at once. In our PDB-trained models, this coupling is clear. Across checkpoints, representation and generation quality are positively correlated, and the strongest of these correlations survive controlling for training step (Table 6.5). The same coupling holds on AFDB-trained models, and in the same encoder-matched form (Appendix A.7). If the two move together, then securing good representations early should secure good generation early as well. REPA reaches an asymptotically higher representation quality almost as soon as training begins (§6.2.1, Figure 6.3), so this pattern is expected.

Metric (400K)	Sampler setting					
	ODE	$\gamma=0$	$\gamma=0.35$	$\gamma=0.45$	$\gamma=0.5$	$\gamma=1.0$
<i>PDB-trained — baseline vs. REPA L9-MPNN</i>						
FPSD $\downarrow$, base	420	881	508	472	488	730
FPSD $\downarrow$, REPA	344	1102	430	410	405	601
Des $\uparrow$, base	0.01	0.84	0.38	0.26	0.20	0.00
Des $\uparrow$, REPA	0.02	0.99	0.72	0.66	0.58	0.04
<i>AFDB-trained — baseline vs. REPA L4-GearNet</i>						
FPSD $\downarrow$, base	501	712	429	429	436	613
FPSD $\downarrow$, REPA	144	654	359	329	317	283
Des $\uparrow$, base	0.03	0.80	0.78	0.74	0.68	0.09
Des $\uparrow$, REPA	0.26	0.99	0.86	0.78	0.74	0.27

Table 6.4: **REPA’s early-training acceleration holds across the sampler-noise axis.** The representative REPA variant per dataset beats the baseline on both FPSD and designability at almost every γ ; the lone exception is PDB FPSD at the degenerate $\gamma=0$. (Absolute values at step 400K; $n=3$ seeds at $\gamma=0.45$ [2 for AFDB], else $n=1$; 1,125 backbones/seed, 250 for designability.)

Representation quality	FPSD		Designability	
	partial	raw	partial	raw
Inverse folding (top-1)	+0.33	+0.30	+0.76	+0.61
Dihedral MAE	+0.42	+0.13	+0.71	+0.36
CATH-A	+0.18	+0.18	+0.41	+0.35

Table 6.5: **Better trunk representations track better generation — strongly for designability, moderately for FPSD.** Partial Pearson correlation controlling for training step, with the raw value alongside; oriented so a positive value means better representation accompanies better generation. ($n=59$ checkpoints, one per variant and step, pooled over the baseline, REPA variants and random control; generation seed-averaged, probe read at one seed.)

REPA climbs the representation– generation envelope faster than the baseline.

On the representation–generation curve posited by the bottleneck hypothesis, the early representation gains place REPA variants further along than the baseline at matched compute (Figure 6.5, shown for the strongest PDB variant). Hence, it reaches a given level of generation quality at less training. We interpret REPA as simply traversing this curve faster, rather than finding a new shortcut.

This representation–generation link is encoder-matched, suggesting the effect is encoder-specific, not generic regularisation. Each encoder’s generation gain lands on the axis where its representations are strongest. GearNet, the better fold encoder (§6.2.1), gives the larger acceleration on distribution match; MPNN, the better local encoder, gives the larger acceleration in designability (Table 6.3). Such axis-matching would be unlikely under a generic auxiliary loss, but we do not claim proof of causality.




Figure 6.5: **At equal compute, our strongest variant achieves better representation and generation quality.** The dashed arrow marks the matched-compute comparison at step 400K. Against the baseline, the strongest PDB variant (REPA-L9-MPNN) has higher fold accuracy (CATH-A) and better generation: lower FPSD (a) and higher designability (b). (Markers $\approx$ 400K-spaced from 100K, with the 400K point bordered; generation 3 seeds (single-seed tail checkpoint), probe single-seed.)

6.2.4 In the long run, REPA gains are data-regime dependent

The short-run REPA-induced acceleration we observe in our headline metrics, FPSD and designability, is universal. Nearly every variant across both data regimes displays the same pattern (§6.2.3). The long run is more contingent. Deep into training, REPA’s gain becomes *data-regime dependent*, which highlights the experimental–synthetic distinction that motivates our report and our experimental design (Chapter 1, §6.1.1). The choice of alignment target matters too, but the encoder that helps is dictated by the regime rather than chosen independently of it.

Each data regime leaves a different gap, and REPA fills the one it is given. On synthetic (AFDB) data, designability comes readily, partly by construction (§6.1.1), while matching the fold distribution is the harder problem. On experimental (PDB) data the reverse holds, as the baseline already matches the distribution well, but leaves room on designability. Figure 6.1 depicts how REPA’s long-run advantage shows wherever the gap is: on distribution match for AFDB, on designability for PDB. We note that designability on AFDB gains as well, but the improvement is small relative to the FPSD gain.

On synthetic data, REPA learns a genuinely better model. Table 6.6 captures the state of our models after 1.3M training steps. At this snapshot, the strongest long-run AFDB variant (identified in Table 6.3, long-run column), REPA-L4-GearNet, beats the baseline on Quality and whole-set (T-W, S-W) metrics at once, *at no meaningful cost to designable-subset metrics* (T-D and S-D). This represents a true pushing of the designability–diversity envelope (§3.6). The 0.02 rise in designable pwTM is within the baseline’s own seed-to-seed scatter, while the designability quality gains clear it (Appendix A.11). This makes REPA-L4-GearNet the canonically better model under that

Variant (1.3M)	Quality		T-W		T-D	S-W	S-D	
	Des $\uparrow$	FPSD $\downarrow$	fJSD-A $\downarrow$	fS-A $\uparrow$	pwTM $\downarrow$	ssJSD2D $\downarrow$	ssJSD2D $\downarrow$	β -strand frac. $\uparrow$
<i>PDB-trained</i>								
Baseline	0.56	416	0.95	6.06	0.16	0.31	0.43	0.09
REPA L4-random (1.2M)	-0.32	+21	-0.37	-0.07	+0.03	-0.16	-0.06	+0.03
REPA L4-GearNet (1.0M)	-0.10	+17	-0.41	+1.29	+0.01	-0.16	-0.04	-0.01
REPA L9-GearNet	-0.07	-22	-0.26	+1.44	+0.12	-0.22	-0.22	+0.17
REPA L4-MPNN	+0.06	+73	-0.13	+0.44	+0.08	-0.14	-0.13	+0.10
REPA L9-MPNN	+0.22	-29	-0.10	+0.84	+0.12	-0.18	-0.21	+0.13
<i>AFDB-trained</i>								
Baseline	0.64	386	1.63	5.45	0.18	0.10	0.20	0.13
REPA L4-random (0.5M)	+0.21	-15	-0.07	-0.35	+0.01	+0.06	-0.01	+0.01
REPA L4-GearNet	+0.11	-71	-0.67	+2.14	+0.02	-0.06	-0.09	+0.03
REPA L9-GearNet (1.0M)	+0.08	-93	-0.50	+1.54	+0.07	-0.07	-0.14	+0.06
REPA L4-MPNN (1.1M)	+0.05	+72	+0.30	-0.48	+0.07	+0.01	-0.06	+0.01
REPA L9-MPNN	+0.12	+1	-0.09	-0.37	-0.00	+0.05	-0.04	-0.02

Table 6.6: **On AFDB, REPA lifts the whole-set distribution cleanly; on PDB, the whole-set gains come with a more concentrated designable subset.** We compare rows within a data regime block, not across them. FPSD uses the training dataset as its reference in each case. Each cell is a mean over generation seeds; the per-seed min-max range is in Appendix A.11 (Table A.9). (Rows tagged with a step, e.g. (1.0M), show that variant’s latest available checkpoint; $n=3$ seeds, except PDB L9-GearNet and AFDB L4-MPNN, $n=1$; 1,125 backbones/seed, 250 for designability.)

framework, not merely a different point on the same envelope. This is learned model behaviour, not a sampler artefact. The same pattern survives the deterministic ODE limit, which reads the velocity field with no injected noise (Appendix A.10). The random-weights control marks the boundary of a genuine gain. At just 0.5M steps, the least training of any variant, it posts the AFDB block’s best designability (+0.21). Yet it improves FPSD only marginally and regresses on fold similarity (fS-A). That designability bump reflects the auxiliary loss, not structural transfer.

On experimental data, REPA finds a different spot on the designability–diversity envelope. At the 1.3M snapshot, across variants, REPA delivers whole-set gains (T-W, S-W) while pushing the designable subset toward β -strand content (S-D; Figure 6.6; per-seed composition, including the opposite-direction AFDB-MPNN routing, in Appendix A.9). However, designable diversity (T-D) drops, as the model appears to collapse onto fewer distinct β -rich folds (Table 6.7). This β -driven dynamic of secondary-structure enhancement and loss of tertiary-structure diversity is far stronger on PDB. The performance of the strongest long-run variant, REPA-L9-MPNN (identified in Table 6.3, long-run column), makes the resultant trade-off clear. While REPA increases designability on PDB, it does so by losing diversity, instead of pushing the frontier out as with AFDB.

The optimal alignment target follows from the data regime. Alignment with ProteinMPNN lifts per-sample designability, while alignment with GearNet lifts the fold distribution (§6.2.3). PDB’s gap is in designability, so ProteinMPNN wins there, with REPA-L9-MPNN proving the best long-run PDB variant. AFDB’s gap is in distribution




Figure 6.6: **On experimental data, REPA enriches the designable set for β -strand folds.** Designable backbones at 1.3M steps on experimental (PDB) data, coloured by secondary structure: baseline (top), REPA-L9-MPNN (bottom). Both produce helical folds, but REPA additionally yields β -rich folds (gold) the baseline rarely does, raising the designable β -strand fraction (Table 6.6).

Designable pwTM↓ Variant	400K steps			1.3M steps		
	$\beta < 10$	10–25	$\beta \geq 25$	$\beta < 10$	10–25	$\beta \geq 25$
<i>PDB-trained</i>						
Baseline	0.16	0.15	0.21	0.15	0.23	0.13
REPA L9-MPNN	0.16	0.21	0.29	0.19	0.23	0.69
<i>AFDB-trained</i>						
Baseline	0.19	0.22	0.16	0.13	0.26	0.14
REPA L4-GearNet	0.16	0.26	0.17	0.22	0.26	0.20

Table 6.7: **On PDB, REPA concentrates the β -rich designable folds onto fewer modes; on AFDB it does not.** The effect is specific to the most β -rich bin ($\beta \geq 25$): PDB-L9-MPNN climbs from 0.29 (400K) to 0.69 (1.3M) while the baseline diversifies to 0.13. Lower- β bins and AFDB-L4-GearNet barely move. Designable-subset pairwise TM, lower = more diverse; columns bin by β -strand fraction (%). Cells pool the designable subset across all available seeds (2–3 per cell) and the five generation lengths. The $\beta \geq 25$ concentration at 1.3M rests on $n=188$ designable backbones for REPA-L9-MPNN against $n=20$ for the baseline, so the 0.69 is not a small-sample artifact.

match, so REPA-L4-GearNet proves stronger. For REPA in a multi-factorial and multi-scale domain like molecules, the data regime dictates which encoder pays off.

6.2.5 What we do not claim

Several tempting claims do not survive our data, and we flag them here.

- *No asymptotic generation quality win on experimental data.* REPA accelerates PDB convergence, but the lead is transient. The baseline matches REPA’s FPSD plateau by ~ 1.4 M steps and edges below it by 1.6M (§6.2.3). The durable advantage on distribution match is on synthetic (AFDB) data, where the baseline plateaus poorly.

- *Co-movement, not mediation.* Representation and generation quality move together. We do not claim one formally causes the other, but we note that the pattern is consistent with the representation bottleneck hypothesis (§6.2.3).
- *Unconditional generation only.* Every experiment here is unconditional: we specify a target length but never a fold class or other structural motif. We do not claim these dynamics carry over to the conditional setting (§2.1).
- *No claim of optimality.* We do not search the configuration space for the best setup of layer, weight, or encoder. With limited compute, variants were also trained to different horizons, so some late comparisons rest on fewer checkpoints than others; we flag these in the text. The question here is whether the mechanism works at all, not how to tune it for maximum gain (§6.1).
- *Pre-convergence regime.* All of our models are likely under-trained against a fully converged Proteina. However, our primary claim is about acceleration, and the early-training boost we observe is real (§6.2.3).

6.3 Discussion

We show that REPA accelerates Proteina’s convergence on generation quality, and suggest that this works through representation. Every trained encoder teaches the trunk to represent structural characteristics that the flow-matching loss never learns on its own. For each encoder, this representation gain is mirrored in the generation gain, on the axis where it is strongest. A random-weights control suggests that the mechanism is indeed genuine structural transfer, not the side effect of an auxiliary loss. Its alignment loss drops more than any trained encoder, yet this buys the least representation quality, and no meaningful generation gain (§6.2.1).

Unlike small molecules, protein backbone generation meets the conditions for REPA. Our small-molecule study set out two conditions for REPA to help (§5.3). There must be headroom, a gap in what the generator represents or produces for the alignment to fill. And there must be a usable teacher, an encoder whose signal differs from what the trunk already learns and transfers to the generative task. Small molecules met neither, and we observed a null result (Chapter 5). Proteins meet both. The null there and the success here are two sides of the same coin.

In molecular generation, REPA is a family of encoder-mediated interventions, not a single mechanism. There is no single best pre-trained encoder. Each buys a different representational factor, so the best choice is likely use-case specific — or, as in our case, data-regime specific (§6.2.4). The dataset establishes the bottleneck, and the encoder routed to that factor is the one that helps.

Geometric convergence between encoders need not make them interchangeable. The alignment signal we measure is small, so we raise this only as a talking point (§6.2.2). Nevertheless, we observe that aligning to one encoder nudged the trunk toward

the others too, which may read as a pull toward a shared structural representation, in the spirit of the Platonic representation hypothesis [66]. Yet the encoders are plainly not interchangeable. Each routes its gain to a different factor (§6.2.4). The two sit together if the encoders share a common core but differ in what they emphasise above it, and REPA transfers both.

One thread we leave open is whether alignment outlives its early purpose.

REPA appears to help most early, and its benefit may fade later in training. On PDB, two observations point this way: the distribution-match lead is transient, and the designable subset concentrates mid-training (§6.2.4). One reading is that the encoder is a fixed target, so once the trunk has taken what it offers, continued alignment keeps pulling it toward the encoder’s own, narrower distribution. A similar arc is reported in image diffusion, where one idea proposes to stop alignment early to preserve its early gains and mitigate its later downsides [13]. We see a superficially similar pattern in molecules, but we need more evidence to know whether the resemblance is real, and if this solution would help.

We carry these results, and the contrast with the small-molecule study of Chapter 5, into this report’s conclusion in Chapter 7.

Chapter 7

Conclusions

Our work is motivated by a tension in the field of molecular generation, as outlined in Chapter 1. Following a wider trend in machine learning, molecular generation has traded hard structural priors for architectural simplicity, and curated experimental data for synthetic scale. Both phenomena dilute the structural signal available to models during training, which exacerbates their representation bottleneck [5] and causes poor convergence behaviour. Representation alignment (REPA) is potentially one cheap way to provide models this signal and accelerate training. This report investigates two questions: does REPA work in the molecular domain, and when does it work at all?

In this concluding chapter, we collect threads from across our report to build answers. We also raise new questions and future work that follow from our report, and invite a larger discussion in this field.

7.1 Does REPA work in the molecular domain?

Our report documents two regimes, small molecules and protein backbones, and presents a different answer for each. On small molecules, no REPA variant left a measurable mark on Tabasco (Chapter 5). On protein backbones, REPA accelerated Proteina’s convergence on the two key measures of generation quality, likely by improving the representations learned by the model (Chapter 6).

What explains these divergent behaviours? At root, the two regimes represent completely different chemistry. A small drug-like molecule and a folded protein backbone are not the same kind of object, even if their in-silico parameterisations appear to squash these distinctions at first glance. That chemistry sets the combinatorial space a generator must cover: modest and topology-dominated for small molecules, vast and hierarchical for proteins. The former presents a more learnable target, so its generators mature sooner. Indeed, by the time we test REPA, the evaluation metrics for small-molecule generation sit at ceiling, and the baseline Tabasco model already learns the information contained in our external encoders. Protein generation, working in a far larger space, is far from this point, and therefore benefits from the intervention.

The protein-backbone result is ultimately a statement about training efficiency, and it pays off along two axes.

The first is *acceleration*: for a fixed compute budget, REPA reaches better generation quality in both the experimental (PDB) and synthetic (AFDB) regimes. Early in training, every variant already leads the baseline on designability, and most lead on distribution match (FPSD) in both regimes (§6.2.3). A cheap auxiliary signal buys faster convergence, which is highly valuable in a data-scarce, prior-light field.

The second axis is *asymptotics*: whether that early lead survives to convergence. Here the answer is not uniform, and it follows the data regime. The two regimes leave their headroom in different places. Synthetic (AFDB) data yields designability cheaply, but leaves the fold distribution hard to match. Experimental (PDB) data is the reverse, with a baseline that already matches the distribution but leaves room on designability (§6.2.4). REPA’s lasting gain lands wherever that gap is. On AFDB the distribution-match lead is permanent, because the baseline plateaus there. On PDB that same lead eventually closes, as the baseline catches up (§6.2.3).

Both axes point the same way as a data-efficiency story. REPA always buys a faster climb, and can offer a lasting advantage when the baseline struggles most. The field’s frontier — larger synthetic corpora, longer backbones, the all-atom setting — is where the generation problem is hardest and an unaided baseline has ground to make up. This may also be where REPA’s payoff is greatest, and where it should be tested next.

7.2 When does REPA work?

The discussion above already hints at our answer, which is that REPA works when two conditions hold together. The evaluation surface must leave *headroom* for a gain to register, and the encoder must be a *suitable teacher* — it must carry structural information the generator does not already learn cheaply.

In this framework, our small-molecules study showed little promise because generation and representation quality metrics were already saturated, and the trunk already learned everything our encoders carried. Indeed, the problem of generating structurally plausible small molecules in-silico appears largely solved. To set appropriate expectations about what this means, we note that structural plausibility is only one desideratum among the many a real design campaign cares about (§2.3), and it is arguably the most tractable of them. The properties that actually determine a molecule’s utility — how it binds a target, metabolises, or synthesises — are downstream of plausibility and far less settled. Moreover, all of this is measured in an in-silico sandbox that is itself a coarse stand-in for real chemistry. The saturated metrics do not suggest that we have mastered small-molecule generation, but that one tractable sub-problem of it looks solved under proxies that are far removed from the wet lab. But this suffices to leave REPA nothing to add.

Protein backbone generation presents a more challenging task, where both representation

and generation metrics are unsaturated, and determining teacher suitability remains difficult. In Chapter 3, we propose a new framework in which to interpret the vast array of relevant metrics, which are complex both in isolation and in their relationships with each other. We also frame the central dynamic that characterises a generator’s quality, the *designability–diversity* trade-off, and the distinction between merely moving along such an envelope and pushing it outward. In Chapter 4, we then propose a set of heuristics to estimate the utility of an encoder as a REPA teacher. We investigate the *information* content of a suite of pre-trained encoders, the *relevance* of that content to the generative task, and the mathematical *conditioning* of their embeddings, and use the most promising candidates in the studies that follow. We note that the approach we propose here is domain-agnostic. The questions we raise are purely statistical, and can be asked of any encoder in any domain with a few modifications.

However, the molecular domain presents unique challenges in how multi-factorial and multi-scale its representations are, especially in contrast to images (§3.2). In this light, our work also presents a new view on REPA: it is not a single mechanism, but rather a *family of interventions*. Every pre-trained encoder emphasises a different factor, so the choice of alignment target is also a choice over the structural factor one seeks to enhance.

7.3 Open questions

We close by looking ahead, and proposing new directions based on our work.

Does REPA work in other scientific domains? Our report opened by placing this work in the wider arc of generative machine learning for the sciences (Chapter 1). The same paradigm of prior-light models, sparse data, and multi-scale representation recurs across many scientific fields. For example, in fluid mechanics, diffusion models are learning to generate turbulent flow fields [22]. Alleviating the representation bottleneck could open the door for more efficient and performant models here, following our work with proteins.

Does our encoder profiling framework generalise? Singh et al. [6] ask the which-encoder question for vision, and answer it with structural metrics tied to the image grid. We attempt to generalise this analysis into a set of domain-agnostic heuristics. An open question is whether these are two views of a single, canonical characterisation of what makes a good alignment target. We propose retrospectively analysing published REPA work across domains, to see if the framework offers useful guidance.

We read our contribution not as a verdict that REPA accelerates protein backbone generation, but as a principled framework for assessing how to improve generative models for science more broadly. With that aspiration, we hope to raise more interesting research questions than we answer, and to push the evolution of this exciting space.

Bibliography

- [1] Jonathan Ho, Ajay Jain, Pieter Abbeel. *Denoising Diffusion Probabilistic Models*. NeurIPS 2020. arXiv:2006.11239.
- [2] Yaron Lipman, Ricky T. Q. Chen, Heli Ben-Hamu, Maximilian Nickel, Matt Le. *Flow Matching for Generative Modeling*. ICLR 2023. arXiv:2210.02747.
- [3] Peter Holderrieth and Ezra Erives. *An Introduction to Flow Matching and Diffusion Models*. MIT 6.S184 lecture notes, 2025. diffusion.csail.mit.edu.
- [4] Yaron Lipman, Marton Havasi, Peter Holderrieth, Neta Shaul, Matt Le, Brian Karrer, Ricky T. Q. Chen, David Lopez-Paz, Heli Ben-Hamu, Itai Gat. *Flow Matching Guide and Code*. 2024. arXiv:2412.06264.
- [5] Sihyun Yu, Sangkyung Kwak, Huiwon Jang, Jongheon Jeong, Jonathan Huang, Jinwoo Shin, Saining Xie. *Representation Alignment for Generation: Training Diffusion Transformers Is Easier Than You Think*. ICLR 2025. arXiv:2410.06940.
- [6] Jaskirat Singh, Xingjian Leng, Zongze Wu, Liang Zheng, Richard Zhang, Eli Shechtman, Saining Xie. *What matters for Representation Alignment: Global Information or Spatial Structure?* 2025. arXiv:2512.10794.
- [7] Chenyu Wang, Cai Zhou, Sharut Gupta, Zongyu Lin, Stefanie Jegelka, Stephen Bates, Tommi Jaakkola. *Learning Diffusion Models with Flexible Representation Guidance*. 2025. arXiv:2507.08980.
- [8] Hyosoon Jang, Hyunjin Seo, Yunhui Jang, Seonghyun Park, Sungsoo Ahn. *Boltz is a Strong Baseline for Atom-level Representation Learning*. 2026. arXiv:2602.13249.
- [9] Xiangdong Zhang, Jiaqi Liao, Shaofeng Zhang, Fanqing Meng, Xiangpeng Wan, Junchi Yan, Yu Cheng. *VideoREPA: Learning Physics for Video Generation through Relational Alignment with Foundation Models*. 2025. arXiv:2505.23656.
- [10] Tri Ton, Ji Woo Hong, Chang D. Yoo. *TARO: Timestep-Adaptive Representation Alignment with Onset-Aware Conditioning for Synchronized Video-to-Audio Synthesis*. ICCV 2025. arXiv:2504.05684.
- [11] Chengqian Zhang, Yucheng Jin, Duo Zhang, Tiejun Li, Han Wang. *CrystalREPA: Transferring Physical Priors from Universal MLIPs to Crystal Generative Models*. 2026. arXiv:2605.08960.

- [12] Runqian Wang and Kaiming He. *Diffuse and Disperse: Image Generation with Representation Regularization*. 2025. arXiv:2506.09027.
- [13] Ziqiao Wang, Wangbo Zhao, Yuhao Zhou, Zekai Li, Zhiyuan Liang, Mingjia Shi, Xuanlei Zhao, Pengfei Zhou, Kaipeng Zhang, Zhangyang Wang, Kai Wang, Yang You. *REPA Works Until It Doesn't: Early-Stopped, Holistic Alignment Supercharges Diffusion Training*. 2025. arXiv:2505.16792.
- [14] Tomas Geffner et al. *Proteina: Scaling Flow-based Protein Structure Generative Models*. ICLR 2025. arXiv:2503.00710.
- [15] C. Vonessen et al. *TABASCO: A Fast, Simplified Model for Molecular Generation with Improved Physical Quality*. 2025. arXiv:2507.00899.
- [16] Marcus Olivecrona, Thomas Blaschke, Ola Engkvist, Hongming Chen. "Molecular de-novo design through deep reinforcement learning". *Journal of Cheminformatics* 9:48 (2017). doi:10.1186/s13321-017-0235-x.
- [17] Alex Zhavoronkov et al. "Deep learning enables rapid identification of potent DDR1 kinase inhibitors". *Nature Biotechnology* 37 (2019), pp. 1038–1040. doi:10.1038/s41587-019-0224-x.
- [18] Joseph L. Watson et al. "de-novo design of protein structure and function with RFdiffusion". *Nature* 620 (2023), pp. 1089–1100. doi:10.1038/s41586-023-06415-8.
- [19] John B. Ingraham et al. "Illuminating protein space with a programmable generative model". *Nature* 623 (2023), pp. 1070–1078. doi:10.1038/s41586-023-06728-8.
- [20] Amil Merchant et al. "Scaling deep learning for materials discovery". *Nature* 624 (2023), pp. 80–85. doi:10.1038/s41586-023-06735-9.
- [21] Claudio Zeni et al. "A generative model for inorganic materials design". *Nature* 639 (2025), pp. 624–632. doi:10.1038/s41586-025-08628-5.
- [22] Tim Whittaker, Romuald A. Janik, Yaron Oz. "Turbulence scaling from deep learning diffusion generative models". *Journal of Computational Physics* 514 (2024), 113239. doi:10.1016/j.jcp.2024.113239.
- [23] Liang Wang, Chao Song, Zhiyuan Liu, Yu Rong, Qiang Liu, Shu Wu, Liang Wang. *Diffusion Models for Molecules: A Survey of Methods and Tasks*. 2025. arXiv:2502.09511.
- [24] Zemeng Lin et al. "Evolutionary-scale prediction of atomic-level protein structure with a language model". *Science* 379.6637 (2023), pp. 1123–1130. doi:10.1126/science.ade2574.
- [25] J. Dauparas et al. "Robust deep learning-based protein sequence design using ProteinMPNN". *Science* 378.6615 (2022), pp. 49–56. doi:10.1126/science.add2187.
- [26] Zuobai Zhang, Minghao Xu, Arian Jamasb, Vijil Chenthamarakshan, Aurelie Lozano, Payel Das, Jian Tang. *Protein Representation Learning by Geometric Structure Pre-training*. ICLR 2023. arXiv:2203.06125.

- [27] Arian R. Jamasb, Alex Morehead, Chaitanya K. Joshi, et al. *Evaluating Representation Learning on the Protein Structure Universe*. ICLR 2024.
- [28] John Ingraham, Vikas K. Garg, Regina Barzilay, Tommi Jaakkola. “Generative Models for Graph-Based Protein Design”. *Advances in Neural Information Processing Systems (NeurIPS)* 32 (2019).
- [29] Martin Steinegger, Johannes Söding. “MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets”. *Nature Biotechnology* 35.11 (2017), pp. 1026–1028. doi:10.1038/nbt.3988.
- [30] Ilyes Batatia, Dávid Péter Kovács, Gregor N. C. Simm, Christoph Ortner, Gábor Csányi. *MACE: Higher Order Equivariant Message Passing Neural Networks for Fast and Accurate Force Fields*. NeurIPS 2022. arXiv:2206.07697.
- [31] Dávid Péter Kovács et al. *MACE-OFF: Transferable Short Range Machine Learning Force Fields for Organic Molecules*. 2023. arXiv:2312.15211.
- [32] Jackson W. Burns et al. “Deep Learning Foundation Models from Classical Molecular Descriptors”. arXiv preprint (2025). arXiv:2506.15792.
- [33] Quentin Garrido, Randall Balestrieri, Laurent Najman, Yann LeCun. *RankMe: Assessing the Downstream Performance of Pretrained Self-Supervised Representations by Their Rank*. ICML 2023. arXiv:2210.02885.
- [34] Michael Heinzinger et al. “Bilingual language model for protein sequence and structure”. *NAR Genomics and Bioinformatics* 6.4 (2024), lqae150. doi:10.1093/nargab/lqae150.
- [35] Jin Su et al. “SaProt: Protein Language Modeling with Structure-aware Vocabulary”. *bioRxiv* (2023). Preprint. doi:10.1101/2023.10.01.560349.
- [36] Christoph Schuhmann et al. *LAION-5B: An open large-scale dataset for training next generation image-text models*. NeurIPS 2022 Datasets and Benchmarks. arXiv:2210.08402.
- [37] Helen M. Berman et al. “The Protein Data Bank”. *Nucleic Acids Research* 28.1 (2000), pp. 235–242. Statistics retrieved Nov 2025, rcsb.org/stats.
- [38] Mihaly Varadi et al. “AlphaFold Protein Structure Database in 2024: providing structure coverage for over 214 million protein sequences”. *Nucleic Acids Research* 52 (2024), D368–D375. doi:10.1093/nar/gkad1011.
- [39] Simon Axelrod and Rafael Gómez-Bombarelli. “GEOM, energy-annotated molecular conformations for property prediction and molecular generation”. *Scientific Data* 9, 185 (2022). doi:10.1038/s41597-022-01288-4.
- [40] Lorna Richardson et al. “MGnify: the microbiome sequence data analysis resource in 2023”. *Nucleic Acids Research* 51 (2023), D753–D759. doi:10.1093/nar/gkac1080. Release statistics retrieved May 2022 (2.4 billion non-redundant sequences): ebi.ac.uk.

- [41] Luciano Brocchieri and Samuel Karlin. “Protein length in eukaryotic and prokaryotic proteomes”. *Nucleic Acids Research* 33.10 (2005), pp. 3390–3400. doi:10.1093/nar/gki615.
- [42] Michael M. Bronstein, Joan Bruna, Taco Cohen, Petar Veličković. *Geometric Deep Learning: Grids, Groups, Graphs, Geodesics, and Gauges*. 2021. arXiv:2104.13478.
- [43] Alexandre Duval, Simon V. Mathis, Chaitanya K. Joshi, Victor Schmidt, Santiago Miret, Fragkiskos D. Malliaros, Taco Cohen, Pietro Liò, Yoshua Bengio, Michael Bronstein. *A Hitchhiker’s Guide to Geometric GNNs for 3D Atomic Systems*. 2024. arXiv:2312.07511.
- [44] Nathaniel Thomas, Tess Smidt, Steven Kearnes, Lusann Yang, Li Li, Kai Kohlhoff, Patrick Riley. *Tensor Field Networks: Rotation- and Translation-Equivariant Neural Networks for 3D Point Clouds*. 2018. arXiv:1802.08219.
- [45] Alexey Dosovitskiy et al. *An Image is Worth 16x16 Words: Transformers for Image Recognition at Scale*. ICLR 2021. arXiv:2010.11929.
- [46] Jinwoo Kim, Tien Dat Nguyen, Seonwoo Min, Sungjun Cho, Moontae Lee, Honglak Lee, Seunghoon Hong. *Pure Transformers are Powerful Graph Learners*. NeurIPS 2022. arXiv:2207.02505.
- [47] John Jumper et al. “Highly accurate protein structure prediction with AlphaFold”. *Nature* 596 (2021), pp. 583–589. doi:10.1038/s41586-021-03819-2.
- [48] Josh Abramson et al. “Accurate structure prediction of biomolecular interactions with AlphaFold 3”. *Nature* 630 (2024), pp. 493–500. doi:10.1038/s41586-024-07487-w.
- [49] Johann Brehmer et al. *Does equivariance matter at scale?* TMLR 2025. arXiv:2410.23179.
- [50] Jason Yim et al. *Fast protein backbone generation with SE(3) flow matching*. 2023. arXiv:2310.05297.
- [51] Yeqing Lin and Mohammed AlQuraishi. *Generating Novel, Designable, and Diverse Protein Structures by Equivariantly Diffusing Oriented Residue Clouds*. ICML 2023. arXiv:2301.12485.
- [52] Tuan Le et al. *Navigating the design space of equivariant diffusion-based generative models for de-novo 3D molecule generation*. ICLR 2024. arXiv:2309.17296.
- [53] Clement Vignac et al. *MiDi: Mixed Graph and 3D Denoising Diffusion for Molecule Generation*. ECML PKDD 2023. arXiv:2302.09048.
- [54] Ross Irwin, Alessandro Tibo, Jon Paul Janet, Simon Olsson. *SemlaFlow: Efficient 3D Molecular Generation with Latent Attention and Equivariant Flow Matching*. AISTATS 2025. arXiv:2406.07266.
- [55] National Institutes of Health. *Regulatory Knowledge Guide for Small Molecules*. NIH SEED, 2024. seed.nih.gov.

- [56] Encyclopaedia Britannica. *What is the difference between a peptide and a protein?* britannica.com.
- [57] Gisbert Schneider. “Automating drug discovery”. *Nature Reviews Drug Discovery* 17 (2018), pp. 97–113. doi:10.1038/nrd.2017.232.
- [58] Martin Buttenschoen, Garrett M. Morris, and Charlotte M. Deane. “PoseBusters: AI-based docking methods fail to generate physically valid poses or generalise to novel sequences”. *Chemical Science* 15 (2024), pp. 3130–3139. arXiv:2308.05777.
- [59] Kristina Preuer, Philipp Renz, Thomas Unterthiner, Sepp Hochreiter, and Günter Klambauer. “Fréchet ChemNet Distance: A Metric for Generative Models for Molecules in Drug Discovery”. *Journal of Chemical Information and Modeling* 58.9 (2018), pp. 1736–1741. doi:10.1021/acs.jcim.8b00234.
- [60] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. “GANs Trained by a Two Time-Scale Update Rule Converge to a Local Nash Equilibrium”. *Advances in Neural Information Processing Systems (NeurIPS)* 30 (2017). arXiv:1706.08500.
- [61] G. Richard Bickerton et al. “Quantifying the chemical beauty of drugs”. *Nature Chemistry* 4 (2012), pp. 90–98. doi:10.1038/nchem.1243.
- [62] Greg Landrum et al. *RDKit: Open-source cheminformatics*. www.rdkit.org.
- [63] Pascal Notin et al. “Machine learning for functional protein design”. *Nature Biotechnology* 42 (2024), pp. 216–228. doi:10.1038/s41587-024-02127-0.
- [64] Yeqing Lin, Minji Lee, Zhao Zhang, and Mohammed AlQuraishi. “Out of Many, One: Designing and Scaffolding Proteins at the Scale of the Structural Universe with Genie 2”. *arXiv preprint* arXiv:2405.15489 (2024). arXiv:2405.15489.
- [65] Christine A. Orengo, A. D. Michie, S. Jones, David T. Jones, M. B. Swindells, Janet M. Thornton. “CATH — a hierarchic classification of protein domain structures”. *Structure* 5.8 (1997), pp. 1093–1108. doi:10.1016/S0969-2126(97)00260-8.
- [66] Minyoung Huh, Brian Cheung, Tongzhou Wang, Phillip Isola. *The Platonic Representation Hypothesis*. ICML 2024. arXiv:2405.07987.
- [67] Gilles Labesse, Nathalie Colloc’h, Joël Pothier, Jean-Paul Mornon. “P-SEA: a new efficient assignment of secondary structure from C α trace of proteins”. *Computer Applications in the Biosciences (CABIOS)* 13.3 (1997), pp. 291–295. doi:10.1093/bioinformatics/13.3.291.
- [68] Patrick Kunzmann, Kay Hamacher. “Biotite: a unifying open source computational biology framework in Python”. *BMC Bioinformatics* 19 (2018), article 346. doi:10.1186/s12859-018-2367-z.

Appendix A

Technical details

A.1 Protein dataset composition and split overlap

Table A.1 summarises the two datasets used in Chapter 6. Both training sets are α/β -dominated and span a substantial fraction of CATH architectures (44.2% PDB, 61.8% AFDB), which is what makes the per-chain CATH fold probe meaningful. Neither random split is sequence-clustered: 98.3% of PDB and 92.2% of AFDB validation chains have a $\geq 30\%$ -identity homolog in their own training set, so absolute in-house scores are inflated and we read rank-order and Δ -from-baseline instead. The cross-database overlap is far lower: only 62.1% of AFDB validation chains have a $\geq 30\%$ -identity hit in PDB training. This is what makes a clean evaluation possible. Filtering AFDB chains clean against *both* training pools leaves ~ 325 proteins at $n \leq 256$, more than five times the ~ 62 left in the same-source PDB validation set, so this cross-database set serves as the blinded probe set for PDB-trained models (§A.3; Chapter 3).

A.2 Choice of CATH fold-probe level

We report CATH *architecture* (CATH-A) as the headline fold-probe level throughout Chapter 6. Table A.2 justifies that choice: Class is too coarse (four buckets, one already near-saturated), Topology too finely-bucketed to probe reliably, and Architecture sits be-

Property	PDB	AFDB (Swiss-Prot)
Origin	Experimental (X-ray, cryo-EM)	Predicted (AlphaFold2, v6)
Residue-length crop n	≤ 256 residues	
Train / val / test chains	273,771 / 3,190 / 323	229,670 / 4,521 / 235
CATH coverage (train)	44.2%	61.8%
Val $\leftrightarrow$ train, $\geq 30\%$ id.	98.3%	92.2%
AFDB-val $\leftrightarrow$ PDB-train, $\geq 30\%$ id.	62.1%	

Table A.1: Properties of the two datasets we study, at the headline $n \leq 256$ regime. Sequence identity is computed with MMseqs2 [29] (**easy-search**, $\geq 30\%$ identity over $\geq 80\%$ alignment coverage).

CATH level	#classes	baseline probe acc.	verdict
C (class)	4	0.733	one class (α/β) is 55% of the data; coarse, already near-saturated — <i>gameable</i>
A (architecture)	~ 40	0.407	balanced and discriminative, with headroom to move — <i>our headline fold metric</i>
T (topology)	~ 1400	0.301	long-tailed (top fold $\sim 18\%$; only ~ 89 classes populated enough to probe); per-class accuracy is unreliable — <i>too many buckets</i>

Table A.2: We read fold-level representation quality off CATH *Architecture*. Class is too coarse to discriminate, Topology too finely-bucketed to probe reliably. Class has 4 buckets (one at 55%, baseline already 0.73); Topology has ~ 1400 imbalanced buckets; Architecture sits between — enough classes to be meaningful, enough examples per class to be learnable — so CATH-A is our headline fold metric in the main text. (PDB-trained baseline, $n \leq 256$; “baseline probe acc.” is a linear probe on the un-aligned trunk, classifying validation chains by CATH code.)

tween — discriminative but learnable. The example here shows the PDB-trained baseline trunk ($n \leq 256$): the probe classifies validation chains by their CATH code and we report the linear-probe top-1 accuracy at each level.

A.3 Leakage-controlled probe evaluation

The random train/val split (§A.1) is not sequence-clustered, so probe scores are exposed to two distinct leakages. *Model leakage* is asymmetric: a model trained on the leaky split has effectively seen near-duplicates of the evaluation proteins, an advantage a differently-curated model (such as an externally-pretrained checkpoint) does not share. *Probe leakage* is symmetric: a probe fit on training chains near-identical to its evaluation set can shortcut by matching sequences rather than learning generalisable structure, inflating every model’s absolute score.

We control these by filtering the evaluation. A *probe-clean* split removes probe leakage alone. The probe’s training chains are filtered to have no $\geq 30\%$ sequence-identity hit to the evaluation set, which is otherwise the full validation set. A *blinded* split removes both: the evaluation proteins are held under 30% sequence identity to all training data.

However, for both our datasets, validation sets are heavily homologous to their own training data. For example, 98% of PDB validation chains have a $\geq 30\%$ hit in PDB training, leaving only ~ 62 clean chains at $n \leq 256$, which is far too few to probe. Hence, we look across datasets. AFDB chains filtered clean against both the PDB and AFDB training pools yield ~ 325 proteins, more than $5\times$ the ~ 62 -chain same-source PDB slice. We use this set as our blinded evaluation set for both PDB-trained and AFDB-trained models (Table A.4). This number suffices for our per-residue probes, as the ~ 325 proteins still

Variant	IF top-1 $\uparrow$	dihedral MAE ($^{\circ}$) $\downarrow$	CATH top-1 acc. $\uparrow$		
			C	A	T
Baseline	$0.129_{\pm 0.004}$	$31.5_{\pm 1.7}$	$0.724_{\pm 0.013}$	$0.408_{\pm 0.007}$	$0.332_{\pm 0.009}$
REPA L4-random	$-0.010_{\pm 0.002}$	$+3.9_{\pm 3.1}$	$+0.049_{\pm 0.005}$	$+0.011_{\pm 0.008}$	$-0.005_{\pm 0.013}$
REPA L4-GearNet [†]	$+0.018$	-9.1	$+0.153$	$+0.206$	$+0.278$
REPA L4-MPNN [†]	$+0.027$	-4.7	$+0.097$	$+0.109$	$+0.125$
REPA L9-GearNet	$+0.023_{\pm 0.002}$	$-6.4_{\pm 0.3}$	$+0.153_{\pm 0.009}$	$+0.267_{\pm 0.006}$	$+0.415_{\pm 0.017}$
REPA L9-MPNN	$+0.026_{\pm 0.002}$	$-5.6_{\pm 4.0}$	$+0.081_{\pm 0.006}$	$+0.063_{\pm 0.003}$	$+0.106_{\pm 0.026}$

Table A.3: Full PDB representation-quality ablation across all six variants. The remaining encoder $\times$ depth combinations behind Table 6.2, at the same 1.0M checkpoint. The encoder-routed pattern holds: GearNet wins the fold probes (CATH C/A/T), ProteinMPNN edges the inverse-folding probe (IF). At matched layer 4, the trained GearNet (L4-GearNet) beats the random control (L4-random) on every probe, so the learned-versus-random gap is not an artefact of injection depth. ($n=3$ seeds, $\pm$ half the range; ([†]) L4-GearNet and L4-MPNN single-seed. Best-layer linear probe.)

yield ~ 43 k residues, which yields full statistical power.

However, the per-chain CATH probe needs more data. Fold classification needs many distinct chains spread across populated fold classes, and the blinded slice is too small and too class-sparse for this. Hence, for the numbers we report in the main text, we relax our clean condition to the probe-clean split on the fuller validation set ($\sim 3,190$ chains). Comparing the splits also decomposes the leakage — the dirty-to-probe-clean drop isolates probe leakage and the probe-clean-to-blinded drop isolates model leakage — and the REPA-over-baseline gap survives in every regime.

A.4 Full representation-quality ablation

The main-text representation table (Table 6.2) shows four rows. Table A.3 gives the full six-variant grid, adding the layer-4 GearNet and ProteinMPNN combinations. Two readings carry over from the main text: the encoder-routed pattern (ProteinMPNN wins the per-residue probes, GearNet the fold probes) holds across all depths, and at matched layer 4 the trained GearNet beats the random control on every probe.

A.5 Representation quality on AFDB

Table A.4 is the AFDB-trained counterpart of the PDB Table 6.2. The fold routing (GearNet $\rightarrow$ CATH) replicates. The per-residue routing does not: inverse folding and the dihedral probe show no consistent REPA effect, unlike the clear MPNN-led per-residue gains on PDB.

However, we note this might reflect a measurement limit. These probes are run on the small cross-database blinded set at a single seed and a single checkpoint, so step-to-step noise is large. For example, the baseline dihedral error alone swings several degrees

Variant	IF top-1 $\uparrow$	dihedral MAE ($^\circ$) $\downarrow$	CATH top-1 acc. $\uparrow$		
			C	A	T
Baseline	0.122	39.1	0.800	0.467	0.167
REPA L4-random [‡]	+0.001	+0.2	+0.133	+0.200	+0.167
REPA L4-GearNet	−0.000	+1.8	+0.067	+0.067	+0.167
REPA L9-GearNet	+0.004	−1.3	+0.067	+0.133	+0.333
REPA L4-MPNN	+0.002	+10.8	+0.000	+0.000	+0.333
REPA L9-MPNN	+0.002	+1.2	+0.067	−0.067	+0.333

Table A.4: On AFDB, REPA’s representation gain concentrates on fold structure. The AFDB counterpart to Table 6.2: REPA-GearNet lifts the CATH fold probes as on PDB, so the fold routing replicates. The per-residue probes (IF, dihedral) show no consistent effect and are noise-dominated at this scale, so we lean on the fold result. ($n \leq 256$ AFDB-trained; best-layer linear probe on the cross-database blinded set (App. A.3); single 1.0M checkpoint, $n=1$ seed. [‡]Random control at its 500K checkpoint.)

	GearNet	ProteinMPNN	ESM2
Baseline	0.6 ^{L6}	0.9 ^{L7}	2.7 ^{L8}
REPA L4-GearNet	2.6 ^{L4†}	2.9 ^{L6}	8.2 ^{L8}
REPA L9-GearNet	22.9 ^{L8†}	26.7 ^{L8}	40.1 ^{L8}
REPA L4-MPNN	4.8 ^{L7}	16.6 ^{L7†}	19.8 ^{L5}
REPA L9-MPNN	5.0 ^{L7}	14.2 ^{L6†}	14.2 ^{L7}

Table A.5: Every REPA variant raises per-residue alignment to all three encoders, including the two it was never aligned to. Across-layer peak per-residue CKNNA (bootstrap median, $\times 10^3$), with the peak trunk layer as a superscript; $k=10$, step 1.0M, $n \leq 256$ PDB-trained. The $\dagger$ marks each model’s own alignment target. Absolute values are small (an order of magnitude below image-domain REPA), so we read the pattern, not the magnitude. ($n=1$ seed; bootstrap medians.)

between adjacent checkpoints. We therefore draw no per-residue conclusion on AFDB and lean on the fold result, where the effect is large enough to clear that noise.

A.6 Representation-alignment matrix

The alignment diagnostic in §6.2.2 reports peak per-residue CKNNA for a single illustrative variant. Table A.5 gives the full model $\times$ encoder matrix behind that reading. As we show in the main text, aligning the trunk to one encoder raises its CKNNA to the other two as well, not just the alignment target. The absolute values stay an order of magnitude below image-domain REPA, so we read the direction and layer pattern rather than the raw magnitude.

A.7 Representation–generation coupling on AFDB

Section 6.2.3 establishes the representation–generation coupling on PDB-trained models (Table 6.5). Table A.6 repeats the analysis for AFDB-trained models. The coupling holds

Representation quality	FPSD		Designability	
	partial	raw	partial	raw
Inverse folding (top-1)	-0.15	-0.14	+0.49	+0.50
Dihedral MAE	+0.05	-0.08	+0.36	+0.12
CATH-A	+0.42	+0.45	+0.28	+0.32

Table A.6: On AFDB too, better trunk representations track better generation. The AFDB counterpart to Table 6.5 (same partial-Pearson method). Generation is FPSD-AFDB and designability; representation probes are read at $n_{\text{train}}=1000$ on a leakage-controlled set (App. A.3). ($n=40$ AFDB checkpoints pooled over the baseline, the REPA variants, and the random control; generation is a 3-seed mean, with single-seed checkpoints only for the under-trained variants (AFDB L9-GearNet, L4-MPNN) and trajectory tails; probe single-seed; 1,125 backbones/seed, 250 for designability.)

here too, and in the same encoder-matched form. Local probes (inverse folding, dihedral) track designability, while the fold probe (CATH-A) tracks FPSD. The off-axis pairs are weak or absent, the signature of an encoder-routed effect rather than a generic one. We read AFDB designability with the proxy caveat of §6.1.1, so we lean on the FPSD column and the routing pattern rather than the absolute designability correlation.

A.8 The ssJSD-2D secondary-structure metric

Proteina’s secondary-structure metric compares the *mean* helix and strand content of a generated set against a reference. This collapses each set to a single point, so it cannot see variance, bimodality, or tails. Hence, a model that matches the average composition while collapsing its spread scores the same as one that reproduces it. ssJSD-2D removes this blind spot by comparing the full joint distribution.

For each backbone we annotate every residue as helix, strand, or coil with a C α -only secondary-structure assignment (P-SEA [67], as implemented in Biotite [68]) and record the fraction of residues in helix (f_H) and in strand (f_E). A set of N backbones is then a cloud of N points in the (f_H, f_E) plane. We bin that plane into a 5×5 grid over $[0, 1]^2$, form normalised two-dimensional histograms for the generated and reference sets, and report the Jensen–Shannon divergence between them (lower is better). Binning the joint distribution, rather than comparing marginal means, lets the metric reward a model for reproducing the *shape* of the secondary-structure distribution and penalise mode collapse onto, say, all- α backbones.

A.9 Secondary-structure composition of the designable subset

Table A.7 reports the per-seed secondary-structure composition of the designable backbones, behind the secondary-structure readings in §6.2.4. We show it at 700K, the step

Variant (700K, $\gamma=0.45$)	β -strand	α -helix	Seeds
<i>PDB-trained</i>			
Baseline	0.22 ± 0.02	0.48 ± 0.03	3
REPA L4-random	0.11 ± 0.01	0.61 ± 0.02	3
REPA L4-GearNet	0.22 ± 0.01	0.40 ± 0.02	3
REPA L9-GearNet	0.18 ± 0.02	0.48 ± 0.03	3
REPA L4-MPNN	0.23 ± 0.01	0.39 ± 0.03	3
REPA L9-MPNN	0.15 ± 0.01	0.54 ± 0.02	3
<i>AFDB-trained</i>			
Baseline	0.16 ± 0.01	0.47 ± 0.01	2
REPA L4-GearNet	0.14 ± 0.00	0.47 ± 0.01	2
REPA L9-GearNet	0.19 ± 0.01	0.38 ± 0.03	3
REPA L9-MPNN	0.11 ± 0.00	0.55 ± 0.01	2

Table A.7: Secondary-structure composition of the designable subset (step 700K, $\gamma=0.45$). Mean β -strand and α -helix fractions over the designable backbones, $\pm$ half the seed range. On AFDB the L9-GearNet and L9-MPNN strand and helix ranges do not overlap across seeds, in opposite directions. (AFDB L4-MPNN omitted: no multi-seed $\gamma=0.45$ data; 2–3 seeds per row, given in the Seeds column; 250 backbones/seed.)

with the most complete multi-seed coverage across variants. On AFDB, the L9-GearNet and L9-MPNN strand and helix ranges do not overlap across seeds, in opposite directions. The remaining rows are included for completeness.

A.10 Deterministic (ODE) sampling across variants

The deterministic (ODE) sampler reads the learned velocity field with no injected noise. This isolates what the trunk has learned from the sampler that draws from it. We note that we use the ODE limit as a diagnostic. It is not the operating point for our models, which use tuned SDE noise (Table 6.4).

Table A.8 gives the all-variant ODE snapshot at 1.3M. On AFDB, the REPA lift holds across every trained encoder. For the strongest variant (L4-GearNet) it comes without concentrating designable diversity (des. pwTM); only L9-GearNet tightens it meaningfully. This further suggests that REPA helps learn a better model, as outlined in §6.2.4.

PDB displays a more subtle pattern. L4-GearNet and L9-MPNN comfortably beat the baseline on designability (Table A.8), but FPSD for REPA variants is generally higher. One possible explanation is that REPA alignment moves the velocity field towards a few folds, as we discuss in §6.2.4. At zero noise, the unsmoothed field then covers the target distribution worse, which inflates FPSD. In this reading, the injected sampler noise then re-broadens these models to recover distribution match.

We read the magnitudes cautiously, as the ODE FPSD is single-seed and noisy. We only use these results to inform our directional understanding of what is happening.

Variant (1.3M, ODE)	Des $\uparrow$	FPSD $\downarrow$	des. pwTM $\downarrow$
<i>PDB-trained</i>			
Baseline	0.07	297	0.27
REPA L4-random	0.03	353	0.42
REPA L4-GearNet	0.20	601	0.31
REPA L9-GearNet	0.08	376	0.34
REPA L4-MPNN	0.10	385	0.46
REPA L9-MPNN	0.23	413	0.29
<i>AFDB-trained</i>			
Baseline	0.18	233	0.14
REPA L4-random *	—	—	—
REPA L4-GearNet	0.29	177	0.17
REPA L9-GearNet	0.36	134	0.25
REPA L4-MPNN	0.15	206	0.19
REPA L9-MPNN	0.18	182	0.15

Table A.8: Deterministic (ODE) sampling at 1.3M: REPA lifts the floor on AFDB, but redistributes it on PDB (designability up, FPSD worse). Designable pwTM is mean pairwise TM over the designable subset (higher = more concentrated). Cells coloured by direction (green better, red worse) within a 0.05 threshold. ($n=1$ seed; 1,125 backbones/seed, 250 for designability. *AFDB L4-random has no checkpoint past 800K.)

Variant (range over seeds)	Des $\uparrow$	FPSD $\downarrow$	fJSD-A $\downarrow$	fS-A $\uparrow$	pwTM $\downarrow$	ssJSD2D (W) $\downarrow$	ssJSD2D (D) $\downarrow$	β frac. $\uparrow$
<i>PDB-trained</i>								
Baseline	0.52–0.61	414–417	0.90–0.99	5.87–6.22	0.14–0.18	0.29–0.33	0.39–0.48	0.05–0.10
REPA L4-random (1.2M)	0.24–0.28	436–443	0.58–0.64	5.99–6.26	0.18–0.21	0.14–0.15	0.35–0.39	0.11–0.13
REPA L4-GearNet (1.0M)	0.40–0.54	424–438	0.51–0.56	7.03–7.73	0.16–0.19	0.15–0.16	0.33–0.42	0.07–0.08
REPA L9-GearNet [†]	0.48	394	0.69	7.49	0.28	0.09	0.21	0.26
REPA L4-MPNN	0.55–0.69	482–497	0.78–0.87	6.45–6.56	0.22–0.27	0.16–0.17	0.29–0.31	0.18–0.20
REPA L9-MPNN	0.75–0.82	382–390	0.84–0.87	6.75–7.03	0.28–0.30	0.13–0.14	0.18–0.25	0.20–0.23
<i>AFDB-trained</i>								
Baseline	0.56–0.71	368–397	1.59–1.70	5.35–5.57	0.15–0.20	0.09–0.11	0.13–0.28	0.11–0.14
REPA L4-random (0.5M)	0.83–0.86	367–375	1.48–1.62	4.93–5.26	0.18–0.20	0.16–0.17	0.18–0.20	0.13–0.14
REPA L4-GearNet	0.73–0.80	309–322	0.90–1.02	7.44–7.87	0.19–0.21	0.04–0.05	0.09–0.12	0.15–0.17
REPA L9-GearNet (1.0M)	0.70–0.74	291–294	1.06–1.17	6.81–7.25	0.23–0.27	0.03–0.04	0.05–0.07	0.19–0.19
REPA L4-MPNN (1.1M) [†]	0.69	458	1.93	4.97	0.25	0.11	0.15	0.13
REPA L9-MPNN	0.76–0.78	382–393	1.52–1.56	5.02–5.15	0.17–0.18	0.14–0.16	0.14–0.18	0.11–0.12

Table A.9: Per-seed min–max spread behind Table 6.6, whose cells report the mean over three generation seeds (42/1042/2042, default sde sampler $n=0.45$). Here we give the min–max range across those seeds, in absolute units. ([†]single seed, no range.)

A.11 Per-seed spread of the 1.3M results

Each cell of Table 6.6 is a mean over three generation seeds. Table A.9 reports the min–max range across those three seeds for the same cells, in absolute units. The most load-bearing case is AFDB L4-GearNet, as references in the main text. Its designable-diversity (pwTM) range overlaps with the baseline, so the 0.02 rise we report is within seed scatter, while its FPSD range stays cleanly below the baseline’s.

Encoder	Dim	atom probe	context- Δ	3D	Floor	Best	Lift	Sparsity	RankMe
CheMeleon (2D graph)	2048	1.000	0.093	1.00	0.43	0.471	+0.04	93.8%	1166
MACE (3D potential)	192	1.000	0.260	0.998	0.86	0.863	+0.005	0.0%	40.6

Table A.10: Full molecule encoder profile, expanding Table 4.2. The atom probe is trivial in QM9 (max 9 atoms). RankMe is high for CheMeleon because its variance is diffuse and 93.8% sparse, not collapsed — higher is not better here.

Encoder	Dim	AA-probe	3D	context- Δ	Floor	Best	Lift	RankMe	PR	Dims@95%	norm
GearNet (CATH-trained)	512	0.137	0.27	0.222	0.425	0.434	+0.009	256.4	37.9	119	79.6
<i>random-init</i>	512	0.127	1.00	0.035	0.952	0.954	+0.003	99.8	1.5	38.7	—
ProteinMPNN (inv-fold)	128	0.327	0.73	0.022	0.835	0.850	+0.014	84.9	33.3	92	3.13
ESM2-650M (last layer)	1280	0.998	N/A	0.098	0.671	0.723	+0.053	1030.5	43.3	993	9.8
PW-GearNet (torsional)	3072	0.928	0.86	0.102	0.710	0.723	+0.013	207.7	5.5	36	37.2
MC-GearNet-Edge	3072	0.146	0.77	0.043	0.855	0.858	+0.002	12.0	1.0	1	1.5×10^6

Table A.11: Full protein encoder profile, expanding Table 4.3. 3D is N/A for sequence-only ESM2; GearNet random-init norms were not separately recorded. MC-GearNet-Edge shows the conditioning failure directly: norm 1.5×10^6 with all variance in one dimension (Dims@95% = 1).

A.12 Full encoder profiles

Tables 4.2 and 4.3 in the main text show only the diagnostics that drive each verdict. Tables A.10 and A.11 give the complete measured set for every candidate encoder. The probe, 3D, Floor, Lift, Sparsity and RankMe columns carry the same meaning as in the main-text tables. The added columns are context- Δ (the within-minus-between cosine spread); Best (the best-projector cosine, with Lift = Best − Floor); PR (participation ratio); Dims@95% (dimensions holding 95% of the variance); and norm (mean L2 embedding norm). The spectral columns — RankMe, PR, Dims@95% and norm — diagnose optimisation tractability. Rank collapse or a norm explosion degrades the gradient signal even when the embedding is informative.